pgAdmin 4 Documentation

Release 9.19

The pgAdmin Development Team

Nov 10, 2026

Contents

1 Getting Started **3**
- 1.1 Deployment . . . 4
- 1.2 Login Page . . . 57
- 1.3 Enabling two-factor authentication (2FA) . . . 58
- 1.4 User Management . . . 60
- 1.5 Change Ownership Dialog . . . 66
- 1.6 Change pgAdmin Password Dialog . . . 68
- 1.7 Lock/Restore Account . . . 69
- 1.8 Enabling LDAP Authentication . . . 70
- 1.9 Enabling Kerberos Authentication . . . 73
- 1.10 Enabling OAUTH2 and OIDC Authentication . . . 76
- 1.11 Enabling Webserver Authentication . . . 86
- 1.12 User Interface . . . 88
- 1.13 Menu Bar . . . 89
- 1.14 Toolbar . . . 96
- 1.15 Object Explorer Filter . . . 96
- 1.16 Tabbed Browser . . . 96
- 1.17 Tree Control . . . 106
- 1.18 Preferences . . . 109
- 1.19 Keyboard Shortcuts . . . 133
- 1.20 Search objects . . . 136

2 External database for pgAdmin user settings **139**
- 2.1 Use SQLite Database . . . 139
- 2.2 Use External Database . . . 139
- 2.3 Use PostgreSQL Database . . . 140

3 Connecting To A Server **141**
- 3.1 Server Group Dialog . . . 141
- 3.2 Server Dialog . . . 142
- 3.3 PostgreSQL Cloud Deployment . . . 151
- 3.4 Master Password . . . 175
- 3.5 Connect to Server . . . 177
- 3.6 Connection Error . . . 178
- 3.7 Import/Export Servers . . . 180

4 Managing Cluster Objects **187**

4.1 Database Dialog . . . 187
4.2 Resource Group Dialog . . . 193
4.3 Login/Group Role Dialog . . . 195
4.4 Tablespace Dialog . . . 202
4.5 Replica Node Dialog . . . 207
4.6 PGD Replication Group Node Dialog . . . 208
4.7 Role Reassign/Drop Own Dialog . . . 210
4.8 Directory Dialog . . . 213

5 Managing Database Objects 217
5.1 Cast Dialog . . . 217
5.2 Using EDB Job Scheduler . . . 220
5.3 Collation Dialog . . . 234
5.4 Domain Dialog . . . 238
5.5 Domain Constraints Dialog . . . 242
5.6 Event Trigger Dialog . . . 246
5.7 Extension Dialog . . . 250
5.8 Foreign Data Wrapper Dialog . . . 252
5.9 Foreign Server Dialog . . . 258
5.10 Foreign Table Dialog . . . 263
5.11 FTS Configuration Dialog . . . 270
5.12 FTS Dictionary Dialog . . . 273
5.13 FTS Parser Dialog . . . 278
5.14 FTS Template Dialog . . . 281
5.15 Function Dialog . . . 284
5.16 Language Dialog . . . 291
5.17 Materialized View Dialog . . . 295
5.18 Package Dialog . . . 299
5.19 Procedure Dialog . . . 304
5.20 Publication Dialog . . . 312
5.21 Schema Dialog . . . 316
5.22 Sequence Dialog . . . 321
5.23 Statistics Dialog . . . 326
5.24 Subscription Dialog . . . 328
5.25 Synonym Dialog . . . 336
5.26 Trigger Function Dialog . . . 339
5.27 Type Dialog . . . 348
5.28 User Mapping Dialog . . . 356
5.29 View Dialog . . . 359

6 Creating or Modifying a Table 365
6.1 Check Dialog . . . 365
6.2 Column Dialog . . . 368
6.3 Compound Trigger Dialog . . . 377
6.4 Exclusion Constraint Dialog . . . 382
6.5 Foreign key Dialog . . . 385
6.6 Index Dialog . . . 392
6.7 Primary key Dialog . . . 396
6.8 RLS Policy Dialog . . . 400
6.9 Rule Dialog . . . 403
6.10 Table Dialog . . . 410
6.11 Trigger Dialog . . . 431
6.12 Unique Constraint Dialog . . . 437

7 Management Basics **441**
7.1 Add Named Restore Point Dialog . . . 441
7.2 Change Server Password Dialog . . . 442
7.3 Grant Wizard . . . 443
7.4 Export Data Using Query Dialog . . . 445
7.5 Import/Export Data Dialog . . . 449
7.6 Maintenance Dialog . . . 454
7.7 Storage Manager . . . 457

8 Backup and Restore **463**
8.1 Backup Dialog . . . 463
8.2 Backup Globals Dialog . . . 471
8.3 Backup Server Dialog . . . 472
8.4 Restore Dialog . . . 477

9 Developer Tools **483**
9.1 Debugger . . . 483
9.2 Query Tool . . . 489
9.3 View/Edit Data . . . 519
9.4 Schema Diff . . . 525
9.5 ERD Tool . . . 530
9.6 PSQL Tool . . . 539
9.7 AI Reports . . . 541

10 Processes **547**
10.1 Process Watcher . . . 548
10.2 Watch the demo . . . 548

11 pgAgent **549**
11.1 Using pgAgent . . . 549
11.2 Installing pgAgent . . . 550
11.3 Creating a pgAgent Job . . . 552

12 pgTimeTable Chains **563**
12.1 Viewing pgTimeTable . . . 563
12.2 Creating a Chain . . . 564
12.3 Chain Task Dialog . . . 567

13 pgAdmin Project Contributions **571**
13.1 Submitting Pull Requests . . . 571
13.2 Code Overview . . . 572
13.3 Coding Standards . . . 576
13.4 Code Snippets . . . 578
13.5 Code Review Notes . . . 591
13.6 Translations . . . 592

14 Release Notes **595**
14.1 Version 9.19 . . . 595
14.2 Version 9.18 . . . 603
14.3 Version 9.17 . . . 607
14.4 Version 9.16 . . . 610
14.5 Version 9.15 . . . 614
14.6 Version 9.14 . . . 617
14.7 Version 9.13 . . . 619
14.8 Version 9.12 . . . 620

14.9 Version 9.11 . . . 621
14.10 Version 9.10 . . . 622
14.11 Version 9.9 . . . 623
14.12 Version 9.8 . . . 624
14.13 Version 9.7 . . . 625
14.14 Version 9.6 . . . 626
14.15 Version 9.5 . . . 627
14.16 Version 9.4 . . . 629
14.17 Version 9.3 . . . 630
14.18 Version 9.2 . . . 631
14.19 Version 9.1 . . . 632
14.20 Version 9.0 . . . 633
14.21 Version 8.14 . . . 634
14.22 Version 8.13 . . . 636
14.23 Version 8.12 . . . 637
14.24 Version 8.11 . . . 638
14.25 Version 8.10 . . . 639
14.26 Version 8.9 . . . 640
14.27 Version 8.8 . . . 642
14.28 Version 8.7 . . . 642
14.29 Version 8.6 . . . 643
14.30 Version 8.5 . . . 645
14.31 Version 8.4 . . . 646
14.32 Version 8.3 . . . 647
14.33 Version 8.2 . . . 648
14.34 Version 8.1 . . . 649
14.35 Version 8.0 . . . 650
14.36 Version 7.8 . . . 652
14.37 Version 7.7 . . . 653
14.38 Version 7.6 . . . 654
14.39 Version 7.5 . . . 655
14.40 Version 7.4 . . . 657
14.41 Version 7.3 . . . 658
14.42 Version 7.2 . . . 658
14.43 Version 7.1 . . . 660
14.44 Version 7.0 . . . 661
14.45 Version 6.21 . . . 663
14.46 Version 6.20 . . . 664
14.47 Version 6.19 . . . 665
14.48 Version 6.18 . . . 666
14.49 Version 6.17 . . . 666
14.50 Version 6.16 . . . 667
14.51 Version 6.15 . . . 669
14.52 Version 6.14 . . . 670
14.53 Version 6.13 . . . 671
14.54 Version 6.12 . . . 673
14.55 Version 6.11 . . . 674
14.56 Version 6.10 . . . 674
14.57 Version 6.9 . . . 675
14.58 Version 6.8 . . . 677
14.59 Version 6.7 . . . 678
14.60 Version 6.6 . . . 678
14.61 Version 6.5 . . . 679
14.62 Version 6.4 . . . 680

14.63 Version 6.3 . . . 681
14.64 Version 6.2 . . . 682
14.65 Version 6.1 . . . 683
14.66 Version 6.0 . . . 684
14.67 Version 5.7 . . . 684
14.68 Version 5.6 . . . 686
14.69 Version 5.5 . . . 686
14.70 Version 5.4 . . . 687
14.71 Version 5.3 . . . 688
14.72 Version 5.2 . . . 689
14.73 Version 5.1 . . . 690
14.74 Version 5.0 . . . 692
14.75 Version 4.30 . . . 693
14.76 Version 4.29 . . . 695
14.77 Version 4.28 . . . 695
14.78 Version 4.27 . . . 696
14.79 Version 4.26 . . . 697
14.80 Version 4.25 . . . 699
14.81 Version 4.24 . . . 700
14.82 Version 4.23 . . . 701
14.83 Version 4.22 . . . 702
14.84 Version 4.21 . . . 703
14.85 Version 4.20 . . . 705
14.86 Version 4.19 . . . 706
14.87 Version 4.18 . . . 707
14.88 Version 4.17 . . . 708
14.89 Version 4.16 . . . 709
14.90 Version 4.15 . . . 711
14.91 Version 4.14 . . . 712
14.92 Version 4.13 . . . 713
14.93 Version 4.12 . . . 714
14.94 Version 4.11 . . . 715
14.95 Version 4.10 . . . 717
14.96 Version 4.9 . . . 717
14.97 Version 4.8 . . . 718
14.98 Version 4.7 . . . 719
14.99 Version 4.6 . . . 720
14.100 Version 4.5 . . . 721
14.101 Version 4.4 . . . 721
14.102 Version 4.3 . . . 723
14.103 Version 4.2 . . . 724
14.104 Version 4.1 . . . 725
14.105 Version 4.0 . . . 726
14.106 Version 3.6 . . . 727
14.107 Version 3.5 . . . 727
14.108 Version 3.4 . . . 728
14.109 Version 3.3 . . . 728
14.110 Version 3.2 . . . 729
14.111 Version 3.1 . . . 730
14.112 Version 3.0 . . . 731
14.113 Version 2.1 . . . 734
14.114 Version 2.0 . . . 736
14.115 Version 1.6 . . . 738
14.116 Version 1.5 . . . 740

14.117 Version 1.4 . . . 741
14.118 Version 1.3 . . . 742
14.119 Version 1.2 . . . 743
14.120 Version 1.1 . . . 745
14.121 Version 1.0 . . . 746

15 Licence **747**

Index **749**



Welcome to pgAdmin 4. pgAdmin is the leading Open Source management tool for Postgres, the world's most advanced Open Source database. pgAdmin 4 is designed to meet the needs of both novice and experienced Postgres users alike, providing a powerful graphical interface that simplifies the creation, maintenance and use of database objects.

CHAPTER 1

Getting Started

Pre-compiled and configured installation packages for pgAdmin 4 are available for a number of desktop environments; we recommend using an installer whenever possible.

In a *Server Deployment*, the pgAdmin application is deployed behind a webserver or with the WSGI interface. If you install pgAdmin in server mode, you will be prompted to provide a role name and pgAdmin password when you initially connect to pgAdmin. The first role registered with pgAdmin will be an administrative user; the administrative role can use the pgAdmin *User Management* dialog to create and manage additional pgAdmin user accounts. When a user authenticates with pgAdmin, the pgAdmin tree control displays the server definitions associated with that login role.

In a *Desktop Deployment*, the pgAdmin application is configured to use the desktop runtime environment to host the program on a supported platform. Typically, users will install a pre-built package to run pgAdmin in desktop mode, but a manual desktop deployment can be installed and though it is more difficult to setup, it may be useful for developers interested in understanding how pgAdmin works.

It is also possible to use a *Container Deployment* of pgAdmin, in which Server Mode is pre-configured for security.

1.1 Deployment

Pre-compiled and configured installation packages for pgAdmin 4 are available for a number of desktop environments; we recommend using an installer whenever possible. If you are interested in learning more about the project, or if a pgAdmin installer is not available for your environment, the pages listed below will provide detailed information about creating a custom deployment.

1.1.1 Configuration Files

There are multiple configuration files that are read at startup by pgAdmin. These files are used for configuration options that:

- may be required to be set prior to startup of pgAdmin as they control how the application will operate.
- system administrators may wish to control across an organisation to enforce security policies.
- are so rarely or unlikely to be changed that it doesn't make sense to allow them to be changed through the user interface.

The configuration files are as follows:

- `config.py`: This is the main configuration file, and should not be modified. It can be used as a reference for configuration settings, that may be overridden in one of the following files.
- `config_distro.py`: This file is read after `config.py` and is intended for packagers to change any settings that are required for their pgAdmin distribution. This may typically include certain paths and file locations. This file is optional, and may be created by packagers in the same directory as `config.py` if needed.
- `config_local.py`: This file is read after `config_distro.py` and is intended for the owner of the installation to change any default or packaging specific settings that they may wish to adjust to meet local preferences or standards.This file is optional, and may be created by users in the same directory as `config.py` if needed.

  Note

  On macOS, `config.py` is located inside the application bundle (`pgAdmin 4.app/Contents/Resources/web/`), which is replaced in its entirety when pgAdmin is upgraded, so a `config_local.py` file created there will be lost. Use `config_system.py` instead, which is stored outside the application bundle.

- `config_system.py`: This file is read after `config_local.py` and is intended for system administrators to include settings that are configured system-wide from a secure location that users cannot normally modify and that is outside of the pgAdmin installation. The location for this file varies based on the platform, and only needs to be created if desired.

Platform	File Location
Linux	/etc/pgadmin/config_system.py
macOS	/Library/Preferences/pgadmin/config_system.py
Windows	%CommonProgramFiles%\pgadmin\config_system.py

Note

If the SERVER_MODE or DATA_DIR settings are changed in `config_distro.py`, `config_local.py`, or `config_system.py` LOG_FILE, SQLITE_PATH, SESSION_DB_PATH, STORAGE_DIR, KER-

BEROS_CCACHE_DIR, and AZURE_CREDENTIAL_CACHE_DIR values will be set based on DATA_DIR unless values are explicitly overridden for any of the variable in any of the above file.

The default `config.py` file is shown below for reference:

```
# -*- coding: utf-8 -*-

##########################################################################
#
# pgAdmin 4 - PostgreSQL Tools
#
# Copyright (C) 2013 - 2026, The pgAdmin Development Team
# This software is released under the PostgreSQL Licence
#
# config.py - Core application configuration settings
#
##########################################################################

import builtins
import logging
import os
import sys
from collections import OrderedDict

# We need to include the root directory in sys.path to ensure that we can
# find everything we need when running in the standalone runtime.
root = os.path.dirname(os.path.realpath(__file__))
if sys.path[0] != root:
    sys.path.insert(0, root)

# The config database connection pool size.
# Setting this to 0 will remove any limit.
CONFIG_DATABASE_CONNECTION_POOL_SIZE = 5
# The number of connections allowed to overflow beyond
# the connection pool size.
CONFIG_DATABASE_CONNECTION_MAX_OVERFLOW = 100

from pgadmin.utils import env, IS_WIN, fs_short_path
from version import APP_VERSION, APP_RELEASE, APP_REVISION, APP_SUFFIX, \
    APP_VERSION_INT
from branding import APP_NAME, APP_ICON, APP_COPYRIGHT, APP_PATH, \
    APP_WIN_PATH, APP_SHORT_NAME, APP_DEFAULT_EMAIL

##########################################################################
# Misc stuff
##########################################################################

# Path to the online help.
HELP_PATH = '../../../docs/en_US/_build/html/'

# Languages we support in the UI
# Babel's locale data for other languages is removed from the packages by
```

(continues on next page)

(continued from previous page)

```
# pkg/prune_site_packages.py, which parses this assignment, so it must stay a
# plain dict literal.
LANGUAGES = {
    'en': 'English',
    'zh_Hans_CN': 'Chinese (Simplified)',
    'zh_Hant_TW': 'Chinese (Traditional)',
    'cs': 'Czech',
    'fr': 'French',
    'de': 'German',
    'id': 'Indonesian',
    'it': 'Italian',
    'ja': 'Japanese',
    'ko': 'Korean',
    'pl': 'Polish',
    'pt_BR': 'Portuguese (Brazilian)',
    'ru': 'Russian',
    'es': 'Spanish',
    'sv': 'Swedish'
}

# DO NOT CHANGE UNLESS YOU KNOW WHAT YOU ARE DOING!
# List of modules to skip when dynamically loading
MODULE_BLACKLIST = ['test']

# DO NOT CHANGE UNLESS YOU KNOW WHAT YOU ARE DOING!
# List of treeview browser nodes to skip when dynamically loading
NODE_BLACKLIST = []

##########################################################################
# Server settings
##########################################################################

# The server mode determines whether or not we're running on a web server
# requiring user authentication, or desktop mode which uses an automatic
# default login.
#
# DO NOT DISABLE SERVER MODE IF RUNNING ON A WEBSERVER!!
#
# We only set SERVER_MODE if it's not already set. That's to allow the
# runtime to force it to False.
#
# NOTE: If you change the value of SERVER_MODE or DATA_DIR in an included
#       config file, you may also need to redefine any values below that are
#       derived from it, notably various paths such as LOG_FILE, SQLITE_PATH,
#       SESSION_DB_PATH, STORAGE_DIR, KERBEROS_CCACHE_DIR, and
#       AZURE_CREDENTIAL_CACHE_DIR

if (not hasattr(builtins, 'SERVER_MODE')) or builtins.SERVER_MODE is None:
    SERVER_MODE = True
else:
    SERVER_MODE = builtins.SERVER_MODE
```

(continues on next page)

(continued from previous page)

```
# HTTP headers to search for CSRF token when it is not provided in the form.
# Default is ['X-CSRFToken', 'X-CSRF-Token']
WTF_CSRF_HEADERS = ['X-pgA-CSRFToken']

# User ID (email address) to use for the default user in desktop mode.
# The default should be fine here, as it's not exposed in the app.
DESKTOP_USER = APP_DEFAULT_EMAIL

# This option allows the user to host the application on a LAN
# Default hosting is on localhost (DEFAULT_SERVER='localhost').
# To host pgAdmin4 over LAN set DEFAULT_SERVER='0.0.0.0' (or a specific
# adaptor address.
#
# NOTE: This is NOT recommended for production use, only for debugging
# or testing. Production installations should be run as a WSGI application
# behind Apache HTTPD.
DEFAULT_SERVER = '127.0.0.1'

# The default port on which the app server will listen if not set in the
# environment by the runtime
DEFAULT_SERVER_PORT = 5050

# This param is used to override the default web server information about
# the web technology and the frameworks being used in the application
# An attacker could use this information to fingerprint underlying operating
# system and research known exploits for the specific version of
# software in use
WEB_SERVER = 'Python'

# Enable X-Frame-Option protection.
# Set to one of "SAMEORIGIN", "ALLOW-FROM origin" or "" to disable.
# Note that "DENY" is NOT supported (and will be silently ignored).
# See https://tools.ietf.org/html/rfc7034 for more info.
X_FRAME_OPTIONS = "SAMEORIGIN"


# The Cross-Origin-Opener-Policy allows a website to control whether
# a new top-level document, opened using Window.open() or by navigating
# to a new page, is opened in the same browsing context group (BCG)
# or in a new browsing context group.
# Set to 'unsafe-none', 'same-origin-allow-popups', 'same-origin',
# or 'noopener-allow-popups'

CROSS_ORIGIN_OPENER_POLICY = "same-origin"


# The Content-Security-Policy header allows you to restrict how resources
# such as JavaScript, CSS, or pretty much anything that the browser loads.
# see https://content-security-policy.com/#source_list for more info
# e.g. "default-src https: data: 'unsafe-inline' 'unsafe-eval';"
#
# A per-request nonce is used in place of 'unsafe-inline' for scripts. The
```

(continues on next page)

(continued from previous page)

```
# literal token {nonce} anywhere in the policy is replaced at runtime with a
# freshly generated nonce that is also emitted on pgAdmin's inline <script>
# tags. To go back to the old permissive policy, set:
#   CONTENT_SECURITY_POLICY = "default-src ws: http: data: blob:" \
#                             " 'unsafe-inline' 'unsafe-eval';"
# Notes:
#  - 'unsafe-inline' is retained for style-src because pgAdmin's UI (React/MUI)
#    injects runtime styles and inline style="" attributes that are not (and
#    cannot be) nonce tagged. WARNING: do NOT add 'nonce-{nonce}' to style-src
#    to tighten this -- per the CSP spec a nonce silently DISABLES
#    'unsafe-inline', which blocks all of MUI's runtime styles and leaves the
#    UI unstyled.
#  - 'unsafe-eval' is NOT listed: production bundles do not need it. This holds
#    only because JsonEditor.jsx passes neither 'queryLanguages' nor a
#    'validator' to vanilla-jsoneditor: its default query language (JSONQuery)
#    composes closures rather than evaluating source, so the eval-capable
#    paths (jsonpath-plus, ajv's runtime compiler and the Lodash query
#    language) stay unreachable. Enabling schema validation or registering
#    another query language would make 'unsafe-eval' necessary again.
#  - Development webpack bundles ARE built with the 'eval' devtool and need
#    'unsafe-eval'. security_headers.py adds it automatically when DEBUG is
#    True (for a nonce based policy), so no manual change is needed for the
#    dev server. Security note: turning DEBUG on in a server-mode deployment
#    therefore relaxes the policy (drops eval protection), and this is not
#    logged.
CONTENT_SECURITY_POLICY = (
    "default-src 'self' ws: http: data: blob:;"
    " script-src 'self' 'nonce-{nonce}';"
    " style-src 'self' 'unsafe-inline';"
    " object-src 'none';"
    " base-uri 'self';"
)

# STRICT_TRANSPORT_SECURITY_ENABLED when set to True will set the
# Strict-Transport-Security header
STRICT_TRANSPORT_SECURITY_ENABLED = False

# The Strict-Transport-Security header tells the browser to convert all HTTP
# requests to HTTPS, preventing man-in-the-middle (MITM) attacks.
# e.g. 'max-age=31536000; includeSubDomains'
STRICT_TRANSPORT_SECURITY = "max-age=31536000; includeSubDomains"

# The X-Content-Type-Options header forces the browser to honor the response
# content type instead of trying to detect it, which can be abused to
# generate a cross-site scripting (XSS) attack.
# e.g. nosniff
X_CONTENT_TYPE_OPTIONS = "nosniff"

# The browser will try to prevent reflected XSS attacks by not loading the
# page if the request contains something that looks like JavaScript and the
# response contains the same data. e.g. '1; mode=block'
X_XSS_PROTECTION = "1; mode=block"
```

(continues on next page)

(continued from previous page)

```
# This param is used to validate ALLOWED_HOSTS for the application
# This will be used to avoid Host Header Injection attack
# ALLOWED_HOSTS = ['225.0.0.0/8', '226.0.0.0/7', '228.0.0.0/6']
# ALLOWED_HOSTS = ['127.0.0.1', '192.168.0.1']
# if ALLOWED_HOSTS= [] then it will accept all ips (and application will be
# vulnerable to Host Header Injection attack)
ALLOWED_HOSTS = []

# Hashing algorithm used for password storage
SECURITY_PASSWORD_HASH = 'pbkdf2_sha512'

# Minimum password length
PASSWORD_LENGTH_MIN = 6

# Reverse Proxy parameters
# You must tell the middleware how many proxies set each header
# so it knows what values to trust.
# See https://tinyurl.com/yyg7r9av
# for more information.

# Number of values to trust for X-Forwarded-For
PROXY_X_FOR_COUNT = 1

# Number of values to trust for X-Forwarded-Proto.
PROXY_X_PROTO_COUNT = 1

# Number of values to trust for X-Forwarded-Host.
PROXY_X_HOST_COUNT = 0

# Number of values to trust for X-Forwarded-Port.
PROXY_X_PORT_COUNT = 1

# Number of values to trust for X-Forwarded-Prefix.
PROXY_X_PREFIX_COUNT = 0

# NOTE: CSRF_SESSION_KEY, SECRET_KEY and SECURITY_PASSWORD_SALT are no
#       longer part of the main configuration, but are stored in the
#       configuration databases 'keys' table and are auto-generated.

# COMPRESSION
COMPRESS_MIMETYPES = [
    'text/html', 'text/css', 'text/xml', 'text/javascript',
    'application/json', 'application/javascript'
]
COMPRESS_LEVEL = 9
COMPRESS_MIN_SIZE = 500

# Set the cache control max age for static files in flask to 1 year
SEND_FILE_MAX_AGE_DEFAULT = 31556952

# This will be added to static urls as url parameter with value as
```

(continues on next page)

(continued from previous page)

```
# APP_VERSION_INT for cache busting on version upgrade. If the value is set as
# None or empty string then it will not be added.
# eg - http:localhost:5050/pgadmin.css?intver=3.13
APP_VERSION_PARAM = 'ver'

# Add the internal version param to below extensions only
APP_VERSION_EXTN = ('.css', '.js', '.html', '.svg', '.png', '.gif', '.ico')

# Data directory for storage of config settings etc. This shouldn't normally
# need to be changed - it's here as various other settings depend on it.
# On Windows, we always store data in %APPDATA%\$(APP_WIN_PATH). On other
# platforms, if we're in server mode we use /var/lib/$(APP_PATH),
# otherwise ~/.$(APP_PATH)
if IS_WIN:
    # Use the short path on windows
    DATA_DIR = os.path.realpath(
        os.path.join(fs_short_path(env('APPDATA')), APP_WIN_PATH)
    )
else:
    if SERVER_MODE:
        DATA_DIR = os.path.join('/var/lib/', APP_PATH)
    else:
        DATA_DIR = os.path.realpath(
            os.path.expanduser('~/' + '.' + APP_PATH + '/')
        )

# An optional login banner to show security warnings/disclaimers etc. at
# login and password recovery etc. HTML may be included for basic formatting,
# For example:
# LOGIN_BANNER = "<h4>Authorised Users Only!</h4>" \
#                "Unauthorised use is strictly forbidden."
LOGIN_BANNER = ""

##########################################################################
# Log settings
##########################################################################

# Debug mode?
DEBUG = False

# Application log level - one of:
#   CRITICAL 50
#   ERROR    40
#   WARNING  30
#   SQL      25
#   INFO     20
#   DEBUG    10
#   NOTSET    0
CONSOLE_LOG_LEVEL = logging.WARNING
FILE_LOG_LEVEL = logging.WARNING

# Log format.
```

(continues on next page)

(continued from previous page)

```
JSON_LOGGER = False
CONSOLE_LOG_FORMAT_JSON = OrderedDict([
    ("time", "asctime"),
    ("message", "message"),
    ("level", "levelname")
])

FILE_LOG_FORMAT_JSON = OrderedDict([
    ("time", "asctime"),
    ("message", "message"),
    ("level", "levelname")
])


CONSOLE_LOG_FORMAT = '%(asctime)s: %(levelname)s\t%(name)s:\t%(message)s'
FILE_LOG_FORMAT = '%(asctime)s: %(levelname)s\t%(name)s:\t%(message)s'

# Log file name. This goes in the data directory, except on non-Windows
# platforms in server mode.
if SERVER_MODE and not IS_WIN:
    LOG_FILE = os.path.join('/var/log', APP_PATH, APP_SHORT_NAME + '.log')
else:
    LOG_FILE = os.path.join(DATA_DIR, APP_SHORT_NAME + '.log')

# Log rotation setting
# Log file will be rotated considering values for LOG_ROTATION_SIZE
# & LOG_ROTATION_AGE. Rotated file will be named in format
# - LOG_FILE.Y-m-d_H-M-S
LOG_ROTATION_SIZE = 10  # In MBs
LOG_ROTATION_AGE = 1440  # In minutes
LOG_ROTATION_MAX_LOG_FILES = 90  # Maximum number of backups to retain
# Include the authenticated username in the X-Remote-User response header so
# it can be captured in the HTTP access log. Disabled by default.
LOG_AUTHENTICATED_USER = False
##########################################################################
# Server Connection Driver Settings
##########################################################################

# The default driver used for making connection with PostgreSQL
PG_DEFAULT_DRIVER = 'psycopg3'

# Maximum allowed idle time in minutes before which releasing the connection
# for the particular session. (in minutes)
MAX_SESSION_IDLE_TIME = 60

##########################################################################
# External Database Settings
#
# All configuration settings are stored by default in the SQLite database.
# In order to use external databases like PostgreSQL sets the value of
# CONFIG_DATABASE_URI like below:
# dialect+driver://username:password@host:port/database
```

(continues on next page)

(continued from previous page)

```
#
# PostgreSQL:
# postgresql://username:password@host:port/database
# Specify Schema Name
# postgresql://username:password@host:port/database?options=-csearch_path=pgadmin
# Using PGPASS file
# postgresql://username@host:port?options=-csearch_path=pgadmin
##########################################################################
CONFIG_DATABASE_URI = ''

##########################################################################
# User account and settings storage
##########################################################################

# The default path to the SQLite database used to store user accounts and
# settings. This default places the file in the same directory as this
# config file, but generates an absolute path for use througout the app.
SQLITE_PATH = env('SQLITE_PATH') or \
    os.path.join(DATA_DIR, APP_SHORT_NAME + '.db')

# SQLITE_TIMEOUT will define how long to wait before throwing the error -
# OperationError due to database lock. On slower system, you may need to change
# this to some higher value.
# (Default: 500 milliseconds)
SQLITE_TIMEOUT = 500

# Allow database connection passwords to be saved if the user chooses.
# Set to False to disable password saving.
ALLOW_SAVE_PASSWORD = True

# Maximum number of history queries stored per user/server/database
MAX_QUERY_HIST_STORED = 20

##########################################################################
# Server-side session storage path
#
# SESSION_DB_PATH (Default: $HOME/.pgadmin4/sessions)
##########################################################################
#
# We use SQLite for server-side session storage. There will be one
# SQLite database object per session created.
#
# Specify the path used to store your session objects.
#
# If the specified directory does not exist, the setup script will create
# it with permission mode 700 to keep the session database secure.
#
# On certain systems, you can use shared memory (tmpfs) for maximum
# scalability, for example, on Ubuntu:
#
# SESSION_DB_PATH = '/run/shm/pgAdmin4_session'
#
```

(continues on next page)

(continued from previous page)

```
##########################################################################
SESSION_DB_PATH = os.path.join(DATA_DIR, 'sessions')

SESSION_COOKIE_NAME = 'pga4_session'

# Session digest method.
# Used as the HMAC algorithm for the session cookie (signing the
# (sid, randval) pair). HMAC-SHA1 is still cryptographically acceptable
# for authentication, but SHA-256 is the modern default and aligns with
# the file-HMAC header introduced for session-on-disk integrity.
# Operators on existing deployments will see all sessions invalidated on
# upgrade regardless (the file-HMAC header is new), so we flip this
# default at the same time rather than leaving SHA-1 as a long-term
# liability.
SESSION_DIGEST_METHOD = 'hashlib.sha256'

##########################################################################
# Mail server settings
##########################################################################

# These settings are used when running in web server mode for confirming
# and resetting passwords etc.
# See: http://pythonhosted.org/Flask-Mail/ for more info
MAIL_SERVER = 'localhost'
MAIL_PORT = 25
MAIL_USE_SSL = False
MAIL_USE_TLS = False
MAIL_USERNAME = ''
MAIL_PASSWORD = ''
MAIL_DEBUG = False

# Flask-Security overrides Flask-Mail's MAIL_DEFAULT_SENDER setting, so
# that should be set as such:
SECURITY_EMAIL_SENDER = 'no-reply@localhost'

##########################################################################
# Mail content settings
##########################################################################

# These settings define the content of password reset emails
SECURITY_EMAIL_SUBJECT_PASSWORD_RESET = "Password reset instructions for %s" \
                                        % APP_NAME
SECURITY_EMAIL_SUBJECT_PASSWORD_NOTICE = "Your %s password has been reset" \
                                         % APP_NAME
SECURITY_EMAIL_SUBJECT_PASSWORD_CHANGE_NOTICE = \
    "Your password for %s has been changed" % APP_NAME

##########################################################################
# Email address validation
##########################################################################
CHECK_EMAIL_DELIVERABILITY = False
SECURITY_EMAIL_VALIDATOR_ARGS = \
```

(continues on next page)

(continued from previous page)

```
    {"check_deliverability": CHECK_EMAIL_DELIVERABILITY}
ALLOW_SPECIAL_EMAIL_DOMAINS = []
# Disables global deliverable check while email validation
GLOBALLY_DELIVERABLE = True
##########################################################################
# Upgrade checks
##########################################################################

# Check for new versions of the application?
UPGRADE_CHECK_ENABLED = True

# Where should we get the data from?
UPGRADE_CHECK_URL = 'https://www.pgadmin.org/versions.json'

# What key should we look at in the upgrade data file?
UPGRADE_CHECK_KEY = 'pgadmin4'

# Which CA file should pgAdmin's own outbound HTTPS requests (upgrade check,
# AI assistant, cloud deployment, OAuth2) verify against?
# Default to cacert.pem in the same directory as config.py et al. If that file
# does not exist, certifi's bundle is used instead, so a server with a
# certificate from a private CA (such as a self-hosted Ollama) needs CA_FILE
# pointing at a bundle that includes that CA. Set to None to use Python's
# default CA store (normally the system store), except for OAuth2, which then
# uses the requests library's own bundle.
CA_FILE = os.path.join(os.path.dirname(os.path.realpath(__file__)),
                       "cacert.pem")

# Check if the detected browser is supported
CHECK_SUPPORTED_BROWSER = True

##########################################################################
# Storage Manager storage url config settings
# If user sets STORAGE_DIR to empty it will show all volumes if platform
# is Windows, '/' if it is Linux, Mac or any other unix type system.
#
# WARNING: an empty STORAGE_DIR exposes the whole filesystem to users in
# server mode, so the guard that stops the binary path from pointing into
# the storage directories (CWE-426) cannot protect that configuration.

# For example:
# 1. STORAGE_DIR = get_drive("C") or get_drive() # return C:/ by default
# where C can be any drive character such as "D", "E", "G" etc
# 2. Set path manually like
# STORAGE_DIR = "/path/to/directory/"
##########################################################################
STORAGE_DIR = os.path.join(DATA_DIR, 'storage')

##########################################################################
# Default locations for binary utilities (pg_dump, pg_restore etc)
#
# These are intentionally left empty in the main config file, but are
```

(continues on next page)

(continued from previous page)

```
# expected to be overridden by packagers in config_distro.py.
#
# A default location can be specified for each database driver ID, in
# a dictionary. Either an absolute or relative path can be specified.
#
# Version-specific defaults can also be specified, which will take priority
# over un-versioned paths.
#
# In cases where it may be difficult to know what the working directory
# is, "$DIR" can be specified. This will be replaced with the path to the
# top-level pgAdmin4.py file. For example, on macOS we might use:
#
# $DIR/../../SharedSupport
#
##########################################################################
DEFAULT_BINARY_PATHS = {
    "pg": "",
    "pg-13": "",
    "pg-14": "",
    "pg-15": "",
    "pg-16": "",
    "pg-17": "",
    "pg-18": "",
    "ppas": "",
    "ppas-13": "",
    "ppas-14": "",
    "ppas-15": "",
    "ppas-16": "",
    "ppas-17": "",
    "ppas-18": ""
}

##########################################################################

# Admin can specify fixed binary paths to prevent users from changing.
# It will take precedence over DEFAULT_BINARY_PATHS.

FIXED_BINARY_PATHS = {
    "pg": "",
    "pg-13": "",
    "pg-14": "",
    "pg-15": "",
    "pg-16": "",
    "pg-17": "",
    "pg-18": "",
    "ppas": "",
    "ppas-13": "",
    "ppas-14": "",
    "ppas-15": "",
    "ppas-16": "",
    "ppas-17": "",
    "ppas-18": ""
```

(continues on next page)

(continued from previous page)

```
}

##########################################################################
# Test settings - used primarily by the regression suite, not for users
##########################################################################

# The default path for SQLite database for testing
TEST_SQLITE_PATH = os.path.join(DATA_DIR, 'test_pgadmin4.db')

##########################################################################
# Allows flask application to response to the each request asynchronously
##########################################################################
THREADED_MODE = True

##########################################################################
# Do not allow SQLALCHEMY to track modification as it is going to be
# deprecated in future
##########################################################################
SQLALCHEMY_TRACK_MODIFICATIONS = False

##########################################################################
# Number of records to fetch in one page in query tool when query result
# set is large and is divided in multiple pages
##########################################################################
DATA_RESULT_ROWS_PER_PAGE = 1000

##########################################################################
# System-wide default for the Geometry Viewer's custom tile provider
# (Query Tool > Data Output > Geometry Viewer). Applies to any user who
# has not saved their own "Custom tile provider ..." preference; a
# per-user preference, once set, always takes precedence over this
# default. Leave "url" empty to keep using the built-in tile layers by
# default (the pre-existing behaviour).
#
# "crs" must be one of "EPSG:3857" (Web Mercator), "EPSG:4326", or
# "EPSG:3395" - the only coordinate reference systems the Geometry
# Viewer's tile layer selector supports.
##########################################################################
DEFAULT_GEOMETRY_VIEWER_PROVIDER = {
    "url": "",
    "name": "Custom",
    "crs": "EPSG:3857",
    "attribution": "",
    "max_zoom": 18
}

##########################################################################
# Allow users to display Gravatar image for their username in Server mode
##########################################################################
SHOW_GRAVATAR_IMAGE = True

##########################################################################
```

(continues on next page)

(continued from previous page)

```
# Set cookie path and options
##########################################################################
COOKIE_DEFAULT_PATH = '/'
COOKIE_DEFAULT_DOMAIN = None
SESSION_COOKIE_DOMAIN = None
SESSION_COOKIE_SAMESITE = 'Lax'
SESSION_COOKIE_SECURE = False
SESSION_COOKIE_HTTPONLY = True

##########################################################################
# Skip storing session in files and cache for specific paths
##########################################################################
SESSION_SKIP_PATHS = [
    '/misc/ping'
]

##########################################################################
# Session expiration support
##########################################################################
# SESSION_EXPIRATION_TIME is the interval in Days. Session will be
# expire after the specified number of *days*.
SESSION_EXPIRATION_TIME = 1

# Make SESSION_EXPIRATION_TIME to 1 week in DESKTOP mode
if not SERVER_MODE:
    SESSION_EXPIRATION_TIME = 7

# CHECK_SESSION_FILES_INTERVAL is interval in Hours. Application will check
# the session files for cleanup after specified number of *hours*.
CHECK_SESSION_FILES_INTERVAL = 24

# USER_INACTIVITY_TIMEOUT is interval in Seconds. If the pgAdmin screen is left
# unattended for <USER_INACTIVITY_TIMEOUT> seconds then the user will
# be logged out. When set to 0, the timeout will be disabled.
# If pgAdmin doesn't detect any activity in the time specified (in seconds),
# the user will be forcibly logged out from pgAdmin. Set to zero to disable
# the timeout.
# Note: This is applicable only for SERVER_MODE=True.
USER_INACTIVITY_TIMEOUT = 0

# OVERRIDE_USER_INACTIVITY_TIMEOUT when set to True will override
# USER_INACTIVITY_TIMEOUT when long running queries in the Query Tool
# or Debugger are running. When the queries complete, the inactivity timer
# will restart in this case. If set to False, user inactivity may cause
# transactions or in-process debugging sessions to be aborted.
OVERRIDE_USER_INACTIVITY_TIMEOUT = True

##########################################################################
# SSH Tunneling supports only for Python 2.7 and 3.4+
##########################################################################
SUPPORT_SSH_TUNNEL = True
# Allow SSH Tunnel passwords to be saved if the user chooses.
```

(continues on next page)

(continued from previous page)

```
# Set to False to disable password saving.
ALLOW_SAVE_TUNNEL_PASSWORD = False

##########################################################################
# Master password is used to encrypt/decrypt saved server passwords
# Applicable for desktop mode only
##########################################################################
MASTER_PASSWORD_REQUIRED = True
##########################################################################

##########################################################################
# Allow to save master password which is used to encrypt/decrypt saved
# passwords in the os level secret like Keychain, password store etc.
# Disabling this will require user to enter master password
# if MASTER_PASSWORD_REQUIRED is set to True. Note: this is applicable only
# in case of Desktop mode.
##########################################################################
USE_OS_SECRET_STORAGE = True
##########################################################################

# pgAdmin encrypts the database connection and ssh tunnel password using a
# master password or pgAdmin login password (for other authentication sources)
# before storing it in the pgAdmin configuration database.
#
# Below setting is used to allow the user to specify the path to a script
# or program that will return an encryption key which will be used to
# encrypt the passwords. This setting is used only in server mode when
# auth sources are oauth, Kerberos, and webserver.
#
# You can pass the current username as an argument to the external script
# by specifying %u in config value.
# E.g. - MASTER_PASSWORD_HOOK = '<PATH>/passwdgen_script.sh %u'
#
# The command is split into arguments and executed directly, without a
# shell, so shell features (pipes, redirection, environment-variable
# expansion, globbing) in this value are not interpreted; put any such
# logic inside the hook script itself. On Windows, a batch file must be
# invoked via an executable wrapper rather than directly. If the path to
# the script/program contains spaces, quote it, e.g. -
# MASTER_PASSWORD_HOOK = '"<PATH WITH SPACES>/passwdgen_script.exe" %u'
##########################################################################
MASTER_PASSWORD_HOOK = None

##########################################################################

# Allows pgAdmin4 to create session cookies based on IP address, so even
# if a cookie is stolen, the attacker will not be able to connect to the
# server using that stolen cookie.
# Note: This can cause problems when the server is deployed in dynamic IP
# address hosting environments, such as Kubernetes or behind load
# balancers. In such cases, this option should be set to False.
##########################################################################
```

(continues on next page)

(continued from previous page)

```
ENHANCED_COOKIE_PROTECTION = True

##########################################################################
# External Authentication Sources
##########################################################################

# Default setting is internal
# External Supported Sources: ldap, kerberos, oauth2
# Multiple authentication can be achieved by setting this parameter to
# ['ldap', 'internal'] or ['oauth2', 'internal'] or
# ['webserver', 'internal'] etc.
# pgAdmin will authenticate the user with ldap/oauth2 whatever first in the
# list, in case of failure the second authentication option will be considered.

AUTHENTICATION_SOURCES = ['internal']

##########################################################################
# MAX_LOGIN_ATTEMPTS which sets the number of failed login attempts that
# are allowed. If this value is exceeded the account is locked and can be
# reset by an administrator. By setting the variable to the value zero
# this feature is deactivated.
##########################################################################
MAX_LOGIN_ATTEMPTS = 3

##########################################################################
# Only consider password to check the failed login attempts, email is
# excluded from this check
LOGIN_ATTEMPT_FIELDS = ['password']
##########################################################################
# LDAP Configuration
##########################################################################

# After ldap authentication, user will be added into the SQLite database
# automatically, if set to True.
# Set it to False, if user should not be added automatically,
# in this case Admin has to add the user manually in the SQLite database.
LDAP_AUTO_CREATE_USER = True

# Connection timeout
LDAP_CONNECTION_TIMEOUT = 10

# Server connection details (REQUIRED)
# example: ldap://<ip-address>:<port> or ldap://<hostname>:<port>
LDAP_SERVER_URI = 'ldap://<ip-address>:<port>'

# The LDAP attribute containing user names. In OpenLDAP, this may be 'uid'
# whilst in AD, 'sAMAccountName' might be appropriate. (REQUIRED)
LDAP_USERNAME_ATTRIBUTE = '<User-id>'

##########################################################################
# 3 ways to configure LDAP as follows (Choose anyone):
```

(continues on next page)

(continued from previous page)

```
# 1. Dedicated User binding

# LDAP Bind User DN Example: cn=username,dc=example,dc=com
# Set this parameter to allow the connection to bind using a dedicated user.
# After the connection is made, the pgadmin login user will be further
# authenticated by the username and password provided
# at the login screen.
LDAP_BIND_USER = None

# LDAP Bind User Password
LDAP_BIND_PASSWORD = None

# OR ####################
# 2. Anonymous Binding

# Set this parameter to allow the anonymous bind.
# After the connection is made, the pgadmin login user will be further
# authenticated by the username and password provided

LDAP_ANONYMOUS_BIND = False

# OR ####################
# 3. Bind as pgAdmin user

# BaseDN (REQUIRED)
# AD example:
# (&(objectClass=user)(memberof=CN=MYGROUP,CN=Users,dc=example,dc=com))
# OpenLDAP example: CN=Users,dc=example,dc=com
LDAP_BASE_DN = '<Base-DN>'

# Configure the bind format string
# Default: LDAP_BIND_FORMAT="
#   {LDAP_USERNAME_ATTRIBUTE}={LDAP_USERNAME},{LDAP_BASE_DN}"
# The current available options are:
# LDAP_USERNAME_ATTRIBUTE, LDAP_USERNAME, LDAP_BASE_DN
# Example: LDAP_BIND_FORMAT="myldapuser@sales.example.com"
#          LDAP_BIND_FORMAT="NET\\myldapuser"
LDAP_BIND_FORMAT = '{LDAP_USERNAME_ATTRIBUTE}={LDAP_USERNAME},{LDAP_BASE_DN}'

##########################################################################

# Search ldap for further authentication (REQUIRED)
# It can be optional while bind as pgAdmin user
LDAP_SEARCH_BASE_DN = '<Search-Base-DN>'

# The LDAP attribute indicates whether the DN (Distinguished Names)
# are case sensitive or not
LDAP_DN_CASE_SENSITIVE = False

# Filter string for the user search.
# For OpenLDAP, '(cn=*)' may well be enough.
# For AD, you might use '(objectClass=user)' (REQUIRED)
```

(continues on next page)

(continued from previous page)

```
LDAP_SEARCH_FILTER = '(objectclass=*)'

# Search scope for users (one of BASE, LEVEL or SUBTREE)
LDAP_SEARCH_SCOPE = 'SUBTREE'

# Use TLS? If the URI scheme is ldaps://, this is ignored.
LDAP_USE_STARTTLS = False

# TLS/SSL certificates. Specify if required, otherwise leave empty
LDAP_CA_CERT_FILE = ''
LDAP_CERT_FILE = ''
LDAP_KEY_FILE = ''

# TLS/SSL certificate Validation (True/False),
# Make it false if certificate validation is not required.
LDAP_CERT_VALIDATE = True
##########################################################################

# Some flaky LDAP servers returns malformed schema. If True, no exception
# will be raised and schema is thrown away but authentication will be done.
# This parameter should remain False, as recommended.
LDAP_IGNORE_MALFORMED_SCHEMA = False

##########################################################################
# Kerberos Configuration
##########################################################################

KRB_APP_HOST_NAME = DEFAULT_SERVER

# If the default_keytab_name is not set in krb5.conf or
# the KRB_KTNAME environment variable is not set then, explicitly set
# the Keytab file

KRB_KTNAME = '<KRB5_KEYTAB_FILE>'

# After kerberos authentication, user will be added into the SQLite database
# automatically, if set to True.
# Set it to False, if user should not be added automatically,
# in this case Admin has to add the user manually in the SQLite database.

KRB_AUTO_CREATE_USER = True

KERBEROS_CCACHE_DIR = os.path.join(DATA_DIR, 'krbccache')

##########################################################################
# Create local directory to store azure credential cache
##########################################################################

AZURE_CREDENTIAL_CACHE_DIR = os.path.join(DATA_DIR, 'azurecredentialcache')

##########################################################################
# pgEdge Starfleet API base URL, used by the cloud deployment wizard
```

(continues on next page)

(continued from previous page)

```
##########################################################################

STARFLEET_API_URL = 'https://api.pgedge.com'

##########################################################################
# OAuth2 Configuration
##########################################################################

# Multiple OAUTH2 providers can be added in the list like [{...},{...}]
# All parameters are required

OAUTH2_CONFIG = [
    {
        # The name of the of the oauth provider, ex: github, google
        'OAUTH2_NAME': None,
        # The display name, ex: Google
        'OAUTH2_DISPLAY_NAME': '<Oauth2 Display Name>',
        # Oauth client id
        'OAUTH2_CLIENT_ID': None,
        # Oauth secret
        'OAUTH2_CLIENT_SECRET': None,
        # URL to generate a token,
        # Ex: https://github.com/login/oauth/access_token
        'OAUTH2_TOKEN_URL': None,
        # URL is used for authentication,
        # Ex: https://github.com/login/oauth/authorize
        'OAUTH2_AUTHORIZATION_URL': None,
        # OpenID Connect discovery URL for the provider. Required when
        # OAUTH2_SCOPE contains 'openid' (so pgAdmin can fetch the JWKS
        # to verify the id_token); optional otherwise.
        # Example: https://<issuer>/.well-known/openid-configuration
        'OAUTH2_SERVER_METADATA_URL': None,
        # Oauth base url, ex: https://api.github.com/
        'OAUTH2_API_BASE_URL': None,
        # Name of the Endpoint, ex: user
        'OAUTH2_USERINFO_ENDPOINT': None,
        # Oauth scope, ex: 'openid email profile'
        # Note that an 'email' claim is required in the resulting profile
        'OAUTH2_SCOPE': None,
        # The claim which is used for the username. If the value is empty the
        # email is used as username, but if a value is provided,
        # the claim has to exist.
        'OAUTH2_USERNAME_CLAIM': None,
        # Font-awesome icon, ex: fa-github
        'OAUTH2_ICON': None,
        # UI button colour, ex: #0000ff
        'OAUTH2_BUTTON_COLOR': None,
        # The additional claims to check on user ID Token or Userinfo response.
        # This is useful to provide additional authorization checks
        # before allowing access.
        # Example for GitLab: allowing all maintainers teams, and a specific
        # developers group to access pgadmin:
```

(continues on next page)

(continued from previous page)

```
        # 'OAUTH2_ADDITIONAL_CLAIMS': {
        #     'https://gitlab.org/claims/groups/maintainer': [
        #           'kuberheads/applications',
        #           'kuberheads/dba',
        #           'kuberheads/support'
        #      ],
        #     'https://gitlab.org/claims/groups/developer': [
        #           'kuberheads/applications/team01'
        #      ],
        # }
        # Example for AzureAD:
        # 'OAUTH2_ADDITIONAL_CLAIMS': {
        #     'groups': ["0760b6cf-170e-4a14-91b3-4b78e0739963"],
        #     'wids': ["cf1c38e5-3621-4004-a7cb-879624dced7c"],
        # }
        'OAUTH2_ADDITIONAL_CLAIMS': None,
        # The claim listing the server groups whose shared servers the user
        # may see (ID token first, then userinfo). When set, shared servers
        # owned by other users are only visible if their server group's name
        # is in the claim; if the claim is missing, none are. The user's own
        # servers are unaffected. Names are matched exactly, and the claim
        # is only read at login.
        # Without mapping, claim values are treated as server group names.
        # Example:
        # 'OAUTH2_SERVER_GROUP_CLAIM': 'pgadmin_server_groups',
        # Optional mapping from claim value -> server group name(s):
        # 'OAUTH2_SERVER_GROUP_CLAIM_MAPPING': {
        #     'readonly': ['RO Server 1', 'RO Server 2']
        # },
        'OAUTH2_SERVER_GROUP_CLAIM': None,
        'OAUTH2_SERVER_GROUP_CLAIM_MAPPING': None,
        # Set this variable to False to disable SSL certificate verification
        # for OAuth2 provider.
        # This may need to set False, in case of self-signed certificates.
        # Ref: https://github.com/psf/requests/issues/6071
        'OAUTH2_SSL_CERT_VERIFICATION': True,
        # set this variable to invalidate the session of the oauth2 provider
        # Example for keycloak:
        # 'OAUTH2_LOGOUT_URL':
        # 'https://example.com/realms/master/protocol/openid-connect/logout?post_logout_
↪redirect_uri={redirect_uri}&id_token_hint={id_token}'
        'OAUTH2_LOGOUT_URL': None
    }
]

# After Oauth authentication, user will be added into the SQLite database
# automatically, if set to True.
# Set it to False, if user should not be added automatically,
# in this case Admin has to add the user manually in the SQLite database.

OAUTH2_AUTO_CREATE_USER = True
```

(continues on next page)

(continued from previous page)

```
# If set to True, and OAuth2 is the only authentication source with exactly
# one provider in OAUTH2_CONFIG, users are sent straight to that provider
# instead of seeing the pgAdmin login page. After logging out, the login
# page is shown so the provider does not log the user straight back in.
# Add ?no_auto_login to the login page URL to display it regardless.
OAUTH2_AUTO_LOGIN = False

##########################################################################
# Webserver Configuration
##########################################################################

WEBSERVER_AUTO_CREATE_USER = True

# REMOTE_USER variable will be used to check the environment variable
# is set or not first, if not available,
# request header will be checked for the same.
# Possible values: REMOTE_USER, HTTP_X_FORWARDED_USER, X-Forwarded-User

WEBSERVER_REMOTE_USER = 'REMOTE_USER'

# Accept the remote user identity from an inbound HTTP request header (not
# just the WSGI/CGI environment). This is required only for reverse proxies
# that pass the identity as a header rather than setting the REMOTE_USER
# CGI variable.
# SECURITY: only enable this when the proxy in front of pgAdmin OVERWRITES
# this header on every request before it reaches pgAdmin; otherwise any
# client that can reach pgAdmin can assert any identity it likes.
WEBSERVER_REMOTE_USER_FROM_HEADER = False

# IP addresses/CIDR ranges of the reverse proxies that are allowed to assert
# the identity header above. An empty list means no peer is trusted, so
# WEBSERVER_REMOTE_USER_FROM_HEADER stays inert even if enabled.
WEBSERVER_TRUSTED_PROXIES = []

# Optional shared secret that the trusted proxy must inject into the request
# (in the header named by WEBSERVER_SHARED_SECRET_HEADER) for the header-based
# identity to be accepted. Leave as None to skip this additional check.
WEBSERVER_SHARED_SECRET = None
WEBSERVER_SHARED_SECRET_HEADER = 'X-Pgadmin-Webserver-Secret'

##########################################################################
# Two-factor Authentication Configuration
##########################################################################

# Set it to True, to enable the two-factor authentication
MFA_ENABLED = True

# Set it to True, to ask the users to register forcefully for the
# two-authentication methods on logged-in.
MFA_FORCE_REGISTRATION = False

# pgAdmin supports Two-factor authentication by either sending an one-time code
```

(continues on next page)

(continued from previous page)

```
# to an email, or using the TOTP based application like Google Authenticator.
MFA_SUPPORTED_METHODS = ["email", "authenticator"]

# NOTE: Please set the 'Mail server settings' to use 'email' as two-factor
#       authentication method.

# Subject for the email verification code
# Default: <APP_NAME> - Verification Code
# e.g.  pgAdmin 4 - Verification Code
MFA_EMAIL_SUBJECT = None

# Number of wrong entries allowed for one emailed verification code. Once
# this many wrong codes have been entered, the code is discarded and the user
# must send a new one. Values below 1 are treated as 1 (the code is discarded
# after the first wrong entry), so the number of attempts is never unlimited.
MFA_EMAIL_CODE_MAX_ATTEMPTS = 5

##########################################################################
# PSQL tool settings
##########################################################################
# This will enable PSQL tool in pgAdmin when running in server mode.
# PSQL is always enabled in Desktop mode, however in server mode it is
# disabled by default because users can run arbitrary commands on the
# server through it.
ENABLE_PSQL = False

##########################################################################
# ENABLE_BINARY_PATH_BROWSING setting is used to enable the browse button
# while selecting binary path for the database server in server mode.
# In Desktop mode it is always enabled and setting is of no use.
##########################################################################
ENABLE_BINARY_PATH_BROWSING = False

##########################################################################
# In server mode, the SHARED_STORAGE setting is used to enable shared storage.
# Specify the name, path, and restricted_access values that should be shared
# between users. When restricted_access is set to True, non-admin users cannot
# upload/add, delete, or rename files/folders in shared storage, only admins
# can do that. Users must provide the absolute path to the folder, and the name
# can be anything they see on the user interface.
# [{ 'name': 'Shared 1', 'path': '/shared_folder',
#   'restricted_access': True/False}]
##########################################################################
SHARED_STORAGE = []

##########################################################################
# AUTO_DISCOVER_SERVERS setting is used to enable the pgAdmin to discover the
# database server automatically on the local machine.
# When it is set to False, pgAdmin will not discover servers installed on
# the local machine.
##########################################################################
AUTO_DISCOVER_SERVERS = True
```

(continues on next page)

(continued from previous page)

```
##########################################################################
# SERVER_HEARTBEAT_TIMEOUT is used to send the server heartbeat to server
# from the client. This will resolve the orphan database issue once
# browser tab is closed.
##########################################################################
SERVER_HEARTBEAT_TIMEOUT = 30  # In seconds

##########################################################################
# SERVER_PASSEXEC_COMMANDS is an allowlist of named commands that may be used
# to retrieve a password for server authentication. Users pick a command by
# name in the server properties; they cannot supply their own. Each value is
# a list holding the executable followed by its arguments, for example:
#
#   SERVER_PASSEXEC_COMMANDS = {
#       'vault': ['/usr/local/bin/get-pg-pass', '--ttl', '300']
#   }
#
# Commands are run directly, without a shell, so no quoting or substitution
# is applied to the arguments. Connection details are passed in these
# environment variables: PGADMIN_PASSEXEC_HOST, PGADMIN_PASSEXEC_PORT,
# PGADMIN_PASSEXEC_USERNAME, PGADMIN_PASSEXEC_DATABASE,
# PGADMIN_PASSEXEC_PGADMIN_USER and PGADMIN_PASSEXEC_AUTH_SOURCE. Only the
# last two identify the pgAdmin user; the host, port, username and database
# are set by whoever edits the server, so commands must authorise on the
# pgAdmin identity and treat the other four as untrusted input.
#
# These variables describe the server itself, and cannot be changed by a
# user who does not own it:
#
#   PGADMIN_PASSEXEC_SHARED: 'true' if the server is shared and owned by
#       another pgAdmin user, otherwise 'false' (including for the owner).
#   PGADMIN_PASSEXEC_SERVER_ID: pgAdmin's numeric id for the server.
#   PGADMIN_PASSEXEC_SERVER_OWNER and
#   PGADMIN_PASSEXEC_SERVER_OWNER_AUTH_SOURCE: the pgAdmin user who owns
#       the server, and how they authenticate.
#   PGADMIN_PASSEXEC_SERVER_GROUP: the name of the owner's server group
#       holding the server; for an OAuth2 user restricted by
#       OAUTH2_SERVER_GROUP_CLAIM, this is the group that granted access.
#
# PGADMIN_PASSEXEC_SHARED does not prove that the owner is an
# administrator, because a server shared before sharing was restricted to
# administrators may be owned by any user. On a shared server, the host,
# port and maintenance database are taken from the owner's server, not from
# the copy kept for each user, whilst PGADMIN_PASSEXEC_USERNAME is each
# user's own. Every user owns their own server groups and can give them any
# name, so the group name proves nothing unless the owner is checked too.
# Commands should decide whether to issue a password based on the pgAdmin
# user and the server owner.
#
# Names may not start with "__". An empty dictionary (the default) turns the
# feature off. This setting is applicable only for server mode.
```

(continues on next page)

(continued from previous page)

```
#
# Upgrading from a release that allowed free-text commands in server mode:
# configure this BEFORE the first start after upgrading. On that start, an
# existing free-text command is converted to the name of the entry whose
# arguments, joined by single spaces, match it exactly, and every other
# command is cleared; the clearing cannot be undone. If the dictionary is
# empty at that start, the conversion is postponed: existing commands stay
# in the configuration database unused, a warning is logged at each start,
# and they are converted or cleared on the first start with at least one
# entry configured.
##########################################################################
SERVER_PASSEXEC_COMMANDS = {}

##########################################################################
# SERVER_PASSEXEC_ENV_PASSTHROUGH lists the names of additional environment
# variables to pass from pgAdmin's environment to the commands defined in
# SERVER_PASSEXEC_COMMANDS, for example ['VAULT_ADDR']. The commands do not
# receive pgAdmin's full environment; they get only PATH, HOME, LANG,
# LANGUAGE, TZ, TMPDIR, TMP, TEMP, USER, LOGNAME, any LC_* variable (and on
# Windows, SYSTEMROOT, SYSTEMDRIVE, PATHEXT, COMSPEC and WINDIR), the
# variables named here, and the PGADMIN_PASSEXEC_* variables, which always
# take precedence. Do not list variables that hold secrets the commands do
# not need. This setting is applicable only for server mode.
##########################################################################
SERVER_PASSEXEC_ENV_PASSTHROUGH = []

##########################################################################
# SERVER_MODE_ALLOWED_SERVICES lists the libpq service names that a server
# may use in server mode, for example ['reporting']. Services are looked up
# in the connection service file of the account pgAdmin runs as
# (~/.pg_service.conf, or the file named by PGSERVICEFILE or found in
# PGSYSCONFDIR), not in a file belonging to the pgAdmin user. A server set
# to use any other service cannot be saved or connected to. An empty list
# (the default) allows no services. This setting is applicable only for
# server mode; any service may be used in desktop mode.
#
# WARNING: listing a service shares its credentials with every pgAdmin
# user. Any user can connect using a listed service, including any
# password, password file or client certificate its entry names, and can
# override the entry's host to send that password to a server of their
# own choosing. psql and the utilities also take the entry's require_auth,
# gssencmode and gsslib in preference to the settings pgAdmin gives them
# for Kerberos, so do not set those in a listed service.
##########################################################################
SERVER_MODE_ALLOWED_SERVICES = []

##########################################################################
# DEPRECATED and ignored: free-text password exec commands are never run in
# server mode. Use SERVER_PASSEXEC_COMMANDS instead.
##########################################################################
ENABLE_SERVER_PASS_EXEC_CMD = False
```

(continues on next page)

(continued from previous page)

```
##########################################################################
# Maximum number of Tags allowed on a server node
##########################################################################
MAX_SERVER_TAGS_ALLOWED = 5

##########################################################################
# Number of records to fetch in one batch for server logs.
##########################################################################

ON_DEMAND_LOG_COUNT = 10000

##########################################################################
# AI/LLM Settings
##########################################################################

# Master switch to enable/disable LLM features entirely.
# When False, all AI/LLM features are disabled and cannot be enabled
# by users through preferences. When True, users can configure their
# preferred LLM provider in preferences.
LLM_ENABLED = True

# Default LLM Provider
# Specifies which LLM provider to use by default when LLM_ENABLED is True.
# Users can override this in their preferences.
# Valid values: 'anthropic', 'openai', 'ollama', 'docker', or '' (disabled)
DEFAULT_LLM_PROVIDER = ''

# Anthropic Configuration
# URL for the Anthropic API endpoint. Leave empty to use the default
# (https://api.anthropic.com/v1). Set a custom URL to use an
# Anthropic-compatible API provider.
ANTHROPIC_API_URL = ''

# Path to a file containing the Anthropic API key. The file should contain
# only the API key with no additional whitespace or formatting.
# Default: ~/.anthropic-api-key
# Note: The API key may be optional when using a custom API URL with a
# provider that does not require authentication.
ANTHROPIC_API_KEY_FILE = '~/.anthropic-api-key'

# The Anthropic model to use for AI features.
# Examples: claude-sonnet-4-20250514, claude-3-5-haiku-20241022
ANTHROPIC_API_MODEL = ''

# OpenAI Configuration
# URL for the OpenAI API endpoint. Leave empty to use the default
# (https://api.openai.com/v1). Set a custom URL to use any
# OpenAI-compatible API provider (e.g., LiteLLM, LM Studio, EXO).
# Include the /v1 path prefix if required by your provider
# (e.g., http://localhost:1234/v1).
OPENAI_API_URL = ''
```

(continues on next page)

(continued from previous page)

```
# Path to a file containing the OpenAI API key. The file should contain
# only the API key with no additional whitespace or formatting.
# Default: ~/.openai-api-key
# Note: The API key may be optional when using a custom API URL with a
# provider that does not require authentication.
OPENAI_API_KEY_FILE = '~/.openai-api-key'

# The OpenAI model to use for AI features.
# Examples: gpt-4o, gpt-4o-mini, gpt-4-turbo
OPENAI_API_MODEL = ''

# Ollama Configuration
# URL for the Ollama API endpoint. Leave empty to disable Ollama.
# Typical value: http://localhost:11434
OLLAMA_API_URL = ''

# The Ollama model to use for AI features.
# Examples: llama3.2, codellama, mistral
OLLAMA_API_MODEL = ''

# Docker Model Runner Configuration
# Docker Desktop 4.40+ includes a built-in model runner with an
# OpenAI-compatible API. No API key is required.
# URL for the Docker Model Runner API endpoint. Leave empty to disable.
# Typical value: http://localhost:12434
# Tip: You can also use the OpenAI provider with a custom API URL for any
# OpenAI-compatible endpoint, including Docker Model Runner.
DOCKER_API_URL = ''

# The Docker Model Runner model to use for AI features.
# Examples: ai/qwen3-coder, ai/llama3.2
DOCKER_API_MODEL = ''

# Allowed LLM API URLs
# A list of scheme://host:port entries that LLM API requests are allowed
# to connect to. Only URLs matching an entry in this list will be permitted.
# This prevents SSRF attacks via user-controlled API URL fields.
# Set to an empty list to disable URL restriction (not recommended).
# Add entries for custom providers (LiteLLM, LM Studio, corporate proxies).
#
# Use ``:*`` to match any port on a host - useful for local self-hosting
# where the user chooses the port. The host check still rejects
# link-local addresses like 169.254.169.254 used by cloud metadata.
#
# Note: the loopback ``:*`` entries below let any logged-in user have
# the pgAdmin server connect to any port on its own loopback interface.
# On multi-user SERVER_MODE deployments, consider replacing them with
# the specific ports you run (e.g. ``http://localhost:11434``) to avoid
# exposing other local services to LLM requests.
ALLOWED_LLM_API_URLS = [
    'https://api.anthropic.com:443',
    'https://api.openai.com:443',
```

(continues on next page)

(continued from previous page)

```
    # Loopback addresses on any port: covers Ollama (11434), Docker
    # Model Runner (12434), LiteLLM (4000), vLLM (8000), LM Studio
    # (1234), text-generation-webui (5000), and any self-hosted
    # OpenAI-compatible endpoint the user runs on their own machine.
    'http://localhost:*',
    'http://127.0.0.1:*',
    'http://[::1]:*',
]

# Maximum Tool Iterations
# The maximum number of tool call iterations allowed during an AI conversation.
# This prevents runaway conversations that could consume excessive resources.
# Users can override this in their preferences.
MAX_LLM_TOOL_ITERATIONS = 20

##########################################################################
# Patch the default config with custom config and other manipulations
##########################################################################
from pgadmin.evaluate_config import evaluate_and_patch_config
locals().update(evaluate_and_patch_config(locals()))
```

1.1.2 Desktop Deployment

pgAdmin may be deployed as a desktop application by configuring the application to run in desktop mode and then utilising the desktop runtime to host the program on a supported Windows, Mac OS X or Linux installation.

The desktop runtime is a standalone application that when launched, runs the pgAdmin server and opens a window to render the user interface.

Note

Pre-compiled and configured installation packages are available for a number of platforms. These packages should be used by end-users whereever possible - the following information is useful for the maintainers of those packages and users interested in understanding how pgAdmin works.

See also

For detailed instructions on building and configuring pgAdmin from scratch, please see the README file in the top level directory of the source code. For convenience, you can find the latest version of the file here, but be aware that this may differ from the version included with the source code for a specific version of pgAdmin.


Configuration

From pgAdmin 4 v2 onwards, the default configuration mode is server, however, this is overridden by the desktop runtime at startup. In most environments, no Python configuration is required unless you wish to override other default settings.


See *Configuration Files* for more information on configuration settings.

Desktop Runtime Standalone Application

The Desktop Runtime is based on Electron which integrates a browser and the Python server creating a standalone application.



Runtime Menu Items




Use the *File Menu* to access the runtime menu items:

Option	Action
View logs...	Click to open the view log dialog to view the pgAdmin 4 logs.
Configure runtime...	Click to open configuration dialog to configure fixed port, port number and connection timeout.

Configuration Dialog

Use the *Configure runtime...* option to access the *Configuration* dialog:



Following are the details of the *Fixed port number?*, *Port Number*, *Connection Timeout*, and 'Open Documentation in Default Browser?' configuration parameters:

Key	Type	Purpose
FixedPort	Boolean	Use a fixed network port number rather than a random one.
PortNumber	Integer	The port number to use, if using a fixed port.
ConnectionTimeout	Integer	The number of seconds to wait for application server startup.
Open Documentation in Default Browser	Boolean	By checking this option, all documentation links will open in the default browser instead of in a new window.


Log dialog

Use the *File Menu* to access the *View Logs* dialog:



Click on the *Reload* button at the bottom to view the latest logs of pgAdmin 4 Server.

When executed, the runtime will automatically try to execute the pgAdmin Python application. If execution fails, it will prompt you with error message displaying a *Configure* button at the bottom. You can configure a fixed port number to avoid clashes of the default random port number with other applications and a connection timeout if desired.



If the error is related to Python Path or pgAdmin Python file then you need to create a file named 'dev_config.json' and specify the following entries:

```
{
    "pythonPath": "/path/to/python.exe",
    "pgadminFile": "/path/to/pgAdmin4.py"
}
```

Note that the *dev_config.py* file should only be required by developers who are working outside of a standard installation.

The configuration settings are stored in *runtime_config.json* file, which will be available on Unix systems (~/.local/share/pgadmin/), on Mac OS X (~/Library/Preferences/pgadmin), and on Windows (%APPDATA%/pgadmin).

For details on the auto-update system for the desktop application, see

Auto-Update of pgAdmin 4 Desktop Application

pgAdmin 4's desktop application includes an automated update system built using Electron's `autoUpdater` module. This feature enables users to receive and install updates seamlessly, ensuring they always have access to the latest features and security fixes.


Supported Platforms

- **macOS:** Fully supported with automatic updates enabled by default
- **Windows:** Not supported
- **Linux:** Not supported

Update Process Overview

1. **Check for Updates:**
   - Automatic check on application startup
   - Manual check available via pgAdmin 4 menu > Check for Updates
   - Uses Electron's `autoUpdater` API to query update server
2. **Download Process:**
   - Updates download automatically when detected
   - Progress shown via notifications
   - Background download prevents interruption of work
3. **Installation Flow:**
   - User prompted to Install & Restart or Restart Later when update ready
   - Update applied during application restart

   The flow chart for the update process is as follows:


App Starts
Platform is macOS?
No
Yes
Register autoUpdater Event Listeners
Automatic or User-initiated Check for Updates
Call /upgrade_check API - pgAdmin Python Server
Update Available?
No
Yes
Fetch update info like ftpUrl, latest version, etc from pgadmin.org/versions.json via /upgrade_check API
Build feed URL for autoUpdate
Set feed URL for autoUpdater
Show Notifier: Update available
Cancel
Download
Call /auto_update API - pgAdmin Python Server
Download Success?
No
Yes
Show Notifier: Update downloaded
Install & Restart
Install Later
App quits, install update, restarts
Continue using current verion
Skip auto-update
Show Notifier: No update available
Show Notifier: Download error
Show Notifier: Update installed
User can install update later
End

User Interface Components

1. **Notification Types:**
    - Update available
    - Download progress
    - Update ready to install
    - Error notifications
2. **Menu Integration:**
    - Check for Updates option in pgAdmin 4 menu
    - Restart to Update option when update available

Error Handling

The system includes comprehensive error handling:

1. **Network Errors:**
    - Connection timeouts
    - Download failures
    - Server unavailability
2. **Installation Errors:**
    - Corrupted downloads
3. **Recovery Mechanisms:**
    - Fallback to manual update
    - Error reporting to logs

Security Considerations

The update system implements below security measures:

1. **Secure Communication:**
    - Protected update metadata

Platform-Specific Notes

1. **macOS:**
    - Uses native update mechanisms
    - Requires signed packages

References

- Electron autoUpdater API Documentation

1.1.3 Server Deployment

pgAdmin may be deployed as a web application by configuring the app to run in server mode and then deploying it either behind a webserver running as a reverse proxy, or using the WSGI interface.

When deployed in server mode, there are two notable differences for users:

- Users must login before they can use pgAdmin. An initial superuser account is created when server mode is initialised, and this user can add additional superusers and non-superusers as required.
- File storage is restricted to a virtual root directory for each individual user under the directory configured using the `STORAGE_DIR` configuration parameter. Users do not have access to the complete filesystem of the server.

The following instructions demonstrate how pgAdmin may be run as a WSGI application under `Apache HTTPD`, using `mod_wsgi`, standalone using `uWSGI` or `Gunicorn`, or under `NGINX` using using `uWSGI` or `Gunicorn`.

See also

For detailed instructions on building and configuring pgAdmin from scratch, please see the README file in the top level directory of the source code. For convenience, you can find the latest version of the file here, but be aware that this may differ from the version included with the source code for a specific version of pgAdmin.

Requirements

Important: Some components of pgAdmin require the ability to maintain affinity between client sessions and a specific database connection (for example, the Query Tool in which the user might run a BEGIN command followed by a number of DML SQL statements, and then a COMMIT). pgAdmin has been designed with built-in connection management to handle this, however it requires that only a single Python process is used because it is not easily possible to maintain affinity between a client session and one of multiple WSGI worker processes.

On Windows systems, the Apache HTTP server uses a single process, multi-threaded architecture. WSGI applications run in `embedded` mode, which means that only a single process will be present on this platform in all cases.

On Unix systems, the Apache HTTP server typically uses a multi-process, single threaded architecture (this is dependent on the `MPM` that is chosen at compile time). If `embedded` mode is chosen for the WSGI application, then there will be one Python environment for each Apache process, each with it's own connection manager which will lead to loss of connection affinity. Therefore one should use `mod_wsgi`'s `daemon` mode, configured to use a single process. This will launch a single instance of the WSGI application which is utilised by all the Apache worker processes.

Whilst it is true that this is a potential performance bottleneck, in reality pgAdmin is not a web application that's ever likely to see heavy traffic unlike a busy website, so in practice should not be an issue.

Future versions of pgAdmin may introduce a shared connection manager process to overcome this limitation, however that is a significant amount of work for little practical gain.

Configuration

In order to configure pgAdmin to run in server mode, it may be necessary to configure the Python code to run in multi-user mode, and then to configure the web server to find and execute the code.

See *Configuration Files* for more information on configuration settings.

Python

From pgAdmin 4 v2 onwards, server mode is the default configuration. If running under the desktop runtime, this is overridden automatically. There should typically be no need to modify the configuration simply to enable server mode to work, however it may be desirable to adjust some of the paths used.

In order to configure the Python code, follow these steps:

1. Create a `config_local.py` file alongside the existing `config.py` file.
2. Edit `config_local.py` and add the following settings. In most cases, the default file locations should be appropriate:

   NOTE: You must ensure the directories specified are writeable by the user that the web server processes will be running as, e.g. apache or www-data. You may specify DATA_DIR in order to create all required directories and files under DATA_DIR folder.

   ```
   LOG_FILE = '/var/log/pgadmin4/pgadmin4.log'
   SQLITE_PATH = '/var/lib/pgadmin4/pgadmin4.db'
   SESSION_DB_PATH = '/var/lib/pgadmin4/sessions'
   STORAGE_DIR = '/var/lib/pgadmin4/storage'
   AZURE_CREDENTIAL_CACHE_DIR = '/var/lib/pgadmin4/azurecredentialcache'
   KERBEROS_CCACHE_DIR = '/var/lib/pgadmin4/kerberoscache'
   ```

4. Run the following command to create the configuration database:

   ```
   # python setup.py setup-db
   ```

5. Change the ownership of the configuration database to the user that the web server processes will run as, for example, assuming that the web server runs as user www-data in group www-data, and that the SQLite path is `/var/lib/pgadmin4/pgadmin4.db`:

   ```
   # chown www-data:www-data /var/lib/pgadmin4/pgadmin4.db
   ```

Hosting

There are many possible ways to host pgAdmin in server mode. Some examples are given below:

Apache HTTPD Configuration (Windows)

Once Apache HTTP has been configured to support `mod_wsgi`, the pgAdmin application may be configured similarly to the example below:

```
<VirtualHost *>
    ServerName pgadmin.example.com
    WSGIScriptAlias / "C:\Program Files\pgAdmin4\web\pgAdmin4.wsgi"
    <Directory "C:\Program Files\pgAdmin4\web">
            Order deny,allow
            Allow from all
    </Directory>
</VirtualHost>
```

Now open the file `C:\Program Files\pgAdmin4\web\pgAdmin4.wsgi` with your favorite editor and add the code below which will activate Python virtual environment when Apache server runs.

```
activate_this = 'C:\Program Files\pgAdmin4\venv\Scripts\activate_this.py'
exec(open(activate_this).read())
```

Note: The changes made in `pgAdmin4.wsgi` file will revert when pgAdmin4 is either upgraded or downgraded.

Apache HTTPD Configuration (Linux/Unix)

Once Apache HTTP has been configured to support `mod_wsgi`, the pgAdmin application may be configured similarly to the example below:

```
<VirtualHost *>
    ServerName pgadmin.example.com

    WSGIDaemonProcess pgadmin processes=1 threads=25 python-home=/path/to/python/
↪virtualenv
    WSGIScriptAlias / /opt/pgAdmin4/web/pgAdmin4.wsgi

    <Directory /opt/pgAdmin4/web>
        WSGIProcessGroup pgadmin
        WSGIApplicationGroup %{GLOBAL}
        Order deny,allow
        Allow from all
    </Directory>
</VirtualHost>
```

Note: If you're using Apache HTTPD 2.4 or later, replace the lines:

```
Order deny,allow
Allow from all
```

with:

```
Require all granted
```

Adjust as needed to suit your access control requirements.

Standalone Gunicorn Configuration

pgAdmin may be hosted by Gunicorn directly simply by running a command such as the one shown below. Note that this example assumes pgAdmin was installed using the Python Wheel (you may need to adjust the path to suit your installation):

```
gunicorn  --bind 0.0.0.0:80 \
          --workers=1 \
          --threads=25 \
          --chdir /usr/lib/python3.13/dist-packages/pgadmin4 \
          pgAdmin4:app
```

Standalone uWSGI Configuration

pgAdmin may be hosted by uWSGI directly simply by running a command such as the one shown below. Note that this example assumes pgAdmin was installed using the Python Wheel (you may need to adjust the path to suit your installation):

```
uwsgi --http-socket 0.0.0.0:80 \
      --processes 1 \
      --threads 25 \
      --chdir /usr/lib/python3.13/dist-packages/pgadmin4/ \
      --mount /=pgAdmin4:app
```

Hosting in a Sub-Directory

Any of the reverse proxy configurations described below can host pgAdmin in a sub-directory of the server (`/pgadmin4` in each of the examples) rather than at its root, but doing so requires that the `SCRIPT_NAME` environment variable is set for the Gunicorn or uWSGI process, whichever is in use.

pgAdmin reads `SCRIPT_NAME` from the process environment once, at startup, and uses it to set `APPLICATION_ROOT` and `SESSION_COOKIE_PATH`, so that URLs, redirects (including the one issued after a successful login) and session cookies are all generated relative to the sub-directory rather than to the root of the server. Without it, a successful login redirects to the root of the server, which typically presents to the user as a redirect loop.

This is a separate mechanism from the per-request `X-Script-Name` header that the NGINX Gunicorn example below sets, and neither substitutes for the other. It is also separate from uWSGI's `--manage-script-name`, which only affects the per-request WSGI environment that uWSGI builds; the uWSGI examples below set `SCRIPT_NAME` alongside it so that both mechanisms agree, and so that the session cookie is confined to the sub-directory rather than being issued for the root of the server.

Reverse Proxy Headers

pgAdmin honours the `X-Script-Name` and `X-Scheme` request headers unconditionally, unlike the `X-Forwarded-*` headers, which are trusted only to the depth configured by the `PROXY_X_*_COUNT` settings. A client that supplied its own `X-Script-Name` could therefore change every URL pgAdmin generates, so the reverse proxy must always either overwrite both headers with values of its own or remove them outright, rather than passing on whatever the client sent. Each of the examples below does one or the other, and a proxy configuration not derived from them should do the same.

NGINX Configuration with Gunicorn

pgAdmin can be hosted by Gunicorn, with NGINX in front of it. Note that these examples assume pgAdmin was installed using the Python Wheel (you may need to adjust the path to suit your installation).

To run with pgAdmin in the root directory of the server, start Gunicorn using a command similar to:

```
gunicorn --bind unix:/tmp/pgadmin4.sock \
         --workers=1 \
         --threads=25 \
         --chdir /usr/lib/python3.13/dist-packages/pgadmin4 \
         pgAdmin4:app
```

And configure NGINX:

```
location / {
    include proxy_params;
    proxy_pass http://unix:/tmp/pgadmin4.sock;
    proxy_set_header X-Script-Name "";
    proxy_set_header X-Scheme "";
}
```

Alternatively, pgAdmin can be hosted in a sub-directory (/pgadmin4 in this case) on the server. Start Gunicorn as when using the root directory, but also set the `SCRIPT_NAME` environment variable for the Gunicorn process, as described in *Hosting in a Sub-Directory*:

```
SCRIPT_NAME=/pgadmin4 gunicorn --bind unix:/tmp/pgadmin4.sock \
                               --workers=1 \
                               --threads=25 \
                               --chdir /usr/lib/python3.13/dist-packages/pgadmin4 \
                               pgAdmin4:app
```

Then configure NGINX:

```
location /pgadmin4/ {
    include proxy_params;
    proxy_pass http://unix:/tmp/pgadmin4.sock;
    proxy_set_header X-Script-Name /pgadmin4;
    proxy_set_header X-Scheme "";
}
```

NGINX Configuration with uWSGI

pgAdmin can be hosted by uWSGI, with NGINX in front of it. Note that these examples assume pgAdmin was installed using the Python Wheel (you may need to adjust the path to suit your installation).

To run with pgAdmin in the root directory of the server, start uWSGI using a command similar to:

```
uwsgi --socket /tmp/pgadmin4.sock \
      --processes 1 \
      --threads 25 \
      --chdir /usr/lib/python3.13/dist-packages/pgadmin4/ \
      --manage-script-name \
      --mount /=pgAdmin4:app
```

And configure NGINX:

```
location / { try_files $uri @pgadmin4; }
location @pgadmin4 {
    include uwsgi_params;
    uwsgi_pass unix:/tmp/pgadmin4.sock;
    uwsgi_param HTTP_X_SCRIPT_NAME "";
    uwsgi_param HTTP_X_SCHEME "";
}
```

Alternatively, pgAdmin can be hosted in a sub-directory (/pgadmin4 in this case) on the server. Start uWSGI, noting that the directory name is specified in the `mount` parameter, and that the `SCRIPT_NAME` environment variable should be set alongside it, as described in *Hosting in a Sub-Directory*:

```
SCRIPT_NAME=/pgadmin4 uwsgi --socket /tmp/pgadmin4.sock \
                            --processes 1 \
                            --threads 25 \
                            --chdir /usr/lib/python3.13/dist-packages/pgadmin4/ \
                            --manage-script-name \
                            --mount /pgadmin4=pgAdmin4:app
```

Then, configure NGINX:

```
location = /pgadmin4 { rewrite ^ /pgadmin4/; }
location /pgadmin4 { try_files $uri @pgadmin4; }
location @pgadmin4 {
  include uwsgi_params;
  uwsgi_pass unix:/tmp/pgadmin4.sock;
  uwsgi_param HTTP_X_SCRIPT_NAME "";
  uwsgi_param HTTP_X_SCHEME "";
}
```

Caddy Configuration with Gunicorn

pgAdmin can be hosted by Gunicorn, with Caddy in front of it as a reverse proxy. Note that these examples assume pgAdmin was installed using the Python Wheel (you may need to adjust the path to suit your installation).

To run with pgAdmin in the root directory of the server, start Gunicorn using a command similar to:

```
gunicorn --bind unix:/run/pgadmin4/pgadmin4.sock \
         --workers=1 \
         --threads=25 \
         --chdir /usr/lib/python3.13/dist-packages/pgadmin4 \
         pgAdmin4:app
```

And configure Caddy:

```
pgadmin.example.com {
    reverse_proxy unix//run/pgadmin4/pgadmin4.sock {
        header_up -X-Script-Name
        header_up -X-Scheme
    }
}
```

Note

The examples deliberately avoid `/tmp` for the socket. The systemd unit shipped with Caddy sets `PrivateTmp=true`, which gives the Caddy process a private `/tmp` directory of its own, so a socket created by Gunicorn or uWSGI in the system `/tmp` is invisible to Caddy, which will report a 502 error for every request. Any directory outside `/tmp` that both processes can access will do, provided the user Caddy runs as has permission to read and write the socket; alternatively, have Gunicorn or uWSGI listen on a TCP port such as `127.0.0.1:5050` and proxy to that instead. Whichever directory is used, it must exist and be writable by the user Gunicorn or uWSGI runs as before the socket can be bound; under systemd, `RuntimeDirectory=pgadmin4` in the unit that starts Gunicorn or uWSGI will create `/run/pgadmin4` on start and remove it on stop. The same applies to the uWSGI examples below.

Note

The two `header_up` directives remove any `X-Script-Name` and `X-Scheme` headers that arrive from the client, for the reasons given in *Reverse Proxy Headers*. Each of the Caddy examples removes both, except that the Gunicorn sub-directory example sets `X-Script-Name` to the sub-directory instead, which likewise replaces whatever the client sent.

Alternatively, pgAdmin can be hosted in a sub-directory (/pgadmin4 in this case) on the server. Start Gunicorn as when using the root directory, but also set the `SCRIPT_NAME` environment variable for the Gunicorn process, as described in *Hosting in a Sub-Directory*:

```
SCRIPT_NAME=/pgadmin4 gunicorn --bind unix:/run/pgadmin4/pgadmin4.sock \
                               --workers=1 \
                               --threads=25 \
                               --chdir /usr/lib/python3.13/dist-packages/pgadmin4 \
                               pgAdmin4:app
```

Then configure Caddy. The request path must be passed through to Gunicorn unchanged, so do not strip the /pgadmin4 prefix; the `X-Script-Name` header is set to the sub-directory, both to tell pgAdmin which requests are made under it and to replace any value the client may have sent; and the path matcher must include both `/pgadmin4` and `/pgadmin4/*`, so that pgAdmin's own redirect to the bare sub-directory path (with no trailing slash) is also proxied, rather than falling through to Caddy's default (and rather unhelpful) empty response for an unmatched path:

```
pgadmin.example.com {
    @pgadmin path /pgadmin4 /pgadmin4/*
    handle @pgadmin {
        reverse_proxy unix//run/pgadmin4/pgadmin4.sock {
            header_up X-Script-Name /pgadmin4
            header_up -X-Scheme
        }
    }
}
```

Caddy Configuration with uWSGI

Caddy does not speak the native uwsgi protocol used by NGINX's `uwsgi_pass`, so uWSGI must be run in HTTP mode instead, using `--http-socket` rather than `--socket`. Note that these examples assume pgAdmin was installed using the Python Wheel (you may need to adjust the path to suit your installation).

To run with pgAdmin in the root directory of the server, start uWSGI using a command similar to:

```
uwsgi --http-socket /run/pgadmin4/pgadmin4.sock \
      --processes 1 \
      --threads 25 \
      --chdir /usr/lib/python3.13/dist-packages/pgadmin4/ \
      --mount /=pgAdmin4:app
```

And configure Caddy, again keeping the socket out of `/tmp` (see *the note above*) and stripping the headers pgAdmin trusts unconditionally (see *the note above*):

```
pgadmin.example.com {
    reverse_proxy unix//run/pgadmin4/pgadmin4.sock {
        header_up -X-Script-Name
        header_up -X-Scheme
    }
}
```

Alternatively, pgAdmin can be hosted in a sub-directory (/pgadmin4 in this case) on the server. Start uWSGI, noting that the directory name is specified in the `mount` parameter, and that the `SCRIPT_NAME` environment variable should still be set alongside it, as described in *Hosting in a Sub-Directory*:

```
SCRIPT_NAME=/pgadmin4 uwsgi --http-socket /run/pgadmin4/pgadmin4.sock \
                            --processes 1 \
                            --threads 25 \
                            --chdir /usr/lib/python3.13/dist-packages/pgadmin4/ \
                            --manage-script-name \
                            --mount /pgadmin4=pgAdmin4:app
```

Then configure Caddy as for the Gunicorn sub-directory example above, except that no `X-Script-Name` header needs to be set: `--manage-script-name` has uWSGI report the mount point to pgAdmin with every request, as in the NGINX uWSGI example above, so the header is only removed:

```
pgadmin.example.com {
    @pgadmin path /pgadmin4 /pgadmin4/*
    handle @pgadmin {
        reverse_proxy unix//run/pgadmin4/pgadmin4.sock {
            header_up -X-Script-Name
            header_up -X-Scheme
        }
    }
}
```

Additional Information

Note

pgAdmin will spawn additional Python processes from time to time, and relies on the *sys.executable* variable in Python to do this. In some cases, you may need to override that value to ensure the correct interpreter is used, instead of the WSGI host process. For example, uWSGI offers the *–py-sys-executable* command line option to achieve this.

1.1.4 Container Deployment

pgAdmin can be deployed in a container using the image at:

https://hub.docker.com/r/dpage/pgadmin4/

There are various tags that you can select from to get the version of pgAdmin that you want, using a command such as this if you're using Docker:

```
docker pull dpage/pgadmin4:<tag name>
```

where <*tag name*> is one of the following:

Tag name	Description
latest	The most recent release.
8.4	A specific version (8.4 in this case).
8	the latest release of a specific major version (major version 8 in this case).
snapshot	The latest nightly test build.

PostgreSQL Utilities

The PostgreSQL utilities *pg_dump*, *pg_dumpall*, *pg_restore* and *psql* are included in the container to allow backups to be created and restored and other maintenance functions to be executed. Multiple versions are included in the following directories to allow use with different versions of the database server:

- PostgreSQL 12: */usr/local/pgsql-12*
- PostgreSQL 13: */usr/local/pgsql-13*
- PostgreSQL 14: */usr/local/pgsql-14*
- PostgreSQL 15: */usr/local/pgsql-15*
- PostgreSQL 16: */usr/local/pgsql-16*

The default binary paths set in the container are as follows:

```
DEFAULT_BINARY_PATHS = {
    'pg-18': '/usr/local/pgsql-18',
    'pg-17': '/usr/local/pgsql-17',
    'pg-16': '/usr/local/pgsql-16',
    'pg-15': '/usr/local/pgsql-15',
    'pg-14': '/usr/local/pgsql-14',
    'pg-13': '/usr/local/pgsql-13'
}
```

this may be changed in the *Preferences*.

Environment Variables

The container will accept the following variables at startup:

PGADMIN_DEFAULT_EMAIL

This is the email address used when setting up the initial administrator account to login to pgAdmin. This variable is required and must be set at launch time.

PGADMIN_DEFAULT_PASSWORD

This is the password used when setting up the initial administrator account to login to pgAdmin. This variable is required and must be set at launch time.

PGADMIN_DEFAULT_PASSWORD_FILE

This is the password used when setting up the initial administrator account to login to pgAdmin. This value should be set to *docker secret* in order to set the password. This variable is supported in docker swarm environment or while creating container with docker compose. PGADMIN_DEFAULT_PASSWORD or PGADMIN_DEFAULT_PASSWORD_FILE variable is required and must be set at launch time.

PGADMIN_DISABLE_POSTFIX

Default: <null>

If left unset, a Postfix server will be started to deliver password reset emails.

If set to any value, the Postfix server will not be started, and pgAdmin will need to be configured to use an external mail server using the *PGADMIN_CONFIG_* options below.

This option is useful if you're running in an environment that prevents the use of sudo to start Postfix, or if you wish to use an external mail server.

PGADMIN_ENABLE_TLS

Default: <null>

If left un-set, the container will listen on port 80 for connections in plain text. If set to any value, the container will listen on port 443 for TLS connections.

When TLS is enabled, a certificate and key must be provided. Typically these should be stored on the host file system and mounted from the container. The expected paths are /certs/server.cert and /certs/server.key

PGADMIN_LISTEN_ADDRESS

Default: [::]

Specify the local address that the servers listens on. The default should work for most users - in IPv4-only environments, this may need to be set to 0.0.0.0.

PGADMIN_LISTEN_PORT

Default: 80 or 443 (if TLS is enabled)

Allows the port that the server listens on to be set to a specific value rather than using the default.

PGADMIN_SERVER_JSON_FILE

Default: /pgadmin4/servers.json

Override the default file path for the server definition list. See the /pgadmin4/servers.json mapped file below for more information. See the format of the Servers JSON file.

PGADMIN_REPLACE_SERVERS_ON_STARTUP

Default: null

By default, the server definitions are only loaded on first launch, i.e. when initializing the configuration database. See PGADMIN_SERVER_JSON_FILE above.

If this variable is set to True, the server definitions will be replaced on every launch. This can be used to declaratively manage the server definitions.

PGADMIN_PREFERENCES_JSON_FILE

Default: /pgadmin4/preferences.json

Override the default file path for the preferences customization at the container creation. See the /pgadmin4/preferences.json mapped file below for more information. See the format of the Preferences JSON file.

PGADMIN_CUSTOM_CONFIG_DISTRO_FILE

Default: /pgadmin4/config_distro.py

Override the default file path for the pgadmin configurations file.This can be used while provisioning container with read only root file system to achieve a more secure pgadmin4 deployment for kubernetes. Note that if you are externally mapping this file, then environment variables passed using *PGADMIN_CONFIG_* suffix will be ignored only when that file exists and is non-empty. A missing or empty file is generated with those values.

PGPASS_FILE

Default: <null> Set this variable to the path of a pgpass file if you want to supply passwords for the servers added in pgAdmin. On startup, the file is copied into the container and used as the `.pgpass` file.

PUID

Default: 5050

The user ID that pgAdmin runs as. This is only used when the container is started as root (for example with `--user root`), in which case the *pgadmin* user is given this UID, the ownership of */var/lib/pgadmin* is changed to match, and pgAdmin is then run as that user rather than as root. It is ignored when the container is started as any other user, which is the default. The value must be numeric, and may not be 0.

PGID

Default: 0

The group ID that pgAdmin runs as. As with *PUID*, this is only used when the container is started as root.

GUNICORN_ACCESS_LOGFILE

Default: - (stdout)

Specify an output file in which to store the Gunicorn access logs, instead of sending them to stdout.

GUNICORN_LIMIT_REQUEST_LINE

Default: 8190

Set the maximum size of HTTP request line in bytes. By default the pgAdmin container uses the maximum limited size offered by Gunicorn as some requests can be quite large. In exceptional cases this value can be set to 0 (zero) to specify "unlimited", however this poses a potential denial of service hazard.

GUNICORN_THREADS

Default: 25

Adjust the number of threads the Gunicorn server uses to handle incoming requests. This should typically be left as-is, except in highly loaded systems where it may be increased.

PGADMIN_CONFIG_*

This is a variable prefix that can be used to override any of the configuration options in pgAdmin's *config.py* file. Add the *PGADMIN_CONFIG_* prefix to any variable name from *config.py* and give the value as a Python expression: `'string value'` (including the quotes) for strings, `True` or `False` for booleans, or `123` for numbers. See below for an example.

*PGADMIN_DEFAULT_* variables, including *PGADMIN_DEFAULT_EMAIL* and *PGADMIN_DEFAULT_PASSWORD*, are ordinary text and take no Python literal quotes. *PGADMIN_CONFIG_* values are written as Python code into */pgadmin4/config_distro.py*, or into the file named by *PGADMIN_CUSTOM_CONFIG_DISTRO_FILE* if that is set. The values `true` and `false`, in any letter case, are written as `True` and `False`. A bare hostname is a Python name, so `MAIL_SERVER = mail.example.com` raises `NameError` at startup.

Quoting added by the shell or by YAML sits outside that Python expression and is removed before the value is written. The *docker run* example below keeps the Python quotes inside shell quotes, for example `-e 'PGADMIN_CONFIG_LOGIN_BANNER="Authorised users only!"'`.

In Docker Compose map syntax, YAML consumes the quotes around a scalar. A YAML-only quoted hostname, `PGADMIN_CONFIG_MAIL_SERVER: "mail.example.com"` or `PGADMIN_CONFIG_MAIL_SERVER: 'mail.example.com'`, reaches the container as `mail.example.com` and cannot serve as a Python string. Nest the Python quotes inside the scalar: `PGADMIN_CONFIG_MAIL_SERVER: "'mail.example.com'"`. The container then writes `MAIL_SERVER = 'mail.example.com'`. `"587"` and `"True"` are already valid Python, so they need no nested quotes. The list form keeps single quotes, as `docker run -e` does (`- PGADMIN_CONFIG_MAIL_SERVER='mail.example.com'`); nesting them there produces `"'mail.example.com'"`, which is valid Python but puts stray quote characters into the value and fails silently rather than at startup. An `env_file` value strips one layer of quotes, so the same nesting as the map form applies there. The Compose example in the Examples section uses the map form for an SMTP server, username, password, and *SECURITY_EMAIL_SENDER*.

Compose substitutes `$VAR` and `${VAR}` in Compose file values, and in double-quoted `env_file` values, so write a literal dollar as `$$`. `"'pa$word'"` reaches the container as `'pa'`, with only a warning about an unset variable. The entrypoint does not expand the value again, so `$$` is the only escaping required.

Settings are written to */pgadmin4/config_distro.py* within the container (or to the file named by *PGADMIN_CUSTOM_CONFIG_DISTRO_FILE*), which is read after */pgadmin4/config.py* and before */pgadmin4/config_local.py*. Any settings given will therefore override anything in config.py, but can be overridden by settings in config_local.py.

The file is generated only when it is missing or empty, typically on first launch, and a non-empty file is left unchanged, including when the container is restarted. To apply corrected *PGADMIN_CONFIG_* values, recreate the container (`docker compose up -d` does this when the environment changes, whereas `docker compose restart` does not), keeping the */var/lib/pgadmin* mapping to retain your data. If the file is on persistent storage, either because it is mapped (not recommended; use */pgadmin4/config_local.py* instead) or because *PGADMIN_CUSTOM_CONFIG_DISTRO_FILE* points there, recreating the container is not enough: edit the file, or empty it so that it is regenerated.

See *Configuration Files* for more information on the available configuration settings.

Mapped Files and Directories

The following files or directories can be mapped from the container onto the host machine to allow configuration to be customised and shared between instances.

Warning

Warning: pgAdmin runs as the *pgadmin* user (UID: 5050) in the *root* group (GID: 0) in the container. You must ensure that all files are readable, and where necessary (e.g. the working/session directory) writeable for this user on the host machine. For example:

```
sudo chown -R 5050:0 <host_directory>
```

When using rootless Podman, user IDs in the container are mapped to a range of subordinate IDs on the host, so changing the ownership of a host directory to 5050 as shown above does not make it writeable by the container. Instead, either add the *U* option to the volume, which has Podman recursively change the ownership of the directory and everything in it to match the container's user, for example:

```
-v /path/to/pgadmin-data:/var/lib/pgadmin:U
```

or start the container as root, which in a rootless container is your own user on the host. The container will change the ownership of */var/lib/pgadmin* and then run pgAdmin as the *pgadmin* user; see *PUID* and *PGID* above. For example:

```
--user root
```

Neither option changes SELinux labels, so on a host with SELinux enforcing, the volume also needs the *z* (shared) or *Z* (private) option to relabel it, for example `-v /path/to/pgadmin-data:/var/lib/pgadmin:Z,U`.

On some filesystems that do not support extended attributes, it may not be possible to run pgAdmin without specifying a value for *PGADMIN_LISTEN_PORT* that is greater than 1024. In such cases, specify an alternate port when launching the container by adding the environment variable, for example:

```
-e 'PGADMIN_LISTEN_PORT=5050'
```

Don't forget to adjust any host-container port mapping accordingly.

/var/lib/pgadmin

This is the working directory in which pgAdmin stores session data, user files, configuration files, and it's configuration database. Mapping this directory onto the host machine gives you an easy way to maintain configuration between invocations of the container.

/pgadmin4/config_local.py

This file can be used to override configuration settings in pgAdmin. Settings found in config.py can be overridden with deployment specific values if required. Settings in config_local.py will also override anything specified in the container environment through *PGADMIN_CONFIG_* prefixed variables.

/pgadmin4/servers.json

If this file is mapped, server definitions found in it will be loaded at launch time. This allows connection information to be pre-loaded into the instance of pgAdmin in the container. Note that server definitions are only loaded on first launch, i.e. when the configuration database is created, and not on subsequent launches using the same configuration database.

/pgadmin4/preferences.json

If this file is mapped, preferences defined in it will be updated at launch time. This allows customization of preferences settings into the instance of pgAdmin in the container. Note that preferences are only set on first launch, i.e. when the configuration database is created, and not on subsequent launches using the same configuration database.

/certs/server.cert

If TLS is enabled, this file will be used as the servers TLS certificate.

/certs/server.key

If TLS is enabled, this file will be used as the key file for the servers TLS certificate.

Examples

Run a simple container over port 80:

```
docker pull dpage/pgadmin4
docker run -p 80:80 \
    -e 'PGADMIN_DEFAULT_EMAIL=user@domain.com' \
    -e 'PGADMIN_DEFAULT_PASSWORD=SuperSecret' \
    -d dpage/pgadmin4
```

Run a simple container over port 80, setting some configuration options:

```
docker pull dpage/pgadmin4
docker run -p 80:80 \
    -e 'PGADMIN_DEFAULT_EMAIL=user@domain.com' \
    -e 'PGADMIN_DEFAULT_PASSWORD=SuperSecret' \
    -e 'PGADMIN_CONFIG_ENHANCED_COOKIE_PROTECTION=True' \
    -e 'PGADMIN_CONFIG_LOGIN_BANNER="Authorised users only!"' \
    -e 'PGADMIN_CONFIG_CONSOLE_LOG_LEVEL=10' \
    -d dpage/pgadmin4
```

Run pgAdmin with Docker Compose, publishing port 80 and sending mail through an external SMTP server. *PGADMIN_DEFAULT_EMAIL* and *PGADMIN_DEFAULT_PASSWORD* are ordinary strings. Each *PGADMIN_CONFIG_* string below includes the Python quotes that YAML would otherwise remove. *PGADMIN_DISABLE_POSTFIX* may be any non-empty value; it is ordinary text, not a Python expression. The named volume keeps */var/lib/pgadmin* when the container is recreated:

```
services:
  pgadmin:
    image: dpage/pgadmin4
    ports:
      - "80:80"
    environment:
      PGADMIN_DEFAULT_EMAIL: user@domain.com
      PGADMIN_DEFAULT_PASSWORD: SuperSecret
      PGADMIN_DISABLE_POSTFIX: "1"
      PGADMIN_CONFIG_MAIL_SERVER: "'mail.example.com'"
      PGADMIN_CONFIG_MAIL_PORT: "587"
      PGADMIN_CONFIG_MAIL_USE_TLS: "True"
      PGADMIN_CONFIG_MAIL_USERNAME: "'smtp-user'"
      PGADMIN_CONFIG_MAIL_PASSWORD: "'s3cret=value'"
      PGADMIN_CONFIG_SECURITY_EMAIL_SENDER: "'pgadmin@example.com'"
    volumes:
      - pgadmin-data:/var/lib/pgadmin

volumes:
  pgadmin-data:
```

Run a TLS secured container using a shared config/storage directory in /private/var/lib/pgadmin on the host, and servers pre-loaded from /tmp/servers.json on the host:

```
docker pull dpage/pgadmin4
docker run -p 443:443 \
    -v /private/var/lib/pgadmin:/var/lib/pgadmin \
```

(continues on next page)

(continued from previous page)

```
    -v /path/to/certificate.cert:/certs/server.cert \
    -v /path/to/certificate.key:/certs/server.key \
    -v /tmp/servers.json:/pgadmin4/servers.json \
    -e 'PGADMIN_DEFAULT_EMAIL=user@domain.com' \
    -e 'PGADMIN_DEFAULT_PASSWORD=SuperSecret' \
    -e 'PGADMIN_ENABLE_TLS=True' \
    -d dpage/pgadmin4
```

Restricted Security Contexts (OpenShift, `--cap-drop=ALL`)

Some platforms refuse to honor Linux file capabilities. The two situations the pgAdmin container handles automatically are:

- `--cap-drop=ALL` (or an equivalent restricted Kubernetes SecurityContext such as OpenShift's `restricted-v2` SCC), which zeros the bounding set and removes `CAP_NET_BIND_SERVICE`. Exec of a capability-tagged binary then fails with `Operation not permitted`.
- `--security-opt=no-new-privileges` (or `allowPrivilegeEscalation: false`), which causes the kernel to silently strip file capabilities on exec. The binary runs, but a subsequent `bind()` to a port below 1024 fails with `EPERM`.

The container's entrypoint reads `/proc/self/status` at startup, detects either condition, switches gunicorn to the non-capability python interpreter, and (when *PGADMIN_LISTEN_PORT* is not set) defaults the listen port to **8080** for plain HTTP and **8443** for TLS instead of 80/443. A message is logged so the choice is visible.

In practice this means a typical OpenShift deployment requires no special build, no setcap, and no custom configuration — only a Service / Route that targets the chosen non-privileged port:

```
docker run --rm -p 8080:8080 \
    --security-opt=no-new-privileges \
    --cap-drop=ALL \
    -e 'PGADMIN_DEFAULT_EMAIL=user@domain.com' \
    -e 'PGADMIN_DEFAULT_PASSWORD=SuperSecret' \
    dpage/pgadmin4
```

If you explicitly set *PGADMIN_LISTEN_PORT*, that value is honored in both the restricted and unrestricted paths.

Reverse Proxying

Sometimes it's desirable to have users connect to pgAdmin through a reverse proxy rather than directly to the container it's running in. The following examples show how this can be achieved. With traditional reverse proxy servers such as Nginx, pgAdmin is running in a container on the same host, with port 5050 on the host mapped to port 80 on the container, for example:

```
docker pull dpage/pgadmin4
docker run -p 5050:80 \
    -e "PGADMIN_DEFAULT_EMAIL=user@domain.com" \
    -e "PGADMIN_DEFAULT_PASSWORD=SuperSecret" \
    -d dpage/pgadmin4
```

pgAdmin X-Forwarded-* Configuration

pgAdmin needs to understand how many proxies set each header so it knows what values to trust. The configuration parameters for the X-Forwarded-* options which are used for this purpose are shown below, along with their default values.

pgAdmin is configured by default to be able to run behind a reverse proxy even on a non-standard port and these config options don't normally need to be changed. If you're running an unusual configuration (such as multiple reverse proxies) you can adjust the configuration to suit.

```
# Number of values to trust for X-Forwarded-For
PROXY_X_FOR_COUNT = 1

# Number of values to trust for X-Forwarded-Proto.
PROXY_X_PROTO_COUNT = 0

# Number of values to trust for X-Forwarded-Host.
PROXY_X_HOST_COUNT = 0

# Number of values to trust for X-Forwarded-Port.
PROXY_X_PORT_COUNT = 1

# Number of values to trust for X-Forwarded-Prefix.
PROXY_X_PREFIX_COUNT = 0
```

HTTP via Nginx

A configuration similar to the following can be used to create a simple HTTP reverse proxy listening for all hostnames with Nginx:

```
server {
    listen 80;
    server_name _;

    location / {
        proxy_set_header Host $host;
        proxy_pass http://localhost:5050/;
        proxy_redirect off;
    }
}
```

If you wish to host pgAdmin under a subdirectory rather than on the root of the server, you must specify the location and set the *X-Script-Name* header which tells the pgAdmin container how to rewrite paths:

```
server {
    listen 80;
    server_name _;

    location /pgadmin4/ {
        proxy_set_header X-Script-Name /pgadmin4;
        proxy_set_header Host $host;
        proxy_pass http://localhost:5050/;
```

(continues on next page)

(continued from previous page)

```
        proxy_redirect off;
    }
}
```

If Nginx is also running in a container, there is no need to map the pgAdmin port to the host, provided the two containers are running in the same Docker network. In such a configuration, the *proxy_pass* option would be changed to point to the pgAdmin container within the Docker network.

HTTPS via Nginx

The following configuration can be used to serve pgAdmin over HTTPS to the user whilst the backend container is serving plain HTTP to the proxy server. In this configuration we not only set *X-Script-Name*, but also *X-Scheme* to tell the pgAdmin server to generate any URLs using the correct scheme. A redirect from HTTP to HTTPS is also included. The certificate and key paths may need to be adjusted as appropriate to the specific deployment:

```
server {
    listen 80;
    return 301 https://$host$request_uri;
}

server {
    listen 443;
    server_name _;

    ssl_certificate /etc/nginx/server.cert;
    ssl_certificate_key /etc/nginx/server.key;

    ssl on;
    ssl_session_cache builtin:1000 shared:SSL:10m;
    ssl_protocols TLSv1 TLSv1.1 TLSv1.2;
    ssl_ciphers HIGH:!aNULL:!eNULL:!EXPORT:!CAMELLIA:!DES:!MD5:!PSK:!RC4;
    ssl_prefer_server_ciphers on;

    location /pgadmin4/ {
        proxy_set_header X-Script-Name /pgadmin4;
        proxy_set_header X-Scheme $scheme;
        proxy_set_header Host $host;
        proxy_pass http://localhost:5050/;
        proxy_redirect off;
    }
}
```

Traefik

Configuring Traefik is straightforward for either HTTP or HTTPS when running pgAdmin in a container as it will automatically configure itself to serve content from containers that are running on the local machine, virtual hosting them at <*container_name*>.<*domain_name*>, where the domain name is that specified in the Traefik configuration. The container is typically launched per the example below:

```
docker pull dpage/pgadmin4
docker run --name "pgadmin4" \
    -e "PGADMIN_DEFAULT_EMAIL=user@domain.com" \
    -e "PGADMIN_DEFAULT_PASSWORD=SuperSecret" \
    -d dpage/pgadmin4
```

Note that the TCP/IP port has not been mapped to the host as it was in the Nginx example, and the container name has been set to a known value as it will be used as the hostname and may need to be added to the DNS zone file.

The following configuration will listen on ports 80 and 443, redirecting 80 to 443, using the default certificate shipped with Traefik. See the Traefik documentation for options to use certificates from LetsEncrypt or other issuers.

```
defaultEntryPoints = ["http", "https"]

[entryPoints]
  [entryPoints.http]
    address = ":80"
      [entryPoints.http.redirect]
        entryPoint = "https"
  [entryPoints.https]
    address = ":443"
      [entryPoints.https.tls]

[docker]
domain = "domain_name"
watch = true
```

If you wish to host pgAdmin under a subdirectory using Traefik, the configuration changes are typically made to the way the container is launched and not to Traefik itself. For example, to host pgAdmin under */pgadmin4/* instead of at the root directory, the Traefik configuration above may be used if the container is launched like this while using the version v1 of Traefik:

```
docker pull dpage/pgadmin4
docker run --name "pgadmin4" \
    -e "PGADMIN_DEFAULT_EMAIL=user@domain.com" \
    -e "PGADMIN_DEFAULT_PASSWORD=SuperSecret" \
    -e "SCRIPT_NAME=/pgadmin4" \
    -l "traefik.frontend.rule=PathPrefix:/pgadmin4" \
    -d dpage/pgadmin4
```

The *SCRIPT_NAME* environment variable has been set to tell the container it is being hosted under a subdirectory (in the same way as the *X-Script-Name* header is used with Nginx), and a label has been added to tell Traefik to route requests under the subdirectory to this container.

While using the Traefik configuration for version v2 for hosting pgAdmin under subdirectory the container is typically launched per the example below:

```
docker pull dpage/pgadmin4
docker run --name "pgadmin4" \
    -e "PGADMIN_DEFAULT_EMAIL=user@domain.com" \
    -e "PGADMIN_DEFAULT_PASSWORD=SuperSecret" \
    -e "SCRIPT_NAME=/pgadmin4" \
    -l "traefik.frontend.pgadmin4.rule=Host(`host.example.com`) && PathPrefix(`/
↪pgadmin4`)" \
    -d dpage/pgadmin4
```

Sharing the data volume across containers (Kubernetes init containers)

A common Kubernetes pattern is to bootstrap a pgAdmin deployment with one or more init containers that share the `/var/lib/pgadmin` volume with the main pgAdmin container — for example, an init container that runs `setup.py load-servers` to import a `servers.json` definition file at each rollout.

The image tag of any such sidecar/init container must NOT be newer than the main pgAdmin container's tag. pgAdmin's configuration database (`pgadmin4.db`) is migrated forward only — destructive operations such as dropping a column are part of normal upgrades. If an init container running `pgadmin4:latest` (or any newer tag) executes `setup.py` against a `pgadmin4.db` that the main, older pgAdmin will then read, the init container's migrations will advance the schema past what the main container's ORM understands, and the main container will fail at runtime with errors like `no such column: <table>.<column>`.

The safe configuration is to pin **both** the main container and every sidecar/init container that touches the data volume to the **same** explicit version tag, and upgrade them together:

```
# Deployment manifest (spec.template.spec): pin every container that
# touches the data volume to the same explicit tag. Do NOT use :latest.
spec:
  template:
    spec:
      initContainers:
        - name: import-servers-json
          image: docker.io/dpage/pgadmin4:9.14   # match the main container
          # ... rest of the init container spec ...
      containers:
        - name: pgadmin
          image: docker.io/dpage/pgadmin4:9.14   # main pgAdmin container
```

If you deploy pgAdmin with a Helm chart, set the equivalent image-tag values for both the main container and every init/sidecar container rather than the raw fields shown above. When upgrading pgAdmin, change every reference to the image tag at the same time so that the main container and any sidecar/init containers move forward together.

Use `strategy: Recreate`, not `RollingUpdate`

Even when every container's image tag is pinned correctly, **a rolling upgrade across pgAdmin versions is unsafe** when the old and new pods share a data volume. Kubernetes' default `RollingUpdate` strategy starts the new pod, waits for it to become healthy, and only *then* terminates the old pod. During that overlap window:

1. The new pod's startup runs `db_upgrade()` and applies any pending migrations to the shared `pgadmin4.db` — including destructive ones (column drops, table renames, type changes).
2. The new pod becomes healthy. The old pod is still alive and still has `pgadmin4.db` open with its older ORM schema metadata.

3. Until Kubernetes terminates the old pod, requests routed to it generate queries that reference the pre-migration schema. Those queries now fail at runtime against the migrated database — for example, `no such column: <table>.<column>` when a column was dropped in this release.


Because pgAdmin's migrations are forward-only with single-step destructive operations (a column dropped in release N+1 is gone immediately, not after a deprecation cycle), there is no safe way for an N-version pod to keep serving against a migrated N+1 schema. Set the deployment strategy to `Recreate`, which terminates the old pod *before* starting the new one:

```
spec:
  strategy:
    type: Recreate   # not RollingUpdate
```

The trade-off is a few seconds of downtime during each upgrade, in exchange for not serving traffic from a pod whose ORM is misaligned with the database schema underneath it. This is the supported upgrade strategy for pgAdmin K8s deployments today.

1.2 Login Page

Use the *Login* page to log in to pgAdmin:



Use the fields in the *Login* page to authenticate your connection. There are two ways to authenticate your connection:


- From pgAdmin version 4.21 onwards, support for LDAP authentication has been added. If LDAP authentication has been enabled for your pgAdmin application, you can use your LDAP credentials to log in to pgAdmin:
  - Provide the LDAP username in the *Email Address/Username* field.
  - Provide your LDAP password in the Password field.
- Alternatively, you can use the following information to log in to pgAdmin:
  - Provide the email address associated with your account in the *Email Address/Username* field.
  - Provide your password in the *Password* field.

Click the *Login* button to securely log into pgAdmin.

Please note that if the pgAdmin server is restarted, then you will be logged out. You need to re-login to continue.

1.2.1 Recovering a Lost Password

If you cannot supply your password, click the *Forgotten your password?* button to launch a password recovery utility.



- Provide the email address associated with your account in the *Email Address* field.
- Click the *Recover Password* button to initiate recovery. An email, with directions on how to reset a password, will be sent to the address entered in the *Email Address* field.

If you have forgotten the email associated with your account, please contact your administrator.

Password recovery works only for accounts using the `INTERNAL` authentication source, which are the only accounts whose password pgAdmin holds. Recovery looks up the email address you enter and acts on the `INTERNAL` account that has it: if one exists, reset instructions are sent for that account. The password of an account authenticated against an external source (`LDAP`, `OAUTH2`, `KERBEROS` or `WEBSERVER`) cannot be recovered here, because it is held by that source; if the email belongs only to such an account, an error asks you to contact that source's administrator. See *Accounts from different authentication sources*.

1.2.2 Avoiding a bruteforce attack

For accounts using the `INTERNAL` authentication source, pgAdmin locks the account after `MAX_LOGIN_ATTEMPTS` consecutive failed logins. The default is 3; set it to zero to disable.

For accounts authenticated against an external identity provider (`LDAP`, `OAUTH2`, `KERBEROS`, `WEBSERVER`), brute-force protection is **not** handled by pgAdmin and `MAX_LOGIN_ATTEMPTS` does not apply. Operators using these sources should:

- Configure account-lockout policy on the upstream provider (for example, Active Directory's account-lockout GPO, OpenLDAP's `ppolicy` overlay, or the OAuth2 provider's rate limits).
- Configure request rate-limiting (for example, `limit_req` in nginx) on the reverse proxy in front of pgAdmin to bound login-attempt volume per source IP.

1.3 Enabling two-factor authentication (2FA)

1.3.1 About two-factor authentication

Two-factor authentication (2FA) is an extra layer of security used when logging into websites or apps. With 2FA, you have to log in with your username and password and provide another form of authentication that only you know or have access to.

1.3.2 Setup two-factor authentication

To set up 2FA for pgAdmin 4, you must configure the Two-factor Authentication settings in *config_local.py* or *config_system.py* (see the *config.py* documentation) on the system where pgAdmin is installed in Server mode. You can copy these settings from *config.py* file and modify the values for the following parameters.

Parameter	Description
MFA_ENABLED	The default value for this parameter is True. To disable 2FA, set the value to *False*
MFA_SUPPORTED_METHODS	Set the authentication methods to be supported e.g. email, authenticator
MFA_EMAIL_SUBJECT	<APP_NAME> - Verification Code e.g. pgAdmin 4 - Verification Code
MFA_EMAIL_CODE_MAX_ATTEMPTS	The number of wrong entries allowed for one emailed verification code, after which the code is discarded and a new one must be sent. The default value is 5. Values below 1 are treated as 1.
MFA_FORCE_REGISTRATION	Force the user to configure the authentication method on login (if no authentication is already configured).

NOTE: You must set the 'Mail server settings' in config_local.py or config_system.py in order to use 'email' as two-factor authentication method (see the config.py documentation).

1.3.3 Configure two-factor authentication

To configure 2FA for a user, you must click on 'Two-factor Authentication' in the *User* menu in right-top corner. It will list down all the supported multi factor authentication methods. Click on 'Setup' of one of those methods and follow the steps for each authentication method. You will see the *Delete* button for the authentication method, which is already been configured. Clicking on *Delete* button will deregister the authentication method for the current user.



You can also force users to configure the two-factor authentication methods on login by setting *MFA_FORCE_REGISTRATION* parameter to *True*.

1.4 User Management


When invoking pgAdmin in desktop mode, a password is randomly generated, and then ignored. If you install pgAdmin in server mode, you will be prompted for an administrator email and password for the pgAdmin client.

When you authenticate with pgAdmin, the server definitions associated with that login role are made available in the tree control.

1.4.1 Users Tab


An administrative user can use the *Users* tab to:

- manage pgAdmin users
- change users role
- change password for a user
- deactivate user
- unlock a locked user



Use the *Search* field to specify a criteria and review a list of users that matches with the specified criteria. You can enter a value that matches the following criteria types: *Authentication source*, *Username*, or *Email*. For example, you can enter *ldap* in the search box and only the records having *ldap* as authentication source will be displayed in the *User Management* table.

To add a user, click the Add (+) button at the top left corner. It will open a dialog where you can fill in details for the new user.



Provide information about the new pgAdmin role in the row:

- Use the *Authentication source* field to select the type of authentication that should be used for the user. If authentication source in the pgAdmin server config has 'internal' only then *Authentication source* field will be disabled. Supported *Authentication source* are internal, ldap, kerberos, oauth2 and webserver.
- Use the *Username* field to provide a username for the user. This field is enabled only when you select authentication source except *internal*. If you select *internal* as authentication source, your email address will be taken as the username.

- Use the *Email* field to provide an email address for the user. Email is a mandatory field for authentication source *internal*.
- **Use the *Role* field to select whether a user is an *Administrator* or a *User*.**
  - Select *Administrator* if the user will have administrative privileges within the pgAdmin client.
  - Select *User* to create a non-administrative user account.
- Use the *Active* switch to enable or disable account activity without deleting an account; by default it is enabled.
- Use the *New password* field to provide the password associated with the user specified in the *Email* field. This field is disabled if you select any authentication source except *internal*.
- Re-enter the password in the *Confirm password* field. This field is disabled if you select any authentication source except *internal*.
- *Locked* switch cannot be changed if is turned off. It can only be changed when the user is locked by trying unsuccessful login attempts. Turn off the switch if you want to unlock the account.

To discard a user, and revoke access to pgAdmin, click the trash icon to the left of the row and confirm deletion in the *Delete user?* dialog. If the user has created some shared servers, then the *Change Ownership* dialog will appear to change the ownership of a shared server.


Users with the *Administrator* role are able to add, edit and remove pgAdmin users, but otherwise have the same capabilities as those with the *User* role.

- Click the *Refresh* button to get latest users list.
- Click the *Help* button (?) to access online help.

1.4.2 Roles Tab


An administrative user can use the *Roles* tab to:

- manage pgAdmin roles
- delete roles



Use the *Search* field to specify criteria and review a list of roles that match the specified criteria. You can enter a value that matches the following criteria types: *Role Name* or *Description*.

To add a role, click the Add (+) button at the top left corner. It will open a dialog where you can fill in details for the new role.



Provide information about the new pgAdmin role in the row:

- Use the *Name* field to specify a unique name for the role.
- Use the *Description* field to provide a brief description of the role.


To delete a role, click the trash icon to the left of the row and confirm deletion in the *Delete role?* dialog. If the role is associated with any users or resources, you may need to reassign those associations before deletion.

Roles allow administrators to group privileges and assign them to users more efficiently. This helps in managing permissions and access control within the pgAdmin client.

- Click the *Refresh* button to get the latest roles list.
- Click the *Help* button (?) to access online help.

1.4.3 Permissions Tab

An administrative user can use the *Permissions* tab to manage pgAdmin permissions for a role.



- Filter permissions using the *Search* field by entering names that match the list.
- Administrators can select permissions from the list of available permissions, and choose to grant or revoke these permissions for specific roles.
- The permissions are applied to the selected role immediately.

Accounts from different authentication sources

pgAdmin treats accounts from different authentication sources as separate accounts, even when they share a username or an email address. Each has its own role, settings and servers:

- A user authenticated by LDAP, Kerberos, OAuth2 or webserver authentication is only ever logged in to the account with their username *and* that authentication source, never to an account from another source with the same username. If there is no such account, and the source does not create one automatically, the login fails; pgAdmin does not log the user in to an account from another source instead.
- An internal login is checked against, and logs in, only the `INTERNAL` account.

- Only an `INTERNAL` account has a password, so *Forgotten your password?* resets only the `INTERNAL` account with the email address given.

The account-lockout setting *MAX_LOGIN_ATTEMPTS* applies only to `INTERNAL` accounts. pgAdmin never locks an account from another authentication source; brute-force protection for those is the responsibility of the directory, identity provider or reverse proxy. When `INTERNAL` and another source are both enabled, a sign-in that fails overall and was tried against an `INTERNAL` account with that username counts towards its lockout; the attempt that reaches the limit reports that the account is now locked. A locked `INTERNAL` account stops only internal sign-in: a user of another source with the same username can still sign in. On a later sign-in with that username, pgAdmin discloses that the `INTERNAL` account is locked only when internal is the only source able to check the password; while another password source such as LDAP is also eligible, it shows a generic failure instead.

The administrator account created when pgAdmin is first set up always uses the `INTERNAL` authentication source. It remains in the pgAdmin database when *AUTHENTICATION_SOURCES* does not include *internal*, although it can then no longer be used to log in. If you use external authentication only, create an administrator account for that source, for example for LDAP:

```
/path/to/python /path/to/setup.py add-external-user ldapuser --auth-source ldap --admin
```

and then deactivate the initial `INTERNAL` administrator account, so that it cannot be used if internal authentication is enabled again later:

```
/path/to/python /path/to/setup.py update-user admin@example.com --inactive
```

Using 'setup.py' command line script

Note

To manage users using `setup.py` script, you must use the Python interpreter that is normally used to run pgAdmin to ensure that the required Python packages are available. In most packages, this can be found in the Python Virtual Environment that can be found in the installation directory. When using platform-native packages, the system installation of Python may be the one used by pgAdmin.

When using PIP wheel package to install pgadmin, all the commands can be used without Python interpreter.

Some of the examples: pgadmin4-cli add-user user1@gmail.com password –role User pgadmin4-cli get-prefs

1.4.4 Manage Users

1.4.5 Add User

To add user, invoke `setup.py` with `add-user` command line option, followed by email and password. role and active will be optional fields. When no role is given, the user is created with the *User* role.

```
/path/to/python /path/to/setup.py add-user user1@gmail.com password

# to specify a role, either you can use --admin for Administrator role or provide the
# role using --role. If both are provided --admin will be used:

/path/to/python /path/to/setup.py add-user user1@gmail.com password --admin
/path/to/python /path/to/setup.py add-user user1@gmail.com password --role User

# to specify user's status
```

(continues on next page)

(continued from previous page)

```
/path/to/python /path/to/setup.py add-user user1@gmail.com password --active
/path/to/python /path/to/setup.py add-user user1@gmail.com password --inactive
```

1.4.6 Add External User

To add external authentication user, invoke `setup.py` with `add-external-user` command line option, followed by username, and the authentication source with `--auth-source` (*oauth2* if it is not given). email, role and status will be optional fields. When no role is given, the user is created with the *User* role.

```
/path/to/python /path/to/setup.py add-external-user user1@gmail.com --auth-source ldap

# to specify an email:

/path/to/python /path/to/setup.py add-external-user ldapuser --auth-source ldap --email␣
↪user1@gmail.com

# to specify a role, either you can use --admin for Administrator role or provide the
# role using --role. If both are provided --admin will be used:

/path/to/python /path/to/setup.py add-external-user ldapuser --auth-source ldap --admin
/path/to/python /path/to/setup.py add-external-user ldapuser --auth-source ldap --role␣
↪User

# to specify user's status

/path/to/python /path/to/setup.py add-external-user user1@gmail.com --auth-source ldap --
↪active
/path/to/python /path/to/setup.py add-external-user user1@gmail.com --auth-source ldap --
↪inactive
```

1.4.7 Update User

To update user, invoke `setup.py` with `update-user` command line option, followed by email address. password, role and active are updatable fields.

```
/path/to/python /path/to/setup.py update-user user1@gmail.com --password new-password

# to specify a role, either you can use --admin for Administrator role or provide the
# role using --role. If both are provided --admin will be used:

/path/to/python /path/to/setup.py update-user user1@gmail.com --admin
/path/to/python /path/to/setup.py update-user user1@gmail.com --role User

# to specify user's status

/path/to/python /path/to/setup.py update-user user1@gmail.com --active
/path/to/python /path/to/setup.py update-user user1@gmail.com --inactive
```

1.4.8 Update External User

To update the external user, invoke `setup.py` with `update-external-user` command line option, followed by username, and the authentication source with `--auth-source` (*oauth2* if it is not given). email, role and active are updatable fields.

```
# to change email address:

/path/to/python /path/to/setup.py update-external-user ldapuser --auth-source ldap --
↪email newemail@gmail.com

# to specify a role, either you can use --admin for Administrator role or provide the
# role using --role. If both are provided --admin will be used:

/path/to/python /path/to/setup.py update-external-user ldapuser --auth-source ldap --
↪admin
/path/to/python /path/to/setup.py update-external-user ldapuser --auth-source ldap --
↪role User

# to change user's status

/path/to/python /path/to/setup.py update-external-user ldapuser --auth-source ldap --
↪active
/path/to/python /path/to/setup.py update-external-user ldapuser --auth-source ldap --
↪inactive
```

1.4.9 Delete User

To delete the user, invoke `setup.py` with `delete-user` command line option, followed by username and auth_source. For Internal users, email address will be used instead of username. the option `--yes` is available to skip the confirmation prompt before deleting the user.

```
/path/to/python /path/to/setup.py delete-user user1@gmail.com --auth-source internal
/path/to/python /path/to/setup.py delete-user user2@gmail.com --auth-source internal --
↪yes
/path/to/python /path/to/setup.py delete-user ldapuser --auth-source ldap
```

1.4.10 Get User

To get the user details, invoke `setup.py` with `get-users` command line option, followed by username/email address.

```
# to list all the users:
/path/to/python /path/to/setup.py get-users

# to get the user's details:
/path/to/python /path/to/setup.py get-users --username user1@gmail.com
```

1.4.11 Load Users

To bulk import users from a JSON file, invoke `setup.py` with `load-users` command line option, followed by the path to the JSON file.

```
/path/to/python /path/to/setup.py load-users /path/to/users.json
```

JSON File Format

The input JSON file must contain a `users` array with user objects:

```
{
    "users": [
        {
            "username": "admin@example.com",
            "email": "admin@example.com",
            "password": "securepassword",
            "role": "Administrator",
            "active": true,
            "auth_source": "internal"
        },
        {
            "username": "ldap_user",
            "email": "ldap_user@example.com",
            "role": "User",
            "active": true,
            "auth_source": "ldap"
        }
    ]
}
```

The command handles errors gracefully:

- Users that already exist are skipped
- Invalid roles are reported and skipped
- Missing passwords for internal auth are reported and skipped
- Passwords shorter than 6 characters are reported and skipped


1.4.12 Output

Each command output can be seen in the json format too by adding –json command line option.

1.5 Change Ownership Dialog


Use the *Change Ownership* dialog to change the ownership of the shared servers. This dialog will appear if a user has been deleted from *User Management* and owned some shared servers.

Choose the user who will own the shared servers from the drop-down.



Click the *Change* button to change the ownership.

The shared servers owned by the user will be deleted if the user is not selected from the drop-down.



Click the *Change* button to change the ownership; click *Close* to exit the dialog.


1.6 Change pgAdmin Password Dialog

It is a good policy to routinely change your password to protect data, even in what you may consider a 'safe' environment. In the workplace, failure to apply an appropriate password policy could leave you in breach of Data Protection laws.

Please consider the following guidelines when selecting a password:

- Ensure that your password is an adequate length; 6 characters should be the absolute minimum number of characters in the password.
- The minimum password length is set by default to six characters. This value can be changed by setting the *PASSWORD_LENGTH_MIN* option to desired length in pgAdmin configuration; see *Configuration Files* for more information.
- Ensure that your password is not open to dictionary attacks. Use a mixture of upper and lower case letters and numerics, and avoid words or names. Consider using the first letter from each word in a phrase that you will remember easily but is an unfamiliar acronym.
- Ensure that your password is changed regularly; at minimum, change it every ninety days.

The guidelines above should be considered a starting point: They are not a comprehensive list and they **will not guarantee security**.



Use the *Change pgAdmin Password* dialog to change the password you use to log in to pgAdmin itself, rather than the password of a database server connection:

- Enter your existing password in the *Current Password* field.
- Enter the desired password for in the *New Password* field.
- Re-enter the new password in the *Confirm Password* field.

Click the *Change* button to change your password; click *Close* to exit the dialog.

Changing your password signs out all of your other active sessions, so anyone using your account elsewhere must sign in again with the new password. The session you change it in stays signed in. When an administrator resets your password from the *User Management* page, all of your sessions are signed out.

1.7 Lock/Restore Account

Account locking/unlocking via user management dialog:

An admin can lock and unlock user from the user management dialog. This allows the admin to lock or restore the user when there are several failed login attempts. This page guides you through configuring per-user locking/restoring. For more details visit *User management*.

Parameter	Description
MAX_LOGIN_ATTEMPTS	Which sets the number of failed login that are allowed. If this value is exceeded, the account is locked and can be reset by an administrator. By setting the variable to the value zero this feature is deactivated.

When Administrator itself gets locked, following steps may be considered to restore it:

- Increase MAX_LOGIN_ATTEMPTS, and try to successfully login to restore the account.

OR

By updating configuration database

SQLite DB (pgAdmin4.db):

- Locate the pgAdmin4.db file and open it using any DB Browser (or DB Browser for SQLite)
- After opening the DB file, head towards 'Execute SQL' section.
- Run below query -

UPDATE USER SET LOCKED = false, LOGIN_ATTEMPTS = 0 WHERE USERNAME = <YOUR_EMAIL_ID>

External database:

- Connect to the database.
- Run below query -

UPDATE USER SET LOCKED = false, LOGIN_ATTEMPTS = 0 WHERE USERNAME = <YOUR_EMAIL_ID>

- Make sure the query changes are committed.

Account locking by failed login attempts:



pgAdmin application is configured to lock a user account when a number of consecutive failed login attempts are exceeded.

MAX_LOGIN_ATTEMPTS is defaulted to 3 unsuccessful login attempts, after which the account would be locked.

The only way to restore the user account is by contacting the Administrator and ask to unlock it.

1.8 Enabling LDAP Authentication

To enable LDAP authentication for pgAdmin, you must configure the LDAP settings in the *config_local.py* or *config_system.py* file (see the *config.py* documentation) on the system where pgAdmin is installed in Server mode. You can copy these settings from *config.py* file and modify the values for the following parameters:

There are 3 ways to configure LDAP:

- Bind as pgAdmin user
- Anonymous bind
- Dedicated user bind

Parameter	Description
AUTHENTICATION_SOURCES	The default value for this parameter is *internal*. To enable LDAP authentication, you must include *ldap* in the list of values for this parameter. you can modify the value as follows: • ['ldap']: pgAdmin will use only LDAP authentication. • ['ldap', 'internal']: pgAdmin will first try to authenticate the user through LDAP. If that authentication fails, then internal user entries of pgAdmin will be used for authentication. • ['internal', 'ldap']: pgAdmin will first try to authenticate the user through internal user entries. If that authentication fails, then LDAP authentication will be used.

continues on next page

Table 5 – continued from previous page

Parameter	Description
LDAP_AUTO_CREATE_USER	Specifies if you want to automatically create a pgAdmin user corresponding to the LDAP user credentials. Please note that LDAP password is not stored in the pgAdmin database.
LDAP_CONNECTION_TIMEOUT	Specifies the connection timeout (in seconds) for LDAP authentication.
LDAP_SERVER_URI	An LDAP URI is a combination of connection protocol (ldap or ldaps), IP address/hostname and port of the directory server that you want to connect to. For example, 'ldap://172.16.209.35:389' is a valid LDAP_SERVER_URI where ldap is the connection protocol, 172.16.209.35 is the IP address and 389 is the port. Port 636 is used for the ldaps communication protocol.
LDAP_USERNAME_ATTRIBUTE	Specifies the LDAP attribute that contains the usernames. For LDAP authentication, you need to enter the value of that particular attribute as username. For example, if you set the value of LDAP_USERNAME_ATTRIBUTE as 'cn' and you have defined 'cn=admin' in your LDAP server entries, you should be able to authenticate by entering 'admin' in the *Email Address / Username* field and its corresponding password in the *Password* field.
LDAP_SEARCH_BASE_DN	Specifies the distinguished name (DN) for the top-most user directory that you want to search. You can use this parameter for limiting the search request to a specific group of users. For example, if you want to search only within the Organizational Unit named sales, you can define the value for LDAP_SEARCH_BASE_DN parameter as following: LDAP_SEARCH_BASE_DN = 'ou=sales,dc=example,dc=com' This is an optional parameter only while binding as pgAdmin user. If you do not specify any value for LDAP_SEARCH_BASE_DN, then the value for LDAP_BASE_DN will be considered for the same.
LDAP_SEARCH_FILTER	Defines the criteria to retrieve matching entries in an LDAP search request. For example, LDAP_SEARCH_FILTER = '(objectclass=HR)' setting searches only for users having HR as their objectClass attribute.
LDAP_SEARCH_SCOPE	Indicates the set of entries at or below the Base DN that maybe considered as potential matches for a search request. You can specify the scope of a search as either a *base*, *level*, or *subtree* search. A *base* search limits the search to the base object. A *level* search is restricted to the immediate children of a base object, but excludes the base object itself. A *subtree* search includes all child objects as well as the base object.
LDAP_DN_CASE_SENSITIVE	Indicates whether the DN (Distinguished Names) are case sensitive or not. Possible values are True or False. By default is set to False.
LDAP_USE_STARTTLS	Specifies if you want to use Transport Layer Security (TLS) for secure communication between LDAP clients and LDAP servers. If you specify the connection protocol in *LDAP_SERVER_URI* as *ldaps*, this parameter is ignored.
LDAP_CA_CERT_FILE	Specifies the path to the trusted CA certificate file. This parameter is applicable only if you are using *ldaps* as connection protocol or you have set *LDAP_USE_STARTTLS* parameter to *True*.
LDAP_CERT_FILE	Specifies the path to the server certificate file. This parameter is applicable only if you are using *ldaps* as connection protocol or you have set *LDAP_USE_STARTTLS* parameter to *True*.

continues on next page

Table 5 – continued from previous page

Parameter	Description
LDAP_KEY_FILE	Specifies the path to the server private key file. This parameter is applicable only if you are using *ldaps* as connection protocol or you have set *LDAP_USE_STARTTLS* parameter to *True*.
LDAP_CERT_VALIDATE	Set this parameter to *False* if you want to bypass the TLS certificate validation. By default it is set to True.
LDAP_IGNORE_MALFORMED_SCHEM	Some flaky LDAP servers returns malformed schema. If this parameter set to *True*, no exception will be raised and schema is thrown away but authentication will be done. This parameter should remain False, as recommended.
Bind as pgAdmin user	
LDAP_BASE_DN	Specifies the base DN from where a server will start the search for users. For example, an LDAP search for any user will be performed by the server starting at the base DN (dc=example,dc=com). When the base DN matches, the full DN (cn=admin,dc=example,dc=com) is used to bind with the supplied password.
Anonymous bind	
LDAP_ANONYMOUS_BIND	Set this parameter to *True* for anonymous binding. After the connection is made, the pgadmin login user will be further authenticated by the username and password provided at the login screen.
Dedicated user bind	
LDAP_BIND_USER	The account of the user to log in for simple bind. Set this parameter to allow the connection to bind using a dedicated user. After the connection is made, the pgadmin login user will be further authenticated by the username and password provided at the login screen. at the login screen.
LDAP_BIND_PASSWORD	Password for simple bind. Specify the value if you have set the LDAP_BIND_USER parameter.

1.8.1 Brute-force protection

pgAdmin's built-in account-lockout setting (`MAX_LOGIN_ATTEMPTS`) applies only to accounts using the `INTERNAL` authentication source. It does **not** rate-limit or lock LDAP-authenticated logins.

When LDAP authentication is enabled, brute-force protection for LDAP credentials is the responsibility of:

- **The directory.** Configure account-lockout policy on the LDAP server itself (for example, OpenLDAP's `ppolicy` overlay, Active Directory's account-lockout GPO, or the equivalent on FreeIPA / 389 Directory Server). The directory is the credential authority and is the correct place to enforce per-account lockout.
- **The reverse proxy or WAF in front of pgAdmin.** Configure request-rate limiting on the login endpoint (for example, `limit_req` in nginx, `stick-table` rules in HAProxy, or the equivalent in your WAF) to bound login-attempt volume per source IP. This is independent of pgAdmin and protects against attackers who would otherwise reach the LDAP server through pgAdmin.

See *Avoiding a bruteforce attack* for the equivalent note on the login page.

1.8.2 Internal accounts

pgAdmin treats accounts from different authentication sources as separate accounts, even when they share a username. An LDAP user is only ever logged in to the LDAP account with that username, and never to an `INTERNAL` account with the same name, so each account keeps its own role and settings.

The administrator account created when pgAdmin is first set up always uses the `INTERNAL` authentication source. It remains in the pgAdmin database when *AUTHENTICATION_SOURCES* is set to *['ldap']*, although it can then no longer be used to log in. If you use LDAP authentication only, create an LDAP administrator account, for example:

```
/path/to/python /path/to/setup.py add-external-user ldapuser --auth-source ldap --admin
```

and then deactivate the initial `INTERNAL` administrator account so that it cannot be used if internal authentication is enabled again later:

```
/path/to/python /path/to/setup.py update-user admin@example.com --inactive
```

When both *internal* and *ldap* are listed in *AUTHENTICATION_SOURCES*, a username and password entered on the login page are tried against each source in turn, in the order they are listed, and the first source that accepts the password signs the user in; the sources listed after it are not tried. Every source listed before it is still tried, so the password is a failed attempt at each of those. If the same username exists as both an internal and an LDAP account, a wrong password sent to the directory is a failed LDAP bind that counts towards the directory's lockout, even when a source listed later (such as the internal account) then accepts the sign-in. pgAdmin's own lockout counter for the internal account increases only when the sign-in fails at every source. Avoid giving an internal and an LDAP account the same username.

When *LDAP_DN_CASE_SENSITIVE* is off, names that differ only in case are the same login. Do not create two accounts whose usernames differ only in case; pgAdmin cannot tell which one a sign-in is for.

See *Accounts from different authentication sources* and *User Management* for more information on the `setup.py` user management commands.

1.9 Enabling Kerberos Authentication

Prerequisite: Kerberos understanding and setup

Reference: https://web.mit.edu/kerberos/

To configure Kerberos authentication, you must setup your Kerberos Server and obtain a ticket on the client using *kinit*.

Note: Active Directory users with Kerberos support do not require kinit.

To enable Kerberos authentication for pgAdmin, you must configure the Kerberos settings in *config_local.py* or *config_system.py* (see the *config.py* documentation) on the system where pgAdmin is installed in Server mode. You can copy these settings from *config.py* file and modify the values for the following parameters.

Parameter	Description
AUTHENTICATION_SOURCES	The default value for this parameter is *internal*. To enable Kerberos authentication, you must include *kerberos* in the list of values for this parameter. you can modify the value as follows: • ['kerberos']: pgAdmin will use only Kerberos authentication. • ['kerberos', 'internal']: pgAdmin will first try to authenticate the user through kerberos. If that authentication fails, then it will return back to the login page where you need to provide internal pgAdmin user credentials for authentication.
KRB_AUTO_CREATE_USER	Set the value to *True* if you want to automatically create a pgAdmin user corresponding to a successfully authenticated Kerberos user. Please note that password is not stored in the pgAdmin database.
KRB_APP_HOST_NAME	Specify the name of *pgAdmin webserver hostname*. Please note that if it is not set, it will take the value of *default_server* parameter.

1.9.1 Keytab file for HTTP Service

- Generate the *Keytab* file for the HTTP service principal HTTP/<host-name>@realm, and copy it to the *pgAdmin* webserver machine. Ensure that the operating system user owning the *pgAdmin* webserver is the owner of this file and should be accessible by that user.
- Please note that either you should set *default_keytab_name* parameter in *krb5.conf* file or the environment variable *KRB5_KTNAME*. If not set then explicitly set *KRB_KTNAME* to the location of your *Keytab* file in the *config_local.py* or *config_system.py* file.

1.9.2 Apache HTTPD Configuration

If the *pgAdmin* server is under the Apache Server, then you need to add the following parameters in *Directory* directive of *Apache HTTPD Configuration*:

- WSGIScriptReloading On
- WSGIPassAuthorization On

1.9.3 Browser settings to configure Kerberos Authentication

You need to configure the browser settings on the client machine to use Kerberos authentication via *SPNEGO*.

- For Mozilla Firefox
  - Open the low level Firefox configuration page by entering *about:config* in the address bar.
  - In the Search text box, enter: *network.negotiate-auth.trusted-uris*
  - Double-click the *network.negotiate-auth.trusted-uris* preference and enter the hostname or the domain of the web server that is protected by Kerberos HTTP SPNEGO. Separate multiple domains and hostnames with a comma.
  - Click OK.
- For Google Chrome
  - On Windows:
    - Open the Control Panel to access the Internet Options dialog.

    * Select the Security tab.
    * Select the Local Intranet zone and click the Sites button.
    * Make sure that the first two options, *Include all local (intranet) sites not listed in other zones* and *Include all sites that bypass the proxy server* are checked.
    * Click Advanced and add the names of the domains that are protected by Kerberos HTTP SPNEGO, one at a time, to the list of websites. For example, myhost.example.com. Click Close.
    * Click OK to save your configuration changes.
  - On Linux or macOS:
    * Add the *–auth-server-whitelist* parameter to the google-chrome command. For example, to run Chrome from a Linux prompt, run the google-chrome command as follows:

```
google-chrome --auth-server-whitelist = "hostname/domain"
```

1.9.4 PostgreSQL Server settings to configure Kerberos Authentication

- To connect the PostgreSQL server with Kerberos authentication, GSSAPI support has to be enabled when PostgreSQL is built and the necessary configuration has to be in place.
- In pgAdmin you need to enable Kerberos authentication for the PostgreSQL server by setting "Kerberos authentication" flag to True in the Server dialog. Once it is enabled, pgAdmin will not prompt for a password and will try to connect to the PostgreSQL server using Kerberos.
- Note that, you have to login into pgAdmin with Kerberos authentication to then connect to PostgreSQL using Kerberos.
- In server mode, the only Kerberos credentials used to connect to a PostgreSQL server are those delegated by a user who logged in to pgAdmin with Kerberos, and only for a server with "Kerberos authentication" enabled. The default credential cache and client keytab of the operating system account that pgAdmin runs as are never used, so a user cannot connect to a server with that account's Kerberos identity.
- To enforce this for Windows SSPI, which uses the logon of the account pgAdmin runs as, and for gssproxy, which environment variables do not stop, in server mode pgAdmin also tells libpq what to use and what to refuse.
  - For a Kerberos-login user's connection to a server with Kerberos authentication enabled, pgAdmin forces `gsslib=gssapi`, replacing any `gsslib` the user set. Without it, a libpq built with both GSSAPI and SSPI answers the server's request with SSPI, which uses the Windows logon of the account pgAdmin runs as and ignores the delegated credentials, whereas `gsslib=gssapi` makes libpq use the delegated credential cache. This helps only with a Windows libpq build that includes both GSSAPI and SSPI, as pgAdmin's Windows packages do. With libpq 16 or later, SSPI is also refused with `require_auth=!sspi`; with an older libpq it is not refused.
  - Every other connection uses `require_auth=!gss,!sspi` and `gssencmode=disable`, merged with the server's own "Require authentication" (`require_auth`) parameter. A server whose `require_auth` allows only `gss` can be used only by a Kerberos-login user connecting to a server with Kerberos authentication enabled, and one that allows only `sspi` cannot be used in server mode.
  - The `require_auth` protection needs libpq 16 or later in pgAdmin. Without it only the `KRB5CCNAME` and `KRB5_CLIENT_KTNAME` isolation applies to connections that may not use Kerberos, which does not cover Windows SSPI or gssproxy. `gssencmode` needs libpq 12 or later; `gsslib` is known to every libpq that pgAdmin supports.
  - psql and the utilities (such as pg_dump) get no `require_auth` in their connection string unless the user set one for the server, which is then merged as above. Their protection is the `PGREQUIREAUTH`, `PGGSSENCMODE`

and PGGSSLIB environment variables. Only a libpq 16 or later in the utility honours PGREQUIREAUTH; an older one ignores it silently.

- A service file entry's settings take precedence over these environment variables for psql and the utilities, whereas pgAdmin's own connections are not affected, because their connection string takes precedence over the service file. Only a service listed in SERVER_MODE_ALLOWED_SERVICES can be used in server mode, so only an entry the administrator has written can do this. Do not set require_auth, gssencmode or gsslib in such an entry unless every pgAdmin user may use what it allows: the KRB5CCNAME and KRB5_CLIENT_KTNAME isolation cannot be overridden by a service file, but require_auth and gsslib in a listed service can re-enable Windows SSPI or gssproxy for the utilities.

1.9.5 Accounts

A Kerberos user is only ever logged in to the Kerberos account whose username is their principal (for example *user@EXAMPLE.COM*), never to an INTERNAL or other account with the same username. If there is no such Kerberos account and *KRB_AUTO_CREATE_USER* is *False*, the login fails.

The administrator account created when pgAdmin is first set up is an INTERNAL account. If you use Kerberos authentication only, create a Kerberos administrator account and deactivate the initial one:

```
/path/to/python /path/to/setup.py add-external-user user@EXAMPLE.COM --auth-source␣
↪kerberos --admin
/path/to/python /path/to/setup.py update-user admin@example.com --inactive
```

See *Accounts from different authentication sources* for more information.

1.9.6 Master Password

In the multi user mode, pgAdmin uses user's login password to encrypt/decrypt the PostgreSQL server password. In the Kerberos authentication, the pgAdmin user does not have the password, so we need an encryption key to store the PostgreSQL server password for the servers which are not configured to use the Kerberos authentication. To accomplish this, set the configuration parameter MASTER_PASSWORD to *True*, so upon setting the master password, it will be used as an encryption key while storing the password. If it is False, the server password can not be stored.

1.10 Enabling OAUTH2 and OIDC Authentication

To enable OAUTH2 or OpenID Connect (OIDC) authentication for pgAdmin, you must configure the OAUTH2 settings in the *config_local.py* or *config_system.py* file (see the *config.py* documentation) on the system where pgAdmin is installed in Server mode. You can copy these settings from *config.py* file and modify the values for the following parameters.

Warning

pgAdmin reads OAuth2 provider settings **only** from the OAUTH2_CONFIG list; each provider is a single dictionary entry within that list. Settings such as OAUTH2_CLIENT_ID or OAUTH2_SSL_CERT_VERIFICATION defined at the top level of the configuration are ignored.

This matters in container deployments. Although most options can be set with an individual PGADMIN_CONFIG_<KEY> environment variable, OAuth2 is the exception: individual variables such as

PGADMIN_CONFIG_OAUTH2_CLIENT_ID or PGADMIN_CONFIG_OAUTH2_SSL_CERT_VERIFICATION will **not** configure a provider. Instead, configure the whole provider list through a single PGADMIN_CONFIG_OAUTH2_CONFIG variable, for example:

```
PGADMIN_CONFIG_OAUTH2_CONFIG="[{'OAUTH2_NAME': 'my-provider', 'OAUTH2_DISPLAY_NAME':
↪'My Provider', 'OAUTH2_CLIENT_ID': '...', 'OAUTH2_CLIENT_SECRET': '...', 'OAUTH2_
↪SERVER_METADATA_URL': 'https://provider.example.com/.well-known/openid-configuration
↪', 'OAUTH2_SCOPE': 'openid email profile', 'OAUTH2_SSL_CERT_VERIFICATION': False}]"
```

If pgAdmin detects per-provider OAuth2 settings at the top level while no provider is configured in OAUTH2_CONFIG, it logs a warning at startup to highlight the misconfiguration.

1.10.1 OAuth2 vs OpenID Connect (OIDC)

pgAdmin supports both OAuth2 and OIDC authentication protocols:

OAuth2 is an authorization framework that allows third-party applications to obtain limited access to user accounts. When using OAuth2, pgAdmin must explicitly call the provider's userinfo endpoint to retrieve user profile information.

OpenID Connect (OIDC) is an identity layer built on top of OAuth2 that provides standardized user authentication and profile information. When using OIDC, user identity information is included directly in the ID token, which is more efficient and secure.

Note

When **OAUTH2_SERVER_METADATA_URL** is configured, pgAdmin treats the provider as an OIDC provider and will:

- Use ID token claims for user identity (sub, email, preferred_username)
- Skip the userinfo endpoint call when ID token contains sufficient information
- Validate the ID token automatically using the provider's public keys

This is the **recommended approach** for modern identity providers like Microsoft Entra ID (Azure AD), Google, Keycloak, Auth0, and Okta.

Parameter	Description
AUTHENTICATION_SOURCES	The default value for this parameter is *internal*. To enable OAUTH2 authentication, you must include *oauth2* in the list of values for this parameter. You can modify the value as follows: • ['oauth2', 'internal']: pgAdmin will display an additional button for authenticating with oauth2
OAUTH2_NAME	The name of the Oauth2 provider, ex: Google, Github
OAUTH2_DISPLAY_NAME	Oauth2 display name in pgAdmin
OAUTH2_CLIENT_ID	Oauth2 Client ID
OAUTH2_CLIENT_SECRET	Oauth2 Client Secret. **Optional for public clients using Authorization Code + PKCE**. For confidential clients (server-side apps), keep this set. For public clients (no secret), pgAdmin will enforce PKCE and perform an unauthenticated token exchange.

continues on next page

Table 7 – continued from previous page

Parameter	Description
OAUTH2_CLIENT_AUTH_METHOD	Client authentication method for the token endpoint. Default behavior uses *OAUTH2_CLIENT_SECRET* (confidential client), or PKCE when no secret is provided (public client). Set to *workload_identity* to authenticate using an Azure Entra ID workload identity (federated credential) without a client secret.
OAUTH2_WORKLOAD_IDENTITY_TOK	When **OAUTH2_CLIENT_AUTH_METHOD** is *workload_identity*, path to the projected OIDC token file (Kubernetes service account JWT). This file must exist at pgAdmin startup.
OAUTH2_TOKEN_URL	Oauth2 Access Token endpoint
OAUTH2_AUTHORIZATION_URL	Endpoint for user authorization
OAUTH2_SERVER_METADATA_URL	**OIDC Discovery URL** (recommended for OIDC providers). When set, pgAdmin will use OIDC flow with automatic ID token validation and user claims from the ID token. Example: *https://login.microsoftonline.com/{tenant}/v2.0/.well-known/openid-configuration*. When using this parameter, OAUTH2_TOKEN_URL and OAUTH2_AUTHORIZATION_URL are optional as they will be discovered automatically.
OAUTH2_API_BASE_URL	Oauth2 base URL endpoint to make requests simple, ex: *https://api.github.com/*
OAUTH2_USERINFO_ENDPOINT	User Endpoint, ex: *user* (for github, or *user/emails* if the user's email address is private) and *userinfo* (for google). **For OIDC providers**, this is optional if the ID token contains sufficient claims (email, preferred_username, or sub).
OAUTH2_SCOPE	Oauth scope, ex: 'openid email profile'. **For OIDC providers**, include 'openid' scope to receive an ID token.
OAUTH2_ICON	The Font Awesome icon to be placed on the oauth2 button. A brand icon name (e.g. fa-github) uses the brands style by default; to use another style, include the style class explicitly (e.g. 'fas fa-key').
OAUTH2_BUTTON_COLOR	Oauth2 button color
OAUTH2_USERNAME_CLAIM	The claim which is used for the username. If the value is empty, **for OIDC providers** pgAdmin will use: 1) email, 2) preferred_username, or 3) sub (in that order). **For OAuth2 providers** without OIDC, email is required. Ex: *oid* (for AzureAD), *email* (for Github), *preferred_username* (for Keycloak)
OAUTH2_AUTO_CREATE_USER	**Set the value to *True* if you want to automatically** create a pgAdmin user corresponding to a successfully authenticated Oauth2 user. Please note that password is not stored in the pgAdmin database.
OAUTH2_AUTO_LOGIN	**Set the value to *True* to send users straight to the OAuth2 provider** instead of showing the pgAdmin login page. This only takes effect when *oauth2* is the only value in AUTHENTICATION_SOURCES and exactly one provider is configured. The default is *False*. See *Skipping the Login Page* below.

continues on next page

Table 7 – continued from previous page

Parameter	Description
OAUTH2_ADDITIONAL_CLAIMS	If a dictionary is provided, pgAdmin will check for a matching key and value on the **ID token first** (for OIDC providers), then fall back to the userinfo endpoint response. In case there is no match with the provided config, the user will receive an authorization error. Useful for checking AzureAD *wids* or *groups*, GitLab *owner*, *maintainer* and *reporter* claims.
OAUTH2_SERVER_GROUP_CLAIM	The name of a claim listing the server groups whose shared servers the user may access. If set, shared servers owned by other users are only visible and accessible if the name of their server group is in the claim. See *Restricting Shared Servers with a Claim* below.
OAUTH2_SERVER_GROUP_CLAIM_MA	An optional dictionary mapping values of the OAUTH2_SERVER_GROUP_CLAIM claim to a server group name or a list of server group names. Values without a mapping are used as server group names unchanged.
OAUTH2_SSL_CERT_VERIFICATION	**Set this variable to False to disable SSL certificate verification for OAuth2 provider.** This may need to set False, in case of self-signed certificates.
OAUTH2_CHALLENGE_METHOD	Enable PKCE workflow. PKCE method name, only *S256* is supported
OAUTH2_RESPONSE_TYPE	Enable PKCE workflow. Mandatory with OAUTH2_CHALLENGE_METHOD, must be set to *code*
OAUTH2_LOGOUT_URL	**The provider's logout endpoint, used to end the user's session with the provider** when they log out of pgAdmin. *{redirect_uri}* and *{id_token}* in the value are replaced with the pgAdmin URL and the user's ID token. Ex: *https://example.com/realms/master/protocol/openid-connect/logout?post_logout_redirect_uri={redirect_uri}&id_token_hint={id_toke* (for Keycloak)

1.10.2 Accounts

An OAuth2 user is only ever logged in to the OAuth2 account whose username is the one resolved from their identity. When *OAUTH2_USERNAME_CLAIM* is set, that claim is used, taken from the ID token if present and otherwise from the userinfo profile. When it is not set, an OIDC provider uses the first of `email`, `preferred_username` or `sub` that is present, and a non-OIDC provider uses the email address. The user is never logged in to an `INTERNAL` or other account with the same username. If there is no such OAuth2 account and *OAUTH2_AUTO_CREATE_USER* is *False*, the login fails. When you provision an administrator account for an OAuth2-only deployment, give it the username your provider resolves to, which may not be the email address.

The administrator account created when pgAdmin is first set up is an `INTERNAL` account. If you use OAuth2 authentication only, create an OAuth2 administrator account and deactivate the initial one:

```
/path/to/python /path/to/setup.py add-external-user user@example.com --auth-source␣
↪oauth2 --admin
/path/to/python /path/to/setup.py update-user admin@example.com --inactive
```

See *Accounts from different authentication sources* for more information.

1.10.3 Redirect URL

The redirect url to configure Oauth2 server is *<http/https>:///<pgAdmin Server URL>/oauth2/authorize* After successful application authorization, the authorization server will redirect the user back to the pgAdmin url specified here. Select https scheme if your pgAdmin server serves over https protocol otherwise select http.

1.10.4 Master Password

In the multi user mode, pgAdmin uses user's login password to encrypt/decrypt the PostgreSQL server password. In the Oauth2 authentication, the pgAdmin does not store the user's password, so we need an encryption key to store the PostgreSQL server password. To accomplish this, set the configuration parameter MASTER_PASSWORD to *True*, so upon setting the master password, it will be used as an encryption key while storing the password. If it is False, the server password can not be stored.

1.10.5 Login Page

After configuration, on restart, you can see the login page with the Oauth2 login button(s).



Skipping the Login Page

If OAuth2 is the only authentication source and a single provider is configured, set OAUTH2_AUTO_LOGIN to *True* to send users straight to the provider rather than showing them the login page with a single button. Note that any LOGIN_BANNER will not be seen in this case.

The login page is still shown after a login fails, so that the error can be read, and after the user logs out, so that they are not logged straight back in by the provider. Setting OAUTH2_LOGOUT_URL for the provider is recommended, so that logging out of pgAdmin also ends the user's session with the provider. To show the login page at any other time, add *?no_auto_login* to its URL, for example *https://pgadmin.example.com/login?no_auto_login*.

1.10.6 PKCE Workflow

Ref: https://oauth.net/2/pkce

To enable PKCE workflow, set the configuration parameters OAUTH2_CHALLENGE_METHOD to *S256* and OAUTH2_RESPONSE_TYPE to *code*. Both parameters are mandatory to enable PKCE workflow.

1.10.7 Public vs Confidential OAuth Clients

OAuth providers support two common client types:

- **Confidential clients** have a client secret and can authenticate to the token endpoint.
- **Public clients** do not have a client secret (or the secret cannot be safely stored).

pgAdmin supports interactive user login for both client types:

- If **OAUTH2_CLIENT_SECRET** is set, pgAdmin treats the provider as a confidential client.
- If **OAUTH2_CLIENT_SECRET** is missing, empty, or set to *None*, pgAdmin treats the provider as a public client and **requires PKCE**.

Note

For public clients, pgAdmin uses Authlib's native behavior to perform an **unauthenticated token exchange** (token endpoint client authentication method: `none`). This is required for Authorization Code + PKCE flows where no client secret is available.

1.10.8 Azure Entra ID Workload Identity (AKS) (No Client Secret)

pgAdmin can authenticate to Microsoft Entra ID (Azure AD) **without a client secret** using an AKS Workload Identity projected service account token (OIDC federated credential).

This is a **confidential client** scenario (server-side app), but client authentication to the token endpoint is performed using a **JWT client assertion**.

Enable workload identity mode

Set the following parameters in your provider configuration:

```
OAUTH2_CONFIG = [{
    'OAUTH2_NAME': 'entra-workload-identity',
    'OAUTH2_DISPLAY_NAME': 'Microsoft Entra ID',
    'OAUTH2_CLIENT_ID': '<Application (client) ID>',
    'OAUTH2_CLIENT_SECRET': None,  # not required
    'OAUTH2_CLIENT_AUTH_METHOD': 'workload_identity',
    'OAUTH2_WORKLOAD_IDENTITY_TOKEN_FILE':
        '/var/run/secrets/azure/tokens/azure-identity-token',
    'OAUTH2_SERVER_METADATA_URL':
        'https://login.microsoftonline.com/<tenant-id>/v2.0/.well-known/openid-
↪configuration',
    'OAUTH2_SCOPE': 'openid email profile',
}]
```

With this configuration:

- pgAdmin will **not** require **OAUTH2_CLIENT_SECRET**.
- pgAdmin will **not** use PKCE for this provider.
- During the token exchange, pgAdmin will send:
  - `client_assertion_type=urn:ietf:params:oauth:client-assertion-type:jwt-bearer`
  - `client_assertion=<projected service account JWT>`

Azure App Registration setup

In Microsoft Entra ID:

- Create an **App registration** for pgAdmin.
- Configure a **Redirect URI** to `<http/https>://<pgAdmin Server URL>/oauth2/authorize`.
- In **Certificates & secrets**, you do **not** need to create a client secret for workload identity.

Federated credential (workload identity) configuration

Add a **Federated credential** to the App registration:

- **Issuer**: your AKS cluster OIDC issuer URL.
- **Subject**: `system:serviceaccount:<namespace>:<serviceaccount-name>`
- **Audience**: typically `api://AzureADTokenExchange`

AKS ServiceAccount example

Example ServiceAccount for AKS Workload Identity:

```
apiVersion: v1
kind: ServiceAccount
metadata:
  name: pgadmin
  namespace: pgadmin
  annotations:
    azure.workload.identity/client-id: "<Application (client) ID>"
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: pgadmin
  namespace: pgadmin
spec:
  template:
    metadata:
      labels:
        azure.workload.identity/use: "true"
    spec:
      serviceAccountName: pgadmin
```

Note

The projected token file path can vary by cluster configuration. In many AKS setups it is provided via the `AZURE_FEDERATED_TOKEN_FILE` environment variable and mounted under `/var/run/secrets/azure/tokens/`.

1.10.9 OIDC Configuration Examples

Using OIDC with Discovery Metadata (Recommended)

When using OIDC providers, configure the **OAUTH2_SERVER_METADATA_URL** parameter to enable automatic discovery and ID token validation:

```
OAUTH2_CONFIG = [{
    'OAUTH2_NAME': 'my-oidc-provider',
    'OAUTH2_DISPLAY_NAME': 'My OIDC Provider',
    'OAUTH2_CLIENT_ID': 'your-client-id',
    'OAUTH2_CLIENT_SECRET': 'your-client-secret',
    'OAUTH2_SERVER_METADATA_URL': 'https://provider.example.com/.well-known/openid-
↪configuration',
    'OAUTH2_SCOPE': 'openid email profile',
    # OAUTH2_USERINFO_ENDPOINT is optional when using OIDC
    # Token and authorization URLs are discovered automatically
}]
```

With this configuration:

- pgAdmin will use the OIDC discovery endpoint to automatically find token and authorization URLs
- User identity will be extracted from ID token claims (sub, email, preferred_username)
- The userinfo endpoint will only be called as a fallback if ID token lacks required claims
- ID token will be automatically validated using the provider's public keys

Using OIDC as a Public Client (No Client Secret) with PKCE

If your OAuth/OIDC application is configured as a **public client** (no client secret), pgAdmin can still perform interactive user login using Authorization Code + PKCE.

```
OAUTH2_CONFIG = [{
    'OAUTH2_NAME': 'my-oidc-public',
    'OAUTH2_DISPLAY_NAME': 'My OIDC Provider (Public Client)',
    'OAUTH2_CLIENT_ID': 'your-client-id',
    # Public client: omit OAUTH2_CLIENT_SECRET or set it to None/empty.
    'OAUTH2_CLIENT_SECRET': None,
    'OAUTH2_SERVER_METADATA_URL': 'https://provider.example.com/.well-known/openid-
↪configuration',
    'OAUTH2_SCOPE': 'openid email profile',
    # PKCE is mandatory for public clients
    'OAUTH2_CHALLENGE_METHOD': 'S256',
    'OAUTH2_RESPONSE_TYPE': 'code',
}]
```

With this configuration:

- pgAdmin enforces PKCE (challenge method + response type)
- The token exchange is performed without a client secret

Username Resolution for OIDC

When **OAUTH2_SERVER_METADATA_URL** is configured (OIDC mode), pgAdmin will resolve the username in the following order:

1. **OAUTH2_USERNAME_CLAIM** (if configured) - checks ID token first, then userinfo
2. **email** claim from ID token or userinfo endpoint
3. **preferred_username** claim from ID token (standard OIDC claim)
4. **sub** claim from ID token (always present in OIDC, used as last resort)

Example with custom username claim:

```
OAUTH2_CONFIG = [{
    # ... other config ...
    'OAUTH2_USERNAME_CLAIM': 'preferred_username',
    # pgAdmin will use 'preferred_username' from ID token for the username
}]
```

Example without custom claim (uses automatic fallback):

```
OAUTH2_CONFIG = [{
    # ... other config ...
    # No OAUTH2_USERNAME_CLAIM specified
    # pgAdmin will try: email -> preferred_username -> sub
}]
```

Additional Claims Authorization with OIDC

When using **OAUTH2_ADDITIONAL_CLAIMS** with OIDC providers, pgAdmin will:

1. Check the ID token claims first (more secure, no additional network call)
2. Fall back to userinfo endpoint response if needed

Example:

```
OAUTH2_CONFIG = [{
    # ... other config ...
    'OAUTH2_ADDITIONAL_CLAIMS': {
        'groups': ['admin-group', 'pgadmin-users'],
        'roles': ['database-admin']
    },
    # pgAdmin will check these claims in ID token first,
    # then userinfo endpoint if not found
}]
```

Restricting Shared Servers with a Claim

OAUTH2_SERVER_GROUP_CLAIM limits which shared servers an OAuth2 user can see, based on a claim from the identity provider such as a list of roles or groups. When it is set:

- A shared server owned by another user is only visible, and can only be connected to, if the name of the server group it is in appears in the claim.
- If the claim is missing for a user, they see no shared servers owned by other users.
- Servers and server groups that the user owns themselves are not affected.
- Users who log in by other methods are not affected.

The claim is read from the ID token first, then from the userinfo endpoint response. Its value may be a string or a list of strings; values of any other type (for example, group objects returned by some providers) are ignored. Server group names are matched exactly, with no trimming or case folding.

OAUTH2_SERVER_GROUP_CLAIM_MAPPING can be used to translate claim values into server group names. A value may map to a single name or a list of names, and values with no mapping are used as server group names unchanged.

The claim is only read when the user logs in, so changes made at the identity provider take effect at the user's next login.

Example:

```
OAUTH2_CONFIG = [{
    # ... other config ...
    'OAUTH2_SERVER_GROUP_CLAIM': 'roles',
    'OAUTH2_SERVER_GROUP_CLAIM_MAPPING': {
        'dba': ['Production', 'Staging'],
        'developer': 'Staging'
    },
    # A user with the roles ['developer', 'Reporting'] can see shared
    # servers in the 'Staging' and 'Reporting' server groups.
}]
```

Legacy OAuth2 Configuration (Without OIDC)

For providers that don't support OIDC discovery, configure all endpoints manually:

```
OAUTH2_CONFIG = [{
    'OAUTH2_NAME': 'github',
    'OAUTH2_DISPLAY_NAME': 'GitHub',
    'OAUTH2_CLIENT_ID': 'your-client-id',
    'OAUTH2_CLIENT_SECRET': 'your-client-secret',
    'OAUTH2_TOKEN_URL': 'https://github.com/login/oauth/access_token',
    'OAUTH2_AUTHORIZATION_URL': 'https://github.com/login/oauth/authorize',
    'OAUTH2_API_BASE_URL': 'https://api.github.com/',
    'OAUTH2_USERINFO_ENDPOINT': 'user',
    'OAUTH2_SCOPE': 'user:email',
    # No OAUTH2_SERVER_METADATA_URL - pure OAuth2 mode
}]
```

In this mode, user identity is retrieved only from the userinfo endpoint.

1.11 Enabling Webserver Authentication

To configure Webserver authentication, you must setup your webserver with any authentication plug-in (such as Shibboleth, HTTP BASIC auth) as long as it sets the REMOTE_USER environment variable. To enable Webserver authentication for pgAdmin, you must configure the Webserver settings in the *config_local.py* or *config_system.py* file (see the *config.py* documentation) on the system where pgAdmin is installed in Server mode. You can copy these settings from *config.py* file and modify the values for the following parameters:

Parameter	Description
AUTHENTICATION_SOURCES	The default value for this parameter is *internal*. To enable Webserver authentication, you must include *webserver* in the list of values for this parameter. you can modify the value as follows: • ['webserver']: pgAdmin will use only Webserver authentication. • ['webserver', 'internal']: pgAdmin will first try to authenticate the user through webserver. If that authentication fails, then it will return back to the login page where you need to provide internal pgAdmin user credentials for authentication.
WEBSERVER_AUTO_CREATE_USER	**Set the value to *True* if you want to automatically** create a pgAdmin user corresponding to a successfully authenticated Webserver user. Please note that password is not stored in the pgAdmin database.
WEBSERVER_REMOTE_USER	**To get the web server remote user details, set this variable to any header or** environment variable name which comes from the web server after webserver authentication. The default value is REMOTE_USER and the possible values are REMOTE_USER, HTTP_X_FORWARDED_USER, X-Forwarded-User.
WEBSERVER_REMOTE_USER_FROM_I	**Set to *True* only if your reverse proxy passes the** authenticated identity as an HTTP request header rather than the REMOTE_USER CGI variable. Defaults to *False*. See the warning below before enabling this.
WEBSERVER_TRUSTED_PROXIES	**A list of IP addresses/CIDR ranges of the reverse proxies** that are allowed to assert the identity header. Required (non-empty) for WEBSERVER_REMOTE_USER_FROM_HEADER to take effect. Defaults to an empty list.
WEBSERVER_SHARED_SECRET	**An optional shared secret that the trusted proxy must inject** into every request, as additional proof that the identity header was set by the proxy and not the client. Defaults to *None* (not checked).

continues on next page

Table 8 – continued from previous page

Parameter	Description
WEBSERVER_SHARED_SECRET_HEAI	**The header name carrying WEBSERVER_SHARED_SECRET.** Defaults to *X-Pgadmin-Webserver-Secret*.

Warning

Setting WEBSERVER_REMOTE_USER to a header-derived name (such as HTTP_X_FORWARDED_USER, or REMOTE-USER/Remote-user) means the identity is read from a client-controlled HTTP request header, not necessarily a value set by your webserver's authentication plug-in. Any client that can reach pgAdmin can set this header itself and impersonate any user, including an existing Administrator, unless you:

- Set `WEBSERVER_REMOTE_USER_FROM_HEADER = True`.
- List every reverse proxy allowed to assert the identity in `WEBSERVER_TRUSTED_PROXIES`.
- Configure your reverse proxy to strip *every* inbound spelling of the header (any hyphen/underscore variant, in any case) before it sets its own, so a client cannot smuggle a value past it.
- Optionally configure `WEBSERVER_SHARED_SECRET` / `WEBSERVER_SHARED_SECRET_HEADER` as an additional proof that the header was set by your proxy.

Without all of the above, pgAdmin does not trust a header-asserted identity and login through it is rejected.

Warning

A user matched via Webserver authentication is only logged in if their *Authentication source* is *webserver*. This prevents a header-asserted identity from ever logging into an account that was created some other way - most importantly, the default administrator account created by pgAdmin's own setup, whose *Authentication source* is *internal*.

If you are enabling Webserver authentication on a site that already has users (including that default administrator) with an *Authentication source* other than *webserver*, none of them will be able to log in through Webserver authentication until you change it. To do so, sign in through another configured authentication source and, for each such user, set *Authentication source* to *webserver* on the *User Management* page. If `AUTHENTICATION_SOURCES` lists only *webserver*, there is no other source to sign in with - temporarily add *internal* back to `AUTHENTICATION_SOURCES`, sign in with the internal administrator's password, fix the affected users' *Authentication source*, then remove *internal* again.

See *Accounts from different authentication sources* for more information.

1.11.1 Master Password

In the multi user mode, pgAdmin uses user's login password to encrypt/decrypt the PostgreSQL server password. In the Webserver authentication, the pgAdmin does not store the user's password, so we need an encryption key to store the PostgreSQL server password. To accomplish this, set the configuration parameter MASTER_PASSWORD to *True*, so upon setting the master password, it will be used as an encryption key while storing the password. If it is False, the server password can not be stored.

Note

Pre-compiled and configured installation packages are available for a number of platforms. These packages should be used by end-users whereever possible - the following information is useful for the maintainers of those packages and users interested in understanding how pgAdmin works.

The pgAdmin 4 client features a highly-customizable display that features drag-and-drop panels that you can arrange to make the best use of your desktop environment.

The tree control provides an elegant overview of the managed servers, and the objects that reside on each server. Right-click on a node within the tree control to access context-sensitive menus that provide quick access to management tasks for the selected object.

The tabbed browser provide quick access to statistical information about each object in the tree control, and pgAdmin tools and utilities (such as the Query tool and the debugger). pgAdmin opens additional feature tabs each time you access the extended functionality offered by pgAdmin tools; you can open, close, and re-arrange feature tabs as needed.

Use the *Preferences* dialog to customize the content and behaviour of the pgAdmin display. To open the *Preferences* dialog, select *Preferences* from the *File* menu.

Help buttons in the lower-left corner of each dialog will open the online help for the dialog. You can access additional Postgres help by navigating through the *Help* menu, and selecting the name of the resource that you wish to open.

You can search for objects in the database using the *Search objects*

1.12 User Interface


pgAdmin 4 supports all PostgreSQL features, from writing simple SQL queries to developing complex databases. It is designed to query an active database (in real-time), allowing you to stay current with modifications and implementations.

Features of pgAdmin 4 include:

- auto-detection and support for objects discovered at run-time
- a live SQL Query Tool with direct data editing
- support for administrative queries
- a syntax-highlighting SQL editor
- redesigned graphical interfaces
- powerful management dialogs and tools for common tasks
- responsive, context-sensitive behavior
- supportive error messages
- helpful hints

- online help and information about using pgAdmin dialogs and tools.

When pgAdmin opens, the interface features a menu bar and a window divided into two panes: the *Object Explorer* tree control in the left pane, and a tabbed browser in the right pane.



Select an icon from the *Quick Links* panel on the *Dashboard* tab to:

- Click the *Add New Server* button to open the *Register - Server dialog* to add a new server definition.
- Click the *Configure pgAdmin* button to open the *Preferences dialog* to customize your pgAdmin client.


Links in the *Getting Started* panel open a new browser tab that provide useful information for Postgres users:

- Click the *PostgreSQL Documentation* link to navigate to the *Documentation* page for the PostgreSQL open-source project; once at the project site, you can review the manuals for the currently supported versions of the PostgreSQL server.
- Click the *pgAdmin Website* link to navigate to the pgAdmin project website. The pgAdmin site features news about recent pgAdmin releases and other project information.
- Click the *Planet PostgreSQL* link to navigate to the blog aggregator for Postgres related blogs.
- Click the *Community Support* link to navigate to the *Community* page at the PostgreSQL open-source project site; this page provides information about obtaining support for PostgreSQL features.

1.13 Menu Bar

The pgAdmin menu bar provides drop-down menus for access to options, commands, and utilities. Its layout adapts based on your deployment: in Web mode, you will see *File*, *Object*, *Tools*, and *Help* menus. In Desktop mode, the *pgAdmin4* application menu replaces the standard *File* menu. Selections may be grayed out which indicates they are disabled for the object currently selected in the *pgAdmin* tree control.


1.13.1 The File Menu



Use the *File* menu available in web mode to access the following options:

Option	Action
Preferences	Click to open the *Preferences* dialog to customize your pgAdmin settings.
Reset Layout	If you have modified the workspace, click to restore the default layout.


1.13.2 The pgAdmin4 Menu



Use the *pgAdmin4* menu available in desktop mode to access the following options:

Option	Action
About pgAdmin 4	Provide pgadmin4 configuration information like version, mode etc.
Preferences/settings	Click to open the *Preferences* dialog to customize your pgAdmin settings.
Reset Layout	If you have modified the workspace, click to restore the default layout.
View Logs	This will show current pgadmin4 logs.
Configure runtime	Click to open a window that allows to configure application port, connection timeout to launch the application. To know more about runtime menu *click here*


1.13.3 The Object Menu



The *Object* menu is context-sensitive. Use the *Object* menu to access the following options (in alphabetical order):

Option	Action
Register 1) *Server* 2) *Deploy Cloud Instance*	Click to open the *Server* dialog to register a server. Click to open the *Cloud Deployment* dialog to deploy an cloud instance.
Change Server Password...	Click to open the *Change Server Password...* dialog to change the server password.
Clear Saved Password	If you have saved the database server password, click to clear the saved password. Enable only when password is already saved.
Clear SSH Tunnel Password	If you have saved the ssh tunnel password, click to clear the saved password. Enable only when password is already saved.
Connect Server	Click to open the *Connect to Server* dialog to establish a connection with a server.
Copy Server...	Click to copy the currently selected server.
Create	Click *Create* to access a context menu that provides context-sensitive selections. Your selection opens a *Create* dialog for creating a new object.
Drop	Click to drop the currently selected object from the server.
Drop (Cascade)	Click to drop the currently selected object and all dependent objects from the server.
Drop (Force)	Click to drop the currently selected database with force option.
Disconnect from server	Click to disconnect from the currently selected server.
Properties...	Click to review or modify the currently selected object's properties.
Refresh	Click to refresh the currently selected object.
Remove Server	Click to remove the currently selected server.
Scripts	Click to open the *Query tool* to edit or view the selected script from the flyout menu.
Trigger(s)	Click to *Disable* or *Enable* trigger(s) for the currently selected table. Options are displayed on the flyout menu.
Truncate	Click to remove all rows from a table/foreign tables (*Truncate*), to remove all rows from a table/foreign tables and its child tables (*Truncate Cascade*) or to remove all rows from a table/foreign tables and automatically restart sequences owned by columns (*Truncate Restart Identity*). Options are displayed on the flyout menu.
View Data	Click to access a context menu that provides several options for viewing data (see below).
ERD For Database	Click to open the ERD tool with automatically generated diagram for the database selected. This option is available only when a database is selected. Options are displayed on the flyout menu.
ERD For Table	Click to open the ERD tool with automatically generated diagram for the table selected. This option is available only when a table is selected. Options are displayed on the flyout menu.


1.13.4 The Tools Menu



Use the *Tools* menu to access the following options (in alphabetical order):

Option	Action
ERD Tool	Click to open the *ERD Tool* and start designing your database.
Grant Wizard...	Click to access the *Grant Wizard* tool.
PSQL Tool	Click to open the *PSQL Tool* and start PSQL in the current database context.
Query tool	Click to open the *Query tool* for the currently selected object.
Schema Diff	Click to open the *Schema Diff* and start comparing two database or two schema.
Backup Globals...	Click to open the *Backup Globals...* dialog to backup cluster objects.
Backup Server...	Click to open the *Backup Server...* dialog to backup a server.
Backup...	Click to open the *Backup...* dialog to backup database objects.
Restore...	Click to access the *Restore* dialog to restore database files from a backup.
Export Data Using Query...	Click to open the *Export Data Using Query...* dialog to export data from a table using query.
Import/Export Data...	Click to open the *Import/Export data...* dialog to import or export data from a table.
Maintenance...	Click to open the *Maintenance...* dialog to VACUUM, ANALYZE, REINDEX, or CLUSTER.
Search Objects...	Click to open the *Search Objects...* and start searching any kind of objects in a database.
AI Reports	Click to access a submenu with AI-powered analysis options (requires *AI configuration*): • *Security Report* - Generate an AI-powered security analysis for the selected server, database, or schema. • *Performance Report* - Generate an AI-powered performance analysis for the selected server or database. • *Design Report* - Generate an AI-powered design review for the selected database or schema.
Add named restore point	Click to open the *Add named restore point...* dialog to take a point-in-time snapshot of the current server state.
Pause replay of WAL	Click to pause the replay of the WAL log.
Resume replay of WAL	Click to resume the replay of the WAL log.
Reload Configuration...	Click to update configuration files without restarting the server.
Storage Manager	Click to open the *Storage Manager* to upload, delete, or download the backup files.

1.13.5 The Help Menu



Use the options on the *Help* menu to access online help documents, or to review information about the pgAdmin installation (in alphabetical order):

Option	Action
Quick Search	Type your keywords in the Quick Search field. Typing at least three characters will display all the matching possibilities under Menu items and the relevant documents under Help articles. Click on the options under Menu items to perform action of particular functionality or object. Click on any of the Help articles to open the help of that topic with highlighted text in a separate window. **Note**:- If any of the option under Menu items is disabled, then it will provide information via info icon.
About pgAdmin 4	Click to open a window where you will find information about pgAdmin; this includes the current version and the current user.
Online Help	Click to open documentation support for using pgAdmin utilities, tools and dialogs. Navigate (in the newly opened tab?) help documents in the left browser pane or use the search bar to specify a topic.
pgAdmin Website	Click to open the *pgAdmin.org* website in a browser window.
PostgreSQL Website	Click to access the PostgreSQL core documentation hosted at the PostgreSQL site. The site also offers guides, tutorials, and resources.


1.14 Toolbar

The pgAdmin toolbar provides shortcut buttons for frequently used features like the Query Tool, View/Edit Data, Search Object and the PSQL Tool. This toolbar is visible on the Object explorer panel. Buttons get enabled/disabled based on the selected object node.



- Use the *Object filter* button to access the Object Filter popup. It helps you filter objects in the Object Explorer tree.
- Use the *Query Tool* button to open the Query Tool in the current database context.
- Use the *View Data* button to view/edit the data stored in a selected table.
- Use the *Filtered Rows* button to access the Data Filter popup to apply a filter to a set of data for viewing/editing.
- Use the *Search objects* button to access the search objects dialog. It helps you search any database object.
- Use the *PSQL Tool* button to open the PSQL in the current database context.

1.15 Object Explorer Filter




Use this tool to filter objects in the Object Explorer by following fields:

- Use the *Tags* field to filter the servers with one or more server tags. The servers with any of the selected tags will be displayed in the Object Explorer. You can also create a new tag by typing in the field and pressing Enter.

Click the **Apply** button to apply the filter. Please note the object explorer will refresh after applying the filter.

1.16 Tabbed Browser


The right pane of the *pgAdmin* window features a collection of tabs that display information about the object currently selected in the *pgAdmin* tree control in the left window. Select a tab to access information about the highlighted object in the tree control.



The graphs and tables on the *Dashboard* tab provides an active analysis of system statistics and the usage statistics for the selected server or database.

Click the *Activity* tab to get the usage statistics for the selected server or database:

- The *Server sessions* or *Database sessions* graph displays the interactions with the server or database.
- The *Transactions per second* graph displays the commits, rollbacks, and total transactions per second that are taking place on the server or database.
- The *Tuples in* graph displays the number of tuples inserted, updated, and deleted on the server or database.
- The *Tuples out* graph displays the number of tuples fetched and returned from the server or database.
- The *Block I/O* graph displays the number of blocks read from the filesystem or fetched from the buffer cache (but not the operating system's file system cache) for the server or database.




Click the *Stat* tab to get the usage statistics for the selected server or database:

The *Stat* panel displays information about sessions, locks, prepared transactions. The information is presented in context-sensitive tables. Use controls located above the table to:


- Click the *Refresh* button to update the information displayed in each table.
- Select *Active sessions only* checkbox to get the information about active sessions only from the list of all the sessions.
- Enter a value in the *Search* box to restrict the table content to one or more sessions that satisfy the search criteria. For example, you can enter a process ID to locate a specific session, or a session state (such as *idle*) to locate all of the sessions that are in an idle state.

You can use icons in the *Sessions* table to review or control the state of a session:

- Use the *Terminate* icon (located in the first column) to stop a session and remove the session from the table. Before the server terminates the session, you will be prompted to confirm your selection.
- Use the *Cancel* icon (located in the second column) to terminate an active query without closing the session. Before canceling the query, the server will prompt you to confirm your selection. When you cancel a query, the value displayed in the *State* column of the table will be updated from *Active* to *Idle*. The session will remain in the table until the session is terminated.
- Use the *Details* icon (located in the third column) to open the *Details* tab; the tab displays information about the selected session.




Click the *Configuration* tab to get the server configuration details.



Click the *Logs* tab to get the server logs.

- Use the Log Format switch to select the format you want. Text/Plain, JSON and CSV are supported. The enable/disable state of the log format depends on the Postgresql.conf setting.
- Use the Logs in tabular format? switch if you want to see the logs in a tabular format.


Click the *System Statistics* tab to get the statistics for the system:



Click the *Summary* tab to get the summary of the system:


- The *OS Information* table displays the basic information about the operating system.

- The *CPU Information* table displays the information about system CPU.
- The *Process & Handle Count* graph displays the total count of processes running and handles opened for the system.




Click the *CPU* tab to get the detailed usage statistics of the system CPU:

- The *CPU Usage* graph displays the percentage of time spent by CPU for user normal process, user niced process, kernel mode process, idle mode.
- The *Load average* graph displays the average load of the system over 1, 5, 10, and 15 minute intervals.
- The *Process CPU Usage* table displays information about CPU for each process ID. Enter a value like process ID or name in the Search box to restrict the table content to one or more processes that satisfy the search criteria.



Click the *Memory* tab to get the detailed usage statistics of the system memory:

- The *Memory Usage* graph displays the size of total, free and used memory per seconds in Gigabytes.
- The *Swap Memory* graph displays the size of total, free and used swap memory per seconds in Gigabytes.
- The *Process Memory Usage* table displays information about memory for each process ID. Enter a value like process ID or name in the Search box to restrict the table content to one or more processes that satisfy the search criteria.




Click the *Storage* tab to get the detailed information of the system storage:

- The *Disk Information* table displays the information about the disk, such as file system type, mount point, total space, used space and free space and count of total, free, used inodes. The pie graph shows the total spaces in Gigabytes and stacked bar graph shows the used and available space in Gigabytes, for different mount points for file system.
- The *Swap Memory* graph displays the size of total, free and used swap memory per seconds in Gigabytes.

The *disk0* panel displays statistics about the only I/O block device of system:


- The *I/O Operations Count* graph displays the count of read and write operations per second.
- The *Data Transfer* graph displays the size of read and writes happened in Gigabytes per second.
- The *Time spent in I/O operations* graph displays the time spent by the device for reading and writing in minutes per second.



The *Properties* tab displays information about the object selected.


Click the *Delete* icon in the toolbar under the browser tab to delete the selected objects in the Properties panel.

Click the *Drop Cascade* icon in the toolbar under the browser tab to delete the selected objects and all dependent objects in the Properties panel.




Click the *Edit* icon in the toolbar under the browser tabs to launch the *Properties* dialog for the selected object.


To preserve any changes to the *Properties* dialog, click the *Save* icon; your modifications will be displayed in the updated *Properties* tab.



Details about the object highlighted in the tree control are displayed in one or more collapsible panels. You can use the arrow to the left of each panel label to open or close a panel.



The *SQL* tab displays the SQL script that created the highlighted object, and when applicable, a (commented out) SQL statement that will *DROP* the selected object. You can copy the SQL statements to the editor of your choice using cut and paste shortcuts.



Statistics	Value
Backends	5
Xact committed	92095209
Xact rolled back	36
Blocks read	5269146
Blocks hit	15431026716
Tuples returned	22491999300
Tuples fetched	6469655717
Tuples inserted	13529
Tuples updated	152
Tuples deleted	98
Last statistics reset	2018-12-21 14:30:08.829322+05:30
Tablespace conflicts	0
Lock conflicts	0
Snapshot conflicts	0
Bufferpin conflicts	0
Deadlock conflicts	0
Temporary files	0
Size of temporary files	0 bytes
Deadlocks	0
Block read time	0
Block write time	0
Size	18 MB


The *Statistics* tab displays the statistics gathered for each object on the tree control; the statistics displayed in the table vary by the type of object that is selected. Click a column heading to sort the table by the data displayed in the column; click again to reverse the sort order. The following table lists some of the statistics that are available:

Panel	Description
PID	The process ID associated with the row.
User	The name of the user that owns the object.
Database	displays the database name.
Backends	displays the number of current connections to the database.
Backend start	The start time of the backend process.
Xact Committed	displays the number of transactions committed to the database within the last week.
Xact Rolled Back	displays the number of transactions rolled back within the last week.
Blocks Read	displays the number of blocks read from memory (in megabytes) within the last week.
Blocks Hit	displays the number of blocks hit in the cache (in megabytes) within the last week.
Tuples Returned	displays the number of tuples returned within the last week.
Tuples Fetched	displays the number of tuples fetched within the last week.
Tuples Inserted	displays the number of tuples inserted into the database within the last week.
Tuples Updated	displays the number of tuples updated in the database within the last week.
Tuples Deleted	displays the number of tuples deleted from the database within the last week.
Last statistics reset	displays the time of the last statistics reset for the database.
Tablespace conflicts	displays the number of queries canceled because of recovery conflict with dropped tablespaces in database.
Lock conflicts	displays the number of queries canceled because of recovery conflict with locks in database.
Snapshot conflicts	displays the number of queries canceled because of recovery conflict with old snapshots in database.
Bufferpin conflicts	displays the number of queries canceled because of recovery conflict with pinned buffers in database.
Temporary files	displays the total number of temporary files, including those used by the statistics collector.
Size of temporary files	displays the size of the temporary files.

continues on next page

Table 9 – continued from previous page


Panel	Description
Deadlocks	displays the number of queries canceled because of a recovery conflict with deadlocks in database.
Block read time	displays the number of milliseconds required to read the blocks read.
Block write time	displays the number of milliseconds required to write the blocks read.
Size	displays the size (in megabytes) of the selected database.



The *Dependencies* tab displays the objects on which the currently selected object depends. If a dependency is dropped, the object currently selected in the pgAdmin tree control will be affected. To ensure the integrity of the entire database structure, the database server makes sure that you do not accidentally drop objects that other objects depend on; you must use the DROP CASCADE command to remove an object with a dependency.


The *Dependencies* table displays the following information:

- The *Type* field specifies the parent object type.
- The *Name* field specifies the identifying name of the parent object.
- The *Restriction* field describes the dependency relationship between the currently selected object and the parent:
  - If the field is *auto*, the selected object can be dropped separately from the parent object, and will be dropped if the parent object is dropped.
  - If the field is *internal*, the selected object was created during the creation of the parent object, and will be dropped if the parent object is dropped.
  - If the field is *normal*, the selected object can be dropped without dropping the parent object.
  - If the field is *blank*, the selected object is required by the system, and cannot be dropped.



The *Dependents* tab displays a table of objects that depend on the object currently selected in the *pgAdmin* browser. A dependent object can be dropped without affecting the object currently selected in the *pgAdmin* tree control.

- The *Type* field specifies the dependent object type.
- The *Name* field specifies the identifying name for the dependent object.
- The *Database* field specifies the database in which the object resides.




Additional tabs open when you access the extended functionality offered by pgAdmin tools (such as the Query tool, Debugger, or SQL editor). Use the close icon (X) located in the upper-right corner of each tab to close the tab when you are finished using the tool. Like permanent tabs, these tabs may be repositioned in the pgAdmin client window.

By default, each time you open a tool, pgAdmin will open a new browser tab. You can control this behavior by modifying the *Display* node of the *Preferences* dialog for each tool. To open the *Preferences* dialog, select *Preferences* from the *File* menu.

1.17 Tree Control

The left pane of the main window displays a tree control (Object explorer) that provides access to the objects that reside on a server.



You can expand nodes in the tree control to view the database objects that reside on a selected server. The tree control expands to display a hierarchical view:

- Use the plus sign (+) to the left of a node to expand a segment of the tree control.
- Click the minus sign (-) to the left of a node to close that node.

You can also **drag and drop** certain objects to the Query Tool which can save time in typing long object names. Text containing the object name will be fully qualified with schema. Double quotes will be added if required. For functions and procedures, the function name along with parameter names will be pasted in the Query Tool.

Access context-sensitive menus by right-clicking on a node of the tree control to perform common tasks. Menus display options that include one or more of the following selections (options appear in alphabetical order):

Option	Action
Add named restore point	Click to create and enter the name of a restore point.
Backup...	Click to open the *Backup...* dialog to backup database objects.
Backup Globals...	Click to open the *Backup Globals...* dialog to backup cluster objects.
Backup Server...	Click to open the *Backup Server...* dialog to backup a server.
Connect Server...	Click to open the *Connect to Server* dialog to establish a connection with a server.
Create	Click to access a context menu that provides context-sensitive selections. Your selection opens a *Create* dialog for creating a new object.
CREATE Script	Click to open the *Query tool* to edit or view the CREATE script.
Debugging	Click through to open the *Debug* tool or to select *Set breakpoint* to stop or pause a script execution.
Drop	Click to drop the currently selected object from the server.
Drop (Cascade)	Click to drop the currently selected object and all dependent objects from the server.
Drop (Force)	Click to drop the currently selected database with force option.
Disconnect Database...	Click to terminate a database connection.
Disconnect from server	Click to disconnect from the currently selected server.
Debugging	Click to access the *Debugger* tool.
Grant Wizard	Click to access the *Grant Wizard* tool.
Maintenance...	Click to open the *Maintenance...* dialog to VACUUM, ANALYZE, REINDEX, or CLUSTER.
Properties...	Click to review or modify the currently selected object's properties.
Refresh...	Click to refresh the currently selected object.
Reload Configuration...	Click to update configuration files without restarting the server.
Restore...	Click to access the *Restore* dialog to restore database files from a backup.
View Data	Use the *View Data* option to access the data stored in a selected table with the *Data Output* tab of the *Query Tool*.


The context-sensitive menus associated with *Tables* and nested *Table* nodes provides additional display options (options appear in alphabetical order):

Option	Action
Import/Export Data...	Click open the *Import/Export...* dialog to import data to or export data from the selected table.
Reset Statistics	Click to reset statistics for the selected table.
Scripts	Click to open the *Query tool* to edit or view the selected script from the flyout menu.
Truncate	Click to remove all rows from a table.
Truncate Cascade	Click to remove all rows from a table and its child tables.
View First 100 Rows	Click to access a data grid that displays the first 100 rows of the selected table.
View Last 100 Rows	Click to access a data grid that displays the last 100 rows of the selected table.
View All Rows	Click to access a a data grid that displays all rows of the selected table.
View Filtered Rows...	Click to access the *Data Filter* popup to apply a filter to a set of data.

1.18 Preferences

Use options in the *Preferences* tab to customize the behavior of the client. To open the *Preferences* tab, select *Preferences* from the *File* menu or click on the *Settings* button at the bottom left corner in case of Workspace layout.

1.18.1 Header




- Use the *Save* button to save any preference changes.
- Use the *Reset all preferences* button to restore all preferences to their default values.
- Use the *Help* button to open preferences help.
- Quickly search all preferences using the *Search* box. It finds matches in both labels and help messages.

The left pane of the *Preferences* tab displays a tree control; each node of the tree control provides access to options that are related to the node under which they are displayed.

1.18.2 The AI Node

Use preferences found in the *AI* node of the tree control to configure AI-powered features and LLM (Large Language Model) providers.



Note: AI features must be enabled in the server configuration (`LLM_ENABLED = True` in `config.py`) for these preferences to be available.

Use the fields on the *AI* panel to configure your LLM provider:

- Use the *Default Provider* drop-down to select your LLM provider. Options include: *Anthropic*, *OpenAI*, *Ollama*, or *Docker Model Runner*.

Anthropic Settings:

- Use the *API URL* field to set a custom API endpoint URL. Leave empty to use the default Anthropic API (`https://api.anthropic.com/v1`). Set a custom URL to use an Anthropic-compatible API provider.

- Use the *API Key File* field to specify the path to a file containing your Anthropic API key. This path refers to the filesystem where the pgAdmin server is running (e.g., inside the container if using Docker). The ~ prefix is expanded to the home directory of the user running the pgAdmin server process. The API key may be optional when using a custom API URL with a provider that does not require authentication.
- Use the *Model* field to select from the available Claude models. Click the refresh button to fetch the latest available models from your configured endpoint.

OpenAI Settings:

- Use the *API URL* field to set a custom API endpoint URL. Leave empty to use the default OpenAI API (`https://api.openai.com/v1`). Set a custom URL to use any OpenAI-compatible API provider (e.g., LiteLLM, LM Studio, EXO, GLM (Z.ai)). Include the `/v1` path prefix if required by your provider (e.g., `http://localhost:1234/v1`).
- Use the *API Key File* field to specify the path to a file containing your OpenAI API key. This path refers to the filesystem where the pgAdmin server is running (e.g., inside the container if using Docker). The ~ prefix is expanded to the home directory of the user running the pgAdmin server process. The API key may be optional when using a custom API URL with a provider that does not require authentication.
- Use the *Model* field to select from the available GPT models. Click the refresh button to fetch the latest available models from your configured endpoint.

Ollama Settings:

- Use the *API URL* field to specify the Ollama server URL (default: `http://localhost:11434`).
- Use the *Model* field to select from the available models or enter a custom model name (e.g., `llama2`, `mistral`). Click the refresh button to fetch the latest available models from your Ollama server.

Docker Model Runner Settings:

- Use the *API URL* field to specify the Docker Model Runner API URL (default: `http://localhost:12434`). Available in Docker Desktop 4.40+.
- Use the *Model* field to select from the available models or enter a custom model name. Click the refresh button to fetch the latest available models from your Docker Model Runner.

Note


You can also use the *OpenAI* provider with a custom API URL for any OpenAI-compatible endpoint, including Docker Model Runner, LM Studio, EXO, hosted services such as GLM (Z.ai), and other local inference servers. This can be useful when you want to use a provider that isn't explicitly listed but supports the OpenAI API format.

Note

With the default allowlist enabled, an administrator must add any API host not already in `ALLOWED_LLM_API_URLS` before pgAdmin can connect to it. By default the list allows the OpenAI and Anthropic APIs and loopback addresses on any port. An empty allowlist disables this restriction.

1.18.3 The Browser Node

Use preferences found in the *Browser* node of the tree control to personalize your workspace.




Use the fields on the *Display* panel to specify general display preferences:

- When the *Auto-expand sole children* switch is set to *True*, child nodes will be automatically expanded if a treeview node is expanded and has only a single child.
- When the *Confirm before Close/Reset in object properties dialog?* switch is set to *True*, pgAdmin will warn you before closing the properties dialog of an object if there are any unsaved changes. On user confirmation, the properties dialog will close.
- When the *Confirm on close or refresh?* switch is set to *True*, pgAdmin will attempt to catch browser close or refresh events and prompt before allowing them to continue.
- Use the *Object explorer state saving interval* field to set the treeview state saving interval. A value of *-1* will disable the treeview state saving functionality.
- When the *Hide shared servers?* switch is set to *True*, the client will hide all the shared servers from the object explorer. **Note:** This option is visible only when pgAdmin is running in server mode.
- When the *Show column data type?* switch is turned off, then the data types of the columns will not be displayed alongside their column names.
- When the *Show empty object collections?* switch is turned off, then all object collections which are empty will be hidden from browser tree.
- When the *Show system objects?* switch is set to *True*, the client will display system objects such as system schemas (for example, *pg_temp*) or system columns (for example, *xmin* or *ctid*) in the tree control.


- When the *Show template databases?* switch is set to *True*, the client will display template databases.

Use the fields on the *Keyboard shortcuts* panel to configure shortcuts for the main window navigation:




- The panel displays a list of keyboard shortcuts available for the main window; select the combination of the modifier keys along with the key to configure each shortcut.

Use the fields on the *Nodes* panel to select the object types that will be displayed in the *Browser* tree control:




- The panel displays a list of database objects; slide the switch located next to each object to *Show* or *Hide* the database object. When querying system catalogs, you can reduce the number of object types displayed to increase speed.

Use the fields on the *Object Breadcrumbs* panel to change object breadcrumbs related settings:




- Use *Enable object breadcrumbs?* to enable or disable object breadcrumbs displayed on object mouse hover.
- Use *Show comment with object breadcrumbs?* to enable or disable the comment visibility which comes displayed with object breadcrumbs.

Use the fields on the *Processes* panel to change processes tab related settings:




- Change *Process details/logs retention days* to the number of days, the process info and logs will be automatically cleared.

Use fields on the *Properties* panel to specify browser properties:



- Include a value in the *Count rows if estimated less than* field to perform a SELECT count(*) if the estimated number of rows in a table (as read from the table statistics) is below the specified limit. After performing the SELECT count(*), pgAdmin will display the row count. The default is 2000.
- Provide a value in the *Maximum job history rows* field to limit the number of rows to show on the statistics tab for pgAgent jobs. The default is 250.


Use field on *Tab settings* panel to specify the tab related properties.




- Use *Debugger tab title placeholder* field to customize the Debugger tab title.
- When the *Dynamic tab size* switch is set to *True*, the tabs will take full size as per the title. This will also apply to already opened tabs.
- Use the *PSQL tool tab title placeholder* field to customize the PSQL tool tab title.
- When the *Open in new browser tab* field is selected for Query tool, Schema Diff or Debugger, it will open in a new browser tab when invoked.
- Use the *Query tool tab title placeholder* field to customize the query tool tab title.
- Use *View/Edit tab title placeholder* field to customize the View/Edit Data tab title.

1.18.4 The Dashboards Node

Expand the *Dashboards* node to specify your dashboard display preferences.



- Set the warning and alert threshold value to highlight the long-running queries on the dashboard.
- When the *Show activity?* switch is set to *True*, activity tables will be displayed on dashboards.
- When the *Show graphs?* switch is set to *True*, graphs will be displayed on dashboards.




Use the fields on the *Refresh rates* panel to specify your refresh rate preferences for the graphs on the *Dashboard* tab:

- Use the *Average load statistics refresh rate* field to specify the number of seconds between average load statistics samples displayed in graphs.
- Use the *Block I/O statistics refresh rate* field to specify the number of seconds between block I/O statistic samples displayed in graphs.
- Use the *CPU usage per process statistics refresh rate* field to specify the number of seconds between CPU usage per process statistics samples displayed in graphs.
- Use the *Handle & Process count statistics refresh rate* field to specify the number of seconds between handle & process count statistics samples displayed in graphs.
- Use the *I/O analysis statistics refresh rate* field to specify the number of seconds between I/O analysis statistics samples displayed in graphs.
- Use the *Memory usage per process statistics refresh rate* field to specify the number of seconds between memory usage per process statistics samples displayed in graphs.
- Use the *Memory usage statistics refresh rate* field to specify the number of seconds between memory usage statistics samples displayed in graphs.
- Use the *PGD replication lag refresh rate* field to specify the number of seconds between PGD replication lag samples displayed in graphs.
- Use the *Percentage of CPU time used by different process modes statistics refresh rate* field to specify the number of seconds between Percentage of CPU time used by different process modes samples displayed in graphs.
- Use the *Session statistics refresh rate* field to specify the number of seconds between session statistic samples displayed in graphs.
- Use the *Swap memory usage statistics refresh rate* field to specify the number of seconds between swap memory usage statistics samples displayed in graphs.
- Use the *Transaction throughput refresh rate* field to specify the number of seconds between transaction throughput samples displayed in graphs.
- Use the *Tuples in refresh rate* field to specify the number of seconds between tuples-in samples displayed in graphs.
- Use the *Tuples out refresh rate* field to specify the number of seconds between tuples-out samples displayed in graphs.

1.18.5 The Debugger Node

Expand the *Debugger* node to specify your debugger display preferences.


Use the fields on the *Keyboard shortcuts* panel to configure shortcuts for the debugger window navigation:




1.18.6 The ERD Tool Node

Expand the *ERD Tool* node to specify your ERD Tool display preferences.

Use the fields on the *Keyboard shortcuts* panel to configure shortcuts for the ERD Tool window navigation:



Use the fields on the *Options* panel to manage ERD preferences.




- Use *Cardinality Notation* to change the cardinality notation format used to present relationship links.


- Use *Format ERD Project File?* if you want to format the .pgerd ERD project file. It's a JSON file which will be formatted.
- Use *Image Download Resolution* to change the ERD image download resolution. Higher values will use higher memory and slower rendering.
- When the *SQL With DROP Table* switch is set to *True*, the SQL generated by the ERD Tool will add DROP table DDL before each CREATE table DDL.
- *Table Relation Depth* is useful when generating an ERD for a table. It allows to set the limit on the depth level pgAdmin should traverse to find the relations. Use -1 to set no limit.

1.18.7 The Editor Node

Expand the *Editor* node to access panels that allow you to specify your preferences for the editor across pgAdmin 4




Use the fields on the *Keyboard shortcuts* panel to configure shortcuts for the editor.



Use the fields on the *Options* panel to manage editor preferences.

- Use the *Auto-indent new line?* switch to specify whether the editor will automatically indent new lines. When set to *True*, the editor will indent new lines according to the indentation of the previous line.
- When the *Brace matching?* switch is set to *True*, the editor will highlight pairs of matched braces.
- When the *Code folding?* switch is set to *False*, the editor will disable code folding. Disabling will improve editor performance with large files.
- Use the *Cursor blink rate* field to adjust the speed at which the text cursor blinks within the editors.
- Use the *Font family* field to be used for all SQL editors. The specified font should already be installed on your system. If the font is not found, the editor will fall back to the default font, Source Code Pro.
- When the *Font ligatures?* switch is set to *True*, ligatures will be enabled in SQL text boxes and editors provided the configured font family supports them.
- Use the *Font size* field to specify the font size that will be used in text boxes and editors.
- When the *Highlight selection matches?* switch is set to *True*, the editor will highlight matched selected text.
- When the *Insert bracket pairs?* switch is set to *True*, the editor will automatically insert paired brackets.
- When the *Line wrapping* switch is set to *True*, the editor will implement line-wrapping behavior.
- When the *Plain text mode?* switch is set to *True*, the editor mode will be changed to text/plain. Keyword highlighting and code folding will be disabled. This will improve editor performance with large files.




Use the fields on the *SQL formatting* panel to specify your preferences for reformatting of SQL.

- Use the *Data type case* option to specify whether to change data types into upper, lower, or preserve case.
- Use the *Expression width* option to specify maximum number of characters in parenthesized expressions to be kept on single line.
- Use the *Function case* option to specify whether to change function names into upper, lower, or preserve case.
- Use the *Identifier case* option to specify whether to change identifiers (object names) into upper, lower, or capitalized case.
- Use the *Keyword case* option to specify whether to change keywords into upper, lower, or preserve case.
- Use *Lines between queries* to specify how many empty lines to leave between SQL statements. If set to zero it puts no new line.
- Use *Logical operator new line* to specify newline placement before or after logical operators (AND, OR, XOR).
- Use *New line before semicolon?* to specify whether to place query separator (;) on a separate line.
- Use the *Spaces around operators?* option to specify whether or not to include spaces on either side of operators.
- Use the *Tab size* option to specify the number of spaces per tab or indent.
- Use the *Use spaces?* option to select whether to use spaces or tabs when indenting.

1.18.8 The Graphs Node


Expand the *Graphs* node to specify your Graphs display preferences.



- Use the *Chart line width* field to specify the width of the lines on the line chart.
- When the *Show graph data points?* switch is set to *True*, data points will be visible on graph lines.
- When the *Show mouse hover tooltip?* switch is set to *True*, a tooltip will appear on mouse hover on the graph lines giving the data point details.
- When the *Use different data point styles?* switch is set to *True*, data points will be visible in a different style on each graph lines.

1.18.9 The Miscellaneous Node

Expand the *Miscellaneous* node to specify miscellaneous display preferences.




Use the fields on the *File Downloads* panel to manage file downloads related preferences.

- When the *Automatically open downloaded files?* switch is set to *True* the downloaded file will automatically open in the system's default application associated with that file type. **Note:** This option is applicable and visible only in desktop mode.
- When the *Enable binary data download?* switch is set to *True*, binary data can be downloaded from the result grid. Default is set to *False* to prevent excessive memory usage on the server.
- When the *Prompt for the download location?* switch is set to *True* a prompt will appear after clicking the download button, allowing you to choose the download location. **Note:** This option is applicable and visible

only in desktop mode.

Note: File Downloads related settings are applicable and visible only in desktop mode.


Use the fields on the *User Interface* panel to set the user interface related preferences.



- Use the *Language* drop-down listbox to select the display language for the client.
- Use the *Layout* drop-down listbox to select the layout for the client. pgAdmin offers two options: the Classic layout, a longstanding and familiar design, and the Workspace layout, which provides distraction free dedicated areas for the Query Tool, PSQL, and Schema Diff tools. 'Workspace' layout is the default layout, but user can change it to 'Classic'.
- When the *Open the Query Tool/PSQL in their respective workspaces* switch is set to *True* then all Query Tool/PSQL tabs will open in their respective workspaces. By default, this setting is False, meaning that Query Tool/PSQL tabs will open in the currently active workspace (either the default or the workspace selected at the time of opening).
- When the *Save the application state?* option is enabled the current state of various tools—such as Query Tool, ERD, Schema Diff, and PSQL—will be saved in the encrypted format. If the application is closed unexpectedly, the tab is accidentally closed, or the page is refreshed, the saved state will be automatically restored for each respective tool. **Note:** Saving the application state will not preserve data for tool tabs opened in separate browser tabs when running in server mode.Any tool referring ad-hoc server connection will not be restored.
- Use the *Themes* drop-down listbox to select the theme for pgAdmin. You'll also get a preview just below the drop down. You can also submit your own themes, check here how. Currently we support Light, Dark, High Contrast and System theme. Selecting System option will follow your computer's settings.

1.18.10 The Paths Node


Expand the *Paths* node to specify the locations of supporting utility and help files.



Use the fields on the *Binary paths* panel to specify the path to the directory that contains the utility programs (pg_dump, pg_dumpall, pg_restore and psql) for monitored databases:

- Use the *EDB Advanced Server Binary Path* grid to specify the location of the EDB Postgres Advanced Server utility programs based on the server version. If the respective path is not set, then pgAdmin will pick up the path for which 'Set as default' is checked else pgAdmin will attempt to find the utilities in standard locations used by EnterpriseDB.
- Use the *PostgreSQL Binary Path* grid to specify the location of the PostgreSQL utility programs based on the server version. If the respective path is not set, then pgAdmin will pick up the path for which 'Set as default' is checked else pgAdmin will attempt to find the utilities in standard locations used by PostgreSQL.

Note: Use the 'Validate path' button to check the existence of the utility programs (pg_dump, pg_dumpall, pg_restore and psql) and their respective versions.




Use the fields on the *Help* panel to specify the location of help files.

- Use the *PostgreSQL Help Path* to specify the path to PostgreSQL documentation.

Please note: the default help paths include the *VERSION* placeholder; the $VERSION$ placeholder will be replaced by the current database version.


1.18.11 The Query Tool Node

Expand the *Query Tool* node to access panels that allow you to specify your preferences for the Query Editor tool.




Use the fields on the *Auto Completion* panel to set the auto completion options.

- When the *Autocomplete on key press* switch is set to *True* then autocomplete will be available on key press along with CTRL/CMD + Space. If it is set to *False* then autocomplete is only activated when CTRL/CMD + Space is pressed.
- When the *Keywords in uppercase* switch is set to *True* then keywords are shown in upper case.




Use the fields on the *CSV/TXT Output* panel to control the CSV/TXT output.

- Use the *CSV field separator* drop-down listbox to specify the separator character that will be used in CSV/TXT output.
- Use the *CSV quote character* drop-down listbox to specify the quote character that will be used in CSV/TXT output.
- Use the *CSV quoting* drop-down listbox to select the fields that will be quoted in the CSV/TXT output; select *Strings*, *All*, or *None*.
- Use the *Replace null values with* option to replace null values with specified string in the output file. Default is set to 'NULL'.
- Use the *Output file encoding* drop-down listbox to specify the character encoding used when saving query results to a file. The default is utf-8; an encoding that is not listed can also be typed in. Any character that the chosen encoding cannot represent is written as a question mark (?).
- Use the *Add byte order mark (BOM)?* switch to add a byte order mark at the start of the saved file when a UTF encoding is used. This helps applications such as Microsoft Excel detect the encoding correctly. This applies to the CSV/TXT output only. The utf-16, utf-32 and utf-8-sig encodings always include a BOM, whatever this is set to.



Use the fields on the *Display* panel to specify your preferences for the Query Tool display.

- When the *Connection status* switch is set to *True*, each new instance of the Query Tool will display connection and transaction status.
- Use the *Connection status refresh rate* field to specify the number of seconds between connection/transaction status updates.
- When the *Show query success notification?* switch is set to *True*, the Query Tool will show notifications on successful query execution.



Use the fields on the *Explain* panel to specify the level of detail included in a graphical EXPLAIN.

- When the *Show buffers?* switch is set to *True*, graphical explain details will include information about buffer usage.
- When the *Show costs?* switch is set to *True*, graphical explain details will include information about the estimated startup and total cost of each plan, as well as the estimated number of rows and the estimated width of each row.
- When the *Show settings?* switch is set to *True*, graphical explain details will include the information on the configuration parameters.
- When the *Show summary?* switch is set to *True*, graphical explain details will include the summary information about the query plan.
- When the *Show timing?* switch is set to *True*, graphical explain details will include the startup time and time spent in each node in the output.
- When the *Show wal?* switch is set to *True*, graphical explain details will include the information on WAL record generation.
- When the *Verbose output?* switch is set to *True*, graphical explain details will include extended information about the query execution plan.


Use the fields on the *Geometry Viewer* panel to configure a custom map tile provider used as a base layer when viewing geometry data.

- Use the *Custom tile provider URL* field to specify the URL template of a custom XYZ tile provider, e.g. `https://myserver.example.com/tiles/{z}/{x}/{y}.png`. The template must contain the `{x}`, `{y}` and `{z}` placeholders, and may contain `{s}` for subdomains (a, b, c). Leave the field empty to disable the custom tile provider.

- Use the *Custom tile provider name* field to specify the display name of the custom tile provider in the layer selector of the Geometry Viewer.
- Use the *Custom tile provider CRS* field to specify the coordinate reference system of the custom tile provider. If it is not EPSG:3857 (Web Mercator), the built-in tile layers will be hidden as they cannot be mixed with other coordinate systems.
- Use the *Custom tile provider attribution* field to specify the attribution text shown on the map. It may contain HTML links.
- Use the *Custom tile provider max zoom* field to specify the maximum zoom level of the custom tile provider.


When a custom tile provider is configured, it is selected as the default base layer of the Geometry Viewer.

An administrator may set a system-wide default for these fields via the `DEFAULT_GEOMETRY_VIEWER_PROVIDER` setting in *Configuration Files*. It applies to any user who has not saved their own values for the fields above; a user's own preferences, once saved, always take precedence over the system-wide default.



Use the fields on the *Graph Visualiser* panel to specify the settings related to graphs.


- Use the *Row Limit* field to specify the maximum number of rows that will be plotted on a chart.



Use the fields on the *Options* panel to manage editor preferences.

- When the *Auto commit?* switch is set to *True*, each successful query is committed after execution.
- When the *Auto rollback on error?* switch is set to *True*, failed queries are rolled back.
- When the *Copy SQL from main window to query tool?* switch is set to *True*, the CREATE sql of the selected object will be copied to query tool when query tool will open.
- When the *Open the file in a new tab?* switch is set to *True*, the editor will open the new file in new tab of the Query Tool.
- When the *Prompt to commit/rollback active transactions?* switch is set to *True*, the editor will prompt the user to commit or rollback changes when exiting the Query Tool while the current transaction is not committed.
- When the *Prompt to save unsaved data changes?* switch is set to *True*, the editor will prompt the user to saved unsaved data when exiting the data editor.
- When the *Prompt to save unsaved query changes?* switch is set to *True*, the editor will prompt the user to saved unsaved query modifications when exiting the Query Tool.
- When the *Show View/Edit Data Promotion Warning?* switch is set to *True* View/Edit Data tool will show promote to Query tool confirm dialog on query edit.
- When the *Sort View Data results by primary key columns?* If set to *True*, data returned when using the View/Edit Data - All Rows option will be sorted by the Primary Key columns by default. When using the First/Last 100 Rows options, data is always sorted.
- When the *Underline query at cursor?* switch is set to *True*, query tool will parse and underline the query at the cursor position.


- When the *Underlined query execute warning?* switch is set to *True*, query tool will warn upon clicking the *Execute Query* button in the query tool. The warning will appear only if *Underline query at cursor?* is set to *False*.
- When the *Use server cursor?* switch is set to *True*, the dataset will be fetched using a server-side cursor after the query is executed.



Use the fields on the *Results grid* panel to specify your formatting preferences for copied data.

- When the *Columns sized by* is set to *Column data*, then data columns will auto-size to the maximum width of the data in the column as loaded in the first batch. If set to *Column name*, the column will be sized to the widest of the data type or column name.
- Use *Data result rows per page* to specify the number of records to fetch in one batch. Changing this value will override DATA_RESULT_ROWS_PER_PAGE setting from config file.
- Use the *Max column data display length* to specify the maximum number of characters to be visible in the data output cell. If the data is larger than this value, it will be truncated.
- Use *Maximum column width* to Specify the maximum width of the column in pixels when 'Columns sized by' is set to *Column data*. If 'Columns sized by' is set to *Column name* then this setting won't have any effect.
- Use the *Result copy field separator* drop-down listbox to select the field separator for copied data.
- Use the *Result copy quote character* drop-down listbox to select the quote character for copied data.
- Use the *Result copy quoting* drop-down listbox to select which type of fields require quoting; select *All*, *None*, or *Strings*.
- When the *Copy with headers?* switch is set to true, the column headers are included by default when copying data from the results grid. This can still be toggled per-copy from the results grid copy options menu.


- When the *Striped rows?* switch is set to true, the result grid will display rows with alternating background colors.



Use the fields on the *Keyboard shortcuts* panel to configure shortcuts for the Query Tool window navigation.

1.18.12 The Schema Diff Node

Expand the *Schema Diff* node to specify your display preferences.



Use the *Ignore Grant/Revoke* switch to ignores the grant and revoke command while comparing the objects.


Use the *Ignore Owner* switch to ignores the owner while comparing the objects.

Use the *Ignore Tablespace* switch to ignores the tablespace while comparing the objects.

Use the *Ignore Whitespace* switch to ignores the whitespace while comparing the string objects. Whitespace includes space, tabs, and CRLF.

1.18.13 The Storage Node

Expand the *Storage* node to specify your storage preferences.



Use the fields on the *Options* panel to specify storage preferences.

- Use the *File dialog view* drop-down listbox to select the style of icons and display format that will be displayed when you open the file manager; select *List* to display a list view, or *Grid* to display folder icons.
- Use the *Last directory visited* field to specify the name of the folder in which the file manager will open.
- Use the *Maximum file upload size(MB)* field on the *Options* panel of the **Storage** node to specify the maximum file size for an upload.
- When the *Show hidden files and folders?* switch is set to *True*, the file manager will display hidden files and folders.

Using 'setup.py' command line script

Note

To manage preferences using `setup.py` script, you must use the Python interpreter that is normally used to run pgAdmin to ensure that the required Python packages are available. In most packages, this can be found in the Python Virtual Environment that can be found in the installation directory. When using platform-native packages, the system installation of Python may be the one used by pgAdmin.

1.18.14 Manage Preferences

1.18.15 Get Preferences

To get all the preferences listed, invoke `setup.py` with `get-prefs` command line option. You can also get this mapping by hovering the individual preference in the Preference UI dialog.

```
/path/to/python /path/to/setup.py get-prefs
```

1.18.16 Save Preferences

To save the preferences, invoke `setup.py` with `set-prefs` command line option, followed by username, preference_key=value and auth_source. Multiple preference can be given too by a space separated. If auth_source is not given, Internal authentication will be consider by default.

```
/path/to/python /path/to/setup.py set-prefs user1@gmail.com sqleditor:editor:comma_
↪first=true

# To specify multiple preferences options
/path/to/python /path/to/setup.py set-prefs user1@gmail.com sqleditor:editor:comma_
↪first=true sqleditor:keyboard_shortcuts:toggle_case=true

# to specify an auth_source
/path/to/python /path/to/setup.py set-prefs user1@gmail.com sqleditor:editor:comma_
↪first=true --auth-source=ldap
```

1.18.17 Updating Preferences preferences.json

To update preferences defined in json file, simply run `setup.py `` with ``set-prefs` command followed by username and JSON file containing the preferences.

```
/path/to/python /path/to/setup.py set-prefs user1@gmail.com --input-file /Users/
↪yogeshmahajan/Desktop/pref.json
```

1.18.18 JSON format

The JSON file simply contains preference_key=value. Preference key value mapping can be obtained by hovering the individual preference in the Preference UI dialog.

The following is an typical example for preferences.json :

```
{
    "preferences":
        {
            "browser:display:show_system_objects":  true,
            "browser:display:show_user_defined_templates": true,
            "browser:display:confirm_on_refresh_close": false,
            "misc:user_interface:theme": "dark",

        }
}
```

1.19 Keyboard Shortcuts

Keyboard shortcuts are provided in pgAdmin to allow easy access to specific functions. Alternate shortcuts can be configured through File > Preferences if desired.

1.19.1 Main Browser Window

When using main browser window, the following keyboard shortcuts are available:

Shortcut (Windows/Linux)	Shortcut (Mac)	Function
Shift + Ctrl + a	Shift + Ctrl + a	Add grid row
Shift + Alt + b	Shift + Option + b	Object explorer
Ctrl + Alt + b	Ctrl + Option + b	Toggle Object Explorer
Shift + Alt + n	Shift + Option + n	Create object
Shift + Alt + d	Shift + Option + d	Delete object
Shift + Alt + g	Shift + Option + g	Direct debugging
Shift + Alt + e	Shift + Option + e	Edit object properties
Shift + Alt + f	Shift + Option + f	File main menu
Shift + Alt + h	Shift + Option + h	Help main menu
Shift + Alt + o	Shift + Option + o	Object main menu
Shift + Alt + q	Shift + Option + q	Open query tool
Shift + Ctrl + f	Shift + Ctrl + f	Quick Search
F5	F5	Refresh object explorer
Shift + Alt + s	Shift + Option + s	Search objects
Ctrl + Alt + Page Up	Ctrl + Option + Page Up	Tabbed panel backward
Ctrl + Alt + Page Down	Ctrl + Option + Page Down	Tabbed panel forward
Shift + Alt + w	Shift + Ctrl + w	Close tab panel
Shift + Alt + l	Shift + Option + l	Tools main menu
Shift + Alt + v	Shift + Option + v	View data

1.19.2 Property Grid Controls

Use the shortcuts below when working with property grid controls:

Shortcut for all platforms	Function
Ctrl + Shift + A	Add row in Grid
Tab	Move focus to the next control
Shift + Tab	Move focus to the previous control
Return	Pick the selected an item in a combo box

1.19.3 SQL Editors

When using the syntax-highlighting SQL editors, the following shortcuts are available:

Shortcut (Windows/Linux)	Shortcut (Mac)	Function
Alt + Left	Option + Left	Move to the beginning of the line
Alt + Right	Option + Right	Move to the end of the line
Ctrl + Alt + Left	Cmd + Option + Left	Move left one word
Ctrl + Alt + Right	Cmd + Option + Right	Move right one word
Ctrl + /	Cmd + /	Comment/Uncomment code (Block)
Ctrl + Shift + d	Cmd + Shift + d	Duplicate current line/selection
Ctrl + a	Cmd + a	Select all
Ctrl + c	Cmd + c	Copy selected text to the clipboard
Ctrl + r	Cmd + r	Redo last edit un-done
Ctrl + v	Cmd + v	Paste text from the clipboard
Ctrl + z	Cmd + z	Undo last edit
Tab	Tab	Indent selected text
Shift + Tab	Shift + Tab	Un-indent selected text
Ctrl + l	Cmd + l	Go to line, column
Ctrl + Space	Ctrl + Space	Auto-complete
Ctrl + f	Cmd + f	Find
Ctrl + Shift + f	Option + Cmd + f	Replace

1.19.4 Query Tool

When using the Query Tool, the following shortcuts are available:

Shortcut (Windows/Linux)	Shortcut (Mac)	Function
Ctrl + o	Cmd + o	Open file
Ctrl + s	Cmd + s	Save file
Alt + Shift + n	Option + Shift + n	Edit options
Alt + Shift + f	Option + Shift + f	Sort/Filter
Alt + Shift + i	Option + Shift + i	Filter options
Alt + Shift + q	Option + Shift + q	Cancel query
F5	F5	Execute Script
Alt + Shift + x	Option + Shift + x	Execute options
F7	F7	EXPLAIN query
Shift + F7	Shift + F7	EXPLAIN ANALYZE query
Shift + Ctrl + m	Shift + Ctrl + m	Commit
Shift + Ctrl + r	Shift + Ctrl + r	Rollback
Alt + Ctrl + a	Option + Ctrl + a	Add row
Ctrl + c	Cmd + c	Copy rows
Alt + Shift + p	Option + Shift + p	Paste rows
Alt + Shift + d	Option + Shift + d	Delete rows
F6	F6	Save data changes
Ctrl + Alt + L	Ctrl + option + L	Clear query
F8	F8	Download Results
Shift + Alt +]	Shift + option +]	Next tab
Shift + Alt + [	Shift + option + [	Previous tab

continues on next page

Table 13 – continued from previous page

Shortcut (Windows/Linux)	Shortcut (Mac)	Function
Shift + Alt + Tab	Shift + option + Tab	Switch Panel
Shift + Ctrl + u	Shift + Ctrl + u	Toggle case of selected text

1.19.5 Debugger

When using the Debugger, the following shortcuts are available:

Shortcut (Windows/Linux)	Shortcut (Mac)	Function
Alt + Shift + x	Option + Shift + x	Clear all breakpoints
Alt + Shift + c	Option + Shift + c	Continue/Start
Alt + Shift + i	Option + Shift + i	Step into
Alt + Shift + o	Option + Shift + o	Step over
Alt + Shift + s	Option + Shift + s	Stop
Alt + Shift + t	Option + Shift + t	Toggle breakpoint
Alt + Shift + q	Option + Shift + q	Edit grid values
Alt + Shift +]	Option + Shift +]	Next tab
Alt + Shift + [	Option + Shift +]	Previous tab
Alt + Shift + Tab	Option + Shift + Tab	Switch Panel

1.19.6 ERD Tool

When using the ERD Tool, the following shortcuts are available:


Shortcut (Windows/Linux)	Shortcut (Mac)	Function
Ctrl + Alt + a	Ctrl + option + a	Add table
Ctrl + Alt + n	Ctrl + option + n	Add/Edit note
Ctrl + Alt + l	Ctrl + option + l	Auto align
Ctrl + Alt + c	Ctrl + option + c	Clone table
Ctrl + Alt + i	Ctrl + option + i	Download image
Ctrl + Alt + d	Ctrl + option + d	Drop table
Ctrl + Alt + e	Ctrl + option + e	Edit table
Ctrl + Alt + s	Ctrl + option + s	Generate SQL
Ctrl + Alt + m	Ctrl + option + m	Many to many link
Ctrl + Alt + o	Ctrl + option + o	One to many link
Ctrl + o	Ctrl + o	Open project
Ctrl + s	Ctrl + s	Save project
Shift + Ctrl + s	Shift + Ctrl + s	Save project as
Ctrl + Alt + t	Ctrl + option + t	Show more/fewer details
Shift + Alt + +	Shift + option + +	Zoom in
Shift + Alt + -	Shift + option + -	Zoom out
Shift + Alt + f	Shift + option + f	Zoom to fit

1.19.7 Inner Tab and Panel Navigation

When using the Query Tool and Debugger, the following shortcuts are available for inner panel navigation:

Shortcut (Windows/Linux)	Shortcut (Mac)	Function
Alt + Shift +]	Option + Shift +]	Move to next tab within a panel
Alt + Shift + [	Option + Shift + [	Move to previous tab within a panel
Alt + Shift + Tab	Option + Shift + Tab	Move between inner panels

1.20 Search objects



With this dialog, you can search for almost any kind of objects in a database.

You can access it by right clicking a database or any of its child nodes and select “Search objects”. You can also access it by hitting the shortcut (default ALT+SHIFT+S).

The minimum pattern length are 3 characters. The search performed is non-casesensitive and will find all objets whose name contains the pattern. You can only search for object names currently. Examples are: abc, %ab%, ab%c, %%%, etc.

The result is presented in the grid with object name, object type and the object path in the *object explorer*. You can double click on a result row to select the object in the *object explorer*. If the object is greyed out, this means that you have not enabled those object types in the *preferences*, so you can't double click on it. You can click on the ellipsis appended to the function and procedure names to see their arguments.

You can filter based on a particular object type by selecting one from the object type dropdown. If the search button is hit when one of the object type is selected then only those types will be fetch from the database. An object type will not be visible in the dropdown if the database server does not support it or if it is not enabled from the *preferences*.

Before using pgAdmin to manage objects that reside on a server, you must define a connection to the server; for more information please see *Connecting to a Server* in the next section.

CHAPTER 2

External database for pgAdmin user settings

The user settings used by pgAdmin are stored in a SQLite database. In this database, many settings are stored, such as preferences, user accounts, auto-discovered servers, and many more.

As SQLite is a file-based database and it can be anywhere in the file system, so it is not designed to take care of failures (no HA support). Furthermore, it isn't designed to handle multiple connections concurrently reading/writing data to it. Example: In environments such as Kubernetes it may be useful to use an alternate backend to avoid using SQLite on non-ephemeral storage and to allow HA of the settings database.

In order to prevent this, pgAdmin now supports storing user settings in an external database using the new 'CONFIG_DATABASE_URI' parameter in the *config.py* file.

2.1 Use SQLite Database

In order to use SQLite Database, make sure CONFIG_DATABASE_URI parameter is set to an empty string like ''. By default it is set to an empty string in the config.py so if you would like to use SQLite database then no need to change anything.

2.2 Use External Database

In order to use an external database, make sure CONFIG_DATABASE_URI parameter is set like "dialect+driver://username:password@host:port/database".

Note It is recommended to create the database in advance.

2.3 Use PostgreSQL Database

Following are the formats to use PostgreSQL as an external database.

Basic syntax:

```
postgresql://username:password@host:port/database
```

Using specific schema (It is recommended to create the schema in advance):

```
postgresql://username:password@host:port/database?options=-csearch_path=<schema name>
```

Using default pgpass path for the service account:

```
postgresql://username@host:port?options=-csearch_path=<schema name>
```

Specifying pgpass file path:

```
postgresql://username@host:port?passfile=<path of the pgpass file>&options=-csearch_path=
↪<schema name>
```


CHAPTER 3

Connecting To A Server

Before you can use the pgAdmin client to manage the objects that reside on your Postgres server, you must define a connection to the server. You can (optionally) use the *Server Group* dialog to create server groups to organize the server connections within the tree control for easier management. To open the *Server Group* dialog, right-click on the *Servers* node of the tree control, and select *Server Group* from the *Create* menu.

3.1 Server Group Dialog

Use the *Server Group* dialog to add a new server group. Assign servers to server groups to simplify management of multiple servers. Server groups are displayed as part of the *pgAdmin* tree control.



Use the *Name* field on the *Server Group* dialog to specify a name that will identify the server group in the *pgAdmin* tree control.


- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

To create server connections in a server group, right click on the named server group and select the *Create* option to open the *Create - Server* dialog.

Use the fields on the *Server* dialog to define the connection properties for each new server that you wish to manage with pgAdmin. To open the *Server* dialog, right-click on the *Servers* node of the tree control, and select *Server* from the *Register* menu.

3.2 Server Dialog

Use the *Server* dialog to describe a connection to a server. Note: you must ensure that the pg_hba.conf file of the server from which you are connecting allows connections from the host of the client.



Use the fields in the *General* tab to identify the server:

- Use the *Name* field to add a descriptive name for the server; the name specified will be displayed in the *Object Explorer*.
- Use the drop-down list box in the *Server group* field to select the parent node for the server; the server will be displayed in the *Object Explorer* control within the specified group.
- Use the color-picker in the *Background* field to specify the background color for the server.
- Use the color-picker in the *Foreground* field to specify the foreground color for the server.
- If the *Connect now?* checkbox is checked, the client will attempt a connection to the server upon completion of the dialog; this is the default
- If the *Shared?* switch is moved to *Yes* then that server can be shared with all the other users. This option is available only to admin users. For more information on users see *User Management Dialog*. Sharing a server, whether in this dialog, through the API or by importing a servers.json file, is restricted to users with the *Administrator* role. Servers that were shared by non-administrator users before this restriction was introduced remain shared until they are un-shared, so administrators should audit them: look for servers with the shared flag set in the configuration database whose owner does not have the *Administrator* role. pgAdmin logs a warning for each such server when it starts in server mode. Such a server can be un-shared by its owner through the server API (a PUT request on the server with `"shared": false`), or by an administrator changing the `shared` column of the server record in the pgAdmin configuration database. The *Shared?* switch in this dialog is shown only

to administrators, and only the owner of a server can change it. Users can access the shared servers with some restrictions - the following operations on shared servers are not permitted:


- Delete the server
- Rename the server
- Rename the group server
- Change of host, port, and maintenance database

Each user of a shared server has their own copy of some of its settings. Tags, colours, the role and the service name are copied from the owner the first time a user opens the server, and each user can then change their copy. The host, port, maintenance database and the general connection parameters (such as *connect_timeout* or *sslmode*) always come from the owner's server definition, so a change the owner makes to them is seen by every user. The owner's password, SSH tunnel credentials, SSL certificate, key and CRL paths, and password file (*passfile*) are never shared: each user must supply their own in the server dialog if they need them.

Please note that once the server is shared, it's icon is changed in the object explorer.

- Use the *Shared Username* field to fill the username of the shared server connection. By default, it will take the username of the server being shared.
- Provide a comment about the server in the *Comments* field.

Click the *Connection* tab to continue.




Use the fields in the *Connection* tab to configure a connection:

- Specify the IP address of the server host, or the fully qualified domain name in the *Host name/address* field. If you provide a unix domain socket, the directory name must begin with a "/".
- Enter the listener port number of the server host in the *Port* field. The default is *5432*.
- Use the *Maintenance database* field to specify the name of the initial database to which the client will connect. If you will be using pgAgent or adminpack objects, the pgAgent schema and adminpack objects should be installed on that database.
- Use the *Username* field to specify the name of a role that will be used when authenticating with the server.
- When *Kerberos authentication?* is set to *True*, pgAdmin will try to connect the PostgreSQL server using Kerberos authentication.

- Use the *Password* field to provide a password that will be supplied when authenticating with the server.
- Check the box next to *Save password?* to instruct pgAdmin to save the password for future use. Use *Clear Saved Password* to remove the saved password.
- Use the *Role* field to specify the name of a role that has privileges that will be conveyed to the client after authentication with the server. This selection allows you to connect as one role, and then assume the permissions of this specified role after the connection is established. Note that the connecting role must be a member of the role specified.
- Use the *Service* field to specify the service name. For more information, see Section 33.16 of the Postgres documentation.

  In server mode, services are read from the connection service file of the account that pgAdmin runs as, so a server can use only a service that the administrator has listed in the `SERVER_MODE_ALLOWED_SERVICES` setting (see *Configuration Files*), which is empty by default. A server that uses any other service cannot be saved, and an existing one fails to connect with an error naming the setting. Listing a service shares its credentials, such as a password in its entry, with every pgAdmin user. The `servicefile` connection parameter cannot be used in server mode, and pgAdmin ignores any `PGPASSWORD` or `PGSERVICE` environment variable set for the account it runs as.

Click the *Parameters* tab to continue.



Use the fields in the *Parameters* tab to configure a connection:

Click on the + button to add a new parameter. Some of the parameters are:

- *Host address* using this field to specify the host IP address may save time by avoiding a DNS lookup on connection, but it may be useful to specify both a host name and address when using Kerberos, GSSAPI, or SSPI authentication methods, as well as for verify-full SSL certificate verification.
- *Password File* field to specify the location of a password file (.pgpass). A .pgpass file allows a user to login without providing a password when they connect. For more information, see Section 33.15 of the Postgres documentation.
- *Connection timeout* field to specify the maximum wait for connection, in seconds. Zero or not specified means wait indefinitely. It is not recommended to use a timeout of less than 2 seconds. By default it is set to 10 seconds.
- *Require authentication* (*require_auth*) field to specify the authentication methods the server may use. In server mode, pgAdmin refuses the GSSAPI and SSPI methods for a connection that may not use Kerberos, as described

in *Enabling Kerberos Authentication*.

- *SSL mode* field to select the type of SSL connection the server should use. For more information about using SSL encryption, see Section 33.18 of the Postgres documentation.

If pgAdmin is installed in Server mode (the default mode), you can use the platform-specific File manager dialog to upload files that support SSL encryption to the server. To access the File manager dialog, click the icon that is located to the right of each of the following fields.

- *Client certificate* field to specify the file containing the client SSL certificate. This file will replace the default *~/.postgresql/postgresql.crt* if pgAdmin is installed in Desktop mode, and *<STORAGE_DIR>/<USERNAME>/.postgresql/postgresql.crt* if pgAdmin is installed in Web mode. This parameter is ignored if an SSL connection is not made.
- *Client certificate key* field to specify the file containing the secret key used for the client certificate. This file will replace the default *~/.postgresql/postgresql.key* if pgAdmin is installed in Desktop mode, and *<STORAGE_DIR>/<USERNAME>/.postgresql/postgresql.key* if pgAdmin is installed in Web mode. This parameter is ignored if an SSL connection is not made.
- *Root certificate* field to specify the file containing the SSL certificate authority. This file will replace the default *~/.postgresql/root.crt*. This parameter is ignored if an SSL connection is not made.
- *Certificate revocation list* field to specify the file containing the SSL certificate revocation list. This list will replace the default list, found in *~/.postgresql/root.crl*. This parameter is ignored if an SSL connection is not made.
- *SSL compression?* is set to *True*, data sent over SSL connections will be compressed. The default value is *False* (compression is disabled). This parameter is ignored if an SSL connection is not made.


Warning

In Server mode, certificates, private keys, and the revocation list are stored in the per-user file storage area on the server, which is owned by the user account under which the pgAdmin server process is run. This means that administrators of the server may be able to access those files; appropriate caution should be taken before choosing to use this feature.

Note

In Server mode, every connection file path (the *Password file*, client certificate and key, root certificate, certificate revocation list, CRL directory and SSL key log file) must resolve inside your storage directory, or inside a *SHARED_STORAGE* entry (see *Configuration Files*) written as *Name:/path*. A path that leaves it through .. or a symbolic link is refused with an "Access denied (…): the path resolves outside your storage directory…" message when connecting or starting a utility. If you used a symbolic link in your storage directory to reach, for example, */etc/pgadmin/certs*, configure that directory as a *SHARED_STORAGE* entry instead (see *Storage Manager*). Every pgAdmin user can use a file in shared storage, so it should hold only shareable files such as a root certificate or CRL, never a private key or a *.pgpass* file.

Click the *SSH Tunnel* tab to continue.




Use the fields in the *SSH Tunnel* tab to configure SSH Tunneling:

You can use the "SSH Tunnel" tab to connect pgAdmin (through an intermediary proxy host) to a server that resides on a network to which the client may not be able to connect directly.

- Set "Use SSH tunneling" to *Yes* to specify that pgAdmin should use an SSH tunnel when connecting to the specified server.
- Specify the name or IP address of the SSH host (through which client connections will be forwarded) in the *Tunnel host* field.
- Specify the port of the SSH host (through which client connections will be forwarded) in the *Tunnel port* field.
- Specify the name of a user with login privileges for the SSH host in the *Username* field.
- Specify the type of authentication that will be used when connecting to the SSH host in the *Authentication* field:
  - Select the *Password* option to specify that pgAdmin will use a password for authentication to the SSH host. This is the default.
  - Select the *Identity file* to specify that pgAdmin will use a private key file when connecting.
- If the SSH host is expecting a private key file for authentication, use the *Identity file* field to specify the location of the key file. In server mode, pgAdmin does not use the private keys, ssh-agent or `~/.ssh/config` of the account pgAdmin runs as; the identity file must be located inside your storage directory.
- If the SSH host is expecting a password of the user name or an identity file if being used, use the *Password* field to specify the password.
- Check the box next to *Prompt for password?* to to have pgAdmin prompt for a password if the identity file includes one. This setting applies only when using an identity file, which may or may not require a password.
- Check the box next to *Save password?* to instruct pgAdmin to save the password for future use. Use *Clear SSH Tunnel Password* to remove the saved password.
- Use the *Keep alive* field to specify interval in seconds defining the period in which, if no data was sent over the connection, a 'keepalive' packet will be sent (and ignored by the remote host). This can be useful to keep

connections alive over a NAT. You can set to 0 for disable keepalive.

Click the *Advanced* tab to continue.



Use the fields in the *Advanced* tab to configure a connection:

- Specify the type of the database restriction that will be used to filter out the databases for restriction in the *DB restriction type* field:
  - Select the *Databases* option to specify the name of the databases that will be used against the pg_database table to limit the databases that you see. This is the default.
  - Select the *SQL* option to provide a SQL restriction that will be used against the pg_database table to limit the databases that you see.
- Use the *DB restriction* field to provide a SQL restriction OR Database names that will be used against the pg_database table to limit the databases that you see. For example, you might enter: *live_db test_db* so that only live_db and test_db are shown in the pgAdmin object explorer.
- In desktop mode, use the *Password exec command* field to specify a shell command to be executed to retrieve a password to be used for SQL authentication. The `stdout` of the command will be used as the SQL password. This may be useful when the password should be generated as a transient authorization token instead of providing a password when connecting in PAM authentication scenarios. You can pass server hostname, port and DB username to the password exec command as variable by providing placeholders like `%HOSTNAME%`, `%PORT%` and `%USERNAME%` which will be replace with the server connection information. Example: `/path/to/script --hostname %HOSTNAME% --port %PORT% --username %USERNAME%`
- In server mode, use the *Password exec command* drop-down list to select one of the commands that the administrator has defined in the `SERVER_PASSEXEC_COMMANDS` setting (see *Configuration Files*). Users cannot enter their own command. The list offers *None* and each configured command name, and is hidden if no commands have been configured. On a shared server, users who do not own the server also see *Inherit from owner*, which is the default for them and uses whatever command the owner has selected; selecting *None* or a named command overrides it for that user only. If a selected command is later removed from the configuration, the server is treated as having no command and a warning is logged.

  The command is run directly, without a shell, and does not receive the full environment of the pgAdmin process. Only `PATH`, `HOME`, `LANG`, `LANGUAGE`, `TZ`, `TMPDIR`, `TMP`, `TEMP`, `USER`, `LOGNAME` and any `LC_*` variable are passed through (and, on Windows, `SYSTEMROOT`, `SYSTEMDRIVE`, `PATHEXT`, `COMSPEC` and `WINDIR`), together with any variables the administrator has named in the `SERVER_PASSEXEC_ENV_PASSTHROUGH` setting. The command also

receives the following variables describing the connection, which take precedence over any variable of the same name: `PGADMIN_PASSEXEC_HOST`, `PGADMIN_PASSEXEC_PORT`, `PGADMIN_PASSEXEC_USERNAME` (the username that connection uses, so a non-owner's own username on a shared server), `PGADMIN_PASSEXEC_DATABASE` (the maintenance database), `PGADMIN_PASSEXEC_PGADMIN_USER` (the pgAdmin user making the connection) and `PGADMIN_PASSEXEC_AUTH_SOURCE` (how that user authenticated to pgAdmin). The following variables describe the server definition itself:

  - `PGADMIN_PASSEXEC_SHARED` is `true` if the server is shared and owned by another pgAdmin user, and `false` otherwise, including when the user making the connection owns a shared server.
  - `PGADMIN_PASSEXEC_SERVER_ID` is the numeric id pgAdmin gave the server.
  - `PGADMIN_PASSEXEC_SERVER_OWNER` and `PGADMIN_PASSEXEC_SERVER_OWNER_AUTH_SOURCE` are the username of the pgAdmin user who owns the server, and how that user authenticates.
  - `PGADMIN_PASSEXEC_SERVER_GROUP` is the name of the owner's server group that holds the server. A user who does not own a shared server can change the group it appears in for them, but this variable always gives the owner's group, which is the one checked against `OAUTH2_SERVER_GROUP_CLAIM` (see *Restricting Shared Servers with a Claim*); for an OAuth2 user restricted by that claim, it is therefore the group that granted access to the server.

  The `stdout` of the command is used as the SQL password.

- Use the *Password exec expiration* field to specify a maximum age, in seconds, of the password generated with a *Password exec command*. In server mode, this field is enabled only when a named command is selected. If not specified, the password will not expire until your pgAdmin session does. Zero means the command will be executed for each new connection or reconnection that is made. If the generated password is not valid indefinitely, set this value to slightly before it will expire.
- Use the *Prepare threshold* field to specify the number of times a query is executed before it is prepared. If it is set to 0, every query is prepared the first time it is executed. If it is set to blank, prepared statements are disabled on the connection. This is particularly useful with external connection poolers, such as PgBouncer, which is not compatible with prepared statements. Set this to blank in such cases.

Note

The password file option is only supported when pgAdmin is using libpq v10.0 or later to connect to the server.

Note


In server mode, the *Password exec command* setting is available only when the administrator has defined at least one command in `SERVER_PASSEXEC_COMMANDS`. Free-text commands are never run in server mode, and when pgAdmin is upgraded, an existing free-text command is kept only if it exactly matches a configured command (its arguments joined by single spaces), in which case it is converted to that command's name; all others are cleared and a warning is logged. This conversion cannot be undone, so `SERVER_PASSEXEC_COMMANDS` must be configured before the first start after upgrading. If it is still empty at that point, the conversion is postponed: existing commands are left in the configuration database unused, a warning giving the number of affected servers is logged at each start, and they are converted or cleared on the first start at which at least one command is configured. Placeholders such as `%HOSTNAME%`, `%PORT%` and `%USERNAME%` are not substituted in server mode, so a command containing them is converted only if the configured arguments contain the same literal text. On a shared server, a user who does not own the server and whose own command is cleared will then inherit the owner's command, if the owner has one. The `ENABLE_SERVER_PASS_EXEC_CMD` setting is deprecated and ignored.

Warning

In server mode, only PGADMIN_PASSEXEC_PGADMIN_USER and PGADMIN_PASSEXEC_AUTH_SOURCE identify the pgAdmin user on whose behalf the command is run. PGADMIN_PASSEXEC_HOST, PGADMIN_PASSEXEC_PORT, PGADMIN_PASSEXEC_USERNAME and PGADMIN_PASSEXEC_DATABASE are set by whoever edits the server definition; on a shared server, a user who does not own the server sets their own username. Commands should therefore decide whether to issue a password based on the pgAdmin identity, and treat the other four variables as untrusted input.


The PGADMIN_PASSEXEC_SHARED, PGADMIN_PASSEXEC_SERVER_ID, PGADMIN_PASSEXEC_SERVER_OWNER, PGADMIN_PASSEXEC_SERVER_OWNER_AUTH_SOURCE and PGADMIN_PASSEXEC_SERVER_GROUP variables cannot be changed by a user who does not own the server. When PGADMIN_PASSEXEC_SHARED is `true`, the server is shared and owned by another user. Only an administrator can share a server, but a server shared before that restriction was introduced may be owned by any user, so this flag is not proof that the owner is an administrator. On a shared server, PGADMIN_PASSEXEC_HOST, PGADMIN_PASSEXEC_PORT and PGADMIN_PASSEXEC_DATABASE are taken from the owner's server, not from the copy kept for each user, whilst PGADMIN_PASSEXEC_USERNAME is each user's own. Every user owns their own server groups and may give them any name, including the name of an administrator's group, so the server group proves nothing on its own: check PGADMIN_PASSEXEC_SHARED and the owner as well. Commands should decide whether to issue a password based on the pgAdmin user and the server owner. When PGADMIN_PASSEXEC_SHARED is `false` and the owner is the user making the connection, every value was set by that user.

Click the *Post Connection SQL* tab to continue.



- Use the *Post Connection SQL* field to write the SQL queries that will be executed in autocommit mode for each connection made to any database on this server.

Click the *Tags* tab to continue.



Use the table in the *Tags* tab to add tags. The tags will be shown on the right side of a server node label in the object explorer tree.


Click on the + button to add a new tag. Some of the parameters are:

- *Text* field to specify the tag name.
- *Color* field to select the accent color of the tag.

- Click the *Save* button to save your work.
- Click the *Close* button to exit without saving your work.
- Click the *Reset* button to return the values specified on the Server dialog to their original condition.


3.2.1 Clear Saved Passwords

Use *Clear Saved Password* functionality to clear the saved password for the database server.



Clear Saved Password shows in the context menu for the selected server as well as under the *Object* menu on the top menu bar.

Use *Clear SSH Tunnel Password* functionality to clear the saved password of SSH Tunnel to connect to the database server.



Clear SSH Tunnel Password shows in the context menu for the selected server as well as under the *Object* menu on the top menu bar.

Note: It will be enabled/visible when the password for the selected database server is already saved.

Alternatively you can use the *Cloud Deployment* wizard to deploy a new PostgreSQL instance in the cloud, and connect to it.


3.3 PostgreSQL Cloud Deployment

A PostgreSQL server can be deployed on the Amazon, Azure, Google cloud or pgEdge Starfleet using this module. In future more cloud provider options will be available.


To launch the *Cloud Deployment...* tool, right click on the *Server Group* or *Server* of the tree control, and select *Deploy a Cloud Instance* from the *Register* menu.

3.3.1 Amazon RDS Cloud Deployment

To deploy a PostgreSQL server on the Amazon cloud, follow the below steps.




Once you launch the tool, select the Amazon RDS option. Click on the *Next* button to proceed further.




In the Credentials dialog, provide the region in which you want to deploy the instance along with the *AWS access key* and *AWS secret access key*. Provide *AWS session token* only if your AWS session is temporary.

To proceed further, click on the next button. Before going further, pgAdmin will validate your credentials.




Use the fields from the Instance Specification tab to specify the Instance details.

- Use the *Instance name* field to add an instance name for the PostgreSQL server; the name specified will be displayed in the *Object Explorer* too.
- Use the *Public IP* field to specify the IP Address range for permitting the inbound traffic.
- Use the *Database version* field to specify the PostgreSQL version to deploy.
- Use the *Instance class* field to allocate the computational, network, and memory capacity required by planned workload of this DB instance.
- Use the *Instance type* field to select the instance type.
- Use the *Storage type* field to select the instance storage type. Three options are available. General Purpose (SSD) storage, Provisioned IOPS (SSD) and Magnetic storage.
- Use the *Allocated storage* field to specify the storage capacity in GiB.
- Use the *Provisioned IOPS* in case of Provisioned IOPS (SSD) storage type.
- Use the *High Availability* option to specify High Availability option. This option creates a standby in a different Availability Zone(AZ).




Use the fields from the Database Details tab to specify the Instance details.

- Use the drop-down list box in the *Server group* field to select the parent node for the server; the server will be displayed in the *Object Explorer* within the specified group.
- Use the *Database name* field to add the database name for the PostgreSQL server.
- Use the *Username* field to specify the name of a role that will be used when authenticating with the server.
- Use the *Password* field to provide a password that will be supplied when authenticating with the server.
- Use the *Confirm password* field to repeat the password.
- Enter the listener port number of the server host in the *Port* field.



At the end, review the Instance details that you provided. Click on Finish button to deploy the instance on Amazon RDS.




Once you click on the finish, one background process will start which will deploy the instance in the cloud and monitor the progress of the deployment. You can view all the background processes with their running status and logs on the *Processes* tab.


The Server will be added to the tree with the cloud deployment icon. Once the deployment is done, the server details will be updated.

3.3.2 Azure Database Cloud Deployment

To deploy a PostgreSQL server on the Azure Database, follow the below steps.



Once you launch the tool, select the Azure Database option. Click on the *Next* button to proceed further.




In the Credentials dialog, select authentication method either interactive browser or Azure CLI. Azure CLI will use the currently logged in identity through the Azure CLI on the local machine. Interactive Browser will open a browser window to authenticate a user interactively.

Use the *Azure tenant* id to specify Azure tenant ID against which user is authenticated.


Clicking the *Click here to authenticate yourself to Microsoft Azure* button, user will be redirected to the Microsoft Azure authentication page in a new browser tab if the Interactive Browser option is selected. Azure CLI authentication can be used only in Desktop mode.

Once authentication is completed, click on the next button to proceed.




Use the fields from the Instance Specification tab to specify the Instance details.

- Use the *Cluster name* field to add a name for the PostgreSQL server; the name specified will be displayed in the *Object Explorer* too.
- Select a subscription from the *Subscription* options which are populated based on user access levels in Azure portal.
- Select the resource group from *Resource Group* dropdown under which the PostgreSQL instance will be created.
- Select the location to deploy PostgreSQL instance from *Location* options.
- Select the availability zone in specified region to deploy PostgreSQL instance from *Availability zone* options.
- Use *Database version* options to specify PostgreSQL database version.
- Use the *Instance class* field to allocate the computational, network, and memory capacity required by planned workload of this DB instance.
- Use the *Instance type* field to select the instance type.
- Use the *Storage size* option to specify the storage capacity.




- Use the *Public IP* field to specify the List of IP Addresses or range of IP Addresses (start IP Address - end IP address) from which inbound traffic should be accepted. Add multiple IP addresses/ranges separated with commas, for example: "192.168.0.50, 192.168.0.100 - 192.168.0.200"
- Use *Zone redundant high availability* option to specify High Availability option. Zone redundant high availability deploys a standby replica in a different zone. The Burstable instance type does not support high availability.



Use the fields from the Database Details tab to specify the PostgreSQL database details.


- Use the drop-down list in the *pgAdmin server group* field to select the parent node for the server; the server will be displayed in the *Object Explorer* within the specified group.
- Use the *Admin username* field to add the database name for the PostgreSQL server.
- Use the *Password* field to provide a password that will be supplied when authenticating with the server.
- Use the *Confirm password* field to repeat the password.

Click on the next button to proceed.




At the end, review the instance details that you provided. Click on Finish button to deploy the instance on Azure Database.

Once you click on the finish, one background process will start which will deploy the instance in the cloud and monitor the progress of the deployment. You can view all the background processes with their running status and logs on the *Processes* tab.




The Server will be added to the tree with the cloud deployment icon. Once the deployment is done, the server details will be updated.




3.3.3 Google Cloud SQL Deployment

To deploy a PostgreSQL server on the Google Cloud SQL, follow the below steps.



Once you launch the tool, select the Google Cloud SQL option. Click on the *Next* button to proceed further.




In the Credentials dialog, select client secret file to authenticate using google.You can download a client secret which is json formatted file from google cloud console once OAuth2 client ID is created.

Note

While creating client OAuth client ID, select Desktop App as application type. Refer this link for creating client secret.


Clicking the *Click here to authenticate yourself to Google* button, user will be redirected to the Google authentication page in a new browser tab.

Once authentication is completed, click on the next button to proceed.




Use the fields from the Instance Specification tab to specify the Instance details.

- Use the *Cluster name* field to add a name for the PostgreSQL server; the name specified will be displayed in the *Object Explorer* too.
- Select the project from *project* dropdown under which the PostgreSQL instance will be created.
- Select the location to deploy PostgreSQL instance from *Location* options.
- Select the availability zone in specified region to deploy PostgreSQL instance from *Availability zone* options.
- Use *Database version* options to specify PostgreSQL database version.
- Use the *Instance class* field to allocate the computational and memory capacity required by planned workload of this DB instance.
- Use the *Instance type* field to select the instance type.
- Specify storage type by selecting option from *Storage type*.
- Use the *Storage capacity* option to specify the storage capacity.




- Use the *Public IP* field to specify the list of IP address range for allowed inbound traffic, for example: 127.0.0.1/32. Add multiple IP addresses/ranges separated with commas.
- Use the *High Availability* option to specify High Availability option. This option creates a standby in a select Secondary Availability Zone.
- Select the secondary availability zone for high availability from *Secondary Availability zone* options.



Use the fields from the Database Details tab to specify the PostgreSQL database details.

- Use the drop-down list in the *pgAdmin server group* field to select the parent node for the server; the server will be displayed in the *Object Explorer* within the specified group.
- Admin username field will be default to postgres. server.
- Use the *Password* field to provide a password that will be supplied when authenticating with the server.
- Use the *Confirm password* field to repeat the password.


Click on the next button to proceed.



At the end, review the instance details that you provided. Click on Finish button to deploy the instance on Azure PostgreSQL.


Once you click on the finish, one background process will start which will deploy the instance in the cloud and monitor the progress of the deployment. You can view all the background processes with their running status and logs on the *Processes* tab.

The Server will be added to the tree with the cloud deployment icon. Once the deployment is done, the server details will be updated.




3.3.4 pgEdge Starfleet Deployment

To deploy a PostgreSQL database on pgEdge Starfleet, follow the steps below. pgAdmin creates a *Managed* database, which Starfleet hosts for you.




Once you launch the tool, select the pgEdge Starfleet option and click on the *Next* button to proceed.



In the Credentials step, enter the *Auth ID* and *Auth secret* of a Starfleet API client. pgAdmin checks them with Starfleet when you click *Next*.


Note

Create the API client in the pgEdge Starfleet console, under *Settings* > *API Clients*. The Auth secret is shown only when the client is created, so keep a copy of it. See the pgEdge Starfleet documentation for details.




Use the fields from the Instance Specification step to specify the database details.

- Use the *Database name* field to name the database. The name may contain lowercase letters and digits only, must start with a letter, and can be up to 50 characters long.
- Use the *Display name* field to optionally set a friendlier name, up to 25 characters long.
- Select the location to deploy the database to from the *Region* field.
- Use the *Size* field to select the size of the database.
- Use the *PostgreSQL version* field to select the PostgreSQL version.
- Use the *Allowed IP addresses* field to list the IPv4 addresses or CIDR ranges that may connect to the database, separated by commas. The field is prefilled with your public IP address. At least one and at most 50 entries are required; IPv6 addresses are not accepted. Without a matching entry the database will not accept connections from pgAdmin.
- Use the *Connect as* field to choose whether pgAdmin connects as *admin* (the database administrator, which is not a superuser) or *app* (an application user).




In the Database Details step, use the *pgAdmin server group* field to select the server group the new server will be registered in.



Finally, review the summary in the Review step and click *Finish* to start the deployment. The progress of the deployment is shown in the same way as for the other cloud providers, and the new server is added to the *Object Explorer* when the database is available. pgAdmin connects with *sslmode* set to *require* and *gssencmode* set to *disable*.

If the deployment fails after the database has been created, for example because pgEdge Starfleet reports it as failed or it does not become available within 30 minutes, pgAdmin removes the server from the *Object Explorer* but does not delete the database. Check the pgEdge Starfleet console, and delete the database there if it is not needed.



pgEdge Starfleet generates the database password. When the deployment finishes, pgAdmin shows it once in the *pgEdge*

Starfleet database password dialog, together with the host and user name.

- Use the *Copy* button to copy the password to the clipboard.
- Use the *Save password* button to save the password with the server. This button is only shown if saving passwords is permitted by the *ALLOW_SAVE_PASSWORD* setting.

The password is not shown again in pgAdmin after the dialog is closed. If you lose it, reset it from the pgEdge Starfleet console.

Note

pgAdmin contacts the Starfleet API at the address given by the *STARFLEET_API_URL* configuration setting, which defaults to *https://api.pgedge.com*. The address must use HTTPS.

A master password is required to secure and later unlock saved server passwords. It is set by the user and can be disabled using config.


3.4 Master Password

Note

pgAdmin 4 uses the operating system password store by default to store the saved server passwords in desktop mode from version 7.2 onwards and Master password will not be required. If the operating system password store is not available then pgAdmin 4 will continue to use a master password as per the configuration settings.

A master password is required to secure and later unlock the saved server passwords. This is applicable for desktop mode and in server mode if authentication source contains OAuth2 or Kerberos or Webserver.

- You are prompted to enter the master password when you open the window for the first time after starting the application.
- Once you set the master password, all the existing saved passwords will be re-encrypted using the master password.
- The server passwords which are saved in the SQLite DB file or External Database are encrypted and decrypted using the master password.



Note

pgAdmin aims to be **secure by default**, however, you can disable the master password by setting the configuration parameter *MASTER_PASSWORD_REQUIRED=False*. See *Configuration Files* for more information on configuration parameters and how they can be changed or enforced across an organisation.

Note


If the master password is disabled, then all the saved passwords will be removed.

Warning


If the master password is disabled, then the saved passwords will be encrypted using a key which is derived from information within the configuration database. Use of a master password ensures that the encryption key does not need to be stored anywhere, and thus prevents possible access to server credentials if the configuration database becomes available to an attacker.

It is **strongly** recommended that you use the master password if you use the *Save Password* option.

- The master password is not stored anywhere on the physical storage. It is temporarily stored in the application memory and it does not get saved when the application is restarted.
- You are prompted to enter the master password when pgAdmin server is restarted.



- If you forget the master password, you can use the *Reset Master Password* button to reset the password.



Warning

Resetting the master password will also remove all saved passwords and close all existing established connections.

After defining a server connection, right-click on the server name, and select *Connect to server* to authenticate with

the server, and start using pgAdmin to manage objects that reside on the server.

3.5 Connect to Server


Use the *Connect to Server* dialog to authenticate with a defined server and access the objects stored on the server through the pgAdmin tree control. To access the dialog, right click on the server name in the *pgAdmin* tree control, and select *Connect Server...* from the context menu.



Provide authentication information for the selected server:

- Use the *Password* field to provide the password of the user that is associated with the defined server.
- Check the box next to *Save Password* to instruct the server to save the password for future connections; if you save the password, you will not be prompted when reconnecting to the database server with this server definition.

When using SSH Tunneling, the *Connect to Server* dialog will prompt for the SSH Tunnel and Database server passwords if not already saved.



Provide authentication information for the selected server:

- Use the *Password* field to provide the password of the user that is associated with the defined server.
- Check the box next to respective *Save Password* to instruct the server to save the password for future connections; if you save the password, you will not be prompted when reconnecting to the database server with this server definition.

The pgAdmin client displays a message in a green status bar in the lower right corner when the server connects successfully.


If you receive an error message while attempting a connection, verify that your network is allowing the pgAdmin host and the host of the database server to communicate. For detailed information about a specific error message, please see the *Connection Error* help page.

To review or modify connection details, right-click on the name of the server, and select *Properties...* from the context menu.

3.6 Connection Error


When connecting to a PostgreSQL server, you may get an error message. If you encounter an error message, please review the message carefully; each error message attempts to incorporate the information you'll need to resolve the problem. For more details about specific errors, please locate the error message in the list below:

Connection to the server has been lost



This error message indicates that the connection attempt has taken longer than the specified threshold; there may be a problem with the connection properties provided on the *Server* dialog, network connectivity issues, or the server may not be running.

could not connect to Server: Connection refused




If pgAdmin displays this message, there are two possible reasons for this:

- the database server isn't running - simply start it.
- the server isn't configured to accept TCP/IP requests on the address shown.

For security reasons, a PostgreSQL server "out of the box" doesn't listen on TCP/IP ports. Instead, it must be enabled to listen for TCP/IP requests. This can be done by adding **listen_addresses='*'**; this will make the server accept connections on any IP interface.

For further information, please refer to the PostgreSQL documentation about runtime configuration.

FATAL: no pg_hba.conf entry




If pgAdmin displays this message when connecting, your server can be contacted correctly over the network, but is not configured to accept your connection. Your client has not been detected as a legal user for the database.

To connect to a server, the pg_hba.conf file on the database server must be configured to accept connections from the host of the pgAdmin client. Modify the pg_hba.conf file on the database server host, and add an entry in the form:

- **host template1 postgres 192.168.0.0/24 md5** for an IPV4 network
- **host template1 postgres ::ffff:192.168.0.0/120 md5** for an IPV6 network

For more information, please refer to the PostgreSQL documentation about client authentication.

FATAL: password authentication failed



The *password authentication failed for user* error message indicates there may be a problem with the password you entered. Retry the password to confirm you entered it correctly. If the error message returns, make sure that you have the correct password, that you are authorized to access the server, and that the access has been correctly configured in the server's postgresql.conf configuration file.


Server definitions (and their groups) can be exported to a JSON file and re-imported to the same or a different system to enable easy pre-configuration of pgAdmin.

3.7 Import/Export Servers

Server definitions (and their groups) can be exported to a JSON file and re-imported to the same or a different system to enable easy pre-configuration of pgAdmin.


3.7.1 Using pgAdmin 4 GUI

To launch the *Import/Export Servers...* tool, navigate through *Tools* on the menu bar to click on the *Import/Export Servers* option.




- Use the *Import/Export* field to select the Server Groups/Servers to be imported or exported.
- Use the *Filename* field to select the JSON file to import servers or create the new file in case of Export where the servers to be exported in the JSON format.
- Use the *Remove all the existing servers?* field to specify whether to remove all the existing servers or not before importing the new selected servers. This field is applicable only in case of Import Servers.

Click the *Next* button to continue, or the *X* button to close the wizard.



- Select the Server Groups/ Servers to be imported/exported.

Click the *Next* button to continue, or the *X* button to close the wizard.



Check the summary of the servers that are going to be imported/exported on the Summary page.

Click the *Finish* button to close the wizard.

3.7.2 Using 'setup.py' command line script

Note

To export or import servers using `setup.py` script, you must use the Python interpreter that is normally used to run pgAdmin to ensure that the required Python packages are available. In most packages, this can be found in the Python Virtual Environment that can be found in the installation directory. When using platform-native packages, the system installation of Python may be the one used by pgAdmin.

Exporting Servers

To export the servers defined in an installation, simply invoke `setup.py` with the `dump-servers` command line option, followed by the name (and if required, path) to the desired output file. By default, servers owned by the desktop mode user will be dumped (pgadmin4@pgadmin.org by default - see the DESKTOP_USER setting in `config.py`). This can be overridden with the `--user` command line option. There can be multiple configurations of pgAdmin on the same system. To dump the servers from specific pgAdmin config DB file, `--sqlite-path` option can be used. It is also recommended to use this option when running pgAdmin in desktop mode. By default SQLITE_PATH setting in `config.py` is taken. For example:

```
/path/to/python /path/to/setup.py dump-servers output_file.json

# or, to specify a non-default user name and auth source (the default is Internal):

/path/to/python /path/to/setup.py dump-servers output_file.json --user user@example.com -
↪-auth_source ldap

# to specify a pgAdmin config DB file:

/path/to/python /path/to/setup.py dump-servers output_file.json --sqlite-path /path/to/
↪pgadmin4.db
```

To export only certain servers, use the `--server` option and list one or more server IDs. For example:

```
/path/to/python /path/to/setup.py dump-servers output_file.json --server 1 --server 2 --
↪server 5
```

Importing Servers

To import the servers defined in a JSON file, simply invoke `setup.py` with the `load-servers` command line option, followed by the name (and if required, path) of the JSON file containing the server definitions. Servers will be owned by the desktop mode user (pgadmin4@pgadmin.org by default - see the DESKTOP_USER setting in `config.py`). This can be overridden with the `--user` command line option. There can be multiple configurations of pgAdmin on the same system. The default behaviour is for the imported servers to be added to the existent list, which might lead to duplicates. This can be overridden with the `--replace` command line option, which will replace the list of servers with the newly imported one. To load the servers into a specific pgAdmin config DB file, `--sqlite-path` option can be used. It is also recommended to use this option when running pgAdmin in desktop mode. By default SQLITE_PATH setting in `config.py` is taken. For example:

```
/path/to/python /path/to/setup.py load-servers input_file.json

# or, to replace the list of servers with the newly imported one:

/path/to/python /path/to/setup.py load-servers input_file.json --replace

# or, to specify a non-default user name and auth source (the default is Internal) to␣
↪own the new servers:

/path/to/python /path/to/setup.py load-servers input_file.json --user user@example.com

# to specify a pgAdmin config DB file:

/path/to/python /path/to/setup.py load-servers input_file.json --sqlite-path /path/to/
↪pgadmin4.db
```

If any Servers are defined with a Server Group that is not already present in the configuration database, the required Group will be created.

JSON format

The JSON file format used when importing or exporting servers is quite straightforward and simply contains a list of servers, with a number of attributes. The following attributes are required to be present in every server definition: Name, Group, Port, Username, SSLMode, MaintenanceDB and one of Host, HostAddr or Service. A shared server may supply SharedUsername in place of Username, in which case the shared username is also used as the username of the imported server.

Password fields cannot be imported or exported.

In desktop mode, `PasswordExecCommand` is the shell command to run, as shown in the example below. In server mode it must instead be the name of a command defined in the `SERVER_PASSEXEC_COMMANDS` setting (see *Configuration Files*), and the same name is written when servers are exported. A server whose `PasswordExecCommand` is not the name of a configured command is still imported, but without a password exec command, and a warning naming the server is printed. `PasswordExecExpiration` is imported only together with a valid command name.

The following example shows both a minimally defined and a fully defined server:

```
{
    "Servers": {
        "1": {
            "Name": "Minimally Defined Server",
            "Group": "Server Group 1",
            "Port": 5432,
            "Username": "postgres",
            "Host": "localhost",
            "MaintenanceDB": "postgres",
            "ConnectionParameters": {
                "sslmode": "prefer",
                "connect_timeout": 10
            }
        },
        "2": {
            "Name": "Fully Defined Server",
            "Group": "Server Group 2",
```

(continues on next page)

(continued from previous page)

```
            "Host": "host.domain.com",
            "Port": 5432,
            "MaintenanceDB": "postgres",
            "Username": "postgres",
            "Role": "my_role_name",
            "Comment": "This server has every option configured in the JSON",
            "DBRestriction": "live_db test_db",
            "Shared": false,
            "SharedUsername": "postgres",
            "BGColor": "#ff9900",
            "FGColor": "#000000",
            "Service": "postgresql-10",
            "UseSSHTunnel": 1,
            "TunnelHost": "192.168.1.253",
            "TunnelPort": 22,
            "TunnelUsername": "username",
            "TunnelAuthentication": 1,
            "TunnelIdentityFile": "/Users/<user>/.ssh/id_rsa.pub",
            "TunnelKeepAlive": 30,
            "PasswordExecCommand": "echo 'test'",
            "PasswordExecExpiration": 100,
            "KerberosAuthentication": true,
            "ConnectionParameters": {
                "sslmode": "prefer",
                "connect_timeout": 10,
                "passfile": "/Users/<user>/.pgpass",
                "sslcert": "/Users/<user>/.ssh/cert"
            },
            "Tags": [
                {
                    "color": "#EC0BB4",
                    "text": "Development"
                }
            ],
            "PostConnectionSQL": "set timezone='America/New_York'"
        }
    }
}
```

Note

If you're running pgAdmin in Server Mode, the values for parameters that require file paths should be specified relative to the user's home directory which is /<DATA_DIR>/storage/<user_id>/. If DATA_DIR is not specified, then it will be /var/lib/pgadmin/storage/<user_id>/

CHAPTER 4


Managing Cluster Objects

Some object definitions reside at the cluster level; pgAdmin 4 provides dialogs that allow you to create these objects, manage them, and control their relationships to each other. To access a dialog that allows you to create a database object, right-click on the object type in the pgAdmin tree control, and select the *Create* option for that object. For example, to create a new database, right-click on the *Databases* node, and select *Create Database...*

4.1 Database Dialog

Use the *Database* dialog to define or modify a database. To create a database, you must be a database superuser or have the CREATE privilege.


The *Database* dialog organizes the development of a database through the following dialog tabs: *General*, *Definition*, *Security*, and *Parameters*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the database:

- Use the *Database* field to add a descriptive name for the database. The name will be displayed in the *pgAdmin* tree control.
- Use the *OID* field to specify the object identifier to be used for the new database. Users can specify the value greater than 16383. This option is available from v15 and above.
- Select the owner of the database from the drop-down listbox in the *Owner* field.
- Store notes about the database in the *Comment* field.

Click the *Definition* tab to continue.




Use the *Definition* tab to set properties for the database:

- Select a character set from the drop-down listbox in the *Encoding* field. The default is *UTF8*.
- Select a template from the drop-down listbox in the *Template* field. If you do not specify a template, the database will use template1.
- Select a tablespace from the drop-down listbox in the *Tablespace* field. The selected tablespace will be the default tablespace used to contain database objects.
- Select the strategy from the drop-down listbox in the *Strategy* field while creating a new database. This option is available from v15 and above.
- Select the locale provider from the drop-down listbox in the *Locale Provider* field to set the default collation for this database. Possible values are: icu, libc and builtin. This option is available from v15 and above. **Note:** The icu and libc options are available from v15 and builtin option is available from v17 onwards.
- Select the collation order from the drop-down listbox in the *Collation* field.
- Select the character classification from the drop-down listbox in the *Character Type* field. This affects the categorization of characters, e.g. lower, upper and digit. The default, or a blank field, uses the character classification of the template database.
- Select the icu locale from the drop-down listbox in the *ICU Locale* to specifies the ICU locale ID if the ICU locale provider is used. This option is available from v15 and above.
- Specify the icu rules in the *ICU Rules* field as additional collation rules to customize the behavior of the default collation of this database. This option is available from v16 and above.

- Select the builtin locale from the drop-down listbox in the *Builtin Locale* if the builtin locale provider is used. This option is available from v17 and above.
- Specify a connection limit in the *Connection Limit* field to configure the maximum number of connection requests. The default value (*-1*) allows unlimited connections to the database.
- If *Template?* is set to *Yes*, the database will be a template database.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign privileges to a role. Click the *Add* icon (+) to set privileges for database objects:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.


Click add to set additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the database. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.

To discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Parameters* tab to continue.




Use the *Parameters* tab to set parameters for the database. Click the *Add* icon (+) to add each parameter:

- Use the drop-down listbox in the *Name* field to select a parameter.
- Use the *Value* field to set a value for the parameter.
- Use the drop-down listbox next to *Role* to select a role to which the parameter setting specified will apply.

Follow these steps to add additional parameter value definitions; to discard a parameter, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Advanced* tab to continue.



Use the *Advanced* tab to set advanced parameters for the database.


- Use *Schema restriction* field to provide a SQL restriction that will be used against the pg_namespace table to limit the schemas that you see. For example, you might enter: *public* so that only *public* is shown in the pgAdmin browser. Separate entries with a comma or tab as you type.

Click the *SQL* tab to continue.

Your entries in the *Database* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

4.1.1 Example

The following is an example of the sql command generated by user selections in the *Database* dialog:



The example creates a database named *hr* that is owned by *postgres*. It allows unlimited connections, and is available to all authenticated users.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

4.2 Resource Group Dialog

Use the *Resource Group* dialog to create a resource group and set values for its resources. A resource group is a named, global group on which various resource usage limits can be defined. The resource group is accessible from all databases in the cluster. To use the *Resource Group* dialog, you must have superuser privileges. Please note that resource groups are supported when connected to EDB Postgres Advanced Server; for more information about using resource groups, please see the EDB Postgres Advanced Server Guide, available at:

https://www.enterprisedb.com/docs/epas/latest/epas_compat_sql/

Fields used to create a resource group are located on the *General* tab. The *SQL* tab displays the SQL code generated by your selections on the *Resource Group* dialog.



Use the fields on the *General* tab to specify resource group attributes:

- Use the *Name* field to add a descriptive name for the resource group. This name will be displayed in the tree control.
- Use the *CPU rate limit (%)* field to set the value of the CPU rate limit resource type assigned to the resource

group. The valid range for a CPU rate limit is from 0 to 1.67772e+07. The default value is 0.

- Use the *Dirty rate limit (KB)* field to set the value of the dirty rate limit resource type assigned to the resource group. The valid range for a dirty rate limit is from 0 to 1.67772e+07. The default value is 0.

Click the *SQL* tab to continue.

Your entries in the *Resource Group* dialog generate a SQL command. Use the *SQL* tab for review; revisit the *General* tab to make any changes to the SQL command.

4.2.1 Example

The following is an example of the sql command generated by selections made in the *Resource Group* dialog:




The example creates a resource group named *acctg* that sets *cpu_rate_limit* to *2*, and *dirty_rate_limit* to *6144*.

- Click the Info button (*i*) to access online SQL syntax reference material.
- Click the Help button (*?*) to access online documentation about Resource Groups.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

4.3 Login/Group Role Dialog

Use the *Login/Group Role* dialog to define a role. A role may be an individual user (with or without login privileges) or a group of users. Note that roles defined at the cluster level are shared by all databases in the cluster.


The *Login/Group Role* dialog organizes the creation and management of roles through the following dialog tabs: *General*, *Definition*, *Privileges*, *Memberships Parameters*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields on the *General* tab to identify the role.

- Use the *Name* field to provide the name of the role. The name will be displayed in the tree control.
- Provide a note about the role in the *Comments* field.


Click the *Definition* tab to continue.



Use the *Definition* tab to set a password and configure connection rules:

- Provide a password that will be associated with the role in the *Password* field.
- Provide an expiration date for the password in the *Account Expires* field (the role does not expire). The expiration date is not enforced when a user logs in with a non-password-based authentication method.
- If the role is a login role, specify how many concurrent connections the role can make in the *Connection Limit* field. The default value (*-1*) allows unlimited connections.


Click the *Privileges* tab to continue.



Use the *Privileges* tab to grant privileges to the role.

- Move the *Can login?* switch to the *Yes* position if the role has login privileges. The default value is *No*.
- Move the *Superuser* switch to the *Yes* position if the role is a superuser within the database. The default value is *No*.
- Move the *Create roles?* switch to the *Yes* position to specify whether a role is permitted to create roles. A role with this privilege can alter and drop roles. The default value is *No*.
- Move the *Create databases* switch to the *Yes* position to control whether a role can create databases. The default value is *No*.
- Move the *Inherit rights from the parent roles?* switch to the *No* position if a role does not inherit privileges. The default value is *Yes*.
- Move the *Can initiate streaming replication and backups?* switch to the *Yes* position to control whether a role can initiate streaming replication or put the system in and out of backup mode. The default value is *No*.
- Move the *Bypass RLS?* switch to the *Yes* position to control whether a role can bypasses every row-level security (RLS) policy. The default value is *No*.

Click the *Membership* tab to continue.




Use the *Membership* tab to define role memberships. A role can be a member of other roles and can have other roles as members.

- Use *Member of* section to specify roles of which the current role is a member. To assign *Admin Option* for a selected role, click on the appropriate checkbox.
- Use *Members* section to specify roles that are members of the current role. To assign *Admin Option* for a selected role, click on the appropriate checkbox.

Click the *Add* icon (+) to add more roles; to discard a role, click the trash icon to the left of the row and confirm the deletion in the *Delete Row* popup.

Note: Apart from *Admin Option*, *Inherit Option* and *Set Option* are available for both *Member of* section and *Members* section from PostgreSQL version >= 16.

Click the *Parameters* tab to continue.




Use the fields on the *Parameters* tab to set session defaults for a selected configuration parameter when the role is connected to a specified database. This tab invokes the ALTER ROLE… SET configuration_parameter syntax. Click the *Add* icon (+) to assign a value for a parameter.

- Use the drop-down listbox in the *Name* field to select a parameter.
- Use the *Value* field to specify a value for the parameter.
- Use the drop-down listbox in the *Database* field to select a database.

Click the *Add* icon (+) to specify each additional parameter; to discard a parameter, click the trash icon to the left of the row and confirm the deletion in the *Delete Row* popup.

Click the *Security* tab to continue.



Use the *Security* tab to define security labels applied to the role. Click the *Add* icon (+) to add each security label selection.

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


To discard a security label, click the trash icon to the left of the row and confirm the deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Login/Group Role* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

4.3.1 Example

The following is an example of the sql command generated by user selections in the *Login/Group Role* dialog:




The example creates a login role named *alice* with *pg_signal_backend* privileges; the role can make unlimited connections to the server at any given time.

- Click the Info button (*i*) to access online SQL help.
- Click the Help button (*?*) to access the documentation for the dialog.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

4.4 Tablespace Dialog


Use The *Tablespace* dialog to define a tablespace. A tablespace allows superusers to define an alternative location on the file system where the data files containing database objects (such as tables and indexes) reside. Tablespaces are only supported on systems that support symbolic links. Note that a tablespace cannot be used independently of the cluster in which it is defined.

The *Tablespace* dialog organizes the definition of a tablespace through the following tabs: *General*, *Definition*, *Parameters*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.




- Use the *Name* field to identify the tablespace with a descriptive name. The name cannot begin with pg_; these names are reserved for system tablespaces.
- Select the owner of the tablespace from the drop-down listbox in the *Owner* field.
- Store notes about the tablespace in the *Comment* field.

Click the *Definition* tab to continue.



- Use the *Location* field to specify an absolute path to a directory that will contain the tablespace.

Click the *Parameters* tab to continue.




Use the *Parameters* tab to set parameters for the tablespace. Click the *Add* icon (+) to add a row to the table below.

- Use the drop-down listbox next to *Name* to select a parameter.
- Use the *Value* field to set a value for the parameter.

Click the *Add* icon (+) to specify each additional parameter; to discard a parameter, click the trash icon to the left of the row and confirm deletion in the *Delete Row* dialog.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels for the tablespace.

Use the *Privileges* panel to assign security privileges. Click the *Add* icon (+) to assign a set of privileges:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privileges to the specified user.

Click the *Add* icon to assign additional sets of privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the tablespace. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label

provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


To discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Tablespace* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

4.4.1 Example

The following is an example of the sql command generated by user selections in the *Tablespace* dialog:



The example shown demonstrates creating a tablespace named *space_01*. It has a *random_page_cost* value equal to *1*.


- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.

- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

4.5 Replica Node Dialog

Use The *Replica Node* dialog to view a standby instance being replicated using log based streaming replication. Streaming replication allows a standby server to stay more up-to-date than is possible with file-based log shipping. The standby connects to the primary, which streams WAL records to the standby as they're generated, without waiting for the WAL file to be filled.

The *Replica Node* dialog organizes the information through the following tabs: *General*, *Replication Slot*



- The *PID* field is the process ID of a WAL sender process.
- The *Username* field is the name of the user logged into this WAL sender process.
- The *App Name* field is the name of the application that is connected to this WAL sender.
- The *Client Address* field is the IP address of the client connected to this WAL sender. If this field is null, it indicates that the client is connected via a Unix socket on the server machine.
- The *Client Hostname* field is the host name of the connected client, as reported by a reverse DNS lookup of client_addr.This field will only be non-null for IP connections, and only when log_hostname is enabled.
- The *Client Port* field is the TCP port number that the client is using for communication with this WAL sender, or -1 if a Unix socket is used.
- The *State* field is the current WAL sender state.

Click the *Replication Slot* tab to continue.



- The *Slot Name* field is a unique, cluster-wide identifier for the replication slot.
- The *Slot Type* field is the slot type - physical or logical
- The *Active* field is True if this slot is currently actively being used.


Other buttons:

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

4.6 PGD Replication Group Node Dialog

Use the *Replication Group Node* dialog to view a PGD group/sub-group. A PGD cluster's nodes are gathered in groups. A group can also contain zero or more subgroups. Subgroups can be used to represent data centers or locations allowing commit scopes to refer to nodes in a particular region as a whole.

The dialog organizes the information through the following tabs: *General*



- The *ID* field is the ID of the node group.
- The *Name* field is the name of the node group.
- The *Location* field is the name of the location associated with the node group.
- The *Type* field is the type of the node group, one of "global", "data", "shard" or "subscriber-only".
- The *Streaming Mode* field is the transaction streaming setting of the node group, one of "off", "file", "writer", "auto" or "default"
- The *Enable Proxy Routing?* field tells whether the node group allows routing from pgd-proxy.
- The *Enable Raft?* field tells whether the node group allows Raft Consensus.

Other buttons:


- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

A group can have multiple servers and will be visible in the object explorer tree.

4.6.1 PGD Replication Server Node Dialog

Use The *Replication Server Node* dialog to view an element that run databases and participate in the PGD cluster. A typical PGD node runs a Postgres database, the BDR extension, and optionally a PGD Proxy service.

The dialog organizes the information through the following tabs: *General*



- The *Sequence ID* field is the identifier of the node used for generating unique sequence numbers.

- The *ID* field is the OID of the node.
- The *Name* field is the name of the node.
- The *Kind* field is the node kind name.
- The *Group Name* field is the PGD group the node is part of.
- The *Local DB Name* field is the database name of the node.


Other buttons:

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

4.7 Role Reassign/Drop Own Dialog

Use the *Reassign/Drop Own* dialog to change the ownership of database objects owned by a database role. This dialog instructs the system to change the ownership of database objects owned by any of the *old_roles* to *new_role*.

The *Reassign/Drop Own* dialog organizes the Reassign & Drop role through General tab.




- Use the *Operation* field to provide Reassign option.
- Provide a new role in the *Reassign Objects to* field; The ownership of all the objects within the selected database, and of all shared objects (databases, tablespaces), owned by the *old_role* will be reassigned to *new_role*.
- Provide a database on which the reassignment is to be carried out.

The above example demonstrates reassigning *old_role* to *new_role*.

Click the *SQL* tab to continue.



Removing database objects owned by a database role.



- Use the *Operation* field to provide Drop option.
- Use the *Cascade?* field to provide Yes, No is default.
- Provide a database on which the drop of objects is to be carried out.

Click the *SQL* tab to continue.



The above examples demonstrates drop owned by *role*.

- Click the *Help* button (?) to access online help.
- Click the *OK* button to save work.
- Click the *Cancel* button to exit without saving work.


4.8 Directory Dialog

Use the Directory dialog to create an alias for a file system directory path. To create directories, you must have the CREATE ANY DIRECTORY system privilege. When you create a directory, you are automatically granted READ and WRITE privileges on the directory, and you can grant READ and WRITE privileges to other users and roles. The superuser can also grant these privileges to other users and roles.

Please note that directories are supported when connected to EDB Postgres Advanced Server. For more information about using directories, please see the EDB Postgres Advanced Server Guide, available at:

https://www.enterprisedb.com/docs/epas/latest/epas_compat_sql/

The *Directory* dialog organizes the definition of a directory through the following tabs: *General*, *Definition*, *Security*, and *SQL*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields on the *General* tab to specify directory attributes:

- Use the *Name* field to add a directory alias name. This name will be displayed in the object explorer.
- Select the owner of the directory from the drop-down listbox in the *Owner* field.

Click the *Definition* tab to continue.



- Use the *Location* field to specify a fully qualified directory path represented by the alias name. The CREATE DIRECTORY command doesn't create the operating system directory. The physical directory must be created independently using operating system commands.

Click the *Security* tab to continue.



NOTE:- This *Security* tab will be only available for EPAS 17.

Use the *Security* tab to assign privileges for the directory.

Use the *Privileges* panel to assign security privileges. Click the *Add* icon (+) to assign a set of privileges:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privileges to the specified user.

Click the *Add* icon to assign additional sets of privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Directory* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

4.8.1 Example

The following is an example of the sql command generated by user selections in the *Directory* dialog:



The example shown demonstrates creating a directory named *test1*. It has a *location* value equal to */home/test_dir*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

CHAPTER 5

Managing Database Objects

pgAdmin 4 provides simple but powerful dialogs that you can use to design and create database objects. Each dialog contains a series of tabs that you use to describe the object that will be created by the dialog; the SQL tab displays the SQL command that the server will execute when creating the object.

To access a dialog that allows you to create a database object, right-click on the object type in the pgAdmin tree control, and select the *Create* option for that object. For example, to create a new cast, right-click on the *Casts* node, and select *Create Cast...*

5.1 Cast Dialog

Use the *Cast* dialog to define a cast. A cast specifies how to convert a value from one data type to another.


The *Cast* dialog organizes the development of a cast through the following dialog tabs: *General* and *Definition*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the cast:

- The *Name* field is disabled. The name that will be displayed in the *pgAdmin* tree control is the *Source* type concatenated with the *Target* type, and is generated automatically when you make selections on the *Cast* dialog *Definition* tab.
- Store notes about the cast in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define parameters:

- Use the drop-down listbox next to *Source type* to select the name of the source data type of the cast.
- Use the drop-down listbox next to *Target type* to select the name of the target data type of the cast.
- Use the drop-down listbox next to *Function* to select the function used to perform the cast. The function's result data type must match the target type of the cast.
- Select *Context* toggle to *Implicit* if the cast is implicit. By default, a cast can be invoked only by an explicit cast request. If the cast is marked *Implicit* then it can be invoked implicitly in any context, whether by assignment or internally in an expression.

Click the *SQL* tab to continue.

Your entries in the *Cast* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

Example

The following is an example of the sql command generated by user selections in the *Cast* dialog:



- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.


5.2 Using EDB Job Scheduler

In the past versions of EPAS, DBMS_SCHEDULER or DBMS_JOBS required the configuration of pgAgent, an essential service for their functionality. Maintaining pgAgent in a production environment is cumbersome. The need for correct configuration, regular updates, and ensuring the service's health added complexity.

EPAS 16 revolutionizes job scheduling by eliminating the need for the pgAgent component. The new version introduces EDB Job Scheduler which is an extension that runs the job scheduler as a background process for the DBMS_SCHEDULER and DBMS_JOB packages.


The EDB Job Scheduler has a scheduler process that starts when the database cluster starts. To start the scheduler process, load the EDB Job Scheduler extension using the **shared_preload_libraries** parameter. After you load the extension, create the extension **'edb_job_scheduler'** and **'dbms_scheduler'** using the CREATE EXTENSION command. The database in which you're creating the extension must be listed in the **edb_job_scheduler.database_list** parameter.

Instructions for configuring the EDB Job Scheduler can be found in the Configuring EDB Job Scheduler.




5.2.1 Check the status of all the jobs

To check the running status of all the jobs select the 'DBMS Job Scheduler' collection node from the object explorer and select the Properties tab.



DBMS Job

Use the *DBMS Job* dialog to create a DBMS Job.



Use the fields in the *General* tab to create job:

- Use the *Name* field to add a descriptive name for the job. The name will be displayed in the *pgAdmin* object explorer.
- Use the *Enabled?* switch to indicate that job should be enabled or disabled.
- Use the *Job Type* field to select the type of the job. Type could be SELF-CONTAINED or PRE-DEFINED. If the Job Type is Self-Contained you need to specify the action and repeat interval in the Action and Repeat tabs respectively. If the Job Type is Pre-Defined you need to specify the existing Program and Schedule names in the Pre-Defined tab.
- Store notes about the job in the *Comment* field.


Click the *Action* tab to continue.



Use the *Action* tab to select the action for the job. This tab is only enabled when the job type is 'SELF-CONTAINED'.


- Use the *Type* field to select the type of the job. Type could be PLSQL BLOCK or STORED PROCEDURE.
- Use the *Procedure* field to select an existing procedure that executes when the job is invoked.
- *Number of Arguments* field is read-only and indicates the quantity of arguments necessary for the chosen procedure.

Click the *Code* tab to continue.




- Use the *Code* field to write the code that executes when the job is invoked. This tab is only enabled when the job type is 'SELF-CONTAINED' and type of the action is set to 'PLSQL BLOCK'.

Click the *Arguments* tab to continue.



- *Arguments* tab outlines the arguments required by the selected procedure in the 'Action' tab. This tab is only enabled when the job type is 'SELF-CONTAINED'.


Click the *Repeat* tab to continue.



Use the *Repeat* tab to select the repeat interval for the job. This tab is only enabled when the job type is 'SELF-CONTAINED'.

- Use the calendar selector in the *Start* field to specify the starting date and time for the job.
- Use the calendar selector in the *End* field to specify the ending date and time for the job.
- Use the *Frequency* field to select the frequency. Frequency is one of the following: YEARLY, MONTHLY, WEEKLY, DAILY, HOURLY, MINUTELY.
- Use the *Date* field to select the date on which job will execute.Date is YYYYMMDD.
- Use the *Months* field to select the months in which the job will execute.
- Use the *Week Days* field to select the days on which the job will execute.
- Use the *Month Days* field to select the numeric days on which the job will execute.
- Use the *Hours* field to select the hour at which the job will execute.
- Use the *Minutes* field to select the minute at which the job will execute.

Click the *Pre-Defined* tab to continue.



Use the *Pre-Defined* tab to select the existing program and schedule to create the job. This tab is only enabled when the job type is 'PRE-DEFINED'.


- Use the *Program Name* field to select the existing program.
- Use the *Schedule Name* field to select an existing schedule.

Click the *SQL* tab to continue.

Your entries in the *DBMS Job* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

Example


The following is an example of the sql command generated by user selections in the *DBMS Job* dialog:



- Click the *Info* button (i) to access online help.
- Click the *Help* button (?) to access dialog help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

DBMS Program


Use the *DBMS Program* dialog to create a DBMS Program.



Use the fields in the *General* tab to create program:

- Use the *Name* field to add a descriptive name for the program. The name will be displayed in the *pgAdmin* object explorer.
- Use the *Enabled?* switch to indicate that program should be enabled or disabled.
- Store notes about the program in the *Comment* field.


Click the *Action* tab to continue.



Use the *Action* tab to select the action for the program:


- Use the *Type* field to select the type of the program. Type could be PLSQL BLOCK or STORED PROCEDURE.
- Use the *Procedure* field to select an existing procedure that executes when the program is invoked.
- *Number of Arguments* field is read-only and indicates the quantity of arguments necessary for the chosen procedure.

Click the *Code* tab to continue.



- Use the *Code* field to write the code that executes when the program is invoked. This tab is only enabled when the type of the program is set to 'PLSQL BLOCK'.

Click the *Arguments* tab to continue.




- *Arguments* tab is a read-only section that outlines the arguments required by the selected procedure in the 'Action' tab.

Click the *SQL* tab to continue.

Your entries in the *DBMS Program* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

Example


The following is an example of the sql command generated by user selections in the *DBMS Program* dialog:



- Click the *Info* button (i) to access online help.
- Click the *Help* button (?) to access dialog help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

DBMS Schedule


Use the *DBMS Schedule* dialog to create a DBMS Schedule.



Use the fields in the *General* tab to create schedule:

- Use the *Name* field to add a descriptive name for the schedule. The name will be displayed in the *pgAdmin* object explorer.
- Store notes about the schedule in the *Comment* field.

Click the *Repeat* tab to continue.



Use the *Repeat* tab to select the repeat interval for the schedule:


- Use the calendar selector in the *Start* field to specify the starting date and time for the schedule.
- Use the calendar selector in the *End* field to specify the ending date and time for the schedule.
- Use the *Frequency* field to select the frequency. Frequency is one of the following: YEARLY, MONTHLY, WEEKLY, DAILY, HOURLY, MINUTELY.
- Use the *Date* field to select the date on which schedule will execute.Date is YYYYMMDD.
- Use the *Months* field to select the months in which the schedule will execute.
- Use the *Week Days* field to select the days on which the schedule will execute.
- Use the *Month Days* field to select the numeric days on which the schedule will execute.
- Use the *Hours* field to select the hour at which the schedule will execute.
- Use the *Minutes* field to select the minute at which the schedule will execute.

Click the *SQL* tab to continue.

Your entries in the *DBMS Schedule* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

Example

The following is an example of the sql command generated by user selections in the *DBMS Schedule* dialog:




- Click the *Info* button (i) to access online help.
- Click the *Help* button (?) to access dialog help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.3 Collation Dialog

Use the *Collation* dialog to define a collation. A collation is an SQL schema object that maps a SQL name to operating system locales. To create a collation, you must have a CREATE privilege on the destination schema.


The *Collation* dialog organizes the development of a collation through the following dialog tabs: *General* and *Definition*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the collation:

- Use the *Name* field to provide a name for the collation. The collation name must be unique within a schema. The name will be displayed in the *pgAdmin* tree control.
- Select the name of the owner from the drop-down listbox in the *Owner* field.
- Select the name of the schema in which the collation will reside from the drop-down listbox in the *Schema* field.
- Store notes about the collation in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to specify the operating system locale settings:


- Use the drop-down listbox next to *Copy collation* to select the name of an existing collation to copy. The new collation will have the same properties as the existing one, but will be an independent object. If you choose to copy an existing collation, you cannot modify the collation properties displayed on this tab.
- Use the drop-down listbox next to *Provider* to select a locale services associated with the collation. Possible values are: icu, libc and builtin. **Note:** The builtin option is available from v17 onwards.
- Use the *Locale* field to specify a locale; a locale specifies language and language formatting characteristics. If you specify this, you cannot specify either of the following parameters. To view a list of locales supported by your Linux system use the command *locale -a*.
- Use the *LC_COLLATE* field to specify a locale with specified string sort order. The locale must be applicable to the current database encoding. (See CREATE DATABASE for details.)
- Use the *LC_CTYPE* field to specify a locale with specified character classification. The locale must be applicable to the current database encoding. (See CREATE DATABASE for details.)
- Move the switch next to *Deterministic* to *YES* to specify whether the collation should use deterministic comparisons. By default, this option is set to true. In a deterministic comparison, strings that are not byte-wise equal are considered unequal, even if they are considered logically equal in the comparison.
- Use the *Rules* field to specify rules for customizing the behavior of the collation. It includes considerations such as character ordering, case sensitivity, and accent sensitivity.
- Use the *Version* field to specify version string to store with the collation object.

Click the *SQL* tab to continue.

Your entries in the *Collation* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.3.1 Example

The following is an example of the sql command generated by user selections in the *Collation* dialog:



The example shown demonstrates creating a collation named *french* that uses the rules specified for the locale, *fr-BI-x-icu*. The collation is owned by *postgres*.

- Click the *Info* button (i) to access online help. For more information about setting a locale, see Chapter 22.1 Locale Support of the PostgreSQL core documentation:


  https://www.postgresql.org/docs/current/locale.html

- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.4 Domain Dialog

Use the *Domain* dialog to define a domain. A domain is a data type definition that may constrain permissible values. Domains are useful when you are creating multiple tables that contain comparable columns; you can create a domain that defines constraints that are common to the columns and re-use the domain definition when creating the columns, rather than individually defining each set of constraints.

The *Domain* dialog organizes the development of a domain through the following tabs: *General*, *Definition*, *Constraints*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields on the *General* tab to identify a domain:

- Use the *Name* field to add a descriptive name for the domain. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to select a role that will own the domain.
- Select the name of the schema in which the domain will reside from the drop-down listbox in the *Schema* field.
- Store notes about the domain in the *Comment* field.

Click the *Definition* tab to continue.




Use the fields in the *Definition* tab to describe the domain:

- Use the drop-down listbox next to *Base type* to specify a data type.
- Use the context-sensitive *Length* field to specify a numeric length for a numeric type.
- Use the context-sensitive *Precision* field to specify the total count of significant digits for a numeric type.
- Specify a default value for the domain data type in the *Default* field. The data type of the default expression must match the data type of the domain. If no default value is specified, then the default value is the null value.

- Move the *Not Null* switch to specify the values of this domain are prevented from being null.
- Use the drop-down listbox next to *Collation* to apply a collation cast. If no collation is specified, the underlying data type's default collation is used. The underlying type must be collatable if COLLATE is specified.

Click the *Constraints* tab to continue.



Use the fields in the *Constraints* tab to specify rules for the domain. Click the *Add* icon (+) to set constraints:


- Use the *Name* field to specify a name for the constraint.
- Use the *Check* field to provide an expression for the constraint.
- Use the *Validate* checkbox to determine whether the constraint will be validated. The default checkbox is checked and sets a validation requirement.

A CHECK clause specifies an integrity test which values of the domain must satisfy. Each constraint must be an expression that produces a Boolean result. Use the key word VALUE to refer to the value being tested. Expressions evaluating to TRUE or UNKNOWN succeed. If the expression produces a FALSE result, an error is reported and the value is not allowed to be converted to the domain type. A CHECK expression cannot contain subqueries nor refer to

variables other than VALUE. If a domain has multiple CHECK constraints, they will be tested in alphabetical order by name.

Click the *Add* icon (+) to set additional constraints; to discard a constraint, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Security* tab to continue.



Use the *Security Labels* panel to assign security labels. Click the *Add* icon (+) to add a label:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to specify each additional label; to discard a label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Domain* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.4.1 Example

The following is an example of the sql command generated by selections made in the *Domain* dialog:




The example shown demonstrates creating a domain named *postal_code* that confirms that the value entered is in proper format.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.5 Domain Constraints Dialog

Use the *Domain Constraints* dialog to create or modify a domain constraint. A domain constraint confirms that the values provided for a domain meet a defined criteria. The *Domain Constraints* dialog implements options of the ALTER DOMAIN command.

The *Domain Constraints* dialog organizes the development of a domain constraint through the following dialog tabs: *General* and *Definition*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the domain constraint:

- Use the *Name* field to add a descriptive name for the constraint. The name will be displayed in the *pgAdmin* tree control.
- Store notes about the constraint in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the domain constraint:

- Use the *Check* field to provide a CHECK expression. A CHECK expression specifies a constraint that the domain must satisfy. A constraint must produce a Boolean result; include the key word VALUE to refer to the value being tested. Only those expressions that evaluate to TRUE or UNKNOWN will succeed. A CHECK expression cannot contain subqueries or refer to variables other than VALUE. If a domain has multiple CHECK constraints, they will be tested in alphabetical order.
- Move the *Validate?* switch to the *No* position to mark the constraint NOT VALID. If the constraint is marked NOT VALID, the constraint will not be applied to existing column data. The default value is *Yes*.

Click the *SQL* tab to continue.

Your entries in the *Domain Constraints* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.5.1 Example

The following is an example of the sql command generated by user selections in the *Domain Constraints* dialog:




The example shown demonstrates creating a domain constraint on the domain *timesheets* named *weekday*. It constrains a value equal to *Friday*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.6 Event Trigger Dialog

Use the *Event Trigger* dialog to define an event trigger. Unlike regular triggers, which are attached to a single table and capture only DML events, event triggers are global to a particular database and are capable of capturing DDL events. Like regular triggers, event triggers can be written in any procedural language that includes event trigger support, or in C, but not in SQL.


The *Event Trigger* dialog organizes the development of a event trigger through the following dialog tabs: *General*, *Definition*, and *Security Labels*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the event trigger:

- Use the *Name* field to add a descriptive name for the event trigger. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to specify the owner of the event trigger.
- Store notes about the event trigger in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the event trigger:

- Select a value from the drop down of *Trigger Enabled* field to specify a status for the trigger: *Enable Disable*, *Replica Always*.
- Use the drop-down listbox next to *Trigger function* to specify an existing function. A trigger function takes an empty argument list, and returns a value of type event_trigger.
- Select a value from the drop down of *Events* field to specify when the event trigger will fire: *DDL COMMAND START*, *DDL COMMAND END*, or *SQL DROP*.
- Use the *When TAG in* field to enter filter values for TAG for which the trigger will be executed. The values must be in single quotes separated by comma.

Click the *Security Labels* tab to continue.



Use the *Security* tab to define security labels applied to the trigger. Click the *Add* icon (+) to add each security label.

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.

Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Event Trigger* dialog generate a SQL command. Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.6.1 Example

The following is an example of the sql command generated by user selections in the *Event Trigger* dialog:



The command creates an event trigger named *accounts* that invokes the procedure named *evt_tri_fun*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.7 Extension Dialog

Use the *Extension* dialog to install a new extension into the current database. An extension is a collection of SQL objects that add targeted functionality to your Postgres installation. The *Extension* dialog adds the functionality of an extension to the current database only; you must register the extension in each database that use the extension. Before you load an extension into a database, you should confirm that any pre-requisite files are installed.

The *Extension* dialog allows you to implement options of the CREATE EXTENSION command through the following dialog tabs: *General* and *Definition*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify an extension:

- Use the drop-down listbox in the *Name* field to select the extension. Each extension must have a unique name.
- Move the switch next to *Cascade?* to the *Yes* position to automatically install any extensions that this extension depends on that are not already installed.
- Store notes about the extension in the *Comment* field.

Click the *Definition* tab to continue.



Use the *Definition* tab to select the *Schema* and *Version*:

- Use the drop-down listbox next to *Schema* to select the name of the schema in which to install the extension's objects.
- Use the drop-down listbox next to *Version* to select the version of the extension to install.

Click the *SQL* tab to continue.

Your entries in the *Extension* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.7.1 Example

The following is an example of the sql command generated by user selections in the *Extension* dialog:



The command creates the *adminpack* extension in the *public* schema. It is version *2.0* of *adminpack*.


- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.8 Foreign Data Wrapper Dialog

Use the *Foreign Data Wrapper* dialog to create or modify a foreign data wrapper. A foreign data wrapper is an adapter between a Postgres database and data stored on another data source.

You must be a superuser to create a foreign data wrapper.


The *Foreign Data Wrapper* dialog organizes the development of a foreign data wrapper through the following dialog tabs: *General*, *Definition*, *Options*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the foreign data wrapper:

- Use the *Name* field to add a descriptive name for the foreign data wrapper. A foreign data wrapper name must be unique within the database. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to select the name of the role that will own the foreign data wrapper.
- Store notes about the foreign data wrapper in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to set parameters:

- Select the name of the handler function from the drop-down listbox in the *Handler* field. This is the name of an existing function that will be called to retrieve the execution functions for foreign tables.
- Select the name of the validator function from the drop-down listbox in the *Validator* field. This is the name of an existing function that will be called to check the generic options given to the foreign data wrapper, as well as options for foreign servers, user mappings and foreign tables using the foreign data wrapper.

Click the *Options* tab to continue.




Use the fields in the *Options* tab to specify options:

- Click the *Add* icon (+) button to add an option/value pair for the foreign data wrapper. Supported option/value pairs will be specific to the selected foreign data wrapper.
- Specify the option name in the *Option* field and provide a corresponding value in the *Value* field.

Click the *Add* icon (+) to specify each additional pair; to discard an option, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Security* tab to continue.



Use the *Security* tab to assign security privileges. Click the *Add* icon (+) to assign a set of privileges.

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privileges to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click add to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Foreign Data Wrapper* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.8.1 Example

The following is an example of the sql command generated by user selections in the *Foreign Data Wrapper* dialog:




The example creates a foreign data wrapper named *lib_qp_debug* that uses pre-existing validator and handler functions, *dblink_fdw_validator* and *libpg_fdw_handler*. Selections on the *Options* tab set *debug* equal to *true*. The foreign data wrapper is owned by *postgres*.

- Click the *Help* button (?) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.9 Foreign Server Dialog

Use the *Foreign Server* dialog to create a foreign server. A foreign server typically encapsulates connection information that a foreign-data wrapper uses to access an external data resource. Each foreign data wrapper may connect to a different foreign server; in the *pgAdmin* tree control, expand the node of the applicable foreign data wrapper to launch the *Foreign Server* dialog.


The *Foreign Server* dialog organizes the development of a foreign server through the following dialog tabs: *General*, *Definition*, *Options*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the foreign server:

- Use the *Name* field to add a descriptive name for the foreign server. The name will be displayed in the *pgAdmin* tree control. It must be unique within the database.
- Use the drop-down listbox next to *Owner* to select a role.
- Store notes about the foreign server in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to set parameters:

- Use the *Type* field to specify a server type.
- Use the *Version* field to specify a server version.

Click the *Options* tab to continue.




Use the fields in the *Options* tab to specify options. Click the *Add* button to create an option clause for the foreign server.

- Specify the option name in the *Option* field.
- Provide a corresponding value in the *Value* field.

Click *Add* to create each additional clause; to discard an option, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Security* tab to continue.



Use the *Security* tab to assign security privileges to the foreign server. Click *Add* before you assign a set of privileges.

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privileges to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click *Add* to assign a new set of privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* dialog.

Click the *SQL* tab to continue.

Your entries in the *Foreign Server* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.9.1 Example

The following is an example of the sql command generated by user selections in the *Foreign Server* dialog:




The example shown demonstrates creating a foreign server for the foreign data wrapper *hdfs_fdw*. It has the name *hdfs_server*; its type is *hiveserver2*. Options for the foreign server include a host and a port.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.10 Foreign Table Dialog

Use the *Foreign Table* dialog to define a foreign table in the current database. Foreign tables define the structure of an external data source that resides on a foreign server.


The *Foreign Table* dialog organizes the development of a foreign table through the following dialog tabs: *General*, *Definition*, *Columns*, *Constraints*, *Options*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the foreign table:

- Use the *Name* field to add a descriptive name for the foreign table. The name of the foreign table must be distinct from the name of any other foreign table, table, sequence, index, view, existing data type, or materialized view in the same schema. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to select the name of the role that will own the foreign table.
- Select the name of the schema in which the foreign table will reside from the drop-down listbox in the *Schema* field.
- Store notes about the foreign table in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the external data source:

- Use the drop-down listbox next to *Foreign server* to select a foreign server. This list is populated with servers defined through the *Foreign Server* dialog.
- Use the drop-down listbox next to *Inherits* to specify a parent table. The foreign table will inherit all of its columns. This field is optional.

Click the *Columns* tab to continue.




Use the fields in the *Columns* tab to add columns and their attributes to the table. Click the *Add* icon (+) to define a column:

- Use the *Name* field to add a descriptive name for the column.
- Use the drop-down listbox in the *Data Type* field to select a data type for the column. This can include array specifiers. For more information on which data types are supported by PostgreSQL, refer to Chapter 8 of the core documentation.

Click the *Add* icon (+) to specify each additional column; to discard a column, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Constraints* tab to continue.




Use the fields in the *Constraints* tab to apply a table constraint to the foreign table. Click the *Add* icon (+) to define a constraint:

- Use the *Name* field to add a descriptive name for the constraint. If the constraint is violated, the constraint name is present in error messages, so constraint names like *col must be positive* can be used to communicate helpful information.
- Use the *Check* field to write a check expression producing a Boolean result. Each row in the foreign table is expected to satisfy the check expression.
- Check the *No Inherit* checkbox to specify that the constraint will not propagate to child tables.
- Uncheck the *Validate* checkbox to disable validation. The database will not assume that the constraint holds for all rows in the table.

Click the *Add* icon (+) to specify each additional constraint; to discard a constraint, click the trash icon to the left of the row and confirm deletion in he *Delete Row* popup.

Click the *Options* tab to continue.




Use the fields in the *Options* tab to specify options to be associated with the new foreign table or one of its columns; the accepted option names and values are specific to the foreign data wrapper associated with the foreign server. Click the *Add* icon (+) to add an option/value pair.

- Specify the option name in the *Option* field. Duplicate option names are not allowed.
- Provide a corresponding value in the *Value* field.

Click the *Add* icon (+) to specify each additional option/value pair; to discard an option, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign privileges to a role. Click the *Add* icon (+) to set privileges for database objects:

- Select the name of the role to which privileges will be assigned from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the function. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Foreign Table* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.10.1 Example

The following is an example of the sql command generated by user selections in the *Foreign Table* dialog:



The example shown demonstrates creating a foreign table *weblogs* with multiple columns.


- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.11 FTS Configuration Dialog

Use the *FTS Configuration* dialog to configure a full text search. A text search configuration specifies a text search parser that can divide a string into tokens, along with dictionaries that can identify searchable tokens.

The *FTS Configuration* dialog organizes the development of a FTS configuration through the following dialog tabs: "*General*, *Definition*, and *Tokens*. The *SQL* tab displays the SQL code generated by dialog selections.

Click the *General* tab to begin.




Use the fields in the *General* tab to identify a FTS configuration:

- Use the *Name* field to add a descriptive name for the FTS configuration. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to specify the role that will own the configuration.
- Select the name of the schema in which the FTS configuration will reside from the drop-down listbox in the *Schema* field.

- Store notes about the FTS configuration in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define parameters:

- Select the name of the text search parser from the drop-down listbox in the *Parser* field.
- Select a language from the drop-down listbox in the *Copy Config* field.

Click the *Tokens* tab to continue.



Use the fields in the *Tokens* tab to add a token:

- Use the *Tokens* field to specify the name of a token.
- Click the *Add* button to create a token.
- Use the *Dictionaries* field to specify a dictionary.

Repeat these steps to add additional tokens; to discard a token, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *FTS Configuration* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.11.1 Example

The following is an example of the sql command generated by user selections in the *FTS Configuration* dialog:




The example shown demonstrates creating a FTS configuration named *english_phrases*. It uses the *default* parser.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.12 FTS Dictionary Dialog

Use the *FTS Dictionary* dialog to create a full text search dictionary. You can use a predefined templates or create a new dictionary with custom parameters.

The *FTS Dictionary* dialog organizes the development of a FTS dictionary through the following dialog tabs: *General*, *Definition*, and *Options*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the dictionary:

- Use the *Name* field to add a descriptive name for the dictionary. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to select the role that will own the FTS Dictionary.
- Select the name of the schema in which the dictionary will reside from the drop-down listbox in the *Schema* field.
- Store notes about the dictionary in the *Comment* field.

Click the *Definition* tab to continue.




Use the field in the *Definition* tab to choose a template from the drop-down listbox:

- Select *ispell* to select the Ispell template. The Ispell dictionary template supports morphological dictionaries, which can normalize many different linguistic forms of a word into the same lexeme. For example, an English Ispell dictionary can match all declensions and conjugations of the search term bank, e.g., banking, banked, banks, banks', and bank's. Ispell dictionaries usually recognize a limited set of words, so they should be followed by another broader dictionary; for example, a Snowball dictionary, which recognizes everything.
- Select *simple* to select the simple template. The simple dictionary template operates by converting the input token to lower case and checking it against a file of stop words. If it is found in the file then an empty array is returned, causing the token to be discarded. If not, the lower-cased form of the word is returned as the normalized lexeme. Alternatively, the dictionary can be configured to report non-stop-words as unrecognized, allowing them to be passed on to the next dictionary in the list.
- Select *snowball* to select the Snowball template. The Snowball dictionary template is based on a project by Martin Porter, inventor of the popular Porter's stemming algorithm for the English language. Snowball now provides stemming algorithms for many languages (see the Snowball site for more information). Each algorithm understands how to reduce common variant forms of words to a base, or stem, spelling within its language. A Snowball dictionary recognizes everything, whether or not it is able to simplify the word, so it should be placed

at the end of the dictionary list. It is useless to have it before any other dictionary because a token will never pass through it to the next dictionary.

- Select *synonym* to select the synonym template. This dictionary template is used to create dictionaries that replace a word with a synonym. Phrases are not supported (use the thesaurus template (Section 12.6.4) for that). A synonym dictionary can be used to overcome linguistic problems, for example, to prevent an English stemmer dictionary from reducing the word Paris to pari.
- Select *thesaurus* to select the thesaurus template. A thesaurus dictionary replaces all non-preferred terms by one preferred term and, optionally, preserves the original terms for indexing as well. PostgreSQL's current implementation of the thesaurus dictionary is an extension of the synonym dictionary with added phrase support.

Click the *Options* tab to continue.



Use the fields in the *Options* tab to provide template-specific options. Click the *Add* icon (+) to add an option clause:

- Specify the name of an option in the *Option* field
- Provide a value for the option in the *Value* field.

Click the *Add* icon (+) to specify each additional option/value pair; to discard an option, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *FTS Dictionary* dialog generate a generate a SQL command. Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.12.1 Example

The following is an example of the sql command generated by user selections in the *FTS Dictionary* dialog:



The example shown demonstrates creating a custom dictionary named *more_stopwords* which is based on the simple template and is configured to use standard English.


- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.

- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.13 FTS Parser Dialog

Use the *FTS Parser* dialog to create a new text search parser. A text search parser defines a method for splitting a text string into tokens and assigning types (categories) to the tokens.

The *FTS Parser* dialog organizes the development of a text search parser through the following dialog tabs: *General*, and *Definition*. The *SQL* tab displays the SQL code generated by dialog selections.




Use the fields in the *General* tab to identify a text search parser:

- Use the *Name* field to add a descriptive name for the parser. The name will be displayed in the *pgAdmin* tree control.
- Select the name of the schema in which the parser will reside from the drop-down listbox in the *Schema* field.

- Store notes about the domain in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define parameters:

- Use the drop-down listbox next to *Start function* to select the name of the function that will initialize the parser.
- Use the drop-down listbox next to *Get next token function* to select the name of the function that will return the next token.
- Use the drop-down listbox next to *End function* to select the name of the function that is called when the parser is finished.
- Use the drop-down listbox next to *Lextypes function* to select the name of the lextypes function for the parser. The lextypes function returns an array that contains the id, alias, and a description of the tokens used by the parser.
- Use the drop-down listbox next to *Headline function* to select the name of the headline function for the parser. The headline function returns an excerpt from the document in which the terms of the query are highlighted.

Click the *SQL* tab to continue.




Your entries in the *FTS Parser* dialog generate a generate a SQL command. Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.14 FTS Template Dialog

Use the *FTS Template* dialog to create a new text search template. A text search template defines the functions that implement text search dictionaries.

The *FTS Template* dialog organizes the development of a text search Template through the following dialog tabs: *General*, and *Definition*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify a template:

- Use the *Name* field to add a descriptive name for the template. The name will be displayed in the *pgAdmin* tree control.
- Select the name of the schema in which the template will reside from the drop-down listbox in the *Schema* field.
- Store notes about the template in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define function parameters:

- Use the drop-down listbox next to *Init function* to select the name of the init function for the template. The init function is optional.
- Use the drop-down listbox next to *Lexize function* to select the name of the lexize function for the template. The lexize function is required.

Click the *SQL* tab to continue.

Your entries in the *FTS Template* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.14.1 Example

The following is an example of the sql command generated by user selections in the *FTS Template* dialog:




The example shown demonstrates creating a fts template named *eng.template* that uses the ispell dictionary.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.15 Function Dialog

Use the *Function* dialog to define a function. If you drop and then recreate a function, the new function is not the same entity as the old; you must drop existing rules, views, triggers, etc. that refer to the old function.


The *Function* dialog organizes the development of a function through the following dialog tabs: *General*, *Definition*, *Code*, *Options*, *Parameters*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify a function:

- Use the *Name* field to add a descriptive name for the function. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to select the name of the role that will own the function.
- Use the drop-down listbox next to *Schema* to select the schema in which the function will be created.
- Store notes about the function in the *Comment* field.

Click the *Definition* tab to continue.




Use the fields in the *Definition* tab to define the function:

- Move the *Custom return type?* switch to provide a user defined return type.
- Use the drop-down listbox next to *Return type* to select the data type returned by the function, if any. If *Custom return type?* is enabled this field will change to an input text field.
- Move the *Returns a set?* switch to indicate if the function returns a set that includes multiple rows. The default is *No*.
- Use the drop-down listbox next to *Language* to select the implementation language. The default is *sql*.
- Use the drop-down listbox next to *Depends on extensions* to select the extension that this function depends on (for example, plpgsql). If set, dropping the extension will automatically drop the function as well.
- Use the fields in the *Arguments* to define an argument. Click the *Add* icon (+) to set parameters and values for the argument:
  - Use the drop-down listbox in the *Data type* field to select a data type.
  - Use the drop-down listbox in the *Mode* field to select a mode. Select *IN* for an input parameter; select *OUT* for an output parameter; select *INOUT* for both an input and an output parameter; or, select *VARIADIC* to specify a VARIADIC parameter.
  - Provide a name for the argument in the *Argument Name* field.
  - Specify a default value for the argument in the *Default Value* field.


Click the *Add* icon (+) to define another argument; to discard an argument, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Code* tab to continue.



- Use the *Code* field to write the code that will execute when the function is called.

Click the *Options* tab to continue.




Use the fields in the *Options* tab to describe or modify the action of the function:

- Use the drop-down listbox next to *Volatility* to select one of the following. *VOLATILE* is the default value.
  - *VOLATILE* indicates that the function value can change even within a single table scan, so no optimizations can be made.
  - *STABLE* indicates that the function cannot modify the database, and that within a single table scan it will consistently return the same result for the same argument values.
  - *IMMUTABLE* indicates that the function cannot modify the database and always returns the same result when given the same argument values.
- Move the *Strict?* switch to indicate if the function always returns NULL whenever any of its arguments are NULL. If *Yes*, the function is not executed when there are NULL arguments; instead a NULL result is assumed automatically. The default is *No*.
- Move the *Security of definer?* switch to specify that the function is to be executed with the privileges of the user that created it. The default is *No*.
- Move the *Window?* switch to indicate that the function is a window function rather than a plain function. The default is *No*. This is currently only useful for functions written in C. The WINDOW attribute cannot be changed when replacing an existing function definition. For more information about the CREATE FUNCTION command, see the PostgreSQL core documentation available at:

  https://www.postgresql.org/docs/current/functions-window.html

- Use the *Estimated cost* field to specify a positive number representing the estimated execution cost for the function, in units of cpu_operator_cost. If the function returns a set, this is the cost per returned row.
- Use the *Estimated rows* field to specify a positive number giving the estimated number of rows that the query planner should expect the function to return. This is only allowed when the function is declared to return a set. The default assumption is 1000 rows.
- Move the *Leak proof?* switch to indicate whether the function has side effects. The default is *No*. This option can only be set by the superuser.
- Use the *Support function* field to specify a planner support function to use for the function.


Click the *Parameters* tab to continue.



Use the fields in the *Parameters* tab to specify settings that will be applied when the function is invoked. Click the *Add* icon (+) to add a *Name*/*Value* field in the table.

- Use the drop-down listbox in the *Name* column in the *Parameters* panel to select a parameter.
- Use the *Value* field to specify the value that will be associated with the selected variable. This field is context-sensitive.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign usage privileges for the function to a role.

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the function. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Function* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.15.1 Example

The following is an example of the sql command generated by selections made in the *Function* dialog:




The example demonstrates creating a *plpgsql* function named *hire_salesmen*. The function has three columns (p_ename, p_sal and p_comm).

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.16 Language Dialog

Use the CREATE LANGUAGE dialog to register a new procedural language.


The *Language* dialog organizes the registration of a procedural language through the following dialog tabs: *General*, *Definition*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify a language:

- Use the drop-down listbox next to *Name* to select a language script.
- Use the drop-down listbox next to *Owner* to select a role.
- Store notes about the language in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define parameters:

- Move the *Trusted?* switch to the *No* position to specify only users with PostgreSQL superuser privilege can use this language. The default is *Yes*.
- When enabled, use the drop-down listbox next to *Handler Function* to select the function that will be called to execute the language's functions.
- When enabled, use the drop-down listbox next to *Inline Function* to select the function that will be called to execute an anonymous code block (DO command) in this language.
- When enabled, use the drop-down listbox next to *Validator Function* to select the function that will be called when a new function in the language is created, to validate the new function.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign privileges to a role. Click the *Add* icon (+) to set privileges for database objects:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the function. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label

provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Language* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.16.1 Example

The following is an example of the sql command generated by user selections in the *Language* dialog:



The example shown demonstrates creating the trusted procedural language named *mylan*.


- Click the *Info* button (i) to access online help.

- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.17 Materialized View Dialog

Use the *Materialized View* dialog to define a materialized view. A materialized view is a stored or cached view that contains the result set of a query. Use the REFRESH MATERIALIZED VIEW command to update the content of a materialized view.

The *Materialized View* dialog organizes the development of a materialized_view through the following dialog tabs: *General*, *Definition*, *Code*, *Parameter*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.




Use the fields in the *General* tab to identify the materialized view:

- Use the *Name* field to add a descriptive name for the materialized view. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to select the role that will own the materialized view.

- Select the name of the schema in which the materialized view will reside from the drop-down listbox in the *Schema* field.
- Store notes about the materialized view in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to maintain the materialized view:


- Move the *With Data* switch to the *Yes* position to specify the materialized view should be populated at creation time. If not, the materialized view cannot be queried until you invoke REFRESH MATERIALIZED VIEW.
- Use the drop-down listbox next to *Tablespace* to select a location for the materialized view.
- Use the drop-down list box next to Access Method to specify the table access method to use to store the contents for the new materialized view; the method needs to be an access method of type TABLE. This field is optional. This option is available from v12 and above.
- Use the *Fill Factor* field to specify a fill factor for the materialized view. The fill factor for a table is a percentage between 10 and 100. 100 (complete packing) is the default.
- Use the drop-down listbox next to *Depends on extensions* to select the extension that this materialized view depends on (for example, edbspl). If set, dropping the extension will automatically drop the materialized view as well.

Click the *Code* tab to continue.



Use the text editor field in the *Code* tab to provide the query that will populate the materialized view. Please note that updating the definition of existing materialized view would result in loss of Parameter(Table, Toast), Security(Privileges & Security labels), Indexes and other dependent objects.

Click the *Parameter* tab to continue.




Use the tabs nested inside the *Parameter* tab to specify VACUUM and ANALYZE thresholds; use the *Table* tab and the *Toast Table* tab to customize values for the table and the associated toast table. To change the default values:

- Move the *Custom auto-vacuum?* switch to the *Yes* position to perform custom maintenance on the materialized view and to select values in the *Vacuum table*. The *Vacuum Table* provides default values for maintenance

operations.

- Changing *Autovacuum enabled?* to *Not set* will reset autovacuum_enabled.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign privileges to a role. Click the *Add* icon (+) to set privileges for the materialized view:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the materialized view. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Materialized View* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.17.1 Example

The following is an example of the sql command generated by user selections in the *Materialized View* dialog:




The example shown creates a query named *new_hires* that stores the result of the displayed query in the *pg_default* tablespace.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.18 Package Dialog

Use the *Package* dialog to create a (user-defined) package specification.


The *Package* dialog organizes the management of a package through the following dialog tabs: *General*, *Header*, *Body*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the package:


- Use the *Name* field to add a descriptive name for the package. The name of a new package must not match any existing package in the same schema.
- Select the schema in which the package will reside from the drop-down listbox in the *Schema* field.
- Store notes about the package in the *Comment* field.

Click the *Header* tab to continue.




Use the *Header* field to define the public interface for the package.

Click the *Body* tab to continue.



Use the *Body* field to provide the code that implements each package object.

Click the *Security* tab to continue.




Use the fields in the *Security* tab to assign EXECUTE privileges for the package to a role. Click the *Add* icon (+) to set privileges for the package:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of a privilege to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row, and confirm the deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Package* dialog generate a SQL command that creates or modifies a package definition:




The example shown demonstrates creating a package named *empinfo* that includes two function and two procedure.

- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to delete any changes to the dialog.

5.19 Procedure Dialog

Use the *Procedure* dialog to create a procedure; procedures are supported by PostgreSQL v11+ and EDB Postgres Advanced Server. The *Procedure* dialog allows you to implement options of the CREATE PROCEDURE command.


The *Procedure* dialog organizes the development of a procedure through the following dialog tabs: *General*, *Definition*, *Code*, *Options*, *Arguments*, *Parameters*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify a procedure:

- Use the *Name* field to add a descriptive name for the procedure. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to select a role.
- Select the name of the schema in which the procedure will reside from the drop-down listbox in the *Schema* field.
- Store notes about the procedure in the *Comment* field.

Click the *Definition* tab to continue.




Use the fields in the *Definition* tab to define the procedure:

- Use the drop-down listbox next to *Language* to select a language. The default is *edbspl*.
- Use the drop-down listbox next to *Depends on extensions* to select the extension that this procedure depends on (for example, edbspl). If set, dropping the extension will automatically drop the procedure as well.
- Use the fields in the *Arguments* section to define an argument. Click *Add* to set parameters and values for the argument:
- Use the drop-down listbox next to *Data type* to select a data type.
- Use the drop-down listbox next to *Mode* to select a mode. Select *IN* for an input parameter; select *OUT* for an output parameter; select *INOUT* for both an input and an output parameter; or, select *VARIADIC* to specify a VARIADIC parameter.
- Write a name for the argument in the *Argument Name* field.
- Specify a default value for the argument in the *Default Value* field.


Click *Add* to define another argument; to discard an argument, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Code* tab to continue.



- Use the *Code* field to specify the code that will execute when the procedure is called.


Click the *Options* tab to continue.



Use the fields in the *Options* tab to describe or modify the behavior of the procedure:

- Use the drop-down listbox under *Volatility* to select one of the following. *VOLATILE* is the default value.
  - *VOLATILE* indicates that the value can change even within a single table scan, so no optimizations can be made.
  - *STABLE* indicates that the procedure cannot modify the database, and that within a single table scan it will consistently return the same result for the same argument values, but that its result could change across SQL statements.
  - *IMMUTABLE* indicates that the procedure cannot modify the database and always returns the same result when given the same argument values.
- Move the *Strict?* switch to indicate if the procedure always returns NULL whenever any of its arguments are NULL. If *Yes*, the procedure is not executed when there are NULL arguments; instead a NULL result is assumed automatically. The default is *No*.
- Move the *Security of definer?* switch to specify that the procedure is to be executed with the privileges of the user that created it. The default is *No*.
- Use the *Estimated cost* field to specify a positive number representing the estimated execution cost for the procedure, in units of cpu_operator_cost. If the procedure returns a set, this is the cost per returned row.
- Move the *Leak proof?* switch to indicate whether the procedure has side effects — it reveals no information about its arguments other than by its return value. The default is *No*.


Click the *Parameters* tab to continue.



Use the fields in the *Parameters* tab to specify settings that will be applied when the procedure is invoked:

- Use the drop-down listbox next to *Parameter Name* in the *Parameters* panel to select a parameter.
- Click the *Add* button to add the variable to *Name* field in the table.
- Use the *Value* field to specify the value that will be associated with the selected variable. This field is context-sensitive.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign execute privileges for the procedure to a role:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click *Add* to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the procedure. Click *Add* to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click *Add* to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Procedure* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.19.1 Example

The following is an example of the sql command generated by selections made in the *Procedure* dialog:



The example demonstrates creating a procedure that returns a list of employees from a table named *emp*. The procedure is a SECURITY DEFINER, and will execute with the privileges of the role that defined the procedure.


- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.20 Publication Dialog

Logical replication uses a *publish* and *subscribe* model with one or more *subscribers* subscribing to one or more *publications* on a publisher node.

Use the *publication* dialog to create a publication. A publication is a set of changes generated from a table or a group of tables or a schema or a group of schemas, and might also be described as a change set or replication set.

The *publication* dialog organizes the development of a publication through the following dialog tabs: *General*, *Tables* and *Options*. The *SQL* tab displays the SQL code generated by dialog selections.




Use the fields in the *General* tab to identify the publication:


- Use the *Name* field to add a descriptive name for the publication. The name will be displayed in the *pgAdmin* tree control.
- The *Owner* field takes the name of the user automatically as current connected user. You can change the owner after creating publication using alter publication.

Click the *Tables* tab to continue.

Tables tab for PostgreSQL version <= 14



Tables tab for PostgreSQL version >= 15



Use the *Tables* tab to set table properties for the publication:

- Move the switch next to *All tables?* to *Yes* to replicate all the tables of the database, including tables created in the future.
- Move the switch next to *Only table?* to *Yes* to replicate only the listed tables excluding all its descendant tables.
- Specify a table or list of tables separated by a comma in *Tables* field to replicate all the listed table. With PostgreSQL 15 forward, specify a table or list of tables to replicate all the listed tables along with specific columns and/or WHERE clause to filter rows.
- With PostgreSQL 15 forward, specify a schema or list of schemas separated by a comma in *Tables In Schema* field to replicate all the listed schemas. This field will be disabled if any columns are selected for tables.

Click the *Options* tab to continue.



Use the *Options* tab to set option properties for the publication:

- Use the *With* section to determine which DML operations will be published by the new publication to the subscribers. Move the switch next to *INSERT*, *UPDATE*, *DELETE*, or *TRUNCATE* to *No* if you do not want to replicate any of these DML operations from Publication to Subscription. By default, all the switches are set to *Yes* allowing all the DML operations.

Note

A published table must have a "replica identity" configured in order to be able to replicate UPDATE and DELETE operations. You can change with ALTER TABLE statement. For more information on replica identity see Logical Replication Publication.

Click the *SQL* tab to continue.

Your entries in the *Publication* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

Example

The following is an example of the sql command generated by user selections in the *Publication* dialog:




The example creates a publication named *pub1* that is owned by *postgres*. It allows replication of all the DML operations.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore all the default settings.

5.21 Schema Dialog

Use the *Schema* dialog to define a schema. A schema is the organizational workhorse of a database, similar to directories or namespaces. To create a schema, you must be a database superuser or have the CREATE privilege.


The *Schema* dialog organizes the development of schema through the following dialog tabs: *General* and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields on the *General* tab to identify the schema.

- Use the *Name* field to add a descriptive name for the schema. The name will be displayed in the *pgAdmin* tree control.
- Select the owner of the schema from the drop-down listbox in the *Owner* field.
- Store notes about the schema in the *Comment* field.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and security labels for the schema.

Click the *Add* icon (+) to assign a set of privileges in the *Privileges* panel:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privileges to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional sets of privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.


Click the *Add* icon (+) to assign a security label in the *Security Labels* panel:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it

merely provides a mechanism for storing them.

Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Default Privileges* tab to continue.



Use the *Default Privileges* tab to grant privileges for tables, sequences, functions and types. Use the tabs nested inside the *Default Privileges* tab to specify the database object and click the *Add* icon (+) to assign a set of privileges:

- Select the name of a role that will be granted privileges in the schema from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privileges to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.


Click the *SQL* tab to continue.

Your entries in the *Schema* dialog generate a SQL command (see an example below). Use the *SQL* tab for review;

revisit or switch tabs to make any changes to the SQL command.

5.21.1 Example

The following is an example of the sql command generated by selections made in the *Schema* dialog:




The example creates a schema named hr; the command grants *USAGE* privileges to *public* and assigns the ability to grant privileges to *alice*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.22 Sequence Dialog

Use the *Sequence* dialog to create a sequence. A sequence generates unique values in a sequential order (not necessarily contiguous).

The *Sequence* dialog organizes the development of a sequence through the following dialog tabs: *General*, *Definition*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.




Use the fields in the *General* tab to identify a sequence:

- Use the *Name* field to add a descriptive name for the sequence. The name will be displayed in the *pgAdmin* tree control. The sequence name must be distinct from the name of any other sequence, table, index, view, or foreign table in the same schema.
- Use the drop-down listbox next to *Owner* to select the name of the role that will own the sequence.
- Use the drop-down listbox next to *Schema* to select the schema in which the sequence will reside.

- Store notes about the sequence in the *Comment* field.

Click the *Definition* tab to continue.




Use the fields in the *Definition* tab to define the sequence:

- Use the *Current Value* field to specify the sequence object's current value. The next nextval will return exactly the specified value, and sequence advancement commences with the following nextval. *This field is only available in the edit mode*.
- Use the *Increment* field to specify which value is added to the current sequence value to create a new value.
- Provide a value in the *Start* field to specify the beginning value of the sequence. The default starting value is MINVALUE for ascending sequences and MAXVALUE for descending ones.
- Provide a value in the *Minimum* field to specify the minimum value a sequence can generate. If this clause is not supplied or NO MINVALUE is specified, then defaults will be used. The defaults are 1 and -263-1 for ascending and descending sequences, respectively.
- Provide a value in the *Maximum* field to specify the maximum value for the sequence. If this clause is not supplied or NO MAXVALUE is specified, then default values will be used. The defaults are 263-1 and -1 for ascending and descending sequences, respectively.
- Provide a value in the *Cache* field to specify how many sequence numbers are to be preallocated and stored in memory for faster access. The minimum value is 1 (only one value can be generated at a time, i.e., no cache), and this is also the default.
- Move the switch next to *Cycled* to the *Yes* position to allow the sequence to wrap around when the MAXVALUE or the MINVALUE has been reached by an ascending or descending sequence respectively. If the limit is reached,

the next number generated will be the MINVALUE or MAXVALUE, respectively. The default is *No*.

- Move the switch next to *Unlogged?* to the *Yes* position to make the sequence Unlogged. The default is *No*. This option is available only on PostgreSQL 15 and above.
- The *OWNED BY* option causes the sequence to be associated with a specific table column, such that if that column (or its whole table) is dropped, the sequence will be automatically dropped as well. The specified table must have the same owner and be in the same schema as the sequence.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels for the sequence.

Use the *Privileges* panel to assign privileges. Click the *Add* icon (+) to set privileges:

- Select the name of a role that will be granted privileges from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected

privilege to the specified user.

- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the sequence. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Sequence* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.22.1 Example

The following is an example of the sql command generated by user selections in the *Sequence* dialog:



The example shown demonstrates a sequence named *seconds*. The sequence will increase in *5* second increments, and stop when it reaches a maximum value equal of *60*.


- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.23 Statistics Dialog

Use the *Statistics* dialog to define extended statistics on one or more columns (or expressions) of a table. Extended statistics let PostgreSQL collect correlation data across columns that can significantly improve query-plan estimates for queries that filter or group by multiple columns.

PostgreSQL introduced `CREATE STATISTICS` in PostgreSQL 10, and added expression statistics in PostgreSQL 14. This dialog is available for PostgreSQL 14 and later, which covers all currently supported PostgreSQL versions.

The *Statistics* dialog organizes options across the *General* and *Definition* tabs. The *SQL* tab displays the SQL command generated by your selections.



Use the fields in the *General* tab to describe the statistics object:


- Use the *Name* field to enter a descriptive name. On PostgreSQL 16 and later the name is optional, and the server will generate one from the table and the columns or expressions if you leave it blank.
- Use the *Owner* field to select the role that will own the statistics object.
- Use the *Schema* field to select the schema in which the statistics object will reside.
- Use the *Table* field to select the table on which the statistics will be collected. The list is filtered to tables in the selected schema.
- Use the *Columns* field to select two or more columns. Hold *Ctrl* (or *Cmd* on macOS) to select multiple columns. At least two columns are required when collecting column based statistics, although a single column is enough when it is combined with an expression.
- Use the *Statistics types* field to choose which kinds of extended statistics to collect:

  - *N-distinct*, which estimates the number of distinct value combinations across the selected columns or expressions.
  - *Dependencies*, which detects functional dependencies between columns, improving estimates for queries with correlated `WHERE` clauses.
  - *MCV (Most Common Values)*, which records the most common combinations of values.

  If you leave the field empty, PostgreSQL collects every kind it supports. Leave it empty for statistics on a single expression, which do not accept a choice of kinds.

- Use the *Comment* field to store an optional note about the statistics object.

Click the *Definition* tab to continue.



- Use the *Expressions* field to enter one or more SQL expressions separated by commas (for example `lower(col1), (col1 + col2)`). Each expression must be enclosed in parentheses unless it is a function call, and the list is passed to the server exactly as you enter it, so an expression may itself contain commas. Expressions may be given instead of columns, or alongside them when you want statistics over a mixture of the two.


When you open the dialog on an existing statistics object, the *Properties* view also reports the statistics target and, for roles with access, the values that `ANALYZE` has collected. Those values are read through the `pg_catalog.pg_stats_ext` view, which only shows them to roles the server allows to see them (the table's owners, on current PostgreSQL releases), so the *Computed Statistics* group is hidden when the current role lacks access.

Click the *SQL* tab to continue.

Your entries in the *Statistics* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes.

5.23.1 Example

The following is an example of the SQL command generated by user selections in the *Statistics* dialog:




- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.24 Subscription Dialog

Use the *Subscription* dialog to create a subscription. A subscription defines the connection to another database and set of publications (one or more) to which it wants to subscribe.


The *subscription* dialog organizes the development of a subscription through the following dialog tabs: *General*, *Connection*, *SSL* and *With*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the subscription:

- Use the *Name* field to add a descriptive name for the subscription. The name will be displayed in the *pgAdmin* tree control.
- The *Owner* field takes the name of the user automatically as current connected user. You can change the owner after creating subscription using alter subscription. Please note that owner of the subscription has superuser privileges.


Click the *Connection* tab to continue.



Use the *Connection* tab to define the connection string to the publisher:

- Use the *Host name/address* field to provide the valid hostname or ip address of the publication.
- Use the *Port* field to provide port number to connect at Postgres Server in which publication is residing.
- Use the *Username* field to provide the name of the user to connect to the publication.
- Use the *Password* to provide the password of the user.
- Use the *Database* field to connect to the database in which publication is residing.
- Use the *Connection timeout* field to specify the maximum wait for connection, in seconds. Zero or not specified means wait indefinetly. It is not recommended to use a timeout of less than 2 seconds.
- Use the *Passfile* field to specify the location of a password file (.pgpass). A .pgpass file allows a user to login without providing a password when they connect. For more information, see Section 33.15 of the Postgres documentation.
- Use the *Publication* field to specify the publication name on the publishers to subscribe to. Click on the refresh button at the end to load the names of the existing publications and then select from the list. You can also write the name of the known publication in the field.

Click the *SSL* tab to continue.



Use the fields in the *SSL* tab to configure SSL:

- Use the drop-down list box in the *SSL* field to select the type of SSL connection the server should use. For more information about using SSL encryption, see Section 33.18 of the Postgres documentation.

If pgAdmin is installed in Server mode (the default mode), you can use the platform-specific File manager dialog to upload files that support SSL encryption to the server. To access the File manager dialog, click the icon that is located to the right of each of the following fields.

- Use the *Client certificate* field to specify the file containing the client SSL certificate. This file will replace the default *~/.postgresql/postgresql.crt* if pgAdmin is installed in Desktop mode, and *<STORAGE_DIR>/<USERNAME>/.postgresql/postgresql.crt* if pgAdmin is installed in Web mode. This parameter is ignored if an SSL connection is not made.
- Use the *Client certificate key* field to specify the file containing the secret key used for the client certificate. This file will replace the default *~/.postgresql/postgresql.key* if pgAdmin is installed in Desktop mode, and *<STORAGE_DIR>/<USERNAME>/.postgresql/postgresql.key* if pgAdmin is installed in Web mode. This parameter is ignored if an SSL connection is not made.


- Use the *Root certificate* field to specify the file containing the SSL certificate authority. This file will replace the default *~/.postgresql/root.crt*. This parameter is ignored if an SSL connection is not made.
- Use the *Certificate revocation list* field to specify the file containing the SSL certificate revocation list. This list will replace the default list, found in *~/.postgresql/root.crl*. This parameter is ignored if an SSL connection is not made.
- When *SSL compression?* is set to *True*, data sent over SSL connections will be compressed. The default value is *False* (compression is disabled). This parameter is ignored if an SSL connection is not made.

Warning

In Server mode, certificates, private keys, and the revocation list are stored in the per-user file storage area on the server, which is owned by the user account under which the pgAdmin server process is run. This means that administrators of the server may be able to access those files; appropriate caution should be taken before choosing to use this feature.

Click the *With* tab to continue.


Create - Subscription
General
Connection
SSL
With
SQL
Copy data?
Specifies whether the existing data in the publications that are being subscribed to should be copied once the replication starts.
Create slot?
Specifies whether the command should create the replication slot on the publisher.This field will be disabled and set to false if subscription connects to same database.Otherwise, the CREATE SUBSCRIPTION call will hang.
Enabled?
Specifies whether the subscription should be actively replicating, or whether it should be just setup but not started yet.
Connect?
Specifies whether the CREATE SUBSCRIPTION should connect to the publisher at all. Setting this to false will change default values of enabled, create_slot and copy_data to false.
Slot name
Name of the replication slot to use. The default behavior is to use the name of the subscription for the slot name.
Synchronous commit
off
The value of this parameter overrides the synchronous_commit setting. The default value is off.
Streaming
On
Off
Parallel
Specifies whether to enable streaming of in-progress transactions for this subscription. By default, all transactions are fully decoded on the publisher and only then sent to the subscriber as a whole.
Close
Reset
Save



Use the *With* tab to define some parameters for a subscription:

- The *Copy data?* switch specifies whether the existing data in the publications that are being subscribed to should be copied once the replication starts. By default it is set to *Yes*.
- The *Create slot?* switch specifies whether the command should create the replication slot on the publisher. By default it is set to *Yes*. Please note: if your publisher and subscriber both are inside same PostgreSQL server then is is set to *No* by default.
- The *Enabled?* switch specifies whether the subscription should be actively replicating, or whether it should be just setup but not started yet. By default it is set to *Yes*.
- The *Connect?* specifies whether the CREATE SUBSCRIPTION should connect to the publisher at all. By default, it is set to *Yes*. Setting this to *No* will change default values of enabled, create_slot and copy_data to *No*.
- Use the *Slot Name* field to specify the name of the replication slot to use. By default, it uses the name of the subscription for the slot name.


- Use the *Synchronous commit* field to override the synchronous_commit setting. By default, it is set to *off*. It is safe to use off for logical replication: If the subscriber loses transactions because of missing synchronization, the data will be sent again from the publisher.
- Use the *Streaming* field to specify whether to enable streaming of in-progress transactions for this subscription. The default value is *off*, meaning all transactions are fully decoded on the publisher and only then sent to the subscriber as a whole. This option is available only on PostgreSQL 14 and above.
- Use the *Binary?* switch to specify whether the subscription will request the publisher to send the data in binary format (as opposed to text). The default is *false*. This option is available only on PostgreSQL 14 and above.
- Use the *Two phase?* switch to specify whether two-phase commit is enabled for this subscription. The default is *false*. This option is available only on PostgreSQL 15 and above.
- Use the *Disable on error?* switch to specify whether the subscription should be automatically disabled if any errors are detected by subscription workers during data replication from the publisher. The default is *false*. This option is available only on PostgreSQL 15 and above.
- Move the *Run as owner?* switch to *true* position to specify all replication actions are performed as the subscription owner. If *false*, replication workers will perform actions on each table as the owner of that table. The default is *false*. This option is available only on PostgreSQL 16 and above.
- Use the *Password required?* to specify whether connections to the publisher made as a result of this subscription must use password authentication. This setting is ignored when the subscription is owned by a superuser. The default is true. Only superusers can set this value to *false*. This option is available only on PostgreSQL 16 and above.
- Use the *Origin* to specify whether the subscription will request the publisher to only send changes that don't have an origin or send changes regardless of origin. The default is *any*. This option is available only on PostgreSQL 16 and above.
- Use the *Failover* to specify whether the replication slots associated with the subscription are enabled to be synced to the standbys so that logical replication can be resumed from the new primary after failover. The default is false. This option is available only on PostgreSQL 17 and above.

Click the *SQL* tab to continue.

Your entries in the *Subscription* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

Example

The following is an example of the sql command generated by user selections in the *Subscription* dialog:




The example creates a subscription named *sub1* that is owned by *postgres*. It will replicate the data from the publication *pub1*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore all the default settings.

5.25 Synonym Dialog

Use the *Synonym* dialog to substitute the name of a target object with a user-defined synonym.


The *Synonym* dialog organizes the development of a synonym through the *General* tab. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the synonym:

- Use the *Name* field to specify the name of synonym. The name will be displayed in the *pgAdmin* tree control.
- Select the name of the schema in which the synonym will reside from the drop-down listbox in the *Schema* field.

In the definition panel, identify the target:



- Use the drop-down listbox next to *Target Type* to select the type of object referenced by the synonym.
- Use the drop-down listbox next to *Target Schema* to select the name of the schema in which the object resides.
- Use the drop-down listbox next to *Target Object* to select the name of the object referenced by the synonym.

Click the *SQL* tab to continue.

Your selections and entries in the *Synonym* dialog generate a SQL command.




The example creates a synonym for the *emp* table named *emp_hist*.

- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.26 Trigger Function Dialog

Use the *Trigger function* dialog to create or manage a trigger_function. A trigger function defines the action that will be invoked when a trigger fires.


The *Trigger function* dialog organizes the development of a trigger function through the following dialog tabs: *General*, *Definition*, *Code*, *Options*, *Parameters* and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the trigger function:

- Use the *Name* field to add a descriptive name for the trigger function. The name will be displayed in the *pgAdmin* tree control. Please note that trigger functions will be invoked in alphabetical order.
- Use the drop-down listbox next to *Owner* to select the role that will own the trigger function.
- Select the name of the schema in which the trigger function will reside from the drop-down listbox in the *Schema* field.
- Store notes about the trigger function in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the trigger function:


- Use the drop-down listbox next to *Return type* to specify the pseudotype that is associated with the trigger function:
  - Select *trigger* if you are creating a DML trigger.
  - Select *event_trigger* if you are creating a DDL trigger.
- Use the drop-down listbox next to *Language* to select the implementation language. The default is *plpgsql*.

Click the *Code* tab to continue.



- Use the *Code* field to write the code that will execute when the trigger function is called.

Click the *Options* tab to continue.




Use the fields in the *Options* tab to describe or modify the action of the trigger function:

- Use the drop-down listbox next to *Volatility* to select one of the following:
  - *VOLATILE* indicates that the trigger function value can change even within a single table scan.
  - *STABLE* indicates that the trigger function cannot modify the database, and that within a single table scan it will consistently return the same result for the same argument values.
  - *IMMUTABLE* indicates that the trigger function cannot modify the database and always returns the same result when given the same argument values.
- Move the *Returns a Set?* switch to indicate if the trigger function returns a set that includes multiple rows. The default is *No*.
- Move the *Strict?* switch to indicate if the trigger function always returns NULL whenever any of its arguments are NULL. If *Yes*, the function is not executed when there are NULL arguments; instead a NULL result is assumed automatically. The default is *No*.

- Move the *Security of definer?* switch to specify that the trigger function is to be executed with the privileges of the user that created it. The default is *No*.
- Move the *Window?* switch to indicate that the trigger function is a window function rather than a plain function. The default is *No*. This is currently only useful for trigger functions written in C.
- Use the *Estimated cost* field to specify a positive number representing the estimated execution cost for the trigger function, in units of cpu_operator_cost. If the function returns a set, this is the cost per returned row.
- Use the *Estimated rows* field to specify a positive number giving the estimated number of rows that the query planner should expect the trigger function to return. This is only allowed when the function is declared to return a set. The default assumption is 1000 rows.
- Move the *Leak proof?* switch to indicate whether the trigger function has side effects. The default is *No*. This option can only be set by the superuser.

Click the *Parameters* tab to continue.




Use the fields in the *Parameters* tab to specify settings that will be applied when the trigger function is invoked. Click the *Add* icon (+) to add a *Name*/*Value* pair to the table below.

- Use the drop-down listbox in the *Name* field to select a parameter.
- Use the *Value* field to specify the value that will be associated with the selected parameter. This field is context-sensitive.

Click the *Add* icon (+) to set additional parameters; to discard a parameter, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign usage privileges for the trigger function to a role. Click the *Add* icon (+) to add a role to the table.

- Select the name of the role from the drop-down listbox in the *Grantee* field.

- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the trigger function. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Trigger function* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit other tabs to modify the SQL command.

5.26.1 Example

The following is an example of the sql command generated by user selections in the *Trigger function* dialog:




The example shown demonstrates creating a trigger function named *emp_stamp*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.27 Type Dialog

Use the *Type* dialog to register a custom data type.

The *Type* dialog organizes the development of a data type through the following dialog tabs: *General*, *Definition*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the custom data type:

- Use the *Name* field to add a descriptive name for the type. The name will be displayed in the *pgAdmin* tree control. The type name must be distinct from the name of any existing type, domain, or table in the same schema.
- Use the drop-down listbox next to *Owner* to select the role that will own the type.
- Select the name of the schema in which the type will reside from the drop-down listbox in the *Schema* field.
- Store notes about the type in the *Comments* field.

Click the *Definition* tab to continue.


Select a data type from the drop-down listbox next to *Type* on the *Definition* tab; the panel below changes to display the options appropriate for the selected data type. Use the fields in the panel to define the data type.

There are five data types:

- *Composite Type*

- *Enumeration Type*
- *Range Type*
- *External Type* (or *Base Type*)
- *Shell Type*

If you select *Composite* in the *Type* field, the *Definition* tab displays the *Composite Type* panel:




Click the *Add* icon (+) to provide attributes of the type. Fields on the *General* panel are context sensitive and may be disabled.

- Use the *Member Name* field to add an attribute name.
- Use the drop-down listbox in the *Type* field to select a datatype.
- Use the *Length/Precision* field to specify the maximum length of a non-numeric type, or the total count of significant digits in a numeric type.
- Use the *Scale* field to specify the number of digits to the right of the decimal point.
- Use the drop-down listbox in the *Collation* field to select a collation (if applicable).

Click the *Add* icon (+) to define an additional member; click the trash icon to the left of the row to discard a row.

If you select the *Enumeration* in the *Type* field, the *Definition* tab displays the *Enumeration Type* panel:




Click the *Add* icon (+) to provide a label for the type.

- Use the *Label* field to add a label, which must be less than 64 bytes long.

Click the *Add* icon (+) after each selection to create additional labels; to discard a label, click the trash icon to the left of the row.

If you select *External*, the *Definition* tab displays the *External Type* panel:



On the *Required* tab:

- Use the drop-down listbox next to the *Input function* field to add an input_function. The input_function converts the type's external textual representation to the internal representation used by the operators and functions defined for the type.
- Use the drop-down listbox next to the *Output function* field to add an output_function. The output_function converts the type's internal representation used by the operators and functions defined for the type to the type's external textual representation.

On the *Optional-1* tab:


- Use the drop-down listbox next to the optional *Receive Function* field to select a receive_function. The optional receive_function converts the type's external binary representation to the internal representation. If this function is not supplied, the type cannot participate in binary input.
- Use the drop-down listbox next to the optional *Send function* field to select a send_function. The optional send_function converts from the internal representation to the external binary representation. If this function is not supplied, the type cannot participate in binary output.
- Use the drop-down listbox next to the optional *Typmod in function* field tab to select a type_modifier_input_function.
- Use the drop-down listbox next to the optional *Typmod out function* field tab to select a type_modifier_output_function. It is allowed to omit the type_modifier_output_function, in which case the default display format is the stored typmod integer value enclosed in parentheses.

- Use the drop-down listbox next to the optional *Analyze function* field to select a function for performing type-specific statistics collection for columns of the data type.
- Use the drop-down listbox next to the optional *Subscript function* field to select a function for allows the data type to be subscripted in SQL commands.
- Use the optional *Internal length* to specify a value for internal representation.
- Specify a default value in the optional *Default* field in cases where a column of the data type defaults to something other than the null value. Specify the default with the DEFAULT key word. (A default can be overridden by an explicit DEFAULT clause attached to a particular column.)
- Use the drop-down listbox next to the optional *Category type* field to help control which implicit cast will be applied in ambiguous situations.
- Move the *Preferred?* switch to *Yes* to specify the selected category type is preferred. The default is *No*.

On the *Optional-2* tab:

- Use the drop-down listbox next to the optional *Element type* field to specify a data type.
- Use the optional *Delimiter* field to indicate the delimiter to be used between values in the external representation of arrays for this data type. The default delimiter is the comma (,). Note that the delimiter is associated with the array element type, not the array type itself.
- Use the drop-down listbox next to *Alignment type* to specify the storage alignment required for the data type. The allowed values (char, int2, int4, and double) correspond with alignment on 1, 2, 4, or 8 byte boundaries.
- Use the drop-down listbox next to optional *Storage type* to select a strategy for storing data.
- Move the *Passed by value?* switch to *Yes* to override the existing data type value. The default is *No*.
- Move the *Collatable?* switch to *Yes* to specify column definitions and expressions of the type may carry collation information through use of the COLLATE clause. The default is *No*.


If you select *Range* in the *Type* field, the *Definition* tab displays the *Range* panel. Fields on the *Range* panel are context-sensitive and may be disabled.



- Use the drop-down listbox next to *Sub-type* to select an associated b-tree operator class (to determine the ordering of values for the range type).
- Use the drop-down listbox next to *Sub-type operator class* to use a non-default operator class.


- Use the drop-down listbox next to *Collation* to use a non-default collation in the range's ordering if the sub-type is collatable.
- Use the drop-down listbox next to *Canonical function* to convert range values to a canonical form.
- Use the drop-down listbox next to *Sub-type diff function* to select a user-defined subtype_diff function.
- Specify the optional *Multirange type name* parameter to specify the name of the corresponding multirange type. If not specified, this name is chosen automatically.

If you select *Shell* in the *Type* field, the *Definition* tab displays the *Shell* panel:



A shell type is a placeholder for a type and has no parameters.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign privileges for the type; click the *Add* icon (+) to grant privileges:

- Select the name of the role that will be granted privileges on the type from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the type. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Type* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.27.1 Example

The following is an example of a sql command generated by user selections made in the *Type* dialog:




The example shown demonstrates creating a data type named *work_order*. The data type is an enumerated type with three labels: new, open and closed.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.28 User Mapping Dialog

Use the *User Mapping* dialog to define a new mapping of a user to a foreign server.


The *User Mapping* dialog organizes the development of a user mapping through the following dialog tabs: *General* and *Options*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the drop-down listbox in the *User* field in the *General* tab to identify the connecting role:

- Select *CURRENT_USER* to use the name of the current role.
- Select *PUBLIC* if no other user-specific mapping is applicable.
- Select a pre-defined role name to specify the name of an existing user.

Click the *Options* tab to continue.



Use the fields in the *Options* tab to specify connection options; the accepted option names and values are specific to the foreign data wrapper associated with the server specified in the user mapping. Click the *Add* button to add an option/value pair.

- Specify the option name in the *Option* field.
- Provide a corresponding value in the *Value* field.

Click *Add* to specify each additional option/value pair; to discard an option, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *User Mapping* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.28.1 Example

The following is an example of the sql command generated by user selections in the *User Mapping* dialog:



The example shown demonstrates a user mapping for the *hdfs_server*. The user is *CURRENT_USER* with a password *secret*.


- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

5.29 View Dialog

Use the *View* dialog to define a view. The view is not physically materialized; the query is executed each time the view is referenced in a query.

The *View* dialog organizes the development of a View through the following dialog tabs: *General*, *Definition*, *Code* and *Security*". The *SQL* tab displays the SQL code generated by dialog selections.

Click the *General* tab to begin.



Use the fields in the *General* tab to identify a view:

- Use the *Name* field to add a descriptive name for the view. The name of the view must be distinct from the name of any other view, table, sequence, index or foreign table in the same schema. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Owner* to select the role that will own the view.
- If applicable, select the name of the schema in which the view will reside from the drop-down listbox in the *Schema* field.

- Store notes about the view in the *Comments* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define properties of the view:


- Set the *Security Barrier* switch to *Yes* to indicate that the view is to act as a security barrier. For more information about defining and using a security barrier rule, see Rules and Privileges of the PostgreSQL documentation.
- Set the *Security Invoker* switch to *Yes* to indicate that the underlying base relations are to be checked against the privileges of the user of the view rather than the view owner. This option is available from PostgreSQL 15 onwards.
- Use the drop-down listbox next to *Check options* to select from *No*, *Local* or *Cascaded*:
  - The *Local* option specifies that new rows are only checked against the conditions defined in the view. Any conditions defined on underlying base views are not checked (unless you specify the CHECK OPTION).
  - The *Cascaded* option specifies new rows are checked against the conditions of the view and all underlying base views.

Click the *Code* tab to continue.



Use the workspace in the *Code* tab to write a query to create a view.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign privileges to a role. Click the *Add* icon (+) to set privileges for the view:

- Select the name of the role that will be granted privileges from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the view. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label

provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *View* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

5.29.1 Example

The following is an example of the sql command generated by user selections in the *View* dialog:



The example shown demonstrates creating a view named *distributor_code*.

- Click the *Info* button (i) to access online help.

- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

CHAPTER 6

Creating or Modifying a Table


pgAdmin 4 provides dialogs that allow you to modify all table properties and attributes.

To access a dialog that allows you to create a database object, right-click on the object type in the pgAdmin tree control, and select the *Create* option for that object. For example, to create a new table, Select a database from the tree control, select the schema under the database, right-click on the *Tables* node, and select *Create Table...*

6.1 Check Dialog

Use the *Check* dialog to define or modify a check constraint. A check constraint specifies an expression that produces a Boolean result that new or updated rows must satisfy for an insert or update operation to succeed.


The *Check* dialog organizes the development of a check constraint through the *General* and *Definition* tabs. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the check constraint:

- Use the *Name* field to provide a descriptive name for the check constraint that will be displayed in the *pgAdmin* tree control. With PostgreSQL 9.5 forward, when a table has multiple check constraints, they will be tested for each row in alphabetical order by name and after NOT NULL constraints.
- Store notes about the check constraint in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the check constraint:


- Provide the expression that a row must satisfy in the *Check* field.
- Move the *No Inherit?* switch to the *Yes* position to specify that this constraint is not automatically inherited by a table's children. The default is *No*, meaning that the constraint will be inherited by any children.
- Move the *Don't validate?* switch to the *No* position to skip validation of existing data; the constraint may not hold for all rows in the table. The default is *Yes*.

Click the *SQL* tab to continue.

Your entries in the *Check* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

Example

The following is an example of the sql command generated by user selections in the *Check* dialog:




The example shown demonstrates creating a check constraint named *jobhist_date_chk* on the *startdate* column of the *jobhist* table.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.2 Column Dialog

Use the *Column* dialog to add a column to an existing table or modify a column definition.


The *Column* dialog organizes the development of a column through the following dialog tabs: *General*, *Definition*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the column:

- Use the *Name* field to add a descriptive name for the column. The name will be displayed in the *pgAdmin* tree control. This field is required.
- Store notes about the column in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to add parameters for the column. (Fields are disabled if inapplicable.)

- Use the drop-down listbox next to *Data Type* to select a data type for the column. For more information on the data types that are supported by PostgreSQL, refer to Chapter 8 of the Postgres core documentation. This field is required.
- Use the *Length/Precision* and *Scale* fields to specify the maximum number of significant digits in a numeric value, or the maximum number of characters in a text value.
- Use the drop-down listbox next to *Collation* to apply a collation setting to the column.
- Use the drop-down listbox next to *Compression* to set the compression method for the column. Compression is supported only for variable-width data types, and is used only when the column's storage mode is main or extended. This option is available from v14 and above.
- Use the drop-down listbox next to *Storage* to set the storage mode for the column. This option is available from v16 and above.


Click the *Constraints* tab to continue.



Use the fields in the *Constraints* tab to specify constraints for the column. (Fields are disabled if inapplicable.)

- Use the *Default Value* field to specify a default data value.
- Move the *Not Null* switch to the *Yes* position to specify the column may not contain null values. The default is *No*.
- Use the *Type* field to specify the column type (NONE/IDENTITY/GENERATED). The default is *NONE*.

Click the *IDENTITY* type to create Identity column.



Use the following fields to create *IDENTITY* column. Identity columns are applicable for PG/EPAS version 10 and above.

- Use the *Identity* field to specify ALWAYS or BY DEFAULT. This clause is used to determine how the sequence value is given precedence over a user-specified value in an INSERT statement.
- Use the *Increment* field to specify which value is added to the current sequence value to create a new value.
- Provide a value in the *Start* field to specify the beginning value of the sequence. The default starting value is MINVALUE for ascending sequences and MAXVALUE for descending ones.
- Provide a value in the *Minimum* field to specify the minimum value a sequence can generate. If this clause is not supplied or NO MINVALUE is specified, then defaults will be used. The defaults are 1 and -263-1 for ascending and descending sequences, respectively.
- Provide a value in the *Maximum* field to specify the maximum value for the sequence. If this clause is not supplied or NO MAXVALUE is specified, then default values will be used. The defaults are 263-1 and -1 for ascending and descending sequences, respectively.

- Provide a value in the *Cache* field to specify how many sequence numbers are to be preallocated and stored in memory for faster access. The minimum value is 1 (only one value can be generated at a time, i.e., no cache), and this is also the default.
- Move the *Cycled* switch to the *Yes* position to allow the sequence to wrap around when the MAXVALUE or the MINVALUE has been reached by an ascending or descending sequence respectively. If the limit is reached, the next number generated will be the MINVALUE or MAXVALUE, respectively. The default is *No*.


Click the *GENERATED* type to create Generated column.



Use the following fields to create *GENERATED* column. Generated columns are applicable for PG/EPAS version 12 and above.

- Use the *Expression* field to specify the generation expression. It can refer to other columns in the table, but not other generated columns. Any functions and operators used must be immutable. References to other tables are not allowed.

Click the *Variables* tab to continue.




Use the *Variables* tab to specify the number of distinct values that may be present in the column; this value overrides estimates made by the ANALYZE command. Click the *Add* icon (+) to add a *Name*/*Value* pair:

- Select the name of the variable from the drop-down listbox in the *Name* field.
  - Select *n_distinct* to specify the number of distinct values for the column.
  - Select *n_distinct_inherited* to specify the number of distinct values for the table and its children.
- Specify the number of distinct values in the *Value* field. For more information, see the documentation for ALTER TABLE.

Click the *Add* icon (+) to specify each additional *Name*/*Value* pair; to discard a variable, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Security* tab to continue.



Use the *Security* tab to assign attributes and define security labels. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Column* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.2.1 Example

The following is an example of the sql command generated by user selections in the *Column* dialog:




The example shown demonstrates creating a column named *sal* in the table named *jobhist*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.3 Compound Trigger Dialog


Use the *Compound Trigger* dialog to create a compound trigger or modify an existing compound trigger. *Compound Trigger* is supported only for EPAS server 12 and above. A compound trigger executes a specified code when certain events occur.

The *Compound Trigger* dialog organizes the development of a compound trigger through the following dialog tabs: *General*, *Events*, and *Code*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the compound trigger:

- Use the *Name* field to add a descriptive name for the compound trigger. This must be distinct from the name of any other compound trigger for the same table. The name will be displayed in the *pgAdmin* tree control.
- Store notes about the compound trigger in the *Comment* field.



- *Trigger enabled* field is available in compound trigger dialog once the trigger is created. You can select one of the four options available.


Click the *Events* tab to continue.



Use the fields in the *Events* tab to specify how and when the compound trigger fires:

- Select the type of event(s) that will invoke the compound trigger; to select an event type, move the switch next to the event to the *YES* position. The supported event types are *INSERT*, *UPDATE*, *DELETE* and *TRUNCATE*. Views cannot have TRUNCATE triggers.
- Use the *When* field to provide a boolean condition that will invoke the compound trigger.
- If defining a column-specific compound trigger, use the *Columns* field to specify the columns or columns that are the target of the compound trigger.

Click the *Code* tab to continue.




Use the *Code* field to specify the code for the five timing events *BEFORE STATEMENT*, *AFTER STATEMENT*, *BEFORE EACH ROW*, *AFTER EACH ROW*, *INSTEAD OF EACH ROW* that will be invoked when the compound trigger fires. Basic template is provided with place holders.

Click the *SQL* tab to continue.

Your entries in the *Compound Trigger* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.3.1 Example

The following is an example of the sql command generated by user selections in the *Compound Trigger* dialog:




The example demonstrates creating a compound trigger named *test_ct*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.4 Exclusion Constraint Dialog

Use the *Exclusion constraint* dialog to define or modify the behavior of an exclusion constraint. An exclusion constraint guarantees that if any two rows are compared on the specified column or expression (using the specified operator), at least one of the operator comparisons will return false or null.


The *Exclusion constraint* dialog organizes the development of an exclusion constraint through the following dialog tabs: *General*, *Definition*, and *Columns*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the exclusion constraint:

- Use the *Name* field to provide a descriptive name for the exclusion constraint. The name will be displayed in the *pgAdmin* tree control.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the exclusion constraint:

- Use the drop-down listbox next to *Tablespace* to select the tablespace in which the index associated with the exclude constraint will reside.
- Use the drop-down listbox next to *Access method* to specify the type of index that will be used when implementing the exclusion constraint:
  - Select *gist* to specify a GiST index.
  - Select *spgist* to specify a space-partitioned GiST index.
  - Select *btree* to specify a B-tree index.
  - Select *hash* to specify a hash index.
- Use the *Fill Factor* field to specify a fill factor for the table and associated index. The fill factor is a percentage between 10 and 100. 100 (complete packing) is the default.
- Move the *Deferrable?* switch to the *Yes* position to specify that the timing of the constraint is deferrable, and can be postponed until the end of the statement. The default is *No*.
- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint is deferred to the end of the statement. The default is *No*.
- Use the *Constraint* field to provide a condition that a row must satisfy to be included in the table.

Click the *Columns* tab to continue.



Use the fields in the *Columns* tab to specify the column(s) or expression(s) to which the constraint applies. Use the *Is expression ?* switch to enable expression text input. Use the drop-down listbox next to *Column* to select a column. Once the *Column* is selected or the *Expression* is entered then click the *Add* icon (+) to provide details of the action on the column/expression:

- The *Col/Exp* field is populated with the selection made in the *Column* drop-down listbox or the *Expression* entered.
- If applicable, use the drop-down listbox in the *Operator class* to specify the operator class that will be used by the index for the column.
- Move the *DESC* switch to *DESC* to specify a descending sort order. The default is *ASC* which specifies an ascending sort order.
- Use the *NULLs order* column to specify the placement of NULL values (when sorted). Specify *FIRST* or *LAST*.
- Use the drop-down list next to *Operator* to specify a comparison or conditional operator.


Use *Include columns* field to specify columns for *INCLUDE* clause of the constraint. This option is available in Postgres 11 and later.

Click the *SQL* tab to continue.

Your entries in the *Exclusion Constraint* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.4.1 Example

The following is an example of the sql command generated by user selections in the *Exclusion Constraint* dialog:




The example shown demonstrates creating an exclusion constraint named *ex_dept_no*. The constraint uses a btree index.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.5 Foreign key Dialog

Use the *Foreign key* dialog to specify the behavior of a foreign key constraint. A foreign key constraint maintains referential integrity between two tables. A foreign key constraint cannot be defined between a temporary table and a permanent table.

The *Foreign key* dialog organizes the development of a foreign key constraint through the following dialog tabs: *General*, *Definition*, *Columns*, and *Action*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the foreign key constraint:

- Use the *Name* field to add a descriptive name for the foreign key. The name will be displayed in the *pgAdmin* tree control.
- Store notes about the foreign key constraint in the *Comment* field.

Click the *Definition* tab to continue.




Use the fields in the *Definition* tab to define the foreign key constraint:

- Move the *Deferrable?* switch to the *Yes* position to specify the timing of the constraint is deferrable and can be postponed until the end of the statement. The default is *No*.
- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint is deferred to the end of the statement. The default is *No*.
- Move the *Match type* switch specify the type of matching that is enforced by the constraint:
  - Select *Full* to indicate that all columns of a multicolumn foreign key must be null if any column is null; if all columns are null, the row is not required to have a match in the referenced table.
  - Select *Simple* to specify that a single foreign key column may be null; if any column is null, the row is not required to have a match in the referenced table.
- Move the *Validated* switch to the *Yes* position to instruct the server to validate the existing table content (against a foreign key or check constraint) when you save modifications to this dialog.
- Move the *Auto FK Index* switch to the *No* position to disable the automatic index feature.

- The field next to *Covering Index* generates the name of an index if the *Auto FK Index* switch is in the *Yes* position; or, this field is disabled.

Click the *Columns* tab to continue.




Use the fields in the *Columns* tab to specify one or more reference column(s). A Foreign Key constraint requires that one or more columns of a table must only contain values that match values in the referenced column(s) of a row of a referenced table:

- Use the drop-down listbox next to *Local column* to specify the column in the current table that will be compared to the foreign table.
- Use the drop-down listbox next to *References* to specify the name of the table in which the comparison column(s) resides.
- Use the drop-down listbox next to *Referencing* to specify a column in the foreign table.

Click the *Add* icon (+) to add a column to the list; repeat the steps above and click the *Add* icon (+) to add additional columns. To discard an entry, click the trash icon to the left of the entry and confirm deletion in the *Delete Row* popup.

Click the *Action* tab to continue.



Use the drop-down listboxes on the *Action* tab to specify behavior related to the foreign key constraint that will be performed when data within the table is updated or deleted:

- Use the drop-down listbox next to *On update* to select an action that will be performed when data in the table is updated.
- Use the drop-down listbox next to *On delete* to select an action that will be performed when data in the table is deleted.

The supported actions are:

NO ACTION	Produce an error indicating that the deletion or update will create a foreign key constraint violation. If the constraint is deferred, this error will be produced at constraint check time if any referencing rows still exist. This is the default.
RESTRICT	Throw an error indicating that the deletion or update would create a foreign key constraint violation. This is the same as NO ACTION except that the check is not deferrable.
CASCADE	Delete any rows referencing the deleted row, or update the values of the referencing column(s) to the new values of the referenced columns, respectively.
SET NULL	Set the referencing column(s) to null.
SET DEFAULT	Set the referencing column(s) to their default values. There must be a row in the referenced table that matches the default values (if they are not null), or the operation will fail.

Click the *SQL* tab to continue.

Your entries in the *Foreign key* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.5.1 Example

The following is an example of the sql command generated by user selections in the *Foreign key* dialog:




The example shown demonstrates creating a foreign key constraint named *jobhist_ref_dept_fk* that matches values in the *jobhist* table *dept_no* column with those of the *dept* table *deptno* column.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.6 Index Dialog

Use the *Index* dialog to create an index on a specified table or materialized view.


The *Index* dialog organizes the development of a index through the following dialog tabs: *General*, *Definition*, and *Columns*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the index:

- Use the *Name* field to add a descriptive name for the index. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Tablespace* to select the tablespace in which the index will reside.
- Store notes about the index in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the index:


- Use the drop-down listbox next to *Access Method* to select an index type:
  - Select *btree* to create a B-tree index. A B-tree index may improve performance when managing equality and range queries on data that can be sorted into some ordering (the default).
  - Select *hash* to create a hash index. A hash index may improve performance when managing simple equality comparisons.
  - Select *gist* to create a GiST index. A GiST index may improve performance when managing two-dimensional geometric data types and nearest-neighbor searches.
  - Select *gin* to create a GIN index. A GIN index may improve performance when managing values with more than one key.
  - Select *spgist* to create a space-partitioned GiST index. A SP-GiST index may improve performance when managing non-balanced data structures.
  - Select *brin* to create a BRIN index. A BRIN index may improve performance when managing minimum and maximum values and ranges.
- Use the drop-down listbox next to *Depends on extensions* to select the extension that this index depends on (for example, edbspl). If set, dropping the extension will automatically drop the index as well.
- Move the switch next to *Only Table?* to the *Yes* position to create the index only on the parent table without recursing to its partitions. This button will be enabled for partition tables only. The default is *No*.
- Move the switch next to *Unique?* to the *Yes* position to check for duplicate values in the table when the index is created and when data is added. The default is *No*.
- Move the switch next to *NULLs not distinct?* to the *Yes* position to treat null values as not distinct. The default is *No*. This option is available only on PostgreSQL 15 and above.
- Move the *Clustered?* switch to the *Yes* position to instruct the server to cluster the table.
- Move the *Concurrent build?* switch to the *Yes* position to build the index without taking any locks that prevent concurrent inserts, updates, or deletes on the table.
- Use the *Constraint* field to provide a constraint expression; a constraint expression limits the entries in the index to those rows that satisfy the constraint.

Click the *With* tab to continue.



- Use the *Fill Factor* field to specify a fill factor for the index. The fill factor specifies how full the selected method will try to fill each index page.
- Use the *Gin pending list limit* field to specify the maximum size of a GIN index's pending list, which is used when fastupdate is enabled. This value is specified in kilobytes.
- Use the *Pages per range* field to specify the number of table blocks that make up one block range for each entry of a BRIN index.
- Select *Buffering* to specify whether the buffering build technique is used to build the index. The default is *Auto*
- Move the switch next to *Deduplicate items?* to the *Yes* position to control usage of the B-tree deduplication technique. The default is *Yes*. This option is available only on PostgreSQL 13 and above.
- Move the switch next to *Fast update?* to the *Yes* position to control usage of the fast update technique. The default is *Yes*.
- Move the switch next to *Autosummarize* to the *Yes* position to define whether a summarization run is queued for the previous page range whenever an insertion is detected on the next one. The default is *No*

Click the *Columns* tab to continue.



Use the fields in the *Columns* tab to specify which column(s) or expression(s) the index queries. Use the *Is expression ?* switch to enable expression sql input. Use the drop-down listbox next to *Column* to select a column. Once the *Column* is selected or the *Expression* is entered then click the *Add* icon (+) to provide details of the action on the column/expression:

- The *Col/Exp* field is populated with the selection made in the *Column* drop-down listbox or the *Expression* entered.
- If enabled, use the drop-down listbox to select an available *Operator class* to specify the type of action performed on the column.
- If enabled, use the drop-down listbox to select *Sort order*:
  - Select *ASC* to specify an ascending sort order (the default);
  - Select *DESC* to specify a descending sort order.
- If enabled, use the drop-down listbox to select *Nulls*:
  - Select *First* to specify nulls sort before non-nulls;
  - Select *Last* to specify nulls sort after non-nulls (the default).
- Use the drop-down listbox in the *Collation* field to select a collation to use for the index.


Use *Include columns* field to specify columns for *INCLUDE* clause of the constraint. This option is available in Postgres 11 and later.

Click the *SQL* tab to continue.

Your entries in the *Index* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.6.1 Example

The following is an example of the sql command generated by user selections in the *Index* dialog:




The example shown demonstrates creating an index named *index_sal* that indexes the values in the *job* column of the *jobhist* table.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.7 Primary key Dialog

Use the *Primary key* dialog to create or modify a primary key constraint. A primary key constraint indicates that a column, or group of columns, uniquely identifies rows in a table. This requires that the values in the selected column(s) be both unique and not null.

The *Primary key* dialog organizes the development of a primary key constraint through the *General* and *Definition* tabs. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the primary key:

- Use the *Name* field to add a descriptive name for the primary key constraint. The name will be displayed in the *pgAdmin* tree control.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the primary key constraint:

- Click inside the *Columns* field and select one or more column names from the drop-down listbox. To delete a selection, click the *x* to the left of the column name. The primary key constraint should be different from any unique constraint defined for the same table; the selected column(s) for the constraints must be distinct.
- Use *Include columns* field to specify columns for *INCLUDE* clause of the index. This option is available in Postgres 11 and later.
- Select the name of the tablespace in which the primary key constraint will reside from the drop-down listbox in the *Tablespace* field.
- Select the name of an index from the drop-down listbox in the *Index* field. This field is optional. Adding a primary key will automatically create a unique B-tree index on the column or group of columns listed in the primary key, and will force the column(s) to be marked NOT NULL.
- Use the *Fill Factor* field to specify a fill factor for the table and index. The fill factor for a table is a percentage between 10 and 100. 100 (complete packing) is the default.
- Move the *Deferrable?* switch to the *Yes* position to specify the timing of the constraint is deferrable and can be

postponed until the end of the statement. The default is *No*.


- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint is deferred to the end of the statement. The default is *No*.

Click the *SQL* tab to continue.

Your entries in the *Primary key* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.7.1 Example

The following is an example of the sql command generated by user selections in the *Primary key* dialog:



The example shown demonstrates creating a primary key constraint named *jobhist_pk* on the *empno* column of the *jobhist* table.

- Click the *Info* button (i) to access online help.

- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.


6.8 RLS Policy Dialog

Use the *RLS Policy* dialog to Create a Row Level Security Policy.

Note

If the Row Level Security is enabled at table level and no policy is created then by default *Deny Policy* is applied. That means, no rows are visible or can be modified for that table.


The *RLS Policy* dialog creates a Row Level Security Policy through the following dialog tabs: *General*, and *Commands*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to define the RLS Policy:

- Use the *Name* field to add a descriptive name for the RLS Policy. The name will be displayed in the *pgAdmin* tree control.
- Use the drop-down listbox next to *Role* to select the Role to which the RLS Policy is to be applied.
- Use the drop-down listbox next to *Type* to select the type of the policy.
- Store notes about the policy in the Comment field.

Click the *Commands* tab to continue.



Use the fields in the *Commands* tab to define the RLS Policy:

- Use the drop-down listbox next to *Event* to select the command to which policy applies. Valid options are ALL, SELECT, INSERT, UPDATE, and DELETE. Default is ALL.
- Use the *Using* field to add a SQL conditional expression returning boolean. This expression will be added to queries that refer to the table if row level security is enabled.
- Use the *With check* field to add a SQL conditional expression returning boolean. This expression will be used in INSERT and UPDATE queries against the table if row level security is enabled.

Click the *SQL* tab to continue.

Your entries in the *RLS Policy* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.8.1 Example

The following is an example of the sql command generated by user selections in the *RLS Policy* dialog:



The example shown demonstrates creating a RLS Policy named *jobhist_rls* that applies the Row Level Security on the *jobhist* table.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.9 Rule Dialog

Use the *Rule* dialog to define or modify a rule for a specified table or view. A PostgreSQL rule allows you to define an additional action that will be performed when a SELECT, INSERT, UPDATE, or DELETE is performed against a table.

The *Rule* dialog organizes the development of a rule through the *General*, *Definition*, *Condition*, *Commands* tabs. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the rule:


- Use the *Name* field to add a descriptive name for the rule. The name will be displayed in the *pgAdmin* tree control. Multiple rules on the same table are applied in alphabetical name order.
- Store notes about the rule in the *Comment* field.

Click the *Definition* tab to continue.




Use the fields in the *Definition* tab to write parameters:

- Click inside the *Event* field to select the type of event that will invoke the rule; event may be *Select*, *Insert*, *Update*, or *Delete*.
- Move the *Do Instead* switch to *Yes* indicate that the commands should be executed instead of the original command; if Do Instead specifies *No*, the rule will be invoked in addition to the original command.




- *Rule enabled* field is available in rule dialog once the rule is created. You can select one of the four options available.

Click the *Condition* tab to continue.



Specify a SQL conditional expression that returns a boolean value in the editor.

Click the *Commands* tab to continue.



Provide a command in the editor that defines the action performed by the rule.

Click the *SQL* tab to continue.

Your entries in the *Rule* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.9.1 Example

The following is an example of the sql command generated by user selections in the *Rule* dialog:




- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.10 Table Dialog

Use the *Table* dialog to create or modify a table.

The *Table* dialog organizes the development of a table through the following dialog tabs: *General*, *Columns*, *Constraints*, *Advanced*, *Parition*, *Parameter*, and *Security*. The *SQL* tab displays the SQL code generated by dialog selections.




Use the fields in the *General* tab to identify the table:

- Use the *Name* field to add a descriptive name for the table. A table cannot have the same name as any existing table, sequence, index, view, foreign table, or data type in the same schema. The name specified will be displayed in the *pgAdmin* tree control. This field is required.
- Select the owner of the table from the drop-down listbox in the *Owner* field. By default, the owner of the table is the role that creates the table.
- Select the name of the schema in which the table will reside from the drop-down listbox in the *Schema* field.
- Use the drop-down listbox in the *Tablespace* field to specify the tablespace in which the table will be stored.
- Move the *Partitioned Table?* switch to the *Yes* in case you want to create a partitioned table. Option is available

for PostgreSQL 10 and above.

- Store notes about the table in the *Comment* field.

Click the *Columns* tab to continue.




Use the drop-down listbox next to *Inherited from table(s)* to specify any parent table(s); the table will inherit columns from the selected parent table(s). Click inside the *Inherited from table(s)* field to select a table name from a drop-down list. Repeat to add any other parent tables. Delete a selected table by clicking the *x* to the left of the parent name. Note that inherited column names and datatypes are not editable in the current dialog; they must be modified at the parent level.

Click the *Add* icon (+) to specify the names of columns and their datatypes in the *Columns* table:

- Use the *Name* field to add a descriptive name for the column.
- Use the drop-down listbox in the *Data type* field to select a data type for the column. This can include array specifiers. For more information on the data types supported by PostgreSQL, refer to Chapter 8 of the core documentation.
- If enabled, use the *Length/Precision* and *Scale* fields to specify the maximum number of significant digits in a numeric value, or the maximum number of characters in a text value.
- Move the *Not NULL?* switch to the *Yes* position to require a value in the column field.
- Move the *Primary key?* switch to the *Yes* position to specify the column is the primary key constraint.

Click the *Add* icon (+) to add additional columns; to discard a column, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *Constraints* tab to continue.



Use the fields in the *Constraints* tab to provide a table or column constraint. Optional constraint clauses specify constraints (tests) that new or updated rows must satisfy for an *INSERT* or *UPDATE* operation to succeed. Select the appropriate constraint type by selecting one of the following tabs on the *Constraints* panel:

Tab Name	Constraint
Primary Key	Provides a unique identifier for each row in the table.
Foreign Key	Maintains referential integrity between two tables.
Check	Requires data satisfies an expression or condition before insertion or modification.
Unique	Ensures that the data contained in a column, or a group of columns, is unique among all the rows in the table.
Exclude	Guarantees that if any two rows are compared on the specified column or expression (using the specified operator), at least one of the operator comparisons will return false or null.

To add a primary key for the table, select the *Primary Key* tab, and click the *Add* icon (+). To define the primary key, click the *Edit* icon to the left of the *Trash* icon. A dialog similar to the *Primary key* dialog (accessed by right clicking on *Constraints* in the *pgAdmin* tree control) opens.

Use the fields in the *General* tab to identify the primary key:


- Use the *Name* field to add a descriptive name for the primary key constraint. The name will be displayed in the *pgAdmin* tree control.
- Provide notes about the primary key in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the primary key constraint:

- Click inside the *Columns* field and select one or more column names from the drop-down listbox. To delete a selection, click the *x* to the left of the column name. The primary key constraint should be different from any unique constraint defined for the same table; the selected column(s) for the constraints must be distinct.
- Select the name of the tablespace in which the primary key constraint will reside from the drop-down listbox in the *Tablespace* field.
- Use the *Fill Factor* field to specify a fill factor for the table and index. The fill factor for a table is a percentage between 10 and 100. 100 (complete packing) is the default.
- Move the *Deferrable?* switch to the *Yes* position to specify the timing of the constraint is deferrable and can be postponed until the end of the statement. The default is *No*.
- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint is deferred to the end of the statement. The default is *No*.



To add a foreign key constraint, select the *Foreign Key* tab, and click the *Add* icon (+). To define the constraint, click the *Edit* icon to the left of the *Trash* icon. A dialog similar to the *Foreign key* dialog (accessed by right clicking on *Constraints* in the *pgAdmin* tree control) opens.

Use the fields in the *General* tab to identify the foreign key constraint:

- Use the *Name* field to add a descriptive name for the foreign key constraint. The name will be displayed in the *pgAdmin* tree control.
- Provide notes about the foreign key in the *Comment* field.

Click the *Definition* tab to continue.




Use the fields in the *Definition* tab to define the foreign key constraint:

- Move the *Deferrable?* switch to the *Yes* position to specify the timing of the constraint is deferrable and can be postponed until the end of the statement. The default is *No*.
- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint is deferred to the end of the statement. The default is *No*.
- Move the *Match type* switch specify the type of matching that is enforced by the constraint:
  - Select *Full* to indicate that all columns of a multicolumn foreign key must be null if any column is null; if all columns are null, the row is not required to have a match in the referenced table.
  - Select *Simple* to specify that a single foreign key column may be null; if any column is null, the row is not required to have a match in the referenced table.
- Move the *Validated* switch to the *Yes* position to instruct the server to validate the existing table content (against a foreign key or check constraint) when you save modifications to this dialog.
- Move the *Auto FK Index* switch to the *No* position to disable the automatic index feature.

- The field next to *Covering Index* generates the name of an index if the *Auto FK Index* switch is in the *Yes* position; or, this field is disabled.

Click the *Columns* tab to continue.




Use the fields in the *Columns* tab to specify one or more reference column(s).

A Foreign Key constraint requires that one or more columns of a table must only contain values that match values in the referenced column(s) of a row of a referenced table:

- Use the drop-down listbox next to *Local column* to specify the column in the current table that will be compared to the foreign table.
- Use the drop-down listbox next to *References* to specify the name of the table in which the comparison column(s) resides.
- Use the drop-down listbox next to *Referencing* to specify a column in the foreign table.

Click the *Add* icon (+) to add a column to the list; repeat the steps above and click the *Add* icon (+) to add additional columns. To discard an entry, click the trash icon to the left of the entry and confirm deletion in the *Delete Row* popup.

Click the *Action* tab to continue.



Use the drop-down listboxes on the *Action* tab to specify behavior related to the foreign key constraint that will be performed when data within the table is updated or deleted:

- Use the drop-down listbox next to *On update* to select an action that will be performed when data in the table is updated.
- Use the drop-down listbox next to *On delete* to select an action that will be performed when data in the table is deleted.


The supported actions are:

NO ACTION	Produce an error indicating that the deletion or update will create a foreign key constraint violation. If the constraint is deferred, this error will be produced at constraint check time if any referencing rows still exist. This is the default.
RESTRICT	Throw an error indicating that the deletion or update would create a foreign key constraint violation. This is the same as NO ACTION except that the check is not deferrable.

continues on next page

Table 2 – continued from previous page

CASCADE	Delete any rows referencing the deleted row, or update the values of the referencing column(s) to the new values of the referenced columns, respectively.
SET NULL	Set the referencing column(s) to null.
SET DEFAULT	Set the referencing column(s) to their default values. There must be a row in the referenced table that matches the default values (if they are not null), or the operation will fail.




To add a check constraint, select the *Check* tab on the panel, and click the *Add* icon (+). To define the check constraint, click the *Edit* icon to the left of the *Trash* icon. A dialog similar to the *Check* dialog (accessed by right clicking on *Constraints* in the *pgAdmin* tree control) opens.

Use the fields in the *General* tab to identify the check constraint:


- Use the *Name* field to add a descriptive name for the check constraint. The name will be displayed in the *pgAdmin* tree control. With PostgreSQL 9.5 forward, when a table has multiple check constraints, they will be tested for each row in alphabetical order by name and after NOT NULL constraints.
- Provide notes about the check constraint in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the check constraint:

- Provide the expression that a row must satisfy in the *Check* field. This field is required.
- Move the *No Inherit?* switch to the *Yes* position to specify that this constraint is not automatically inherited by a table's children. The default is *No*, meaning that the constraint will be inherited by any children.
- Move the *Don't validate?* switch to the *No* position to skip validation of existing data; the constraint may not hold for all rows in the table. The default is *Yes*.



To add a unique constraint, select the *Unique* tab on the panel, and click the *Add* icon (+). To define the constraint, click the *Edit* icon to the left of the *Trash* icon. A dialog similar to the *Unique constraint* dialog (accessed by right clicking on *Constraints* in the *pgAdmin* tree control) opens.

Use the fields in the *General* tab to identify the unique constraint:


- Use the *Name* field to add a descriptive name for the unique constraint. The name will be displayed in the *pgAdmin* tree control.
- Provide notes about the unique constraint in the *Comment* field.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the unique constraint:

- Click inside the *Columns* field and select one or more column names from the drop-down listbox. To delete a selection, click the *x* to the left of the column name. The unique constraint should be different from the primary key constraint defined for the same table; the selected column(s) for the constraints must be distinct.
- Select the name of the tablespace in which the unique constraint will reside from the drop-down listbox in the *Tablespace* field.
- Use the *Fill Factor* field to specify a fill factor for the table and index. The fill factor for a table is a percentage between 10 and 100. 100 (complete packing) is the default.
- Move the *Deferrable?* switch to the *Yes* position to specify the timing of the constraint is deferrable and can be postponed until the end of the statement. The default is *No*.
- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint is deferred to the end of the statement. The default is *No*.




To add an exclusion constraint, select the *Exclude* tab on the panel, and click the *Add* icon (+). To define the constraint, click the *Edit* icon to the left of the *Trash* icon. A dialog similar to the *Exclusion constraint* dialog (accessed by right clicking on *Constraints* in the *pgAdmin* tree control) opens.

Use the fields in the *General* tab to identify the exclusion constraint:

- Use the *Name* field to provide a descriptive name for the exclusion constraint. The name will be displayed in the *pgAdmin* tree control.
- Provide notes about the exclusion constraint in the *Comment* field.


Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the exclusion constraint:

- Use the drop-down listbox next to *Tablespace* to select the tablespace in which the index associated with the exclude constraint will reside.
- Use the drop-down listbox next to *Access method* to specify the type of index that will be used when implementing the exclusion constraint:
  - Select *gist* to specify a GiST index (the default).
  - Select *spgist* to specify a space-partitioned GiST index.
  - Select *btree* to specify a B-tree index.
  - Select *hash* to specify a hash index.
- Use the *Fill Factor* field to specify a fill factor for the table and associated index. The fill factor is a percentage between 10 and 100. 100 (complete packing) is the default.
- Move the *Deferrable?* switch to the *Yes* position to specify that the timing of the constraint is deferrable, and can be postponed until the end of the statement. The default is *No*.
- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint is deferred to the end of the statement. The default is *No*.
- Use the *Constraint* field to provide a condition that a row must satisfy to be included in the table.


Click the *Columns* tab to continue.



Use the fields in the *Columns* tab to specify the column(s) to which the constraint applies. Use the drop-down listbox next to *Column* to select a column and click the *Add* icon (+) to provide details of the action on the column:

- The *Column* field is populated with the selection made in the *Column* drop-down listbox.
- If applicable, use the drop-down listbox in the *Operator class* to specify the operator class that will be used by the index for the column.
- Move the *DESC* switch to *DESC* to specify a descending sort order. The default is *ASC* which specifies an ascending sort order.
- Move the *NULLs order* switch to *LAST* to define an ascending sort order for NULLs. The default is *FIRST* which specifies a descending order.
- Use the drop-down list next to *Operator* to specify a comparison or conditional operator.

Click the *Advanced* tab to continue.



Use the fields in the *Advanced* tab to define advanced features for the table:

- Move the *RLS Policy?* switch to the *Yes* position to enable the Row Level Security.
- Move the *Force RLS Policy?* to the *Yes* position to force the policy on the owner of the table.
- Use the drop-down listbox next to *Of type* to copy the table structure from the specified composite type. Please note that a typed table will be dropped if the type is dropped (with DROP TYPE ... CASCADE).
- Use the drop-down list box next to Access Method to specify the table access method to use to store the contents for the new table; the method needs to be an access method of type TABLE. This field is optional. This option is available from v12 and above.
- Use the *Fill Factor* field to specify a fill factor for the table. The fill factor for a table is a percentage between 10 and 100. 100 (complete packing) is the default.
- Use the *Toast tuple target* field to set toast_tuple_target storage parameter of the table. The toast_tuple_target value is in bytes and has minimum value of 128. This field will be enabled only for PostgreSQL version >= 11
- Use the *Parallel workers* field to set parallel_workers storage parameter of the table. The parallel_workers sets the number of workers that should be used to assist a parallel scan of the table. This field will be enabled only for PostgreSQL version >= 9.6
- Move the *Has OIDs?* switch to the *Yes* position to specify that each row within a table has a system-assigned object identifier. The default is *No*.
- Move the *Unlogged?* switch to the *Yes* position to disable logging for the table. Data written to an unlogged table is not written to the write-ahead log. Any indexes created on an unlogged table are automatically unlogged as well. The default is *No*.


Use the fields in the **Like** box to specify which attributes of an existing table from which a table will automatically copy column names, data types, and not-null constraints; after saving the new or modified table, any changes to the original table will not be applied to the new table.

- Use the drop-down listbox next to *Relation* to select a reference table.

- Move the switch next to *With default values?* to the *Yes* position to copy default values.
- Move the switch next to *With constraints?* to the *Yes* position to copy table and column constraints.
- Move the switch next to *With indexes?* to the *Yes* position to copy indexes.
- Move the switch next to *With storage?* to the *Yes* position to copy storage settings.
- Move the switch next to *With comments?* to the *Yes* position to copy comments.
- Move the switch next to *With compression?* to the *Yes* position to copy compression method. This option is available only on PostgreSQL 14 and above.
- Move the switch next to *With generated?* to the *Yes* position to copy generation expressions of copied column. This option is available only on PostgreSQL 12 and above.
- Move the switch next to *With identity?* to the *Yes* position to copy any identity specifications of copied column.
- Move the switch next to *With statistics?* to the *Yes* position to copy extended statistics.

With PostgreSQL 10 forward, the *Partition* tab will be visible.

Click the *Partition* tab to continue.



Use the fields in the *partition* tab to create the partitions for the table:

- Select a partition type from the *Partition Type* selection box. There are 3 options available; Range, List and Hash. Hash option will only enable for PostgreSQL version >= 11.

Use the *Partition Keys* panel to define the partition keys. Click the *Add* icon (+) to add each partition keys selection:

- Select a partition key type in the *Keytype* field.
- Select a partition column in the *Column* field if Column option selected for *Keytype* field .
- Specify the expression in the *Expression* field if Expression option selected for the *Keytype* field.


Use the *Partitions* panel to define the partitions of a table. Click the *Add* icon (+) to add each partition:

- Move the *Operation* switch to *attach* to attach the partition, by default it is *create*.
- Use the *Name* field to add the name of the partition.
- If partition type is Range or List then *Default* field will be enabled.
- If partition type is Range then *From* and *To* fields will be enabled.
- If partition type is List then *In* field will be enabled.
- If partition type is Hash then *Modulus* and *Remainder* fields will be enabled.


Users can create a partition and define them as a partitioned table. Click the *Edit* icon to expand the properties of a partition. Use the *Partition* tab to create that partition as a partitioned table.

- Move the *Partitioned Table?* switch to the *Yes* in case you want to create a partitioned table.
- Select a partition type from the *Partition Type* selection box.
- Use the *Partition Keys* panel to define the partition keys.

View of multi level Partitioned Table in object explorer:



Click the *Parameter* tab to continue.




Use the tabs nested inside the *Parameter* tab to specify VACUUM and ANALYZE thresholds; use the *Table* tab and the *Toast Table* tab to customize values for the table and the associated toast table:

- Move the *Custom auto-vacuum?* switch to the *Yes* position to perform custom maintenance on the table and to select values in the *Vacuum table*. The *Vacuum Table* provides default values for maintenance operations.
- Changing *Autovacuum enabled?* to *Not set* will reset autovacuum_enabled.

Provide a custom value in the *Value* column for each metric listed in the *Label* column.

Click the *Security* tab to continue.



Use the *Security* tab to assign privileges and define security labels.

Use the *Privileges* panel to assign privileges to a role. Click the *Add* icon (+) to set privileges for database objects:

- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privilege to the specified user.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.

Click the *Add* icon (+) to assign additional privileges; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Use the *Security Labels* panel to define security labels applied to the function. Click the *Add* icon (+) to add each security label selection:

- Specify a security label provider in the *Provider* field. The named provider must be loaded and must consent to the proposed labeling operation.
- Specify a security label in the *Security Label* field. The meaning of a given label is at the discretion of the label provider. PostgreSQL places no restrictions on whether or how a label provider must interpret security labels; it merely provides a mechanism for storing them.


Click the *Add* icon (+) to assign additional security labels; to discard a security label, click the trash icon to the left of the row and confirm deletion in the *Delete Row* popup.

Click the *SQL* tab to continue.

Your entries in the *Table* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.10.1 Example

The following is an example of the sql command generated by user selections in the *Table* dialog:




The example shown demonstrates creating a table named *jobhist*. It has six columns and a primary key constraint on the *empno and startdate* column.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.11 Trigger Dialog

Use the *Trigger* dialog to create a trigger or modify an existing trigger. A trigger executes a specified function when certain events occur.


The *Trigger* dialog organizes the development of a trigger through the following dialog tabs: *General*, *Definition*, *Events*, and *Code*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the trigger:


- Use the *Name* field to add a descriptive name for the trigger. This must be distinct from the name of any other trigger for the same table. The name will be displayed in the *pgAdmin* tree control. Note that if multiple triggers of the same kind are defined for the same event, they will be fired in alphabetical order by name.
- Store notes about the trigger in the *Comment* field.

Click the *Definition* tab to continue.




Use the fields in the *Definition* tab to define the trigger:

- Move the *Row trigger?* switch to the *No* position to disassociate the trigger from firing on each row in a table. The default is *Yes*.
- Move the *Constraint trigger?* switch to the *Yes* position to specify the trigger is a constraint trigger.
- If enabled, move the *Deferrable?* switch to the *Yes* position to specify the timing of the constraint trigger is deferrable and can be postponed until the end of the statement. The default is *No*.
- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint trigger is deferred to the end of the statement causing the triggering event. The default is *No*.
- Use the drop-down listbox next to *Trigger Function* to select a trigger function or procedure.
- Use the *Arguments* field to provide an optional (comma-separated) list of arguments to the function when the trigger is executed. The arguments are literal string constants.



- *Trigger enabled* field is available in trigger dialog once the trigger is created. You can select one of the four options available.

Click the *Events* tab to continue.



Use the fields in the *Events* tab to specify how and when the trigger fires:

- Use the drop-down listbox next to the *Fires* fields to determine if the trigger fires *BEFORE* or *AFTER* a specified event. The default is *BEFORE*.
- Select the type of event(s) that will invoke the trigger; to select an event type, move the switch next to the event to the *YES* position. The supported event types are *INSERT*, *UPDATE*, *DELETE*, and *TRUNCATE*.
- Use the *When* field to provide a boolean condition that will invoke the trigger.
- If defining a column-specific trigger, use the *Columns* field to specify the columns or columns that are the target of the trigger.

Click the *Code* tab to continue.



Use the *Code* field to specify any additional code that will be invoked when the trigger fires.

Click the *SQL* tab to continue.

Your entries in the *Trigger* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.11.1 Example

The following is an example of the sql command generated by user selections in the *Trigger* dialog:




The example demonstrates creating a trigger named *emp_trigger*.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

6.12 Unique Constraint Dialog

Use the *Unique constraint* dialog to define a unique constraint for a specified table. Unique constraints ensure that the data contained in a column, or a group of columns, is unique among all the rows in the table.

The *Unique constraint* dialog organizes the development of a unique constraint through the following dialog tabs: *General* and *Definition*. The *SQL* tab displays the SQL code generated by dialog selections.



Use the fields in the *General* tab to identify the unique constraint:

- Use the *Name* field to add a descriptive name for the unique constraint. The name will be displayed in the *pgAdmin* tree control.

Click the *Definition* tab to continue.



Use the fields in the *Definition* tab to define the unique constraint:


- Click inside the *Columns* field and select one or more column names from the drop-down listbox. To delete a selection, click the *x* to the left of the column name. The unique constraint should be different from the primary key constraint defined for the same table; the selected column(s) for the constraints must be distinct.
- Use *Include columns* field to specify columns for *INCLUDE* clause of the constraint. This option is available in Postgres 11 and later.
- Select the name of the tablespace in which the unique constraint will reside from the drop-down listbox in the *Tablespace* field.
- Select the name of an index from the drop-down listbox in the *Index* field. This field is optional. Adding a unique constraint will automatically create a unique B-tree index on the column or group of columns listed in the constraint, and will force the column(s) to be marked NOT NULL.
- Use the *Fill Factor* field to specify a fill factor for the table and index. The fill factor for a table is a percentage between 10 and 100. 100 (complete packing) is the default.
- Move the *Deferrable?* switch to the *Yes* position to specify the timing of the constraint is deferrable and can be postponed until the end of the statement. The default is *No*.
- If enabled, move the *Deferred?* switch to the *Yes* position to specify the timing of the constraint is deferred to the end of the statement. The default is *No*.
- Move the *NULLs not distinct?* switch to the *Yes* position to treat null values as not distinct. The default is *No*. This option is available only on PostgreSQL 15 and above.

Click the *SQL* tab to continue.

Your entries in the *Unique constraint* dialog generate a SQL command (see an example below). Use the *SQL* tab for review; revisit or switch tabs to make any changes to the SQL command.

6.12.1 Example

The following is an example of the sql command generated by user selections in the *Unique constraint* dialog:



The example shown demonstrates creating a unique constraint named *jobhist_unique* on the *empno* column of the *jobhist* table.

- Click the *Info* button (i) to access online help.
- Click the *Save* button to save work.
- Click the *Close* button to exit without saving work.
- Click the *Reset* button to restore configuration parameters.

CHAPTER 7

Management Basics

pgAdmin provides point and click dialogs that help you perform server management functions. Dialogs simplify tasks such as managing named restore points, granting user privileges, and performing VACUUM, ANALYZE and REINDEX functions.

7.1 Add Named Restore Point Dialog

Use the *Add named restore point* dialog to take a named snapshot of the state of the server for use in a recovery file. To create a named restore point, the server's postgresql.conf file must specify a *wal_level* value of *replica*, *logical*, or *minimal*. You must be a database superuser to create a restore point.



When the *Restore point name* window launches, use the field *Enter the name of the restore point to add* to provide a descriptive name for the restore point.

For more information about using a restore point as a recovery target, please see the PostgreSQL documentation.

- Click the *OK* button to save the restore point.
- Click the *Cancel* button to exit without saving work.


7.2 Change Server Password Dialog

It is a good policy to routinely change your password to protect data, even in what you may consider a 'safe' environment. In the workplace, failure to apply an appropriate password policy could leave you in breach of Data Protection laws.

Please consider the following guidelines when selecting a password:

- Ensure that your password is an adequate length; 6 characters should be the absolute minimum number of characters in the password.
- The minimum password length is set by default to six characters. This value can be changed by setting the *PASSWORD_LENGTH_MIN* option to desired length in pgAdmin configuration; see *Configuration Files* for more information.
- Ensure that your password is not open to dictionary attacks. Use a mixture of upper and lower case letters and numerics, and avoid words or names. Consider using the first letter from each word in a phrase that you will remember easily but is an unfamiliar acronym.
- Ensure that your password is changed regularly; at minimum, change it every ninety days.

The guidelines above should be considered a starting point: They are not a comprehensive list and they **will not guarantee security**.



Use the *Change Server Password* dialog to change the password of the role that pgAdmin uses to connect to the database server, rather than the password you use to log in to pgAdmin itself:

- The name displayed in the *User* field is the role for which you are modifying the password; it is the role that is associated with the server connection that is highlighted in the tree control.
- Enter the password associated with the role in the *Current Password* field.
- Enter the desired password for in the *New Password* field.
- Re-enter the new password in the *Confirm Password* field.

Click the *Change* button to change your password.

Click the *Close* button to exit without changing your password.


Click the *Reset* button to reset the values.

7.3 Grant Wizard

The *Grant Wizard* tool is a graphical interface that allows you to manage the privileges of one or more database objects in a point-and-click environment. A search box, dropdown lists, and checkboxes facilitate quick selections of database objects, roles and privileges.

The wizard organizes privilege management through a sequence of windows: *Object Selection*, *Privileges Selection* and *Review Selection*. The *Review Selection* window displays the SQL code generated by wizard selections.


To launch the *Grant Wizard* tool, select a database object in the *pgAdmin* tree control, then navigate through *Tools* on the menu bar to click on the *Grant Wizard* option.



Use the fields in the *Object Selection* window to select the object or objects on which you are modifying privileges. Use the *Search by object type or name* field to locate a database object, or use the scrollbar to scroll through the list of all accessible objects.

- Each row in the table lists object identifiers; check the checkbox in the left column to include an object as a target of the Grant Wizard. The table displays:
  - The object type in the *Object Type* field
  - The schema in which the object resides in the *Schema* field
  - The object name in the *Name* field.

Click the *Next* button to continue, or the *X* button to close the wizard without modifying privileges.



Use the fields in the *Privileges Selection* window to grant privileges. If you grant a privilege WITH GRANT OPTION, the Grantee will have the right to grant privileges on the object to others. If WITH GRANT OPTION is subsequently revoked, any role who received access to that object from that Grantee (directly or through a chain of grants) will lose their privileges on the object.

- Click the *Add* icon (+) to assign a set of privileges.
- Select the name of the role from the drop-down listbox in the *Grantee* field.
- Click inside the *Privileges* field. Check the boxes to the left of one or more privileges to grant the selected privileges to the specified user. If privileges have previously been granted on a database object, unchecking a privilege for a group or user will result in revoking that privilege.
- The current user, who is the default grantor for granting the privilege, is displayed in the *Grantor* field.
- Click the *Add* icon (+) to assign a set of privileges to another role; to discard a privilege, click the trash icon to the left of the row and confirm deletion in the *Delete Row* dialog.

For more information about granting privileges on database objects, see the PostgreSQL core documentation.

Click the *Next* button to continue, the *Back* button to select or deselect additional database objects, or the *X* button to close the wizard without modifying privileges.

Your entries in the *Grant Wizard* tool generate a SQL command; you can review the command in the *Review Selection* window (see an example below).

7.3.1 Example

The following is an example of the sql command generated by user selections in the *Grant Wizard* tool:




- Click the *Back* button to select or deselect additional database objects, roles and privileges.
- Click the *Finish* button to save selections and exit the wizard.

7.4 Export Data Using Query Dialog


Use the *Export Data Using Query* dialog to copy data to a file.

The *Export Data Using Query* dialog organizes the export of data through the *General*, *Options* and *Query* tabs.




Use the fields in the *General* tab to specify export preferences:

- Enter the name of the target file in the *Filename* field. Optionally, select the *Browse* icon (ellipsis) to the right to navigate into a directory and select a file.
- Use the drop-down listbox in the *Format* field to specify the file type. Select:
  - *binary* for a .bin file.
  - *csv* for a .csv file.
  - *text* for a .txt file.
- Use the drop-down listbox in the *Encoding* field to specify the type of character encoding.



- Use the fields in the *Options* tab to specify additional information:
  - Move the *Header* switch to the *Yes* position to include the table header with the data rows. If you include the table header, the first row of the file will contain the column names.
  - If you are exporting data, specify the delimiter that will separate the columns within the target file in the *Delimiter* field. The separating character can be a colon, semicolon, a vertical bar, or a tab.
  - Specify a quoting character used in the *Quote* field. Quoting can be applied to string columns only (i.e. numeric columns will not be quoted) or all columns regardless of data type. The character used for quoting can be a single quote or a double quote.
  - Specify a character that should appear before a data character that matches the *QUOTE* value in the *Escape* field.
  - Use the *NULL String* field to specify a string that will represent a null value within the source or target file.


Click the *Query* tab to continue.



Use the fields in the *Query* tab to write the query that will be exported:


- Use the *Export Data Query* field to specify a SELECT, VALUES, INSERT, UPDATE, DELETE, or MERGE command whose results are to be copied.
- Use *Force Quote columns* field to forces quoting to be used for all non-NULL values in each specified column. NULL output is never quoted. This is a creatable select control. If you would like to quote all columns then provide only '*' in the field.

After completing the *Export Data Using Query* dialog, click the *OK* button to perform the export. pgAdmin will notify you when the background process completes:



Use the *View Processes* button on the notification to open the *Process Watcher* and review detailed information about the execution of the command that performed the export:

Use the **End Process** button to end the Export process.




Note

If you are running *pgAdmin* in *Server Mode* you can click on the  icon in the process watcher window to open the file location in the Storage Manager. You can use the *Storage Manager* to download the exported file on the client machine .

7.5 Import/Export Data Dialog


Use the *Import/Export data* dialog to copy data from a table to a file, or copy data from a file into a table.

The *Import/Export data* dialog organizes the import/export of data through the *General*, *Options* and *Columns* tabs.



Use the fields in the *General* tab to specify import and export preferences:


- Move the *Import/Export* switch to the *Import* position to specify that the server should import data to a table from a file. The default is *Import*.
- Enter the name of the source or target file in the *Filename* field. Optionally, select the *Browse* icon (ellipsis) to the right to navigate into a directory and select a file.
- Use the drop-down listbox in the *Format* field to specify the file type. Select:
  - *binary* for a .bin file.
  - *csv* for a .csv file.
  - *text* for a .txt file.
- Use the drop-down listbox in the *Encoding* field to specify the type of character encoding.
- use the drop-down listbox in the *On Error* field to specify how to behave when encountering an error converting a columns input value into its data type. An error_action value of stop means fail the command, while ignore means discard the input row and continue with the next one. The default is stop. This option is available from PG/EPAS version 17 and above.
- use the drop-down listbox in the *Log Verbosity* field to specify the amount of messages emitted by a COPY command: default or verbose. This is currently used in Import only when ON_ERROR option is set to ignore. This option is available from PG/EPAS version 17 and above.



- Use the fields in the *Options* tab to specify additional information:
  - Move the *Header* switch to the *Yes* position to include the table header with the data rows. If you include the table header, the first row of the file will contain the column names.
  - Move the *Freeze* switch to the *Yes* position to requests copying the data with rows already frozen, just as they would be after running the VACUUM FREEZE command.
  - If you are exporting data, specify the delimiter that will separate the columns within the target file in the *Delimiter* field. The separating character can be a colon, semicolon, a vertical bar, or a tab.
  - Specify a quoting character used in the *Quote* field. Quoting can be applied to string columns only (i.e. numeric columns will not be quoted) or all columns regardless of data type. The character used for quoting can be a single quote or a double quote.
  - Specify a character that should appear before a data character that matches the *QUOTE* value in the *Escape* field.
  - Use the *NULL String* field to specify a string that will represent a null value within the source or target file.

– Use the *Default String* field to specify a string that will represent a default value. Each time the string is found in the input file, the default value of the corresponding column will be used. This option is available from PG/EPAS version 16 and above.


Click the *Columns* tab to continue.



Use the fields in the *Columns* tab to select the columns that will be imported or exported:


- Click inside the *Columns to export/import* field to deselect one or more columns from the drop-down listbox. To delete a selection, click the *x* to the left of the column name. Click an empty spot inside the field to access the drop-down list.
- If enabled, click inside the *Force Quote columns* field to forces quoting to be used for all non-NULL values in each specified column. NULL output is never quoted. To delete a column, click the *x* to the left of the column name.
- If enabled, click inside the *NOT NULL columns* field to select one or more columns that will not be checked for a NULL value. To delete a column, click the *x* to the left of the column name.
- If enabled, click inside the *NULL columns* field to match the specified columns values against the null string, even if it has been quoted, and if a match is found set the value to NULL. To delete a column, click the *x* to the left of the column name.

After completing the *Import/Export data* dialog, click the *OK* button to perform the import or export. pgAdmin will notify you when the background process completes:



Use the *View Processes* button on the notification to open the *Process Watcher* and review detailed information about the execution of the command that performed the import or export:

Use the **End Process** button to end the Import/Export process.



Note


If you are running *pgAdmin* in *Server Mode* you can click on the  icon in the process watcher window to open the file location in the Storage Manager. You can use the *Storage Manager* to download the exported file on the client machine .

7.6 Maintenance Dialog

Use the *Maintenance* dialog to VACUUM, ANALYZE, REINDEX or CLUSTER a database or selected database objects.

While this utility is useful for ad-hoc maintenance purposes, you are encouraged to perform automatic VACUUM jobs on a regular schedule.


Select a button next to *Maintenance operation* to specify the type of maintenance:



- Click *VACUUM* to scan the selected database or table to reclaim storage used by dead tuples.
  - Move the *FULL* switch to the *Yes* position to compact tables by writing a completely new version of the table file without dead space.
  - Move the *FREEZE* switch to the *Yes* position to freeze data in a table when it will have no further updates.
  - Move the *ANALYZE* switch to the *Yes* position to issue ANALYZE commands whenever the content of a table has changed sufficiently.
  - Move the *DISABLE PAGE SKIPPING* switch to the *Yes* position to disable all page-skipping behavior.
  - Move the *SKIP LOCKED* switch to the *Yes* position to specify that VACUUM should not wait for any conflicting locks to be released when beginning work on a relation. This option is available from v12


onwards.

- Move the *TRUNCATE* switch to the *Yes* position to specify that VACUUM should attempt to truncate off any empty pages at the end of the table and allow the disk space for the truncated pages to be returned to the operating system. This option is available from v12 onwards.
- Move the *PROCESS TOAST* switch to the *Yes* position to specify that VACUUM should attempt to process the corresponding TOAST table for each relation, if one exists. This option is available from v14 onwards.
- Move the *PROCESS MAIN* switch to the *Yes* position to specify that VACUUM should attempt to process the main relation. This option is available from v16 onwards.
- Move the *SKIP DATABASE STATS* switch to the *Yes* position to specify that VACUUM should skip updating the database-wide statistics about oldest unfrozen XIDs. This option is available from v16 onwards.
- Move the *ONLY DATABASE STATS* switch to the *Yes* position to specify that VACUUM should do nothing except update the database-wide statistics about oldest unfrozen XIDs . This option is available from v16 onwards.
- Use the *INDEX CLEANUP* field to force VACUUM to process indexes when there are more than zero dead tuples.
- Use the *PARALLEL* field to specify index vacuum and index cleanup phases of VACUUM in parallel using integer background workers. This option is available from v13 onwards.
- Use the *BUFFER USAGE LIMIT* field to specify the Buffer Access Strategy ring buffer size for VACUUM. This size is used to calculate the number of shared buffers which will be reused as part of this strategy. This option is available from v16 onwards




- Click *ANALYZE* to update the stored statistics used by the query planner. This enables the query optimizer to select the fastest query plan for optimal performance.
  - Move the *SKIP LOCKED* switch to the *Yes* position to specify that ANALYZE should not wait for any conflicting locks to be released when beginning work on a relation. This option is available from v12 onwards.

- Use the *BUFFER USAGE LIMIT* field to specify the Buffer Access Strategy ring buffer size for ANALYZE. This size is used to calculate the number of shared buffers which will be reused as part of this strategy. This option is available from v16 onwards



- Click *REINDEX* to rebuild any index in case it has degenerated due to the insertion of unusual data patterns. This happens, for example, if you insert rows with increasing index values, and delete low index values.
  - Move the *SYSTEM* switch to the *Yes* position to recreate all indexes on system catalogs within the current database. This option is enabled only when database object is selected.
  - Move the *CONCURRENTLY* switch to the *Yes* position to rebuild the index without taking any locks that prevent concurrent inserts, updates, or deletes on the table. This option is available from v12 onwards.
  - Use the *TABLESPACE* field to specify that indexes will be rebuilt on a new tablespace. This option is available from v14 onwards.



- Click *CLUSTER* to instruct PostgreSQL to cluster the selected table.

To exclude status messages from the process output, move the *Verbose Messages* switch to the *No* position; by default, status messages are included.

When you've completed the dialog, click *OK* to start the background process; to exit the dialog without performing maintenance operations, click *Cancel*.


pgAdmin will run the maintenance process in the background. You can view all the background processes with their running status and logs on the *Processes* tab.

7.7 Storage Manager

Storage Manager is a feature that helps you manage your systems storage device. You can use *Storage Manager* to:

- Download, upload, or manage operating system files. To use this feature, *pgAdmin* must be running in *Server Mode* on your client machine.
- The shared storage option allows users to access the shared storages that are shared by admin users.
- Download *backup* or *export* files (custom, tar and plain text format) on a client machine.
- Download *export* dump files of tables.

You can access *Storage Manager* from the *Tools* Menu.



Use icons on the top of the *Storage Manager* window to manage storage:

Use the `Folder` icon  to access shared storage. In order to enable shared storage, admins need to add the SHARED_STORAGE variable to the config file. Users can access the shared storage with this and share files with one another.

Use the `Home` icon  to return to the home directory.

Use the `Up Arrow` icon  to return to the previous directory.


Use the `Refresh` icon  to display the most-recent files available.

Select the `Download` icon  to download the selected file.

Use the `New Folder` icon  to add a new folder.

Use the *Format* drop down list to select the format of the files to be displayed; choose from *sql*, *csv*, or *All Files*.

7.7.1 Shared Storage




In the storage manager, `My Storage` is the pgAdmin user's storage directory, and other listed directories are shared storages set by the pgAdmin server administrator. Using these, pgAdmin users can have common storages to share files. pgAdmin server administrator can configure the shared storages using the *config file*. Storages can be marked as restricted to give read-only access to non-admin pgAdmin users.

Note

You must ensure the directories specified are writeable by the user that the web server processes will be running as, e.g. apache or www-data.*


7.7.2 Other Options



Menu	Behavior
Rename	Click the *Rename* option to rename a file/folder.
Delete	Click the *Delete* option to rename a file/folder.
Upload	Click the *Upload* option to upload multiple files to the current folder.
List View	Click the *List View* option to to display all the files and folders in a list view.
Grid View	Click the *Grid View* option to to display all the files and folders in a grid view.
Show Hidden Files	Click the *Show Hidden Files* option to view hidden files and folders.

You can also download backup files through *Storage Manager* at the successful completion of the backups taken through *Backup Dialog*, *Backup Global Dialog*, or *Backup Server Dialog*.

At the successful completion of a backup, click on the icon to open the current backup file in *Storage Manager* on the *process watcher* window.


Process Watcher - Backing up an object on the server
Backing up an object on the server 'PostgreSQL 10 (localhost:5432)' from database 'edbstore'...
Running command:
/Library/PostgreSQL/10/bin/pg_dump --file "/Users/nidhibhammar/.pgadmin/storage/nidhi.bhammar_enterprisedb.com/table_customers" --host "localhost" --port "5432" --username "postgres" --no-password --verbose --format=c --blobs --table "edbuser.customers" "edbstore"
Start time: Tue Nov 03 2020 12:36:02 GMT+0530 (India Standard Time)
Stop Process
pg_dump: reading policies for table "edbuser.customers"
pg_dump: reading row security enabled for table "edbuser.customers_customerid_seq"
pg_dump: reading policies for table "edbuser.customers_customerid_seq"
pg_dump: reading publications
pg_dump: reading publication membership
pg_dump: reading publication membership for table "edbuser.customers"
pg_dump: reading subscriptions
pg_dump: reading large objects
pg_dump: reading dependency data
pg_dump: saving encoding = UTF8
pg_dump: saving standard_conforming_strings = on
pg_dump: saving search_path =
pg_dump: dumping contents of table "edbuser.customers"
Successfully completed.
Execution time: 0.86 seconds

CHAPTER 8


Backup and Restore

A powerful, but user-friendly Backup and Restore tool provides an easy way to use pg_dump, pg_dumpall, and pg_restore to take backups and create copies of databases or database objects for use in a development environment.

8.1 Backup Dialog

pgAdmin uses the *pg_dump* utility to provide an easy way to create a backup in a plain-text or archived format. You can then use a client application (like *psql* or the *Query Tool*) to restore a plain-text backup file, or use the Postgres *pg_restore* utility to restore an archived backup. The *pg_dump* utility must have read access to all database objects that you want to back up.

You can backup a single table, a schema, or a complete database. Select the name of the backup source in the *pgAdmin* tree control, right click to open the context menu, and select *Backup...* to open the *Backup* dialog. The name of the object selected will appear in the dialog title bar.




Use the fields in the *General* tab to specify parameters for the backup:

- Enter the name of the backup file in the *Filename* field. Optionally, select the *Browser* icon (...) to the right to navigate into a directory and select a file that will contain the archive.
- Use the drop-down listbox in the *Format* field to select the format that is best suited for your application. Each format has advantages and disadvantages:
  - Select *Custom* to create a custom archive file that you can use with *pg_restore* to create a copy of a database. Custom archive file formats must be restored with *pg_restore*. This format offers the opportunity to select which database objects to restore from the backup file. *Custom* archive format is recommended for medium to large databases as it is compressed by default.
  - Select *Tar* to generate a tar archive file that you can restore with *pg_restore*. The tar format does not support compression.
  - Select *Plain* to create a plain-text script file. A plain-text script file contains SQL statements and commands that you can execute at the *psql* command line to recreate the database objects and load the table data. A plain-text backup file can be edited in a text editor, if desired, before using the *psql* program to restore database objects. *Plain* format is normally recommended for smaller databases; script dumps are not recommended for blobs. The SQL commands within the script will reconstruct the database to the last saved state of the database. A plain-text script can be used to reconstruct the database on another machine, or (with modifications) on other architectures.
  - Select *Directory* to generate a directory-format archive suitable for use with *pg_restore*. This file format creates a directory with one file for each table and blob being dumped, plus a *Table of Contents* file describing the dumped objects in a machine-readable format that *pg_restore* can read. This format is compressed by default.
- Use the *Compression Ratio* field to select a compression level for the backup. Specify a value of zero to mean


use no compression; specify a maximum compression value of 9. Please note that tar archives do not support compression.

- Use the *Encoding* drop-down listbox to select the character encoding method that should be used for the archive.
- Use the *Number of Jobs* field (when applicable) to specify the number of tables that will be dumped simultaneously in a parallel backup.
- Use the dropdown listbox next to *Rolename* to specify the role that owns the backup.


Click the *Data Options* tab to continue. Use the fields in the *Data Options* tab to provide options related to data or pgAdmin objects that correspond to *pg_dump*.




- Move switches in the **Sections** field box to select a portion of the object that will be backed up.
  - Move the switch next to *Pre-data* to the *Yes* position to include all data definition items not included in the data or post-data item lists.
  - Move the switch next to *Data* to the *Yes* position to backup actual table data, large-object contents, and sequence values.
  - Move the switch next to *Post-data* to the *Yes* position to include definitions of indexes, triggers, rules, and constraints other than validated check constraints.



- Move switches in the **Type of objects** field box to specify details about the type of objects that will be backed up.
  - Move the switch next to *Only data* to the *Yes* position to limit the back up to data.
  - Move the switch next to *Only schemas* to limit the back up to schema-level database objects.
  - Move the switch next to *Only statistics* to the *Yes* position to limit the back up to optimizer statistics. **Note:** This option is visible only for database server greater than or equal to 18.
  - Move the switch next to *Blobs* to the *No* position to exclude large objects in the backup.




- Move switches in the **Do not save** field box to select the objects that will not be included in the backup.
  - Move the switch next to *Owner* to the *Yes* position to exclude commands that set object ownership.
  - Move the switch next to *Privileges* to the *Yes* position to exclude commands that create access privileges.
  - Move the switch next to *Tablespaces* to the *Yes* position to exclude tablespaces.
  - Move the switch next to *Unlogged table data* to the *Yes* position to exclude the contents of unlogged tables.
  - Move the switch next to *Comments* to the *Yes* position to exclude commands that set the comments. **Note:** This option is visible only for database server greater than or equal to 11.
  - Move the switch next to *Publications* to the *Yes* position to exclude publications.
  - Move the switch next to *Subscriptions* to the *Yes* position to exclude subscriptions.
  - Move the switch next to *Security labels* to the *Yes* position to exclude Security labels.
  - Move the switch next to *Toast compressions* to the *Yes* position to exclude Toast compressions. **Note:** This option is visible only for database server greater than or equal to 14.
  - Move the switch next to *Table access methods* to the *Yes* position to exclude Table access methods. **Note:** This option is visible only for database server greater than or equal to 15.
  - Move the switch next to *Row security policies* to the *Yes* position to exclude row security policies. **Note:** This option is visible only for database server greater than or equal to 18.
  - Move the switch next to *Data* to the *Yes* position to exclude data from the backup. **Note:** This option is visible only for database server greater than or equal to 18.
  - Move the switch next to *Schema* to the *Yes* position to exclude schema (the data definitions) from the backup. **Note:** This option is visible only for database server greater than or equal to 18.
  - Move the switch next to *Statistics* to the *Yes* position to exclude optimizer statistics. **Note:** This option is visible only for database server greater than or equal to 18.



Click the *Query Options* tab to continue. Use these additional fields to specify the type of statements that should be included in the backup.

- Move the switch next to *Use INSERT commands* to the *Yes* position to dump the data in the form of INSERT statements rather than using a COPY command. Please note: this may make restoration from backup slow.
- Use the *Maximum rows per INSERT command* field to controls the maximum number of rows per INSERT command. **Note:** This option is visible only for database server greater than or equal to 12.
- Move the switch next to *On conflict do nothing to INSERT command* towards right position to add ON CONFLICT DO NOTHING to INSERT command. This option is not valid unless *Use INSERT commands*, *Use Column INSERTS* or *Maximum rows per INSERT command* is also specified. **Note:** This option is visible only for database server greater than or equal to 12.
- Move the switch next to *Include CREATE DATABASE statement* to the *Yes* position to include a command in the backup that creates a new database when restoring the backup.
- Move the switch next to *Include DROP DATABASE statement* to the *Yes* position to include a command in the backup that will drop any existing database object with the same name before recreating the object during a backup.
- Move the switch next to *Include IF EXISTS clause* to the *Yes* position to add an IF EXISTS clause to drop databases and other objects. This option is not valid unless *Include DROP DATABASE statement* is also set.




Click the *Table Options* tab to continue. Use the fields in the *Table Options* tab related to tables that should be included in the backup.


- Move the switch next to *Use Column INSERTS* to the *Yes* position to dump the data in the form of INSERT statements and include explicit column names. Please note: this may make restoration from backup slow.
- Move the switch next to *Load via partition root* to the *Yes* position, so when dumping a COPY or INSERT statement for a partitioned table, target the root of the partitioning hierarchy which contains it rather than the partition itself. **Note:** This option is visible only for database server greater than or equal to 11.
- Move the switch next to *Enable row security* to the *Yes* position to set row_security to on instead, allowing the user to dump the parts of the contents of the table that they have access to. This option is relevant only when dumping the contents of a table which has row security.
- Use the *Include table(s) and Children* field to dump the tables and any partitions or inheritance child tables of the tables matching the pattern. **Note:** This option is visible only for database server greater than or equal to 16.
- The Exclude patterns field is utilized to exclude patterns in the following manner:
- Use the *Table(s)* field to not dump the tables matching the pattern. Multiple patterns can be given separated by space.
- Use the *Table(s) data* field to not dump data for any tables matching the pattern. Multiple patterns can be given separated by spaces.
- Use the *Table(s) and children* field to not dump the tables and any partitions or inheritance child tables of the tables matching the pattern. **Note:** This option is visible only for database server greater than or equal to 16.
- Use the *Table(s) data and children* field to not dump data for the tables and any partitions or inheritance child

tables of the tables matching the table pattern. **Note:** This option is visible only for database server greater than or equal to 16.

Click the *Options* tab to continue. Use the fields in the *Options* tab to provide other backup options.




- Move switches in the **Disable** field box to specify the type of statements that should be excluded from the backup.
  - Move the switch next to *Triggers* (active when creating a data-only backup) to the *Yes* position to include commands that will disable triggers on the target table while the data is being loaded.
  - Move the switch next to *$ quoting* to the *Yes* position to enable dollar quoting within function bodies; if disabled, the function body will be quoted using SQL standard string syntax.



- Move switches in the **Miscellaneous** field box to specify miscellaneous backup options.
  - Move the switch next to *Verbose messages* to the *No* position to instruct *pg_dump* to exclude verbose messages.
  - Move the switch next to *Force double quotes on identifiers* to the *Yes* position to force the quoting of all identifiers.
  - Move the switch next to *Use SET SESSION AUTHORIZATION* to the *Yes* position to include a statement that will use a SET SESSION AUTHORIZATION command to determine object ownership (instead of an ALTER OWNER command).
  - Move the switch next to *Dump statistics* to the *Yes* position to include optimizer statistics in the backup. It cannot be combined with *Only data*, *Only schemas* or *Do not save Statistics*. **Note:** This option is visible only for database server greater than or equal to 18.

- Move the switch next to *Sequence data* to the *Yes* position to include sequence data that would normally be excluded. **Note:** This option is visible only for database server greater than or equal to 18.
- Use the *Exclude schema* field to not dump schemas whose name matches pattern.
- Use the *Extra float digits* field to use the specified value when dumping floating-point data, instead of the maximum available precision.
- Use the *Lock wait timeout* field to specify a timeout rather than waiting indefinitely to acquire shared table locks at the beginning of the dump. If unable to lock a table within the specified timeout, the operation will fail.

Click the *Objects* tab to continue.



- **Select the objects from tree to take backup of selected objects only.**
  - If Schema is selected then it will take the backup of that selected schema only.
  - If any Table, View, Materialized View, Sequences, or Foreign Table is selected then it will take the backup of those selected objects.


When you've specified the details that will be incorporated into the pg_dump command:

- Click the *Backup* button to build and execute a command that builds a backup based on your selections on the *Backup* dialog.
- Click the *Cancel* button to exit without saving work.

pgAdmin will run the backup process in the background. You can view all the background processes with their running status and logs on the *Processes* tab.

8.2 Backup Globals Dialog

Use the *Backup Globals* dialog to create a plain-text script that recreates all of the database objects within a cluster, and the global objects that are shared by those databases. Global objects include tablespaces, roles, and object properties. You can use the pgAdmin *Query Tool* to play back a plain-text script, and recreate the objects in the backup.



Use the fields in the *General* tab to specify the following:

- Enter the name of the backup file in the *Filename* field. Optionally, select the *Browser* icon (ellipsis) to the right to navigate into a directory and select a file that will contain the archive.
- Use the drop-down listbox next to *Role name* to specify a role with connection privileges on the selected server. The role will be used for authentication during the backup.

Move switches in the **Miscellaneous** field box to specify the type of statements that should be included in the backup.


- Move the *Verbose messages* switch to the *No* position to exclude status messages from the backup. The default is *Yes*.
- Move the *Force double quote on identifiers* switch to the *Yes* position to name identifiers without changing case. The default is *No*.

Click the *Backup* button to build and execute a command based on your selections; click the *Cancel* button to exit without saving work.

pgAdmin will run the backup process in the background. You can view all the background processes with their running status and logs on the *Processes* tab.

8.3 Backup Server Dialog


Use the *Backup Server* dialog to create a plain-text script that will recreate the selected server. You can use the pgAdmin *Query Tool* to play back a plain-text script, and recreate the server.



Use the fields in the *General* tab to specify the following:


- Enter the name of the backup file in the *Filename* field. Optionally, select the *Browser* icon (ellipsis) to the right to navigate into a directory and select a file that will contain the archive.
- Use the *Encoding* drop-down listbox to select the character encoding method that should be used for the archive. **Note:** This option is visible only for database server greater than or equal to 11.
- Use the drop-down listbox next to *Role name* to specify a role with connection privileges on the selected server. The role will be used for authentication during the backup.

Click the *Data Options* tab to continue. Use the fields in the *Data Options* tab to provide options related to data or pgAdmin objects that correspond to *pg_dumpall*.




- Move switches in the **Type of objects** field box to specify details about the type of objects that will be backed up.
  - Move the switch next to *Only data* to the *Yes* position to limit the back up to data.

- Move the switch next to *Only schemas* to limit the back up to schema-level database objects.
- Move the switch next to *Only tablespaces* to limit the back up to tablespaces only.
- Move the switch next to *Only roles* to limit the back up to roles only.
- Move the switch next to *Only statistics* to the *Yes* position to limit the back up to optimizer statistics. **Note:** This option is visible only for database server greater than or equal to 18.




- Move switches in the **Do not save** field box to select the objects that will not be included in the backup.
  - Move the switch next to *Owner* to the *Yes* position to exclude commands that set object ownership.
  - Move the switch next to *Role passwords* to the *Yes* position to exclude passwords for roles.
  - Move the switch next to *Privileges* to the *Yes* position to exclude commands that create access privileges.
  - Move the switch next to *Tablespaces* to the *Yes* position to exclude tablespaces.
  - Move the switch next to *Unlogged table data* to the *Yes* position to exclude the contents of unlogged tables.
  - Move the switch next to *Comments* to the *Yes* position to exclude commands that set the comments. **Note:** This option is visible only for database server greater than or equal to 11.
  - Move the switch next to *Publications* to the *Yes* position to exclude publications.
  - Move the switch next to *Subscriptions* to the *Yes* position to exclude subscriptions.
  - Move the switch next to *Security labels* to the *Yes* position to exclude Security labels.
  - Move the switch next to *Toast compressions* to the *Yes* position to exclude Toast compressions. **Note:** This option is visible only for database server greater than or equal to 14.
  - Move the switch next to *Table access methods* to the *Yes* position to exclude Table access methods. **Note:** This option is visible only for database server greater than or equal to 15.
  - Move the switch next to *Row security policies* to the *Yes* position to exclude row security policies. **Note:** This option is visible only for database server greater than or equal to 18.

- Move the switch next to *Data* to the *Yes* position to exclude data from the backup. **Note:** This option is visible only for database server greater than or equal to 18.
- Move the switch next to *Schema* to the *Yes* position to exclude schema (the data definitions) from the backup. **Note:** This option is visible only for database server greater than or equal to 18.
- Move the switch next to *Statistics* to the *Yes* position to exclude optimizer statistics. **Note:** This option is visible only for database server greater than or equal to 18.



Click the *Query Options* tab to continue. Use these additional fields to specify the type of statements that should be included in the backup.


- Move the switch next to *Use INSERT commands* to the *Yes* position to dump the data in the form of INSERT statements rather than using a COPY command. Please note: this may make restoration from backup slow.
- Use the *Maximum rows per INSERT command* field to controls the maximum number of rows per INSERT command. **Note:** This option is visible only for database server greater than or equal to 12.
- Move the switch next to *On conflict do nothing to INSERT command* towards right position to add ON CONFLICT DO NOTHING to INSERT command. This option is not valid unless *Use INSERT commands*, *Use Column INSERTS* or *Maximum rows per INSERT command* is also specified. **Note:** This option is visible only for database server greater than or equal to 12.
- Move the switch next to *Include DROP DATABASE statement* to the *Yes* position to include a command in the backup that will drop any existing database object with the same name before recreating the object during a backup.
- Move the switch next to *Include IF EXISTS clause* to the *Yes* position to add an IF EXISTS clause to drop databases and other objects. This option is not valid unless *Include DROP DATABASE statement* is also set.




Click the *Table Options* tab to continue. Use the fields in the *Table Options* tab related to tables that should be included in the backup.

- Move the switch next to *Use Column INSERTS* to the *Yes* position to dump the data in the form of INSERT statements and include explicit column names. Please note: this may make restoration from backup slow.
- Move the switch next to *Load via partition root* to the *Yes* position, so when dumping a COPY or INSERT statement for a partitioned table, target the root of the partitioning hierarchy which contains it rather than the partition itself. **Note:** This option is visible only for database server greater than or equal to 11.

Click the *Options* tab to continue. Use the fields in the *Options* tab to provide other backup options.



- Move switches in the **Disable** field box to specify the type of statements that should be excluded from the backup.
  - Move the switch next to *Triggers* (active when creating a data-only backup) to the *Yes* position to include commands that will disable triggers on the target table while the data is being loaded.
  - Move the switch next to *$ quoting* to the *Yes* position to enable dollar quoting within function bodies; if disabled, the function body will be quoted using SQL standard string syntax.



- Move switches in the **Miscellaneous** field box to specify miscellaneous backup options.
  - Move the switch next to *Verbose messages* to the *No* position to instruct *pg_dumpall* to exclude verbose messages.
  - Move the switch next to *Force double quotes on identifiers* to the *Yes* position to force the quoting of all identifiers.
  - Move the switch next to *Use SET SESSION AUTHORIZATION* to the *Yes* position to include a statement that will use a SET SESSION AUTHORIZATION command to determine object ownership (instead of an ALTER OWNER command).
  - Move the switch next to *Dump statistics* to the *Yes* position to include optimizer statistics in the backup. It cannot be combined with *Only data*, *Only schemas* or *Do not save Statistics*. **Note:** This option is visible only for database server greater than or equal to 18.
  - Move the switch next to *Sequence data* to the *Yes* position to include sequence data that would normally be excluded. **Note:** This option is visible only for database server greater than or equal to 18.
  - Use the *Exclude database* field to not dump databases whose name matches pattern.
  - Use the *Extra float digits* field to use the specified value when dumping floating-point data, instead of the maximum available precision.
  - Use the *Lock wait timeout* field to specify a timeout rather than waiting indefinitely to acquire shared table locks at the beginning of the dump. If unable to lock a table within the specified timeout, the operation will fail.

When you've specified the details that will be incorporated into the pg_dumpall command:


- Click the *Backup* button to build and execute a command that builds a backup based on your selections on the *Backup Server* dialog.
- Click the *Cancel* button to exit without saving work.

pgAdmin will run the backup process in the background. You can view all the background processes with their running status and logs on the *Processes* tab.

8.4 Restore Dialog

The *Restore* dialog provides an easy way to use a Custom, tar, or Directory format backup taken with the pgAdmin *Backup* dialog to recreate a database or database object. The *Backup* dialog invokes options of the pg_dump client utility; the *Restore* dialog invokes options of the pg_restore client utility.


You can use the *Query Tool* to play back the script created during a plain-text backup made with the *Backup* dialog. For more information about backing up or restoring, please refer to the documentation for pg_dump or pg_restore.




Use the fields on the *General* tab to specify general information about the restore process:

- Use the drop-down listbox in the *Format* field to select the format of your backup file.
  - Select *Custom or tar* to restore from a custom archive file to create a copy of the backed-up object.
  - Select *Plain* to restore a plain SQL backup. When selecting this option all the other options will not be applicable. **Note:** The plain SQL restore process is executed in the backend using the psql command with the restrict option. The purpose of restrict is to enhance security by preventing dangerous commands embedded in a plain text dump file from being executed on a PostgreSQL server.
  - Select *Directory* to restore from a compressed directory-format archive.
- Enter the complete path to the backup file in the *Filename* field. Optionally, select the *Browse* icon (ellipsis) to the right to navigate into a directory and select the file that contains the archive.
- Use the *Number of Jobs* field to specify if pg_restore should use multiple (concurrent) jobs to process the restore. Each job uses a separate connection to the server.
- Use the drop-down listbox next to *Rolename* to specify the role that will be used to authenticate with the server during the restore process.


Click the *Data Options* tab to continue. Use the fields in the *Data Options* tab to provide options related to data or pgAdmin objects that correspond to *pg_restore*.




- Move switches in the **Sections** field box to specify the content that will be restored:
  - Move the switch next to *Pre-data* to the *Yes* position to restore all data definition items not included in the data or post-data item lists.
  - Move the switch next to *Data* to the *Yes* position to restore actual table data, large-object contents, and sequence values.
  - Move the switch next to *Post-data* to the *Yes* position to restore definitions of indexes, triggers, rules, and constraints (other than validated check constraints).



- Move switches in the **Type of objects** field box to specify the objects that will be restored:
  - Move the switch next to *Only data* to the *Yes* position to limit the restoration to data.
  - Move the switch next to *Only schema* to limit the restoration to schema-level database objects.
  - Move the switch next to *Only statistics* to the *Yes* position to limit the restoration to optimizer statistics. **Note:** This option is visible only for database server greater than or equal to 18.




- Move switches in the **Do not save** box to specify which objects will not be restored:
  - Move the switch next to *Owner* to the *Yes* position to exclude commands that set object ownership.
  - Move the switch next to *Privileges* to the *Yes* position to exclude commands that create access privileges.
  - Move the switch next to *Tablespaces* to the *Yes* position to exclude tablespaces.
  - Move the switch next to *Comments* to the *Yes* position to exclude commands that set the comments. **Note:** This option is visible only for database server greater than or equal to 11.
  - Move the switch next to *Publications* to the *Yes* position to exclude publications.
  - Move the switch next to *Subscriptions* to the *Yes* position to exclude subscriptions.
  - Move the switch next to *Security labels* to the *Yes* position to exclude Security labels.
  - Move the switch next to *Table access methods* to the *Yes* position to exclude Table access methods. **Note:** This option is visible only for database server greater than or equal to 15.
  - Move the switch next to *Row security policies* to the *Yes* position to exclude row security policies. **Note:** This option is visible only for database server greater than or equal to 18.
  - Move the switch next to *Data* to the *Yes* position to exclude data from the restore. **Note:** This option is visible only for database server greater than or equal to 18.
  - Move the switch next to *Schema* to the *Yes* position to exclude schema (the data definitions) from the restore. **Note:** This option is visible only for database server greater than or equal to 18.
  - Move the switch next to *Statistics* to the *Yes* position to exclude optimizer statistics from the restore. **Note:** This option is visible only for database server greater than or equal to 18.



Click the *Query Options* tab to continue. Use these additional fields to specify the type of statements that should be included in the restore:

- Move the switch next to *Include CREATE DATABASE statement* to the *Yes* position to include a command that creates a new database before performing the restore.
- Move the switch next to *Clean before restore* to the *Yes* position to drop each existing database object (and data) before restoring.


- Move the switch next to *Include IF EXISTS clause* to the *Yes* position to add an IF EXISTS clause to drop databases and other objects. This option is not valid unless *Clean before restore* is also set.
- Move the switch next to *Single transaction* to the *Yes* position to execute the restore as a single transaction (that is, wrap the emitted commands in *BEGIN/COMMIT*). This ensures that either all the commands complete successfully, or no changes are applied. This option implies *–exit-on-error*.



Click the *Table Options* tab to continue. Use the fields in the *Table Options* tab related to tables that should be included in the backup.

- Move the switch next to *Enable row security* to the *Yes* position to set row_security to on instead, allowing the user to dump the parts of the contents of the table that they have access to. This option is relevant only when dumping the contents of a table which has row security.
- Move the switch next to *No data for failed tables* to the *Yes* position to ignore data that fails a trigger.

Click the *Options* tab to continue. Use the fields in the *Options* tab to provide other restore options.



- Move switches in the **Disable** box to specify the type of statements that should be excluded from the restore:
  - Move the switch next to *Triggers* (active when creating a data-only restore) to the *Yes* position to include commands that will disable triggers on the target table while the data is being loaded.
- Move switches in the **Miscellaneous/Behavior** box to specify miscellaneous restore options:
  - Move the switch next to *Verbose messages* to the *No* position to instruct *pg_restore* to exclude verbose messages.
  - Move the switch next to *Use SET SESSION AUTHORIZATION* to the *Yes* position to include a statement that will use a SET SESSION AUTHORIZATION command to determine object ownership (instead of an ALTER OWNER command).
  - Move the switch next to *Exit on error* to the *Yes* position to instruct *pg_restore* to exit restore if there is an error in sending SQL commands. The default is to continue and to display a count of errors at the end of the restore.
  - Use the *Exclude schema* field to not dump schemas whose name matches pattern.

When you've specified the details that will be incorporated into the pg_restore command, click the *Restore* button to start the process, or click the *Cancel* button to exit without saving your work. A popup will confirm if the restore is successful.


pgAdmin will run the restore process in the background. You can view all the background processes with their running status and logs on the *Processes* tab.

CHAPTER 9

Developer Tools

The pgAdmin *Tools* menu displays a list of powerful developer tools that you can use to execute and analyze complex SQL commands, manage data, and debug PL/SQL code.

9.1 Debugger



The debugger may be used to debug PL/pgSQL functions in PostgreSQL, as well as EDB-SPL functions, stored procedures and packages in EDB Postgres Advanced Server. The Debugger is available as an extension for your PostgreSQL installation, and is distributed as part of Advanced Server. You must have superuser privileges to use the debugger.

Before using the debugger, you must modify the *postgresql.conf* file, adding the server-side debugger components to the value of the *shared_preload_libraries* parameter, for example:


shared_preload_libraries = '$libdir/plugin_debugger'

After modifying the *shared_preload_libraries* parameter, restart the server to apply the changes.


The debugger may be used for either in-context debugging or direct debugging of a target function or procedure. When you use the debugger for in-context debugging, you set a breakpoint at the first line of a program; when a session invokes the target, control is transferred to the debugger. When using direct debugging, the debugger prompts you for any parameters required by the target, and then allows you to step through the code.

9.1.1 In-context Debugging

To set a breakpoint at the first line of a program, right-click the name of the object you would like to debug, and select *Set breakpoint* from the *Debugging* sub-menu. The debugger window will open, waiting for another session to invoke the program.




When another session invokes the target, the debugger will display the code, allowing you to add break points, or step through line-by-line. The other session is suspended until the debugging completes; then control is returned to the session.



9.1.2 Direct Debugging

To use the debugger for direct debugging, right click on the name of the object that you wish to debug in the pgAdmin tree control and select *Debug* from the *Debugging* sub-menu. The debugger window will open, prompting you for any values required by the program:




Use the fields on the *Debugger* dialog to provide a value for each parameter:

- The *Name* field contains the formal parameter name.
- The *Type* field contains the parameter data type.
- Check the *Null?* checkbox to indicate that the parameter is a NULL value.
- Check the *Expression?* checkbox if the Value field contains an expression.


- Use the *Value* field to provide the parameter value that will be passed to the program. When entering parameter values, type the value into the appropriate cell on the grid, or, leave the cell empty to represent NULL, enter '' (two single quotes) to represent an empty string, or to enter a literal string consisting of just two single quotes, enter ''. PostgreSQL 8.4 and above supports variadic function parameters. These may be entered as a comma-delimited list of values, quoted and/or cast as required.
- Check the *Use default?* checkbox to indicate that the program should use the value in the Default Value field.
- The *Default Value* field contains the default value of the parameter.

Provide values required by the program, and click the *Debug* button to start stepping through the program. The values of the arguments provided here are saved. The values will be pre-filled next time the dialog opens. To clear the values, use the *Clear All* button.



9.1.3 Using the Debugger

The main debugger window consists of two panels and a context-sensitive toolbar. Use toolbar icons to manage breakpoints and step into or through code; hover over an icon for a tooltip that identifies the option associated with the icon. The toolbar options are:




Option	Action	Shortcut
Step into	Click the *Step into* icon to execute the currently highlighted line of code.	Option/Alt + Shift + I
Step over	Click the *Step over* icon to execute a line of code, stepping over any sub-functions invoked by the code. The sub-function executes, but is not debugged unless it contains a breakpoint.	Option/Alt + Shift + O
Continue/Start	Click the *Continue/Start* icon to execute the highlighted code, and continue until the program encounters a breakpoint or completes.	Option/Alt + Shift + C
Toggle breakpoint	Use the *Toggle breakpoint* icon to enable or disable a breakpoint (without removing the breakpoint).	Option/Alt + Shift + T
Clear all breakpoints	Click the *Clear all breakpoints* icon to remove all breakpoints from the program.	Option/Alt + Shift + X
Stop	Click the *Stop* icon to halt the execution of a program.	Option/Alt + Shift + S

continues on next page

Table 1 – continued from previous page

Option	Action	Shortcut
Help	Click the *Help* icon to open debugger documentation.	


The top panel of the debugger window displays the program body; click in the grey margin next to a line number to add a breakpoint. The highlighted line in the top panel is the line that is about to execute.




The lower panel of the debugger window provides a set of tabs that allow you to review information about the program:

- The *Parameters* tab displays the value of each parameter.
- The *Local* variables tab displays the current value of the program variables.
- The *Messages* tab displays any messages returned by the server (errors, warnings and informational messages).
- The *Results* tab displays the server message when the program completes.
- The *Stack* tab displays the list of functions that have been invoked, but which have not yet completed.

As you step through a program, the *Local variables* tab displays the current value of each variable:



When you step into a subroutine, the *Stack* tab displays the call stack, including the name of each caller, the parameter values for each caller (if any), and the line number within each caller:



Select a caller to change focus to that stack frame and display the state of the caller in the upper panel.


When the program completes, the *Results* tab displays the message returned by the server. If the program encounters an error, the *Messages* tab displays details:



9.2 Query Tool

The Query Tool is a powerful, feature-rich environment that allows you to execute arbitrary SQL commands and review the result set. You can access the Query Tool via the *Query Tool* menu option on the *Tools* menu, or through the context menu of select nodes of the Object explorer control. The Query Tool allows you to:

- Issue ad-hoc SQL queries.
- Execute arbitrary SQL commands.
- Edit the result set of a SELECT query if it is *updatable*.
- Displays current connection and transaction status as configured by the user.
- Save the data displayed in the output panel to a CSV file.
- Review the execution plan of a SQL statement in either a text, a graphical format or a table format (similar to https://explain.depesz.com).
- View analytical information about a SQL statement.



	oid [PK] oid	relname name	relnamespace oid	reltype oid	reloftype oid	relowner oid	relam oid	relfilenode oid	reltablespace oid	relpages integer	reltuples real	relallvisible integer	reltoastrelid oid	relhasindex boolean	relisshared boolean	relpersister "char"
1	16386	users_id_seq	2200	0	0	16384	0	16386	0	1	1	0	0	false	false	p
2	16387	users	2200	16389	0	16384	2	16387	0	0	-1	0	0	true	false	p
3	16392	users_pkey	2200	0	0	16384	403	16392	0	1	0	0	0	false	false	p
4	16394	users_email_key	2200	0	0	16384	403	16394	0	1	0	0	0	false	false	p
5	16414	test1	2200	16416	0	16385	2	16414	0	0	-1	0	0	false	false	p
6	2619	pg_statistic	11	12029	0	10	2	2619	0	19	406	19	2840	true	false	p
7	1247	pg_type	11	71	0	10	2	0	0	14	601	14	4171	true	false	p
8	2836	pg_toast_1255	99	0	0	10	2	0	0	1	3	1	0	true	false	p
9	2837	pg_toast_1255_index	99	0	0	10	403	0	0	1	0	0	0	false	false	p
10	4171	pg_toast_1247	99	0	0	10	2	0	0	0	0	0	0	true	false	p
11	4172	pg_toast_1247_index	99	0	0	10	403	0	0	1	0	0	0	false	false	p
12	2830	pg_toast_2604	99	0	0	10	2	2830	0	0	0	0	0	true	false	p
13	2831	pg_toast_2604_index	99	0	0	10	403	2831	0	1	0	0	0	false	false	p
14	2832	pg_toast_2606	99	0	0	10	2	2832	0	0	0	0	0	true	false	p
15	2833	pg_toast_2606_index	99	0	0	10	403	2833	0	1	0	0	0	false	false	p
16	4157	pg_toast_2612	99	0	0	10	2	4157	0	0	0	0	0	true	false	p
17	4158	pg_toast_2612_index	99	0	0	10	403	4158	0	1	0	0	0	false	false	p
18	4159	pg_toast_2600	99	0	0	10	2	4159	0	0	0	0	0	true	false	p
19	4160	pg_toast_2600_index	99	0	0	10	403	4160	0	1	0	0	0	false	false	p

You can open multiple copies of the Query tool in individual tabs simultaneously. To close a copy of the Query tool, click the *X* of the tab.

The Query Tool features two panels:


- The upper panel displays the *SQL Editor*. You can use the panel to enter, edit, or execute a query or a script. It also shows the *History* tab which can be used to view the queries that have been executed in the session, a *Scratch Pad* which can be used to hold text snippets during editing, and an *AI Assistant* tab for generating SQL from natural language (when AI is configured). If the Scratch Pad is closed, it can be re-opened (or additional ones opened) by right-clicking in the SQL Editor and other panels and adding a new panel.
- The lower panel displays the *Data Output* panel. The tabbed panel displays the result set returned by a query, information about a query's execution plan, server messages related to the query's execution and any asynchronous notifications received from the server.

9.2.1 Query Tool in Workspace Layout

The workspace layout offers a distraction-free, dedicated area for the Query Tool. When the Query Tool workspace is accessed, the Welcome page opens by default.

Note: In the Workspace layout, all Query Tool and View/Edit Data tabs open within the Query Tool workspace.

In the classic UI, users must connect to a database server and navigate to the database node before using the Query Tool. However, with the introduction of the Workspace layout and Welcome page, users can seamlessly connect to any ad-hoc server, even if it is not registered in the Object Explorer.



- Select *Existing Server* from the dropdown to connect to a server already listed in the Object Explorer. It is optional.
- Provide the *Server Name* for ad-hoc servers.
- Specify the IP address of the server host, or the fully qualified domain name in the *Host name/address* field.
- Enter the listener port number of the server host in the *Port* field.
- Use the *Database* field to specify the name of the database to which the client will connect.
- Use the *User* field to specify the name of a user that will be used when authenticating with the server.
- Use the *Password* field to provide a password that will be supplied when authenticating with the server.
- Use the *Role* field to specify the name of a role that has privileges that will be conveyed to the client after authentication with the server.
- Use the *Service* field to specify the service name. For more information, see Section 33.16 of the Postgres documentation.
- Use the fields in the *Connection Parameters* to configure the connection parameters.

After filling in all the required fields, click the Connect & Open Query Tool button to launch the Query Tool with the provided server details. If the password is not supplied, you will be prompted to enter it.

9.2.2 Toolbar


The toolbar is described in the following subsections.

Query Tool Toolbar

The *Query Tool* toolbar uses context-sensitive icons that provide shortcuts to frequently performed tasks. If an icon is highlighted, the option is enabled; if the icon is grayed-out, the task is disabled.

Note

The *Query Tool* and *View/Edit Data* tools are actually different operating modes of the same tool. Some controls will be disabled in either mode.



Hover over an icon in pgAdmin to display a tooltip that describes the icon's functionality.


File Options

Icon	Behavior	Shortcut
Open File	Click the *Open File* icon to display a previously saved query in the same tab of the SQL Editor. To open the file in a new tab, select *Open in a new tab?* option from the dropdown.	Cmd/Ctrl + O
Save File	Click the *Save* icon to perform a quick-save of a previously saved query, or to access the *Save* menu: • Select *Save* to save the selected content of the SQL Editor panel in a file. • Select *Save As* to open a new browser dialog and specify a new location to which to save the selected content of the SQL Editor panel.	Cmd/Ctrl + S

Filter/Limit Options

Icon	Behavior	Shortcut
Filter	Click the *Filter* icon to set filtering and sorting criteria for the data when in *View/Edit data mode*. Click the down arrow to access other filtering and sorting options: • In the *SQL Filter*, you can enter a SQL query as filtering criteria. In *Data Sorting*, you can select the column and specify the order for sorting. • Click *Filter by Selection* to show only the rows containing the values in the selected cells. • Click *Exclude by Selection* to show only the rows that do not contain the values in the selected cells. • Click *Remove Sort/Filter* to remove any previously selected sort or filtering options.	Option/Alt + F
Limit Selector	Select a value in the *Limit Selector* to limit the size of the dataset to a number of rows.	Option/Alt + R

Query Editing Options



Icon	Behavior	Shortcut
Edit	Use the *Edit* menu to search, replace, or navigate the code displayed in the SQL Editor:	Option/Alt + Shift + N
	Select *Find* to provide a search target, and search the SQL Editor contents.	Cmd/Ctrl + F
	Select *Replace* to locate and replace (with prompting) individual occurrences of the target.	Cmd/Ctrl + R
	Select *Go to Line/Column* to go to specified line number and column position	Cmd/Ctrl + L
	Select *Indent Selection* to indent the currently selected text.	Tab
	Select *Unindent Selection* to remove indentation from the currently selected text.	Shift + Tab
	Select *Toggle Comment* to comment/uncomment any lines that contain the selection in SQL style.	Cmd/Ctrl + /
	Select *Clear Query* to clear the query editor window.	Option/Alt + Ctrl + L
	Select *Format SQL* to format the selected SQL or all the SQL if none is selected	Cmd/Ctrl + K

Query Execution




Icon	Behavior	Shortcut
Stop	Click the *Stop* icon to cancel the execution of the currently running query.	Option + Shift + Q
Execute script	Click the *Execute script* icon to either execute or refresh the query highlighted in the SQL editor panel. Click the down arrow to access other execution options: • Add a check next to *Auto rollback on error?* to instruct the server to automatically roll back a transaction if an error occurs during the transaction. • Add a check next to *Auto commit?* to instruct the server to automatically commit each transaction. Any changes made by the transaction will be visible to others, and durable in the event of a crash.	F5
Execute query	Click the *Execute query* icon to either execute the query where the cursor is present or refresh the query highlighted in the SQL editor panel.	Option+F5 (MAC) Alt+F5 (Others)
Explain	Click the *Explain* icon to view an explanation plan for the current query. The result of the EXPLAIN is displayed graphically on the *Explain* tab of the output panel, and in text form on the *Data Output* tab.	F7
Explain analyze	Click the *Explain analyze* icon to invoke an EXPLAIN ANALYZE command on the current query. Navigate through the *Explain Options* menu to select options for the EXPLAIN command: • Select *Buffers* to include information on buffer usage. • Select *Costs* to include information on the estimated startup and total cost of each plan node, as well as the estimated number of rows and the estimated width of each row. • Select *Generic Plan* to include the information on the Generic Plan. • Select *Memory* to include the information on memory consumption by the query planning phase. • Select *Serialize* to include information on the cost of serializing the query's output data, that is converting it to text or binary format to send to the client. • Select *Settings* to include the information on the configuration parameters. • Select *Summary* to include the summary information about the query plan. • Select *Timing* to include information about the startup time and the amount of time spent in each node of the query. • Select *Verbose* to display additional information regarding the query plan. • Select *Wal* to include the information on WAL record generation.	Shift + F7
Commit	Click the *Commit* icon to commit the transaction.	Shift + Ctrl + M

continues on next page

Table 5 – continued from previous page

Icon	Behavior	Shortcut
Rollback	Click the *Rollback* icon to rollback the transaction.	Shift + Ctrl + R
Macros	Click the *Macros* icon to manage the macros. You can create, edit or clear the macros through the *Manage Macros* option.	


Data Editing Options



Icon	Behavior	Shortcut
Add row	Click the *Add row* icon to add a new row	
Copy	Click the *Copy* icon to copy the content with or without header: • **Click the *Copy* icon to copy the content that is currently highlighted in the Data Output** panel. • Click *Copy with headers* to copy the highlighted content along with the header.	Cmd/Ctrl + C
Paste	Click the *Paste* icon to paste a previously copied row with or without serial/identity values: • Click the *Paste* icon to paste a previously copied row into a new row. • Click the *Paste with SERIAL/IDENTITY values?* if you want to paste the copied column values in the serial/identity columns. Note that copied row having *Bytea* datatype cell will be pasted as *Null*.	Option/Alt + Shift + P
Delete	Click the *Delete* icon to mark the selected rows for deletion. These marked rows get deleted when you click the *Save Data Changes* icon.	Option/Alt + Shift + D
Save Data Changes	Click the *Save Data Changes* icon to save data changes (insert, update, or delete) in the Data Output Panel to the server.	F6
Save results to file	Click the Save results to file icon to save the result set of the current query. By default it is saved as a delimited text file (CSV, if the field separator is set to a comma). Use the adjacent drop-down list to instead save the results as JSON or XML. This button is only enabled when a query has been executed and there are results in the data grid. You can specify the CSV/TXT settings (including the output file encoding and byte order mark) in the Preferences dialog under Query Tool -> CSV/TXT Output.	F8
Graph Visualiser	Use the Graph Visualiser button to generate graphs of the query results.	
SQL	Use the SQL button to check the current query that gave the data.	

Pagination Options


Icon	Behavior	Shortcut
Rows Range	Show the current row numbers visible in the data grid.	
Edit Range	Click to open the from and to rows range inputs to allow setting them.	
Show Entire Range	Click to get all the rows and set the from and to rows range	
Page No	Enter the page no you want to jump to out of total shown next to this input	
First Page	Click to go to the first page.	
Previous Page	Click to go to the previous page.	
Next Page	Click to go to the next page.	
Last Page	Click to go to the last page.	



One can click the edit range button to open rows range editor:

- From and to range should be between 1 and total rows.
- The range can be applied by clicking the *Apply* button or by pressing enter in the range inputs.
- Once the range is applied, pgAdmin will recalculate the rows per page. The pagination will then behave based on the new rows per page.
- It may be possible that on pressing next page button, the new rows range is not next to manually enterred range.

Status Bar




The status bar shows the following information:


- **Total rows**: The total number of rows returned by the query.
- **Query complete**: The time is taken by the query to complete.
- **Rows selected**: The number of rows selected in the data output panel.
- **Changes staged**: This information shows the number of rows added, deleted, and updated.
- **LF/CRLF**: It shows the end of line sequence to be used for the editor. When opening an empty editor, it will be decided based on OS. And when opening an existing file, it will be based on file end of lines. One can change the EOL by clicking on any of the options.
- **Ln**: In the Query tab, it is the line number at which the cursor is positioned.
- **Col**: In the Query tab, it is the column number at which the cursor is positioned

9.2.3 The SQL Editor Panel


The *SQL editor* panel is a workspace where you can manually provide a query, copy a query from another source, or read a query from a file. The SQL editor features syntax coloring and autocompletion.




To use autocomplete, begin typing your query; when you would like the Query editor to suggest object names or commands that might be next in your query, press the Control+Space key combination. For example, type "*SELECT * FROM*" (without quotes, but with a trailing space), and then press the Control+Space key combination to select from a popup menu of autocomplete options.




After entering a query, select the *Execute script* icon from the toolbar. The complete contents of the SQL editor panel will be sent to the database server for execution. To execute only a section of the code that is displayed in the SQL editor, highlight the text that you want the server to execute, and click the *Execute script* icon.




You can also execute a query based on cursor position. Query tool will detect a query and underline it when cursor position changes. Now, to execute the current underlined query, hit the *Execute query* button on the toolbar. If a section is highlighted then it will behave like normal execute.



The warning will appear only if *Underline query at cursor?* is set to *False* and the *Underlined query execute warning?* switch is set to *True* Preferences Query tool's Options.



The message returned by the server when a command executes is displayed on the *Messages* tab. If the command is successful, the *Messages* tab displays execution details.




Options on the *Edit* menu offer functionality that helps with code formatting and commenting:

- The auto-indent feature will automatically indent text to the same depth as the previous line when you press the Return key.
- Block indent text by selecting two or more lines and pressing the Tab key.
- Implement or remove SQL style or toggle C style comment notation within your code.

You can also **drag and drop** certain objects from the treeview which can save time in typing long object names. Text containing the object name will be fully qualified with schema. Double quotes will be added if required. For functions and procedures, the function name along with parameter names will be pasted in the Query Tool.

9.2.4 Query History Panel

Use the *Query History* tab to review activity for the current session:



The Query History tab displays information about recent commands:

- The date and time that a query was invoked.
- The text of the query.
- The number of rows returned by the query.
- The amount of time it took the server to process the query and return a result set.
- Messages returned by the server (not noted on the *Messages* tab).
- The source of the query (indicated by icons corresponding to the toolbar).

You can show or hide the queries generated internally by pgAdmin (during 'View/Edit Data' or 'Save Data' operations).


You can remove a single query by selecting it and clicking on the *Remove* button. If you would like to remove all of the histories from the *Query History* tab, then click on the *Remove All* button.

By using the *Copy* button, you can copy a particular query to the clipboard, and with the *Copy to Query Editor* button, you can copy a specific query to the Query Editor tab. During this operation, all existing content in the Query Editor is erased.

Query History is maintained across sessions for each database on a per-user basis when running in Query Tool mode. In View/Edit Data mode, history is not retained. By default, the last 20 queries are stored for each database. This can be adjusted in `config_local.py` or `config_system.py` (see the *config.py* documentation) by overriding the *MAX_QUERY_HIST_STORED* value. See the *Deployment* section for more information.

9.2.5 AI Assistant Panel

The *AI Assistant* tab provides a chat-style interface for generating SQL queries from natural language descriptions. This feature requires an AI provider to be configured in *Preferences* > *AI*. For configuration details, see the *Preferences* documentation.



To use the AI Assistant:

1. Click on the *AI Assistant* tab in the upper panel, or use the *AI Assistant* toolbar button.
2. Type a description of the SQL query you need in natural language.
3. Press Enter or click the send button to submit your request.
4. The AI will analyze your database schema and generate appropriate SQL.

The AI Assistant displays conversations with your messages and AI responses. When the AI generates SQL, it appears in a syntax-highlighted code block with action buttons:

- **Insert** - Insert the SQL at the current cursor position in the SQL Editor.
- **Replace** - Replace all content in the SQL Editor with the generated SQL.
- **Copy** - Copy the SQL to the clipboard.

The AI Assistant maintains conversation context, allowing you to refine queries iteratively. For example, you can ask for a query and then follow up with "also add a filter for active users" to modify the previous result.


Tips for effective use:

- Be specific about table and column names if you know them.
- Describe the desired output format (e.g., "show count by category").
- For complex queries, break down requirements step by step.
- Use the *Clear* button to start a fresh conversation.

Note: The AI Assistant uses database schema inspection tools to understand your database structure. It supports SELECT, INSERT, UPDATE, DELETE, and DDL statements. All generated queries should be reviewed before execution. See *Data Handling and Provider Selection* for details of the information that is transmitted to your configured LLM provider.

9.2.6 The Data Output Panel

The *Data Output* panel displays data and statistics generated by the most recently executed query.



	oid [PK] oid	relname name	relnamespace oid	reltype oid	reloftype oid	relowner oid	relam oid	relfilenode oid	reltablespace oid	relpages integer	reltuples real	relallvisible integer	reltoastrelid oid	relhasindex boolean	relisshared boolean	relpersister "char"
1	16386	users_id_seq	2200	0	0	16384	0	16386	0	1	1	0	0	false	false	p
2	16387	users	2200	16389	0	16384	2	16387	0	0	-1	0	0	true	false	p
3	16392	users_pkey	2200	0	0	16384	403	16392	0	1	0	0	0	false	false	p
4	16394	users_email_key	2200	0	0	16384	403	16394	0	1	0	0	0	false	false	p
5	16414	test1	2200	16416	0	16385	2	16414	0	0	-1	0	0	false	false	p
6	2619	pg_statistic	11	12029	0	10	2	2619	0	19	406	19	2840	true	false	p
7	1247	pg_type	11	71	0	10	2	0	0	14	601	14	4171	true	false	p
8	2836	pg_toast_1255	99	0	0	10	2	0	0	1	3	1	0	true	false	p
9	2837	pg_toast_1255_index	99	0	0	10	403	0	0	1	0	0	0	false	false	p
10	4171	pg_toast_1247	99	0	0	10	2	0	0	0	0	0	0	true	false	p
11	4172	pg_toast_1247_index	99	0	0	10	403	0	0	1	0	0	0	false	false	p
12	2830	pg_toast_2604	99	0	0	10	2	2830	0	0	0	0	0	true	false	p
13	2831	pg_toast_2604_index	99	0	0	10	403	2831	0	1	0	0	0	false	false	p
14	2832	pg_toast_2606	99	0	0	10	2	2832	0	0	0	0	0	true	false	p
15	2833	pg_toast_2606_index	99	0	0	10	403	2833	0	1	0	0	0	false	false	p
16	4157	pg_toast_2612	99	0	0	10	2	4157	0	0	0	0	0	true	false	p
17	4158	pg_toast_2612_index	99	0	0	10	403	4158	0	1	0	0	0	false	false	p
18	4159	pg_toast_2600	99	0	0	10	2	4159	0	0	0	0	0	true	false	p
19	4160	pg_toast_2600_index	99	0	0	10	403	4160	0	1	0	0	0	false	false	p

The *Data Output* tab displays the result set of the query in a table format. You can:


- Select and copy from the displayed result set.
- Use the *Save results to file* icon to save the content of the *Data Output* tab as a comma-delimited file.
- Edit the data in the result set of a SELECT query if it is updatable.
- Move between pages of data result.

A result set is updatable if:

- All columns are either selected directly from a single table, or are not table columns at all (e.g. concatenation of 2 columns). Only columns that are selected directly from the table are editable, other columns are read-only.
- All the primary key columns or OIDs of the table are selected in the result set.

Any columns that are renamed or selected more than once are also read-only.

Editable and read-only columns are identified using pencil and lock icons (respectively) in the column headers.



	oid [PK] oid	relname name	relnamespace oid	reltype oid	reloftype oid	relowner oid
1	2619	pg_statistic	11	12029	0	10
2	1247	pg_type	11	71	0	10
3	2836	pg_toast_1255	99	0	0	10
4	2837	pg_toast_1255_index	99	0	0	10
5	4171	pg_toast_1247	99	0	0	10

The psycopg2 driver version should be equal to or above 2.8 for updatable query result sets to work.

An updatable result set is identical to the *Data Grid* in View/Edit Data mode, and can be modified in the same way.

If Auto-commit is off, the data changes are made as part of the ongoing transaction, if no transaction is ongoing a new one is initiated. The data changes are not committed to the database unless the transaction is committed.


If any errors occur during saving (for example, trying to save NULL into a column with NOT NULL constraint) the data changes are rolled back to an automatically created SAVEPOINT to ensure any previously executed queries in the ongoing transaction are not rolled back.

All rowsets from previous queries or commands that are displayed in the *Data Output* panel will be discarded when you invoke another query; open another Query Tool tab to keep your previous results available.

9.2.7 Explain Panel

To generate the *Explain* or *Explain Analyze* plan of a query, click on *Explain* or *Explain Analyze* button in the toolbar.

More options related to *Explain* and *Explain Analyze* can be selected from the drop down on the right side of *Explain Analyze* button in the toolbar.



Please note that pgAdmin generates the *Explain [Analyze]* plan in JSON format.

Note: If multiple queries are present and none is selected, *Explain [Analyze]* runs the query located at the cursor position.


On successful generation of *Explain* plan, it will create three tabs/panels under the Explain panel.

- Graphical

Please note that *EXPLAIN VERBOSE* cannot be displayed graphically. Click on a node icon on the *Graphical* tab to review information about that item; a popup window will display on the right side with the information about the selected object. For information on JIT statistics, triggers and a summary, click on the button on top-right corner; a similar popup window will be displayed when appropriate.

Use the download button on top left corner of the *Explain* canvas to download the plan as an SVG file.

Note: Download as SVG is not supported on Internet Explorer.



Note that the query plan that accompanies the *Explain analyze* is available on the *Data Output* tab.

- Table


Table tab shows the plan details in table format, it generates table format similar to *explain.depesz.com*. Each row of the table represent the data for a *Explain Plan Node*. It may contain the node information, exclusive timing, inclusive

timing, actual vs planned rows differences, actual rows, planned rows, loops.

background color of the exclusive, inclusive, and Rows X columns may vary based on the difference between actual vs planned.


If percentage of the exclusive/inclusive timings of the total query time is: > 90 - Red color > 50 - Orange (between red and yellow) color > 10 - Yellow color

If planner mis-estimated number of rows (actual vs planned) by 10 times - Yellow color 100 times - Orange (between Red and Yellow) color 1000 times - Red color




- Statistics

Statistics tab shows two tables: 1. Statistics per Plan Node Type 2. Statistics per Table



- AI Insights

The *AI Insights* tab provides AI-powered analysis of query execution plans, identifying performance bottlenecks and suggesting optimizations. This tab is only available when an AI provider is configured in *Preferences* > *AI*.



When you switch to the AI Insights tab, the AI analyzes the execution plan and provides:

Performance Bottlenecks - Issues identified in the query plan, such as:

- Sequential scans on large tables that could benefit from indexes
- Significant differences between estimated and actual row counts
- Expensive sort or hash operations
- Nested loops with high iteration counts

Recommendations - Concrete suggestions to improve query performance:

- Index creation statements with appropriate columns
- ANALYZE commands to update table statistics
- Configuration parameter adjustments
- Query restructuring suggestions


Each recommendation that includes SQL (such as CREATE INDEX statements) has action buttons to *Copy* the SQL to the clipboard or *Insert* it into the Query Editor.

Click the *Regenerate* button to request a fresh analysis of the current plan.


Note: AI analysis is generated on-demand when you first click the AI Insights tab or when a new explain plan is generated while the tab is active. The analysis provides guidance but all suggested changes should be carefully evaluated before applying to production databases.

9.2.8 Messages Panel

Use the *Messages* tab to view information about the most recently executed query:



If the server returns an error, the error message will be displayed on the *Messages* tab, and the syntax that caused the error will be underlined in the SQL editor. If a query succeeds, the *Messages* tab displays how long the query took to complete and how many rows were retrieved:




9.2.9 Notifications Panel


Use the *Notifications* tab to view the notifications using PostgreSQL *Listen/ Notify* feature. For more details see PostgreSQL documentation.

Example:


1. Execute *LISTEN "foo"* in first *Query Tool* session



2. In the another *Query Tool* session, execute *Notify* command or *pg_notify* function to send the notification of the event together with the payload.




3. You can observe the *Notification* tab in the first *Query Tool* session where it shows the Recorded time, Event, Process ID, and the Payload of the particular channel.




9.2.10 Graph Visualiser Panel

Click the Graph Visualiser button in the toolbar to generate the *Graphs* of the query results. The graph visualiser supports Line Charts, Stacked Line Charts, Bar Charts, Stacked Bar Charts, and Pie Charts.




- Graph Type

Choose the type of the graph that you would like to generate.




- X Axis

Choose the column whose value you wish to display on X-axis from the *X Axis* dropdown. Select the *<Row Number>* option to use the number of rows as labels on the X-axis.



- Y Axis


Choose the columns whose value you wish to display on Y-axis from the *Y Axis* dropdown. Users can choose multiple columns. Choose the <*Select All*> option from the drop-down menu to select all the columns.



- Download and Zoom button

Zooming is performed by clicking and selecting an area over the chart with the mouse. The *Zoom to original* button will bring you back to the original zoom level.

Click the *Download* button on the button bar to download the chart.



Line Chart

The *Line Chart* can be generated by selecting the 'Line Chart' from the Graph Type drop-down, selecting the X-axis and the Y-axis, and clicking on the 'Generate' button. Below is an example of a chart of employee names and their salaries.



Set *Use different data point styles?* option to true in the *Preferences*, to show data points in a different style on each graph lines.

Stacked Line Chart

The *Stacked Line Chart* can be generated by selecting the 'Stacked Line Chart' from the Graph Type drop-down, selecting the X-axis and the Y-axis, and clicking on the 'Generate' button.



Bar Chart

The *Bar Chart* can be generated by selecting the 'Bar Chart' from the Graph Type drop-down, selecting the X-axis and the Y-axis, and clicking on the 'Generate' button.




Stacked Bar Chart

The *Stacked Bar Chart* can be generated by selecting the 'Stacked Bar Chart' from the Graph Type drop-down, selecting the X-axis and the Y-axis, and clicking on the 'Generate' button.




Pie Chart

The *Pie Chart* can be generated by selecting the 'Pie Chart' from the Graph Type drop-down, selecting the Label and Value, and clicking on the 'Generate' button.



9.2.11 Connection Status


Use the *Connection status* feature to view the current connection and transaction status by clicking on the status icon in the Query Tool:




9.2.12 Change connection

User can connect to another server or database from existing open session of query tool.

- Click on the connection link next to connection status.
- Now click on the *<New Connection>* option from the dropdown.




- Now select server, database, user, and role to connect and click on the 'Save' button.




- A newly created connection will now get listed in the options.
- To connect, select the newly created connection from the dropdown list.

9.2.13 Macros


Query Tool Macros enable you to execute pre-defined SQL queries with a single key press. Pre-defined queries can contain the placeholder $SELECTION$. Upon macro execution, the placeholder will be replaced with the currently selected text in the Query Editor pane of the Query Tool.




To create a macro, select the *Manage Macros* option from the *Macros* menu on the *Query Tool*. Select the key you wish to use, enter the name of the macro, and the query, optionally including the selection placeholder, and then click the *Save* button to store the macro.




To add a query to macros, write and select your query, then go to the *Macros* menu in the Query Tool and click *Add to macros*. Your query will be automatically saved to macros.



To delete a macro, select the macro on the *Manage Macros* dialogue, and then click the *Delete* button. The server will prompt you for confirmation to delete the macro.



To execute a macro, simply select the appropriate shortcut keys, or select it from the *Macros* menu.




9.2.14 Server Side Cursor

Server-side cursors allow partial retrieval of large datasets, making them particularly useful when working with very large result sets. However, they may offer lower performance in typical, everyday usage scenarios.

To enable server-side cursors:

- Go to Preferences > Query Tool > Options and set "Use server cursor?" to True.
- Alternatively, you can enable it on a per-session basis via the Query Tool's Execute menu.



Limitations:


1. Transaction Requirement: Server-side cursors work only in transaction mode. If enabled pgAdmin will automatically ensure queries run within a transaction.

2. Limited Use Case: Use server-side cursors only when fetching large datasets.

3. Pagination Limitation: In the Result Grid, the First and Last page buttons will be disabled, as server-side cursors do not return a total row count. Consequently, the total number of rows will not be displayed after execution.

9.3 View/Edit Data

To view or modify data, right click on a table or view name in the *Object Explorer*. When the context menu opens, use the *View/Edit Data* menu to specify the number of rows you would like to display in the editor panel.



To modify the content of a table, each row in the table must be uniquely identifiable. If the table definition does not include an OID or a primary key, the displayed data is read only. Simple, automatically-updatable views (a single base table, with no `INSTEAD OF` triggers or rewrite rules, whose base table's primary key columns are all exposed in the view under their original names) can also be edited; updating and deleting rows is supported, but inserting new rows through a view is not, so the *Add row* and *Paste* buttons are disabled when editing a view. Materialized views, views based on more than one table, views exposing only part of a composite primary key, and views relying on `INSTEAD OF` triggers or rules created with `CREATE RULE` remain read only.

The editor features a toolbar that allows quick access to frequently used options, and a work environment divided into two panels:

- The upper panel displays the SQL command that was used to select the content displayed in the lower panel.
- The lower panel (the Data Grid) displays the data selected from the table or view.

9.3.1 The View/Edit Data Toolbar

The *Query Tool* and *View/Edit Data* tools are actually different operating modes of the same tool. Some controls will be disabled in either mode. Please see *The Query Tool Toolbar* for a description of the available controls.

9.3.2 The Data Grid

The top row of the data grid displays the name of each column, the data type, and if applicable, the number of characters allowed. A column that is part of the primary key will additionally be marked with [PK].

To modify the displayed data:

- To change a numeric value within the grid, double-click the value to select the field. Modify the content in the square in which it is displayed.
- To change a non-numeric value within the grid, double-click the content to access the edit bubble. After modifying the content of the edit bubble, click the *Ok* button to display your changes in the data grid, or *Cancel* to exit the edit bubble without saving.

To enter a newline character, click Ctrl-Enter or Shift-Enter. Newline formatting is only displayed when the field content is accessed via an edit bubble.

To add a new row to the table, enter data into the last (unnumbered) row of the table. As soon as you store the data, the row is assigned a row number, and a fresh empty line is added to the data grid.

To write a SQL NULL to the table, simply leave the field empty. When you store the new row, the server will fill in the default value for that column. If you store a change to an existing row, the value NULL will explicitly be written.


To write an empty string to the table, enter the special string '' (two single quotes) in the field. If you want to write a string containing solely two single quotes to the table, you need to escape these quotes, by typing ''

To delete a row, press the *Delete* toolbar button. A popup will open, asking you to confirm the deletion.


To commit the changes to the server, select the *Save Data* toolbar button.

Geometry Data Viewer

If PostGIS is installed, you can view GIS objects in a map by selecting row(s) and clicking the 'View Geometry' button in the column. If no rows are selected, the entire data set will be rendered:



You can adjust the layout by dragging the title of the panel. To view the properties of the geometries directly in map, just click the specific geometry:




Note

- *Supported data types:* The Geometry Viewer supports 2D and 3DM geometries in EWKB format including *Point, LineString, Polygon MultiPoint, MultiLineString, MultiPolygon and GeometryCollection*.
- *SRIDs:* If there are geometries with different SRIDs in the same column, the viewer will render geometries with the same SRID in the map. If SRID=4326 the OSM tile layer will be added into the map.
- *Custom tile provider:* A custom map tile provider ({z}/{x}/{y} URL template, in EPSG:3857, EPSG:4326 or EPSG:3395) can be configured as a base layer via *Preferences* > *Query Tool* > *Geometry Viewer*. When configured, it is selected as the default base layer.
- *Data size:* For performance reasons, the viewer will render no more than 100000 geometries, totaling up to 20MB.
- *Internet access:* An internet connection is required for the Geometry Viewer to function correctly.

JSON Data Editor

A built-in JSON editor is provided for *JSON/JSONB Data*. Double-clicking on a JSON/JSONB data type cell in the data grid will open the JSON Editor. The editor provides different modes to view and edit JSON data.



Code Mode: Provides a way to format and compact JSON data. Also provides the ability to repair JSON data by fixing quotes and escape characters, removing comments and JSONP notation, and turning JavaScript objects into JSON.

Tree Mode: Enables changing, adding, moving, removing, and duplicating fields and values. Provides the ability to search and highlight data.


Form Mode: Allows editing only the values in JSON data, thereby providing the ability to keep the data structure unchanged while editing.

Preview Mode: Provides the ability to check data before saving and also shows the size of the current JSON data. Allows formatting and compacting JSON data as well.


Editor Toolbar

Different options are provided to manipulate json data.

Code/Preview mode:



Tree/Form mode:



Icon	Behavior	Available in mode
Format Json	Click to *Format Json* format json data with proper indentation.	Code, Preview
Compact Json	Click to *Compact Json* get compacted json data.	Code, Preview


continues on next page

Table 8 – continued from previous page

Icon	Behavior	Available in mode
Sort	Click to *Sort* icon to set sorting criteria for the data using file values.	Code, Preview, Tree
Transform	Click to *Transform* to filter data using JSME query language.	Code, Preview, Tree
Undo	Click to *Undo* to undo last action performed on data.	Code, Preview, Tree, Form
Redo	Click to *Redo* to repeat last action performed on data.	Code, Preview, Tree, Form
Mode	Click the *Mode* dropdown to change the display mode of the editor. Different modes available are Code, Preview, Tree, and Form.	Code, Tree, Form, Preview
Expand All	Click *Expand All* to expand JSON data.	Tree, Form
Collapse All	Click *Collapse All* to collapse JSON data.	Tree, Form
Search Box	Enter partial/complete string to search in data.	Tree, Form

9.3.3 Sort/Filter options dialog

You can access *Sort/Filter options dialog* by clicking on Sort/Filter button. This allows you to specify an SQL Filter to limit the data displayed and data sorting options in the edit grid window:



- Use *SQL Filter* to provide SQL filtering criteria. These will be added to the "WHERE" clause of the query used to retrieve the data. For example, you might enter:

```
id > 25 AND created > '2018-01-01'
```

- Use *Data Sorting* to sort the data in the output grid

To add new column(s) in data sorting grid, click on the [+] icon.

- Use the drop-down *Column* to select the column you want to sort.
- Use the drop-down *Order* to select the sort order for the column.
- Use the drop-down *NULLs* to select the NULL values order for the column.

To delete a row from the grid, click the trash icon.

- Click the *Save* button to save work.
- Click the *Close* button to discard current changes and close the dialog.

View/Edit Data Filter


You can access *Data Filter dialog* by clicking on *Filtered Rows* toolbar button visible on the Browser panel or by selecting *View/Edit Data -> Filtered Rows* context menu option.

This allows you to specify an SQL Filter to limit the data displayed in the edit grid window:



9.3.4 Promote View/Edit Data to Query Tool

A View/Edit Data tab can be converted to a Query Tool Tab just by editing the query. Once you start editing, it will ask if you really want to move away from View/Edit.



You can disable the dialog by selecting the "Don't Ask again" checkbox. If you wish to resume the confirmation dialog, you can do it from "Preferences -> Query Tool -> Editor -> Show View/Edit Data Promotion Warning?"

Once you chose to continue, you won't be able to use the features of View/Edit mode like the filter and sorting options, limit, etc. It is a one-way conversion. It will be a query tool now.

9.4 Schema Diff

Schema Diff is a feature that allows you to compare objects between two databases or two schemas. Use the *Tools* menu to access Schema Diff.

The Schema Diff feature allows you to:


- Compare and synchronize the database objects (from source to target).
- Visualize the differences between database objects.
- List the differences in SQL statement for target database objects.
- Generate synchronization scripts.

Note:

- The source and target database servers must be of the same major version.
- If you compare two **schemas** then dependencies won't be resolved.

Click on *Schema Diff* under the *Tools* menu to open a selection panel. To compare **databases** choose the source and target servers, and databases. To compare **schemas** choose the source and target servers, databases, and schemas. After selecting the objects, click on the *Compare* button.

You can open multiple copies of *Schema Diff* in individual tabs simultaneously. To close a copy of Schema Diff, click the *X* in the upper-right hand corner of the tab bar. You can rename the panel title by right-clicking and select the "Rename Panel" option.




Use the *Preferences* dialog to specify following:

- *Schema Diff* should open in a new browser tab. Set *Open in new browser tab* option to true.
- *Schema Diff* should ignore the whitespaces while comparing string objects. Set *Ignore whitespaces* option to true.
- *Schema Diff* should ignore the owner while comparing objects. Set *Ignore owner* option to true.

9.4.1 Schema Diff in Workspace Layout

The workspace layout offers a distraction-free, dedicated area for the Schema Diff. By default, the Schema Diff workspace button remains disabled until at least one Schema Diff tab is opened.

Note: In the Workspace layout, all Schema Diff tabs open within the Schema Diff workspace.




The *Schema Diff* panel is divided into two panels; an Object Comparison panel and a DDL Comparison panel.

The Schema Diff Object Comparison Panel

In the object comparison panel, you can select the source and target servers of the same major version, and databases to be compared. You can select any server listed under the object explorer whether it is connected or disconnected. If you select a server that is not connected then it will prompt you for the password before using the server.


Next, select the databases that will be compared. The databases can be the same or different (and within the same server or from different servers).



Use the drop-down near to *Compare* button to ignore owner, whitespace, tablespace and grants.

- Ignore Owner – Select to ignore the owner while comparing the objects.
- Ignore Whitespace – Select to ignore the whitespace while comparing the string objects. Whitespace includes space, tabs, and CRLF.
- Ignore Tablespace – Select to ignore the tablespace while comparing the objects.
- Ignore Grant/Revoke – Select to ignore the grant and revoke command while comparing the objects.


After you select servers, and databases, click on the *Compare* button to obtain the *Comparison Result*.



Use the drop-down lists of Database Objects to view the DDL statements.

In the upper-right hand corner of the object comparison panel is a *Filter* option that you can use to filter the database objects based on the following comparison criteria:

- Identical – If the object is found in both databases with the same SQL statement, then the comparison result is identical.
- Different – If the object is found in both databases but have different SQL statements, then the comparison result is different.
- Source Only – If the object is found in source database only and not in target database, then the comparison result is source only.
- Target Only – If the object is found in target database only and not in source database, then the comparison result is target only.



Click on any of the database objects in the object comparison panel to display the DDL Statements of that object in the


DDL Comparison panel.

Click the *Help* icon to open Schema Diff documentation.

Schema Diff DDL Comparison Panel

The *DDL Comparison* panel displays three columns:

- The first column displays the DDL statement of the object from the source database.
- The second column displays the DDL statement of the object from the target database.
- The third column displays the difference in the SQL statement of the target database object.




You can review the DDL statements of all the database objects to check for the differences in the SQL statements.

Also, you can generate the SQL script of the differences found in the target database object based on the SQL statement of the source database object. To generate the script, select the checkboxes of the database objects in the object comparison panel and then click on the *Generate Script* button in the upper-right hand corner of the object comparison panel.

Select the database objects and click on the *Generate Script* button to open the *Query Tool* in a new tab, with the difference in the SQL statement displayed in the *Query Editor*.

If you have clicked on the database object to check the difference generated in the *DDL Comparison* Panel, and you have not selected the checkbox of the database object, pgAdmin will open the *Query Tool* in a new tab, with the differences in the SQL statements displayed in the *Query Editor*.

You can also use the *Copy* button to copy the difference generated in the *DDL Comparison* panel.




Apply the SQL Statement in the target database to synchronize the databases.

9.5 ERD Tool

The Entity-Relationship Diagram (ERD) tool is a database design tool that provides a graphical representation of database tables, columns, and inter-relationships. ERD can give sufficient information for the database administrator to follow when developing and maintaining the database. The ERD Tool allows you to:

- Design and visualize the database tables and their relationships.
- Add notes to the diagram.
- Auto-align the tables and links for cleaner visualization.
- Save the diagram and open it later to continue working on it.
- Generate ready to run SQL from the database design.
- Generate the database diagram for an existing database.
- Drag and drop tables from object explorer to the diagram.



You can open multiple copies of the ERD tool in individual tabs simultaneously. You can also generate an ERD from a database, schema or a table.

- The ERD for database will fetch all the tables from all the schemas of the database and plot them with foreign key links.
- The ERD for schema will fetch all the tables from a schema and plot them with foreign key links. If any table refers to a table in another schema, then that link/foreign key will be removed.
- The ERD for table will fetch all the tables linked directly or indirectly to mentioned table. You can change the depth of traversal from *Preferences*.

9.5.1 Toolbar

The *ERD Tool* toolbar uses context-sensitive icons that provide shortcuts to frequently performed tasks. The option is enabled for the highlighted icon and is disabled for the grayed-out icon.

Hover over an icon on Toolbar to display a tooltip that describes the icon's functionality.

9.5.2 File Options

Icon	Behavior	Shortcut
Open File	Click the *Open File* icon to load a previously saved diagram.	Cmd/Ctrl + O
Save	Click the *Save* icon to perform a quick-save of a previously saved diagram, or to save the diagram to a file.	Cmd/Ctrl + S
Save as	Click the *Save As* to open a new browser dialog and specify a new location to save the diagram. You need to click the down arrow beside the save button to see *Save As*.	Ctrl + Shift + S

9.5.3 Export Options

Icon	Behavior	Shortcut
Generate SQL	Click the *Generate SQL* icon to generate the DDL SQL for the diagram and open a query tool with the generated SQL ready for execution. You can select the option *With DROP Table* if you wish to have DROP Table DDL statements before each CREATE Table DDL. You can see the option by clicking the down arrow beside the SQL button.	Option/Alt + Ctrl + S
Download image	Click the *Download image* icon to save the ERD diagram in an image format.	Option/Alt + Ctrl + I

9.5.4 Editing Options

Icon	Behavior	Shortcut
Search table	Click to search for a table in the diagram. Selecting a table from the search results will bring it into view and highlight it.	Option/Alt + Ctrl + F
Add table	Click this button to add a new table to the diagram. On clicking, this will open a table dialog where you can put the table details.	Option/Alt + Ctrl + A
Edit table	Click this button to edit a table on the diagram. On clicking, this will open a table dialog where you can change table details. This will enable when a table is selected.	Option/Alt + Ctrl + E
Clone table	Click this button to clone the complete table structure, name it with a auto generated name and put it in the diagram.	Option/Alt + Ctrl + C
Drop table/link	You can drop a table or link using this button. You need to select a table or link and click on this button to drop it.	Option/Alt + Ctrl + D

9.5.5 Table Relationship Options

Icon	Behavior	Shortcut
1-1	Click this button to open a one-to-one relationship dialog to add a relationship between the two tables. The selected table becomes the referencing table.	Option/Alt + Ctrl + B
1-M	Click this button to open a one-to-many relationship dialog to add a relationship between the two tables. The selected table becomes the referencing table and will have the *many* endpoint of the link.	Option/Alt + Ctrl + O
M-M	Click this button to open a many-to-many relationship dialog to add a relationship between the two tables. This option will create a new table based on the selected columns for the two relating tables and link them.	Option/Alt + Ctrl + M

9.5.6 Node Color Options

Icon	Behavior
Fill Color	Use Fill Color to change the background color of a table node. This is helpful if you want to identify a group of tables. Once set, all the newly added tables will take the same color.
Text Color	Use Text Color to change the text color of a table node based on the fill color to make text easily readable.


9.5.7 Utility Options

Icon	Behavior	Shortcut
Add/Edit note	Click this button to make notes on tables nodes while designing the database.	Option/Alt + Ctrl + N
Auto align	Click this button to auto-align all tables and links to make them look cleaner.	Option/Alt + Ctrl + L
Show details	Click this button to toggle the column details visibility. It allows you to show few or more column details.	Option/Alt + Shift + D
Cardinality Notation	Change the cardinality notation format used to present relationship links. Options available are - Crow's Foot Notation and Chen Notation.	

9.5.8 Zoom Options

Icon	Behavior	Shortcut
Zoom to fit	Click this button to zoom in/out automatically and fit all the tables to the view.	Option/Alt + Shift + F
Zoom in	Click this button to zoom in the diagram.	Option/Alt + Shift + "+"
Zoom out	Click this button to zoom out the diagram.	Option/Alt + Shift + "-"

9.5.9 Table Dialog




The table dialog allows you to:

- Change the table structure details.

- It can be used to edit an existing table or add a new one.
- Refer *table dialog* for information on different fields.


9.5.10 Table Node



The table node shows table details in a graphical representation:

- The top bar has a *details toggle button* that is used to toggle column details visibility. There is also a *note button* that is visible only if there is some note added. You can click on this button to quickly change the note.
- The first row shows the schema name of the table. Eg. *public* in above image.
- The second row shows the table name. Eg. *users* in above image.
- All other rows below the table name are the columns of the table along with data type. If the column is a primary key then it will have lock key icon eg. id is the primary key in above image. Otherwise, it will have column icon.
- You can click on the node and drag to move on the canvas.
- Upon double click on the table node or by clicking the edit button from the toolbar, the table dialog opens where you can change the table details. Refer *table dialog* for information on different fields.


9.5.11 The One to One Link Dialog



The one to one link dialog allows you to:

- Add a one to one relationship between two tables.
- *Local Table* is the table that references a table and has the *one* end point.
- *Local Column* the column that references.
- *Select Constraint* To implement a one-to-one relationship, the *Local Column* must have a primary key or unique constraint. The default is a unique constraint. Please note that this field is visible only when the selected *Local Column* does not have either of the mentioned constraints.
- *Referenced Table* is the table that is being referred and has the *one* end point.
- *Referenced Column* the column that is being referred.


9.5.12 The One to Many Link Dialog



The one to many link dialog allows you to:

- Add a foreign key relationship between two tables.
- *Local Table* is the table that references a table and has the *many* end point.
- *Local Column* the column that references.
- *Referenced Table* is the table that is being referred and has the *one* end point.
- *Referenced Column* the column that is being referred.

9.5.13 The Many to Many Link Dialog




The many to many link dialog allows you to:

- Add a many to many relationship between two tables.

- It creates a relationship tables having columns derived from the two tables and link them to the tables.
- *Left Table* is the first table that is to be linked. It will receive the *one* endpoint of the link with the new relation table.
- *Left Column* the column of the first table, that will always be a primary key.
- *Right Table* is the second table that is to be linked. It will receive the *one* endpoint of the link with the new relation table.
- *Right Column* the column of the second table, that will always be a primary key.

9.5.14 The Table Link




The table link shows relationship between tables:

- The single line endpoint of the link shows the column that is being referred.
- The three line endpoint of the link shows the column that refers.

- If one of the columns that is being referred or that refers is removed from the table then the link will get dropped.
- You can click on the link and drag to move on the canvas.

9.5.15 The Table Notes




- You can use the notes popup to mark some notes while designing the database.
- You open the pop-up using the toolbar note button.
- If some note is added to a table then it will have notes button on the table node. You can click on the button to check/update notes.

9.6 PSQL Tool

The PSQL tool allows users to connect to PostgreSQL or EDB Advanced server using the psql command line interface through their browser.

- Open the PSQL tool from the Tools or object explorer context menu, or use PSQL tool button at the top of the object explorer.
- PSQL will connect to the current connected database from the object explorer.



You can open multiple instances of the PSQL tool in individual tabs simultaneously. To close the PSQL tool, click the *X* in the upper-right hand corner of the tab bar.

Note: On the Windows platform, this feature is available on Windows 10 (1809 version), and Windows Server 2019 and onwards.


Note: The PSQL tool is always available when pgAdmin is running in Desktop mode, but is disabled by default in Server mode. This is because users can run arbitrary shell commands through psql which may be considered a security risk in some deployments. System Administrators can enable the use of the PSQL tool in the pgAdmin configuration by setting the *ENABLE_PSQL* option to *True*; see *Configuration Files* for more information.

9.6.1 PSQL Tool in Workspace Layout

The workspace layout offers a distraction-free, dedicated area for the PSQL Tool. When the PSQL Tool workspace is accessed, the Welcome page opens by default.

Note: In the Workspace layout, all PSQL tabs open within the PSQL Tool workspace.

In the classic UI, users must connect to a database server and navigate to the database node before using the PSQL Tool. However, with the introduction of the Workspace layout and Welcome page, users can seamlessly connect to any ad-hoc server, even if it is not registered in the Object Explorer.



- Select *Existing Server* from the dropdown to connect to a server already listed in the Object Explorer. It is optional.
- Provide the *Server Name* for ad-hoc servers.
- Specify the IP address of the server host, or the fully qualified domain name in the *Host name/address* field.
- Enter the listener port number of the server host in the *Port* field.
- Use the *Database* field to specify the name of the database to which the client will connect.
- Use the *User* field to specify the name of a user that will be used when authenticating with the server.
- Use the *Password* field to provide a password that will be supplied when authenticating with the server.
- Use the *Role* field to specify the name of a role that has privileges that will be conveyed to the client after authentication with the server.
- Use the *Service* field to specify the service name. For more information, see Section 33.16 of the Postgres documentation.
- Use the fields in the *Connection Parameters* to configure the connection parameters.

After filling in all the required fields, click the Connect & Open PSQL Tool button to launch the PSQL Tool with the provided server details. If the password is not supplied, you will be prompted to enter it.

9.7 AI Reports

AI Reports is a feature that provides AI-powered database analysis and insights using Large Language Models (LLMs). Use the *Tools* → *AI Reports* menu to access the various AI-powered reports.

The AI Reports feature allows you to:

- Generate security reports to identify potential security vulnerabilities and configuration issues.
- Create performance reports with optimization recommendations for queries and configurations.
- Perform design reviews to analyze database schema structure and suggest improvements.

Prerequisites:

Before using AI Reports, you must:


1. Ensure AI features are enabled in the server configuration (set `LLM_ENABLED` to `True` in `config.py`).
2. Configure an LLM provider in *Preferences* → *AI*.

Note:

- AI Reports using cloud providers (Anthropic, OpenAI) require an active internet connection. Local providers (Ollama, Docker Model Runner) do not require internet access.
- API usage may incur costs depending on your LLM provider's pricing model. Local providers (Ollama, Docker Model Runner) are free to use.
- The quality and accuracy of reports depend on the LLM provider and model configured.

9.7.1 Configuring AI Reports

To configure AI Reports, navigate to *File* → *Preferences* → *AI* (or click the *Settings* button and select *AI*).



Select your preferred LLM provider from the dropdown:

Anthropic
Use Claude models from Anthropic, or any Anthropic-compatible API provider.

- **API URL**: Custom API endpoint URL (leave empty for default: https://api.anthropic.com/v1).
- **API Key File**: Path to a file containing your Anthropic API key (obtain from https://console.anthropic.com/). This path refers to the filesystem where the pgAdmin server is running (e.g., inside the container if using Docker). The ~ prefix is expanded to the home directory of the user running the pgAdmin server process. Optional when using a custom URL with a provider that does not require authentication.
- **Model**: Select from available Claude models (e.g., claude-sonnet-4-20250514).

OpenAI
Use GPT models from OpenAI, or any OpenAI-compatible API provider (e.g., LiteLLM, LM Studio, EXO, hosted services such as GLM (Z.ai), or local inference servers).

- **API URL**: Custom API endpoint URL (leave empty for default: https://api.openai.com/v1). Include the `/v1` path prefix if required by your provider.
- **API Key File**: Path to a file containing your OpenAI API key (obtain from https://platform.openai.com/). This path refers to the filesystem where the pgAdmin server is running (e.g., inside the container if using Docker). The ~ prefix is expanded to the home directory of the user running the pgAdmin server process. Optional when using a custom URL with a provider that does not require authentication.
- **Model**: Select from available GPT models (e.g., gpt-4).

Ollama
Use locally-hosted open-source models via Ollama. Requires a running Ollama instance.

- **API URL**: The URL of your Ollama server (default: http://localhost:11434).
- **Model**: Enter the name of the Ollama model to use (e.g., llama2, mistral).

Docker Model Runner
Use models running in Docker Desktop's built-in model runner (available in Docker Desktop 4.40+). No API key is required.

- **API URL**: The URL of the Docker Model Runner API (default: http://localhost:12434).

- **Model**: Select from available models or enter a custom model name.

Note

You can also use the *OpenAI* provider with a custom API URL for any OpenAI-compatible endpoint, including Docker Model Runner and other local inference servers. pgAdmin sends `max_tokens` by default and learns to use `max_completion_tokens` when a server explicitly rejects it. When the `ALLOWED_LLM_API_URLS` configuration setting is non-empty, custom API URLs must match one of its entries; an empty list permits any URL.

After configuring your provider, click *Save* to apply the changes.

9.7.2 Data Handling and Provider Selection

When a cloud LLM provider is configured, pgAdmin transmits information about your database to that provider's API. Depending on the feature in use, this may include schema definitions such as table, column, index and constraint names and data types; server and database configuration settings read from `pg_settings`; query text; and EXPLAIN plan output. The *AI Assistant* in the Query Tool is also able to run queries against your database, within a read-only transaction and limited to 1000 rows, so row data may be included where the assistant determines it is needed to answer a question.

None of this is transmitted unless you invoke an AI feature, and none of it is transmitted at all when no provider has been configured, which is the default; when AI features have been disabled by the administrator through the `LLM_ENABLED` setting; or when a locally hosted provider such as Ollama or Docker Model Runner is configured.

Each provider processes this data under its own terms of service, privacy policy and legal jurisdiction, and operates its infrastructure in locations of its own choosing. If you work in an environment subject to data residency requirements, procurement policies, or sector-specific rules governing the handling of database metadata, review both the provider's terms and your own organisation's policies before enabling a cloud provider.


The providers listed in pgAdmin reflect the APIs that pgAdmin is able to communicate with. Their inclusion is not a recommendation, and no provider is enabled by default.

9.7.3 Security Reports

Security Reports analyze your PostgreSQL server, database, or schema for potential security vulnerabilities and configuration issues.

To generate a security report:

1. In the *Browser* tree, select a server, database, or schema.
2. Choose *Tools* → *AI Reports* → *Security* from the menu, or right-click the object and select *Security* from the context menu.
3. The report will be generated and displayed in a new tab.



Security Report Scope:

- **Server Level**: Analyzes server configuration, authentication settings, roles, and permissions.
- **Database Level**: Reviews database-specific security settings, roles with database access, and object permissions.
- **Schema Level**: Examines schema permissions, object ownership, and access controls.

Each report includes:

- **Security Findings**: Identified vulnerabilities or security concerns.
- **Risk Assessment**: Severity levels for each finding (Critical, High, Medium, Low).
- **Recommendations**: Specific actions to remediate security issues.
- **Best Practices**: General security recommendations for PostgreSQL.

9.7.4 Performance Reports

Performance Reports analyze query performance, configuration settings, and provide optimization recommendations.

To generate a performance report:

1. In the *Browser* tree, select a server or database.
2. Choose *Tools* → *AI Reports* → *Performance* from the menu, or right-click the object and select *Performance* from the context menu.
3. The report will be generated and displayed in a new tab.

Performance Report Scope:

- **Server Level**: Analyzes server configuration parameters, resource utilization, and overall server performance metrics.
- **Database Level**: Reviews database-specific configuration, query performance, index usage, and table statistics.

Each report includes:

- **Performance Metrics**: Key performance indicators and statistics.
- **Configuration Analysis**: Review of relevant configuration parameters.
- **Query Optimization**: Recommendations for improving slow queries.
- **Index Recommendations**: Suggestions for adding, removing, or modifying indexes.
- **Capacity Planning**: Resource utilization trends and recommendations.

9.7.5 Design Review Reports

Design Review Reports analyze your database schema structure and suggest improvements for normalization, naming conventions, and best practices.

To generate a design review report:

1. In the *Browser* tree, select a database or schema.
2. Choose *Tools* → *AI Reports* → *Design* from the menu, or right-click the object and select *Design* from the context menu.
3. The report will be generated and displayed in a new tab.

Design Review Scope:

- **Database Level**: Reviews overall database structure, schema organization, and cross-schema dependencies.
- **Schema Level**: Analyzes tables, views, functions, and other objects within the schema.

Each report includes:

- **Schema Structure Analysis**: Review of table structures, relationships, and constraints.
- **Normalization Review**: Recommendations for database normalization (1NF, 2NF, 3NF, etc.).
- **Naming Conventions**: Suggestions for consistent naming patterns.
- **Data Type Usage**: Review of data type choices and recommendations.
- **Index Design**: Analysis of indexing strategy.
- **Best Practices**: General PostgreSQL schema design recommendations.

9.7.6 Working with Reports

All AI reports are displayed in a dedicated panel with the following features:

Report Display
Reports are formatted as Markdown and rendered with syntax highlighting for SQL code.

Toolbar Actions

- **Stop** - Cancel the current report generation. This is useful if the report is taking too long or if you want to change parameters.
- **Regenerate** - Generate a new report for the same object. Useful when you want to get a fresh analysis or if data has changed.
- **Download** - Download the report as a Markdown (.md) file. The filename includes the report type, object name, and date for easy identification.

Multiple Reports
You can generate and view multiple reports simultaneously. Each report opens in a new tab, allowing you to compare reports across different servers, databases, or schemas.

Report Management
Each report tab can be closed individually by clicking the *X* in the tab. Panel titles show the object name and report type for easy identification.

Copying Content
You can select and copy text from reports to use in documentation or share with your team.

9.7.7 Troubleshooting

"AI features are disabled in the server configuration"
The administrator has disabled AI features on the server. Contact your pgAdmin administrator to enable the `LLM_ENABLED` configuration option.

"Please configure an LLM provider in Preferences"
You need to configure an LLM provider before using AI Reports. See *Configuring AI Reports* above.

"Please connect to the server/database first"
You must establish a connection to the server or database before generating reports.

API Connection Errors

- Verify your API key is correct (for Anthropic and OpenAI).
- Check your internet connection (for cloud providers).
- For Ollama, ensure the Ollama server is running and accessible.
- For Docker Model Runner, ensure Docker Desktop 4.40+ is running with the model runner enabled.
- Check that your firewall allows connections to the LLM provider's API.


Report Generation Fails

- Check the pgAdmin logs for detailed error messages.
- Verify the database connection is still active.
- Ensure the selected model is available for your account/subscription.

CHAPTER 10

Processes

There are certain tasks which pgAdmin runs in the background. The processes running in the background can be viewed in the processes tab. It shows the process details of Backup, Restore, Maintenance, Import/Export and Cloud instance creation.



The columns of the processes table shows:


- The *PID* of the forked OS process.
- The *Type* of the task being performed.
- The *Server* name for which the task is.
- The *Object* can be a database, table, mview or anything which gives more info.
- The *Start Time* of the process, sorted descending by default.
- The current *Status* of the process. It can be Running, Finished, Failed, Terminated.
- The *Time Taken* to complete. It will keep updating if it is running.

There are two action buttons on each row:

- The *Stop Process* button allows you to kill a running process.
- The *More details* button allows you to open the process watcher which shows the process logs and other details.

You can also select the checkboxes and click on *Delete and Acknowledge* button on the top to clear the process info and logs.

10.1 Process Watcher



The Process Watcher logs all the activity associated with the process/task and provides additional information for troubleshooting Use the **End Process** button to end the process.

Note

If you are running *pgAdmin* in *Server Mode* you can click on the  icon in the process watcher window to open the file location in the Storage Manager. You can use the *Storage Manager* to download the backup file on the client machine .

10.2 Watch the demo

https://youtu.be/jjP6O_xuHxE

CHAPTER 11

pgAgent

pgAgent is a job scheduling agent for Postgres databases, capable of running multi-step batch or shell scripts and SQL tasks on complex schedules.

pgAgent is distributed independently of pgAdmin. You can download pgAgent from the download area of the pgAdmin website.

11.1 Using pgAgent

pgAgent is a scheduling agent that runs and manages jobs; each job consists of one or more steps and schedules. If two or more jobs are scheduled to execute concurrently, pgAgent will execute the jobs in parallel (each with its own thread).

A step may be a series of SQL statements or an operating system batch/shell script. Each step in a given job is executed when the previous step completes, in alphanumeric order by name. Switches on the *pgAgent Job* dialog (accessed through the *Properties* context menu) allow you to modify a job, enabling or disabling individual steps as needed.

Each job is executed according to one or more schedules. Each time the job or any of its schedules are altered, the next runtime of the job is re-calculated. Each instance of pgAgent periodically polls the database for jobs with the next runtime value in the past. By polling at least once every minute, all jobs will normally start within one minute of the specified start time. If no pgAgent instance is running at the next runtime of a job, it will run as soon as pgAgent is next started, following which it will return to the normal schedule.

When you highlight the name of a defined job in the pgAdmin tree control, the *Properties* tab of the main pgAdmin window will display details about the job, and the *Statistics* tab will display details about the job's execution.

11.1.1 Security Concerns

pgAgent is a very powerful tool, but does have some security considerations that you should be aware of:

Database password - *DO NOT* be tempted to include a password in the pgAgent connection string - on Unix systems it may be visible to all users in *ps* output, and on Windows systems it will be stored in the registry in plain text. Instead, use a libpq *~/.pgpass* file to store the passwords for every database that pgAgent must access. Details of this technique may be found in the PostgreSQL documentation on .pgpass file.

System/database access - all jobs run by pgAgent will run with the security privileges of the pgAgent user. SQL steps will run as the user that pgAgent connects to the database as, and batch/shell scripts will run as the operating system user that the pgAgent service or daemon is running under. Because of this, it is essential to maintain control over the users that are able to create and modify jobs. By default, only the user that created the pgAgent database objects will be able to do this - this will normally be the PostgreSQL superuser.

11.2 Installing pgAgent

pgAgent runs as a daemon on Unix systems, and a service on Windows systems. In most cases it will run on the database server itself - for this reason, pgAgent is not automatically configured when pgAdmin is installed. In some cases however, it may be preferable to run pgAgent on multiple systems, against the same database; individual jobs may be targeted at a particular host, or left for execution by any host. Locking prevents execution of the same instance of a job by multiple hosts.

11.2.1 Database setup

Before using pgAdmin to manage pgAgent, you must create the pgAgent extension in the maintenance database registered with pgAdmin. To install pgAgent on a PostgreSQL host, connect to the *postgres* database, and navigate through the *Tools* menu to open the Query tool. For server versions 9.1 or later, and pgAgent 3.4.0 or later, enter the following command in the query window, and click the *Execute* icon:

```
CREATE EXTENSION pgagent;
```

This command will create a number of tables and other objects in a schema called 'pgagent'.

The database must also have the pl/pgsql procedural language installed - use the PostgreSQL CREATE LANGUAGE command to install pl/pgsql if necessary. To install pl/pgsql, enter the following command in the query window, and click the *Execute* icon:

```
CREATE LANGUAGE plpgsql;
```

11.2.2 Daemon installation on Unix

Note

pgAgent is available in Debian/Ubuntu (DEB) and Redhat/Fedora (RPM) packages for Linux users, as well as source code. See the pgAdmin Website. for more information.

To install the pgAgent daemon on a Unix system, you will normally need to have root privileges to modify the system startup scripts. Modifying system startup scripts is quite system-specific so you should consult your system documentation for further information.

The program itself takes few command line options, most of which are only needed for debugging or specialised configurations:

```
Usage:
  /path/to/pgagent [options] <connect-string>

options:
  -f run in the foreground (do not detach from the terminal)
  -t <poll time interval in seconds (default 10)>
  -r <retry period after connection abort in seconds (>=10, default 30)>
  -s <log file (messages are logged to STDOUT if not specified)>
  -l <logging verbosity (ERROR=0, WARNING=1, DEBUG=2, default 0)>
```

The connection string is a standard PostgreSQL libpq connection string (see the PostgreSQL documentation on the connection string for further details). For example, the following command line will run pgAgent against a server listening on the localhost, using a database called 'pgadmin', connecting as the user 'postgres':

```
/path/to/pgagent hostaddr=127.0.0.1 dbname=postgres user=postgres
```

11.2.3 Service installation on Windows

Note

pgAgent is available in a pre-built installer if you use EnterpriseDB's PostgreSQL Installers. Use the StackBuilder application to download and install it. If installed in this way, the service will automatically be created and the instructions below can be ignored.

pgAgent can install itself as a service on Windows systems. The command line options available are similar to those on Unix systems, but include an additional parameter to tell the service what to do:

```
Usage:
  pgAgent REMOVE <serviceName>
  pgAgent INSTALL <serviceName> [options] <connect-string>
  pgAgent DEBUG [options] <connect-string>

  options:
    -u <user or DOMAIN\user>
    -p <password>
    -d <displayname>
    -t <poll time interval in seconds (default 10)>
    -r <retry period after connection abort in seconds (>=10, default 30)>
    -l <logging verbosity (ERROR=0, WARNING=1, DEBUG=2, default 0)>
```

The service may be quite simply installed from the command line as follows (adjust the path as required):

```
"C:\Program Files\pgAgent\bin\pgAgent" INSTALL pgAgent -u postgres -p secret␣
↪hostaddr=127.0.0.1 dbname=postgres user=postgres
```


You can then start the service at the command line using *net start pgAgent*, or from the *Services* control panel applet. Any logging output or errors will be reported in the Application event log. The DEBUG mode may be used to run pgAgent from a command prompt. When run this way, log messages will output to the command window.

11.3 Creating a pgAgent Job

pgAgent is a scheduling agent that runs and manages jobs; each job consists of steps and schedules.

To create or manage a job, use the pgAdmin tree control to browse to the server on which the pgAgent database objects were created. The tree control will display a *pgAgent Jobs* node, under which currently defined jobs are displayed. To add a new job, right click on the *pgAgent Jobs* node, and select *Create pgAgent Job...* from the context menu.

When the pgAgent dialog opens, use the tabs on the *pgAgent Job* dialog to define the steps and schedule that make up a pgAgent job.



Use the fields on the *General* tab to provide general information about a job:


- Provide a name for the job in the *Name* field.
- Move the *Enabled* switch to the *Yes* position to enable a job, or *No* to disable a job.
- Use the *Job Class* drop-down to select a class (for job categorization).
- Use the *Host Agent* field to specify the name of a machine that is running pgAgent to indicate that only that machine may execute the job. Leave the field blank to specify that any machine may perform the job.

> **Note**
>
> It is not always obvious what value to specify for the Host Agent in order to target a job step to a specific machine. With pgAgent running on the required machines and connected to the scheduler database, you can use the following query to view the hostnames as reported by each agent:


```
SELECT jagstation FROM pgagent.pga_jobagent
```

Use the hostname exactly as reported by the query in the Host Agent field.

- Use the *Comment* field to store notes about the job.



Use the *Steps* tab to define and manage the steps that the job will perform. Click the Add icon (+) to add a new step; then click the compose icon (located at the left side of the header) to open the step definition dialog:




Use fields on the step definition dialog to define the step:

- Provide a name for the step in the *Name* field; please note that steps will be performed in alphanumeric order by name.
- Use the *Enabled* switch to include the step when executing the job (*True*) or to disable the step (*False*).
- Use the *Kind* switch to indicate if the job step invokes SQL code (*SQL*) or a batch script (*Batch*).
  - If you select *SQL*, use the *Code* tab to provide SQL code for the step.
  - If you select *Batch*, use the *Code* tab to provide the batch script that will be executed during the step.

Note

The fields *Connection type*, *Database* and *Connection string* are only applicable when *SQL* is selected because *Batch* cannot be run on remote servers.

- Use the *Connection type* switch to indicate if the step is performed on a local server (*Local*) or on a remote host (*Remote*). If you specify a remote connection should be used for the step, the *Connection string* field will be enabled, and you must provide a libpq-style connection string.
- Use the *Database* drop-down to select the database on which the job step will be performed.
- Use the *Connection string* field to specify a libpq-style connection string to the remote server on which the step will be performed. For more information about writing a connection string, please see the PostgreSQL documentation.
- Use the *On error* drop-down to specify the behavior of pgAgent if it encounters an error while executing the step. Select from:
  - *Fail* - Stop the job if you encounter an error while processing this step.
  - *Success* - Mark the step as completing successfully, and continue.
  - *Ignore* - Ignore the error, and continue.
- Use the *Comment* field to provide a comment about the step.




Use the context-sensitive field on the step definition dialog's *Code* tab to provide the SQL code or batch script that will be executed during the step:


- If the step invokes SQL code, provide one or more SQL statements in the *SQL query* field.
- If the step performs a batch script, provide the script in the *Script* field. If you are running on a Windows server, standard batch file syntax must be used. When running on a Linux server, any shell script may be used, provided

that a suitable interpreter is specified on the first line (e.g. *#!/bin/sh*).

When you've provided all of the information required by the step, click the compose icon to close the step definition dialog. Click the add icon (+) to add each additional step, or select the *Schedules* tab to define the job schedule.




Click the Add icon (+) to add a schedule for the job; then click the compose icon (located at the left side of the header) to open the schedule definition dialog:



Use the fields on the schedule definition tab to specify the days and times at which the job will execute.

- Provide a name for the schedule in the *Name* field.
- Use the *Enabled* switch to indicate that pgAgent should use the schedule (*Yes*) or to disable the schedule (*No*).
- Use the calendar selector in the *Start* field to specify the starting date and time for the schedule.
- Use the calendar selector in the *End* field to specify the ending date and time for the schedule.
- Use the *Comment* field to provide a comment about the schedule.

Select the *Repeat* tab to define the days on which the schedule will execute.



Use the fields on the *Repeat* tab to specify the details about the schedule in a cron-style format. The job will execute on each date or time element selected on the *Repeat* tab.

Click within a field to open a list of valid values for that field; click on a specific value to add that value to the list of selected values for the field. To clear the values from a field, click the X located at the right-side of the field.


Use the fields within the *Days* box to specify the days on which the job will execute:

- Use the *Week Days* field to select the days on which the job will execute.
- Use the *Month Days* field to select the numeric days on which the job will execute. Specify the *Last Day* to indicate that the job should be performed on the last day of the month, irregardless of the date.
- Use the *Months* field to select the months in which the job will execute.

Use the fields within the *Times* box to specify the times at which the job will execute:

- Use the *Hours* field to select the hour at which the job will execute.
- Use the *Minutes* field to select the minute at which the job will execute.

Select the *Exceptions* tab to specify any days on which the schedule will *not* execute.




Use the fields on the *Exceptions* tab to specify days on which you wish the job to not execute; for example, you may wish for jobs to not execute on national holidays.

Click the Add icon (+) to add a row to the exception table, then:


- Click within the *Date* column to open a calendar selector, and select a date on which the job will not execute. Specify <*Any*> in the *Date* column to indicate that the job should not execute on any day at the time selected.
- Click within the *Time* column to open a time selector, and specify a time on which the job will not execute. Specify <*Any*> in the *Time* column to indicate that the job should not execute at any time on the day selected.

When you've finished defining the schedule, you can use the *SQL* tab to review the code that will create or modify your job.



Click the *Save* button to save the job definition, or *Close* to exit the job without saving. Use the *Reset* button to remove your unsaved entries from the dialog.

After saving a job, the job will be listed under the *pgAgent Jobs* node of the pgAdmin tree control of the server on which it was defined. The *Properties* tab in the main pgAdmin window will display a high-level overview of the selected job, and the *Statistics* tab will show the details of each run of the job.



To modify an existing job or to review detailed information about a job, right-click on a job name, and select *Properties* from the context menu.

CHAPTER 12

pgTimeTable Chains

pg_timetable is a PostgreSQL-based scheduling agent that runs and manages what are called *Chains*. Each chain is composed of a set of Tasks to be executed in the order they should run. A chain is assigned a single schedule using an extended cron-style format. This UI has been tested with pg_timetable 6.3.0 and above.

A task may be a series of *SQL* statements, a *BUILTIN* pg_timetable command (such as sending email) or an operating system *PROGRAM* program/batch/shell script.

Switches on the *pgTimeTable Chain* dialog (accessed through the *Properties* context menu) allow you to modify a chain or disable the whole chain, as well as modify tasks within the chain.

When you highlight the name of a defined chain in the pgAdmin tree control, the *Properties* tab of the main pgAdmin window will display details about the chain, and the *Statistics* tab will display details about the chain's execution. There are also statistics about each task.

pg_timetable supports the ability to have more than one job agent running at a time. Job agents can be deployed on various platforms and binaries are readily available to deploy on Linux, Windows, and Mac.

For complete installation instructions, configuration options, and command-line usage, please refer to the pg_timetable documentation.

If you are migrating from pgAgent or another PostgreSQL based scheduler, pg_timetable provides migration SQL queries to help in that migration. See the migration tools on GitHub for details.

12.1 Viewing pgTimeTable


To enable viewing of the *pgTimeTable Chains* node, enable it on the File -> Preferences -> Nodes. It will only show if the schema *timetable* and associated tables exist in your maintenance database.

12.2 Creating a Chain

Note that pg_timetable is not installed via *CREATE EXTENSION*. Instead you use a pgTimeTable agent to install the necessary tables. To create or manage a chain, use the pgAdmin tree control to browse to the server on which the timetable schema exists. The tree control will display a *pgTimeTable Chains* node, under which currently defined chains are displayed.

To add a new chain, right click on the *pgTimeTable Chains* node, and select *Create pgTimeTable Chain...* from the context menu.

When the chain dialog opens, use the tabs on the dialog to define the chain and its tasks.



Use the fields on the *General* tab to provide general information about the chain:

- Provide a name for the chain in the *Name* field.
- Move the *Enabled* switch to the *Yes* position to enable the chain, or *No* to disable it.

- Use the *Max instances* field to specify the number of parallel instances (clients) that may execute this chain simultaneously. Leave the field blank to allow unlimited parallel execution.
- Use the *Timeout (ms)* field to specify the maximum number of milliseconds the chain may run before it is aborted. A value of *0* means no timeout.
- Move the *Self-destruct* switch to *Yes* to have the chain delete itself after a successful run.
- Move the *Exclusive execution* switch to *Yes* to pause all other parallel chains while this chain is executing.
- Use the *Host agent* field to specify the client name of the agent running pgTimeTable that should execute this chain. Leave the field blank to allow any available host to run the chain.

> **Note**
>
> You can query the `timetable.active_session` view to see the client names reported by running pgTimeTable agents:
>
> ```
> SELECT DISTINCT client_name FROM timetable.active_session
> ```
>
> Use the client name exactly as reported by the query in the *Host agent* field.


- Use the *On error* field to specify the behavior when an error occurs. Accepted values are:
  - *NULL* - Use the default error handling.
  - *LOG* - Log the error and continue execution.
  - *ABORT* - Abort the chain on error.
- Use the *Schedule* field to specify a cron-style schedule for the chain. The format consists of a single field with 5 slots. As with regular cron, you can use a comma (,) for multiple values and an asterisk (*) as a wildcard for all. E.g. *20 1,5 * * *** would run at 1:20 and 5:20 AM. The timezone is always the timezone of the server the pgTimeTable database resides on.

```
* * * * *
| | | | |
| | | | +---- day of the week (0 - 7) (0 and 7 = Sunday)
| | | +------ month (1 - 12)
| | +-------- day of the month (1 - 31)
| +---------- hour (0 - 23)
+------------ minute (0 - 59)
```

  If you leave the field blank it runs every minute (the effective schedule is * * * * *).

In addition to cron syntax, pgTimeTable supports additional special case formats. Namely *@after*, *@every*, *@reboot*.

The *@every* and *@after* should be followed with additional arguments. For example *@every 2 hours*.




Use the *Tasks* tab to define and manage the tasks that the chain will execute. Click the Add icon (+) to add a new task. Tasks are executed in order of their *Order* value.

Click the compose icon (located at the left side of the header) to open the task definition dialog. See *Chain Task Dialog* below for details on defining a task.

When you have finished defining the chain, you can use the *SQL* tab to review the SQL that will create or modify your chain.

Click the *Save* button to save the chain, or *Close* to exit without saving. Use the *Reset* button to remove your unsaved entries from the dialog.


After saving a chain, the chain will be listed under the *pgTimeTable Chains* node of the pgAdmin tree control. The *Properties* tab in the main pgAdmin window will display a high-level overview of the selected chain, and the *Statistics* tab will show the details of each execution run.



To modify an existing chain or to review detailed information about a chain, right-click on a chain name, and select *Properties* from the context menu.

12.3 Chain Task Dialog

A chain task defines a single unit of work to be performed as part of a chain. Each chain can contain one or more tasks, which are executed sequentially in order.




Use the fields on the *General* tab to define the task:

- Provide a name for the task in the *Name* field.
- Use the *Order* field to specify the execution order of the task within the chain. Tasks are executed in ascending order by this value.
- Use the *Kind* drop-down to select the type of task:
  - *SQL* - The task executes SQL statements.
  - *PROGRAM* - The task executes an operating system command.
  - *BUILTIN* - The task executes one of the built-in pgTimeTable commands.
- When *Kind* is set to *SQL*, use the *Connection string* field to optionally specify a libpq-style connection string for a remote database. Leave the field blank to execute against the pgTimeTable database.

  Note


  The *Connection string* field is only available when the pgTimeTable extension version supports it (version 5.x or later). It is ignored for *PROGRAM* and *BUILTIN* task kinds.

- Move the *Ignore error* switch to *Yes* to continue chain execution even if this task fails. Set to *No* to stop the chain when an error occurs.



Use the *Code* tab to provide the code or command for the task. The content of the *Code* tab depends on the selected *Kind*:

- If *Kind* is *SQL*, provide one or more SQL statements in the *SQL* field. Use `$1`, `$2`, etc. as parameter placeholders that will be substituted from the *Parameters* collection.
- If *Kind* is *PROGRAM*, provide the full path and arguments of the program to execute in the *Program* field.
- If *Kind* is *BUILTIN*, select one of the following internal commands from the *Internal Command* drop-down:
  - *NoOp* - No operation; the task completes immediately.
  - *Sleep* - Pause execution for a duration specified by a parameter.
  - *Log* - Write a message to the pgTimeTable log.
  - *SendMail* - Send an email (requires parameters for recipient, subject, and body).
  - *Download* - Download a file from a URL.
  - *CopyFromFile* - Copy data from a file into a database table.
  - *CopyToFile* - Copy data from a database table to a file.
  - *Shutdown* - Shut down the pgTimeTable service.




Use the *Parameters* sub-collection to define parameter values that will be substituted into the task command. Click the Add icon (+) to add a new parameter row:

- Use the *Order* column to specify the parameter position (`$1`, `$2`, etc.).
- Use the *Value* column to provide the parameter value. The value may be a plain string or a JSON value.

Click the compose icon to close the task definition dialog, then click *Save* on the chain dialog to save all changes.

Refer to pg_timetable samples for the kind of parameters expected for each type.

Both the Chain and Tasks have a statistics tab, which show the results of past runs of tasks.



CHAPTER 13

pgAdmin Project Contributions

pgAdmin is an open-source project that invites you to get involved in the development process. For more information about contributing to the pgAdmin project, contact the developers on the pgAdmin mailing list pgadmin-hackers@postgresql.org to discuss any ideas you might have for enhancements or bug fixes.

In the following sections, you'll find detailed information about the development process used to develop, improve, and maintain the pgAdmin client.

13.1 Submitting Pull Requests

Before developing a feature or bug fix for pgAdmin you should always contact the developers on the mailing list pgadmin-hackers@postgresql.org to discuss your plans. This ensures that others know what you are doing and can then avoid duplicating your work, and in the case of large changes, gives the community the chance to discuss and refine your ideas before investing too much time writing code that may later be rejected.

You should always develop changes against a checkout of the source code from the GIT source code repository, and not a release tarball. This ensures that you're working with the latest code on the branch and makes it easier to generate Pull Requests correctly.

As of September 2022, the pgAdmin source repository can found at https://github.com/pgadmin-org/pgadmin4. A typical workflow for a relatively simple change might look as follows:

1. Visit the pgAdmin 4 project on GitHub, and click the *Fork* button to create your own development repository in your GitHub account.
2. Checkout a local copy of the source code with a command like:

```
$ git clone https://github.com/<your GitHub username>/pgadmin4.git
```

3. Develop and test your change in your local development environment.
4. Review your changes and check them thoroughly to ensure they meet the pgAdmin *Coding Standards*, and review them against the *Code Review Notes* to minimise the chances of them being rejected.

5. Once you're happy with your change, commit it with a suitable message. Include a one-line summary at the top, and if appropriate, further paragraphs following a blank line after the summary.
6. Push your changes to your fork of the repository.
7. Back in GitHub, create a new Pull Request against the *pgadmin-org/pgadmin4 master* branch.

   Note

   Each Pull Request should encompass a single bug fix or feature as a single commit. If necessary, you should squash multiple commits for larger changes or features into a single commit before submitting.

8. Your Pull Request will be reviewed by one or more members of the development team and either accepted or sent back with requested changes. In some cases it may be rejected if the change is not considered appropriate - this is why it's important to discuss your work with the team before spending any significant time on it.

For more complex changes, you may wish to use a *Feature Branch* in your fork of the pgAdmin repository, and use that to create the Pull Request.

Note

This is a simple example of a workflow. You may choose to use other tools such as the GitHub CLI instead; documenting such tools and workflows is outside the scope of the pgAdmin documentation however.

13.2 Code Overview

The bulk of pgAdmin is a Python web application written using the Flask framework on the backend, and HTML5 with CSS3,ReactJS on the front end. A desktop runtime is also included for users that prefer a desktop application to a web application, which is written using Electron.

13.2.1 Runtime

The runtime is based on Electron which integrates a browser and the Python server creating a standalone application. The source code can be found in the **/runtime** directory in the source tree.

13.2.2 Web Application

The web application forms the bulk of pgAdmin and can be found in the **/web** directory in the source tree. The main file is **pgAdmin4.py** which can be used to run the built-in standalone web server, or as a WSGI application for production use.

Configuration

The core application configuration is found in **config.py**. This file includes all configurable settings for the application, along with descriptions of their use. It is essential that various settings are configured prior to deployment on a web server; these can be overridden in **config_local.py** or **config_system.py** (see the *config.py* documentation) to avoid modifying the main configuration file.

User Settings

When running in desktop mode, pgAdmin has a single, default user account that is used for the desktop user. When running in server mode, there may be unlimited users who are required to login prior to using the application. pgAdmin utilised the **Flask-Security** module to manage application security and users, and provides options for self-service password reset and password changes etc.

Whether in desktop or server mode, each user's settings are stored in a SQLite OR external database which is also used to store the user accounts. This is initially created using the **setup.py** script which will create the database file and schema within it, and add the first user account (with administrative privileges) and a default server group for them. A **settings** table is also used to store user configuration settings in a key-value fashion. Although not required, setting keys (or names) are typically formatted using forward slashes to artificially namespace values, much like the pgAdmin 3 settings files on Linux or Mac.

Note that the local configuration must be setup prior to **setup.py** being run. The local configuration will determine how the script sets up the database, particularly with regard to desktop vs. server mode.

13.2.3 pgAdmin Core

The heart of pgAdmin is the **pgadmin** package. This contains the globally available HTML templates used by the Jinja engine, as well as any global static files such as images, Javascript and CSS files that are used in multiple modules.

The work of the package is handled in it's constructor, **__init__.py**. This is responsible for setting up logging and authentication, dynamically loading other modules, and a few other tasks.

13.2.4 Modules

Units of functionality are added to pgAdmin through the addition of modules. Theses are Python object instance of classes, inherits the PgAdminModule class (a Flask Blueprint implementation), found in **web/pgadmin/utils.py**. It provide various hook points for other modules to utilise (primarily the default module - the browser).

To be recognised as a module, a Python package must be created. This must:

1) Be placed within the **web/pgadmin/** directory, and

2) Implements pgadmin.utils.PgAdminModule class

3) An instance variable (generally - named **blueprint**) representing that particular class in that package.

Each module may define a **template** and **static** directory for the Blueprint that it implements. To avoid name collisions, templates should be stored under a directory within the specified template directory, named after the module itself. For example, the **browser** module stores it's templates in **web/pgadmin/browser/templates/browser/**. This does not apply to static files which may omit the second module name.

In addition to defining the Blueprint, the **views** module is typically responsible for defining all the views that will be rendered in response to client requests, we must provide a REST API url(s) for these views. These must include appropriate route and security decorators. Take a look at the NodeView class, which uses the same approach as Flask's MethodView, it can be found in **web/pgadmin/browser/utils.py**. This specific class is used by browser nodes for creating REST API url(s) for different operation on them. i.e. list, create, update, delete, fetch children, get statistics/reversed

SQL/dependencies/dependents list for that node, etc. We can use the same class for other purpose too. You just need to inherit that class, and overload the member variables operations, parent_ids, ids, node_type, and then register it as node view with PgAdminModule instance.

Most pgAdmin modules will also implement the **hooks** provided by the PgAdminModule class. This is responsible for providing hook points to integrate the module into the rest of the application - for example, a hook might tell the caller what CSS files need to be included on the rendered page, or what menu options to include and what they should do. Hook points need not exist if they are not required. It is the responsibility of the caller to ensure they are present before attempting to utilise them.

Hooks currently implemented are:

```
class MyModule(PgAdminModule):
    """
    This is class implements the pgadmin.utils.PgAdminModule, and
    implements the hooks
    """


    ...

    def get_own_stylesheets(self):
        """
        Returns:
            list: the stylesheets used by this module, not including any
                  stylesheet needed by the submodules.
        """
        return [url_for('static', 'css/mymodule.css')]

    def get_own_javascripts(self):
        """
        Returns:
            list of dict:
            - contains the name (representation for this javascript
              module), path (url for it without .js suffix), deps (array of
              dependents), exports window object by the javascript module,
              and when (would you like to load this javascript), etc
              information for this module, not including any script needed
              by submodules.
        """
        return [
            {
                'name': 'pgadmin.extension.mymodule',
                'path': url_for('static', filename='js/mymodule'),
                'exports': None,
                'when': 'server'
                }
            ]

    def get_own_menuitems(self):
        """
        Returns:
            dict: the menuitems for this module, not including
                  any needed from the submodules.
        """
```

(continues on next page)

(continued from previous page)

```
        return {
            'help_items': [
                MenuItem(
                    name='mnu_mymodule_help',
                    priority=999,
                    # We need to create javascript, which registers itself
                    # as module
                    module="pgAdmin.MyModule",
                    callback='about_show',
                    icon='fa fa-info-circle',
                    label=gettext('About MyModule'
                    )
                ]
            }
    def get_panels(self):
        """
        Returns:
            list: a list of panel objects to add implemented in javascript
                  module
        """
        return []
    ...



blueprint = MyModule('mymodule', __name__, static_url_path='/static')
```

pgAdmin Modules may include any additional Python modules that are required to fulfill their purpose, as required. They may also reference other dynamically loaded modules, but must use the defined hook points and fail gracefully in the event that a particular module is not present.

13.2.5 Nodes

Nodes are very similar to modules, it represents an individual node or, collection object on the object explorer treeview. To recognised as a node module, a Python package (along with javascript modules) must be created. This must:

1) Be placed within the **web/pgadmin/browser/** directory, and

2) Implements the BrowserPluginModule, and registers the node view, which exposes required the REST APIs

3) An instance of the class object

13.2.6 Front End

pgAdmin uses javascript extensively for the front-end implementation. It uses require.js to allow the lazy loading (or, say load only when required), ReactJS with CSS and MaterialUI for UI look and feel. We have divided each module in small chunks as much as possible. Not all javascript modules are required to be loaded (i.e. loading a javascript module for database will make sense only when a server node is loaded completely.) Please look at the javascript files node.js, browser.js, menu.js, panel.js, etc for better understanding of the code.

13.3 Coding Standards

pgAdmin uses multiple technologies and multiple languages, each of which have their own coding standards.

13.3.1 General

In all languages, indentations should be made with 4 spaces, and excessively long lines wrapped where appropriate to ensure they can be read on smaller displays (80 characters is used in many places, but this is not a required maximum size as it's quite wasteful on modern displays). Typically lines should not be longer than 120 characters.

Comments should be included in all code where required to explain its purpose or how it works if not obvious from a quick review of the code itself.

13.3.2 CSS 3

CSS3 is used for styling and layout throughout the application.

Most custom styling comes from individual modules which may advertise static stylesheets to be included in the module that is loading them via hooks.

Styling overrides (for example, to alter the look and feel) will typically be found in the **overrides.css** file in the main static file directory for the application.

Styling should never be applied inline in HTML, always through an external stylesheet, which should contain comments as appropriate to explain the usage or purpose for the style.

Styles should be specified clearly, one per line. For example:

```
/* iFrames should have no border */
iframe {
    border-width: 0;
}

/* Ensure the codemirror editor displays full height gutters when resized */
.CodeMirror, .CodeMirror-gutters {
    height: 100% !important;
}
```

All stylesheets must be CSS3 compliant.

13.3.3 HTML 5

HTML 5 is used for page structure throughout the application, in most cases being rendered from templates by the Jinja2 template engine in Flask.

All HTML must be HTML 5 compliant.

13.3.4 Javascript

Client-side code is written in Javascript using ReactJS and various plugins. Whilst much of the code is rendered from static files, there is also code that is rendered from templates using Jinja2 (often to inject the users settings) or constructed on the fly from module hooks.

A typical Javascript function might be formatted like this (this snipped is from a template):

```
// Delete a server group
function delete_server_group(item) {
    alertify.confirm(
        'Delete server group?',
        'Are you sure you wish to delete the server group "{0}"?'.replace('{0}', tree.
↪getLabel(item)),
        function() {
            var id = tree.getId(item)
            $.post("{{ url_for('NODE-server-group.delete') }}", { id: id })
                .done(function(data) {
                    if (data.success == 0) {
                        report_error(data.errormsg, data.info);
                    } else {
                        var next = tree.next(item);
                        var prev = tree.prev(item);
                        tree.remove(item);
                        if (next.length) {
                            tree.select(next);
                        } else if (prev.length) {
                            tree.select(prev);
                        }
                    }
                }
            )
        },
        null
    )
}
```

Note the use of a descriptive function name, using the underscore character to separate words in all lower case, and short but descriptive lower case variable names.

Note

From version 3.0 onwards, new or refactored code should be written using ES6 features and conventions.

13.3.5 Python

Python is used for the backend web server. All code must be compatible with Python 2.7 and should include PyDoc comments whilst following the official Python coding standards defined in PEP 8. An example function along with the required file header is shown below:

```
##########################################################################
#
# pgAdmin 4 - PostgreSQL Tools
#
# Copyright (C) 2013 - 2026, The pgAdmin Development Team
# This software is released under the PostgreSQL Licence
#
##########################################################################

"""Integration hooks for server groups."""

from flask import render_template, url_for
from flask.ext.security import current_user

from pgadmin.settings.settings_model import db, ServerGroup

def get_nodes():
    """Return a JSON document listing the server groups for the user"""
    groups = ServerGroup.query.filter_by(user_id=current_user.id)

    value = ''
    for group in groups:
        value += '{"id":%d,"label":"%s","icon":"icon-server-group","inode":true},' \
                 % (group.id, group.name)

    value = value[:-1]

    return value
```

13.4 Code Snippets

This document contains code for some of the important classes, listed as below:

- *PgAdminModule*
- *NodeView*
- *BaseDriver*
- *BaseConnection*

13.4.1 PgAdminModule

PgAdminModule is inherited from Flask.Blueprint module. This module defines a set of methods, properties and attributes, that every module should implement.

```
class PgAdminModule(Blueprint):
    """
    Base class for every PgAdmin Module.

    This class defines a set of method and attributes that
    every module should implement.
    """

    def __init__(self, name, import_name, **kwargs):
        kwargs.setdefault('url_prefix', '/' + name)
        kwargs.setdefault('template_folder', 'templates')
        kwargs.setdefault('static_folder', 'static')
        self.submodules = []
        self.parentmodules = []

        super().__init__(name, import_name, **kwargs)

    def register_preferences(self):
        # To be implemented by child classes
        pass

    def register(self, app, options):
        """
        Override the default register function to automagically register
        sub-modules at once.
        """

        # Sub-classes populate self.submodules from their own register(),
        # but the blueprint objects themselves are module level singletons,
        # so registering one against a second application instance (which
        # happens whenever more than one app is created in a single
        # process, as the regression suite does) would otherwise leave a
        # duplicate entry behind for every sub-module. Anything that walks
        # self.submodules then does its work once per duplicate; in Schema
        # Diff's case that means generating the same DDL several times
        # over.
        self.submodules = list(dict.fromkeys(self.submodules))

        super().register(app, options)

        def create_module_preference():
            # Create preference for each module by default
            if hasattr(self, 'LABEL'):
                self.preference = Preferences(self.name, self.LABEL)
            else:
                self.preference = Preferences(self.name, None)

            self.register_preferences()
```

(continues on next page)

(continued from previous page)

```
        # Create and register the module preference object and preferences for
        # it just before starting app
        app.register_before_app_start(create_module_preference)

        for module in self.submodules:
            if self not in module.parentmodules:
                module.parentmodules.append(self)
            if app.blueprints.get(module.name) is None:
                app.register_blueprint(module)
                app.register_logout_hook(module)

    def get_own_messages(self):
        """
        Returns:
            dict: the i18n messages used by this module, not including any
                messages needed by the submodules.
        """
        return dict()

    def get_own_menuitems(self):
        """
        Returns:
            dict: the menuitems for this module, not including
                any needed from the submodules.
        """
        return defaultdict(list)

    def get_exposed_url_endpoints(self):
        """
        Returns:
            list: a list of url endpoints exposed to the client.
        """
        return []

    @property
    def messages(self):
        res = self.get_own_messages()

        for module in self.submodules:
            res.update(module.messages)
        return res

    @property
    def menu_items(self):
        menu_items = self.get_own_menuitems()
        for module in self.submodules:
            for key, value in module.menu_items.items():
                menu_items[key].extend(value)
        menu_items = dict((key, sorted(value, key=attrgetter('priority')))
                          for key, value in menu_items.items())
        return menu_items
```

(continues on next page)

(continued from previous page)

```
    @property
    def exposed_endpoints(self):
        res = self.get_exposed_url_endpoints()

        for module in self.submodules:
            res += module.exposed_endpoints

        return res
```

13.4.2 NodeView

The NodeView class exposes basic REST APIs for different operations used by the pgAdmin Browser. The basic idea has been taken from Flask's MethodView class. Because we need a lot more operations (not, just CRUD), we can not use it directly.

```
class NodeView(View, metaclass=type(MethodView)):
    """
    A PostgreSQL Object has so many operaions/functions apart from CRUD
    (Create, Read, Update, Delete):
    i.e.
    - Reversed Engineered SQL
    - Modified Query for parameter while editing object attributes
      i.e. ALTER TABLE ...
    - Statistics of the objects
    - List of dependents
    - List of dependencies
    - Listing of the children object types for the certain node
      It will used by the browser tree to get the children nodes

    This class can be inherited to achieve the diffrent routes for each of the
    object types/collections.

       OPERATION   |             URL              | HTTP Method |    Method
    ---------------+------------------------------+-------------+--------------
    List           | /obj/[Parent URL]/           | GET         | list
    Properties     | /obj/[Parent URL]/id         | GET         | properties
    Create         | /obj/[Parent URL]/           | POST        | create
    Delete         | /obj/[Parent URL]/id         | DELETE      | delete
    Update         | /obj/[Parent URL]/id         | PUT         | update

    SQL (Reversed  | /sql/[Parent URL]/id         | GET         | sql
    Engineering)   |
    SQL (Modified  | /msql/[Parent URL]/id        | GET         | modified_sql
    Properties)    |

    Statistics     | /stats/[Parent URL]/id       | GET         | statistics
    Dependencies   | /dependency/[Parent URL]/id  | GET         | dependencies
    Dependents     | /dependent/[Parent URL]/id   | GET         | dependents

    Nodes          | /nodes/[Parent URL]/         | GET         | nodes
```

(continues on next page)

(continued from previous page)

```
    Current Node    | /nodes/[Parent URL]/id      | GET         | node

    Children        | /children/[Parent URL]/id   | GET         | children

    NOTE:
    Parent URL can be seen as the path to identify the particular node.

    i.e.
    In order to identify the TABLE object, we need server -> database -> schema
    information.
    """
    operations = dict({
        'obj': [
            {'get': 'properties', 'delete': 'delete', 'put': 'update'},
            {'get': 'list', 'post': 'create'}
        ],
        'nodes': [{'get': 'node'}, {'get': 'nodes'}],
        'sql': [{'get': 'sql'}],
        'msql': [{'get': 'modified_sql'}],
        'stats': [{'get': 'statistics'}],
        'dependency': [{'get': 'dependencies'}],
        'dependent': [{'get': 'dependents'}],
        'children': [{'get': 'children'}]
    })

    @classmethod
    def generate_ops(cls):
        cmds = []
        for op in cls.operations:
            idx = 0
            for ops in cls.operations[op]:
                meths = []
                for meth in ops:
                    meths.append(meth.upper())
                if len(meths) > 0:
                    cmds.append({
                        'cmd': op, 'req': (idx == 0),
                        'with_id': (idx != 2), 'methods': meths
                    })
                idx += 1
        return cmds

    # Inherited class needs to modify these parameters
    node_type = None
    # Inherited class needs to modify these parameters
    node_label = None
    # This must be an array object with attributes (type and id)
    parent_ids = []
    # This must be an array object with attributes (type and id)
    ids = []

    @classmethod
```

(continues on next page)

(continued from previous page)

```
    def get_node_urls(cls):
        assert cls.node_type is not None, \
            "Please set the node_type for this class ({0})".format(
                str(cls.__class__.__name__))
        common_url = '/'
        for p in cls.parent_ids:
            common_url += '<{0}:{1}>/'.format(str(p['type']), str(p['id']))

        id_url = None
        for p in cls.ids:
            id_url = '{0}<{1}:{2}>'.format(
                common_url if not id_url else id_url,
                p['type'], p['id'])

        return id_url, common_url

    def __init__(self, **kwargs):
        self.cmd = kwargs['cmd']

    # Check the existance of all the required arguments from parent_ids
    # and return combination of has parent arguments, and has id arguments
    def check_args(self, **kwargs):
        has_id = has_args = True
        for p in self.parent_ids:
            if p['id'] not in kwargs:
                has_args = False
                break

        for p in self.ids:
            if p['id'] not in kwargs:
                has_id = False
                break

        return has_args, has_id and has_args

    def dispatch_request(self, *args, **kwargs):
        http_method = flask.request.method.lower()
        if http_method == 'head':
            http_method = 'get'

        assert self.cmd in self.operations, \
            'Unimplemented command ({0}) for {1}'.format(
                self.cmd,
                str(self.__class__.__name__)
            )

        has_args, has_id = self.check_args(**kwargs)

        assert (
            self.cmd in self.operations and
            (has_id and len(self.operations[self.cmd]) > 0 and
             http_method in self.operations[self.cmd][0]) or
```

(continues on next page)

(continued from previous page)

```
            (not has_id and len(self.operations[self.cmd]) > 1 and
             http_method in self.operations[self.cmd][1]) or
            (len(self.operations[self.cmd]) > 2 and
             http_method in self.operations[self.cmd][2])
        ), \
            'Unimplemented method ({0}) for command ({1}), which {2} ' \
            'an id'.format(http_method,
                           self.cmd,
                           'requires' if has_id else 'does not require')
        meth = None
        if has_id:
            meth = self.operations[self.cmd][0][http_method]
        elif has_args and http_method in self.operations[self.cmd][1]:
            meth = self.operations[self.cmd][1][http_method]
        else:
            meth = self.operations[self.cmd][2][http_method]

        method = getattr(self, meth, None)

        if method is None:
            return make_json_response(
                status=406,
                success=0,
                errormsg=gettext(
                    'Unimplemented method ({0}) for this url ({1})').format(
                        meth, flask.request.path
                    )
                )

        return method(*args, **kwargs)

    @classmethod
    def register_node_view(cls, blueprint):
        cls.blueprint = blueprint
        id_url, url = cls.get_node_urls()

        commands = cls.generate_ops()

        for c in commands:
            cmd = c['cmd'].replace('.', '-')
            if c['with_id']:
                blueprint.add_url_rule(
                    '/{0}{1}'.format(
                        c['cmd'], id_url if c['req'] else url
                    ),
                    view_func=cls.as_view(
                        '{0}{1}'.format(
                            cmd, '_id' if c['req'] else ''
                        ),
                        cmd=c['cmd']
                    ),
                    methods=c['methods']
```

(continues on next page)

(continued from previous page)

```
                )
            else:
                blueprint.add_url_rule(
                    '/{0}'.format(c['cmd']),
                    view_func=cls.as_view(
                        cmd, cmd=c['cmd']
                    ),
                    methods=c['methods']
                )

    def children(self, *args, **kwargs):
        """Build a list of treeview nodes from the child nodes."""
        children = self.get_children_nodes(*args, **kwargs)

        # get_children_nodes may return a Flask Response (e.g. an error
        # response) instead of a list of nodes. In that case return it as-is
        # rather than trying to iterate/sort it.
        if isinstance(children, flask.Response):
            return children

        # Return sorted nodes based on label
        return make_json_response(
            data=sorted(
                children, key=lambda c: c['label']
            )
        )

    def get_children_nodes(self, *args, **kwargs):
        """
        Returns the list of children nodes for the current nodes. Override this
        function for special cases only.

        :param args:
        :param kwargs: Parameters to generate the correct set of tree node.
        :return: List of the children nodes
        """
        children = []

        for module in self.blueprint.submodules:
            children.extend(module.get_nodes(*args, **kwargs))

        return children
```

13.4.3 BaseDriver

```
class BaseDriver(metaclass=DriverRegistry):
    """
    class BaseDriver():

    This is a base class for different server types.
    Inherit this class to implement different type of database driver
    implementation.

    (For PostgreSQL/EDB Postgres Advanced Server, we will be using psycopg)

    Abstract Properties:
    -------- ----------
    * Version (string):
        Current version string for the database server

    * libpq_version (string):
        Current version string for the used libpq library

    Abstract Methods:
    -------- -------
    * get_connection(*args, **kwargs)
    - It should return a Connection class object, which may/may not be
      connected to the database server.

    * release_connection(*args, **kwargs)
    - Implement the connection release logic

    * gc()
    - Implement this function to release the connections assigned in the
      session, which has not been pinged from more than the idle timeout
      configuration.

    Callbacks registered with register_session_gc_callback() are called
    with the session id whenever gc_timeout() releases that session's
    connections, so modules caching per-session state that holds those
    connections can drop it.
    """

    _session_gc_callbacks = []

    @classmethod
    def register_session_gc_callback(cls, callback):
        """
        Register callback(session_id) to be run when the connections of an
        idle session are released by gc_timeout().
        """
        if callback not in BaseDriver._session_gc_callbacks:
            BaseDriver._session_gc_callbacks.append(callback)

    @staticmethod
    def run_session_gc_callbacks(session_id):
```

(continues on next page)

(continued from previous page)

```
        for callback in BaseDriver._session_gc_callbacks:
            try:
                callback(session_id)
            except Exception as e:
                current_app.logger.exception(e)

    @property
    @abstractmethod
    def version(cls):
        pass

    @property
    @abstractmethod
    def libpq_version(cls):
        pass

    @abstractmethod
    def get_connection(self, *args, **kwargs):
        pass

    @abstractmethod
    def release_connection(self, *args, **kwargs):
        pass

    @abstractmethod
    def gc_timeout(self):
        pass
```

13.4.4 BaseConnection

```
class BaseConnection(metaclass=ABCMeta):
    """
    class BaseConnection()

        It is a base class for database connection. A different connection
        drive must implement this to expose abstract methods for this server.

        General idea is to create a wrapper around the actual driver
        implementation. It will be instantiated by the driver factory
        basically. And, they should not be instantiated directly.


    Abstract Methods:
    -------- -------
    * connect(**kwargs)
      - Define this method to connect the server using that particular driver
        implementation.

    * execute_scalar(query, params, formatted_exception_msg)
      - Implement this method to execute the given query and returns single
```

(continues on next page)

(continued from previous page)

```
      datum result.

  * execute_async(query, params, formatted_exception_msg)
    - Implement this method to execute the given query asynchronously and
    returns result.

  * execute_void(query, params, formatted_exception_msg)
    - Implement this method to execute the given query with no result.

  * execute_2darray(query, params, formatted_exception_msg)
    - Implement this method to execute the given query and returns the result
      as a 2 dimensional array.

  * execute_dict(query, params, formatted_exception_msg)
    - Implement this method to execute the given query and returns the result
      as an array of dict (column name -> value) format.

  * def async_fetchmany_2darray(records=-1, formatted_exception_msg=False):
    - Implement this method to retrieve result of asynchronous connection and
      polling with no_result flag set to True.
      This returns the result as a 2 dimensional array.
      If records is -1 then fetchmany will behave as fetchall.

  * connected()
    - Implement this method to get the status of the connection. It should
      return True for connected, otherwise False.  This is a local check
      only (e.g. inspecting driver-level state) and may not detect
      server-side disconnects.  Use ping() when a network-level check is
      required.

  * reset()
    - Implement this method to reconnect the database server (if possible)

  * transaction_status()
    - Implement this method to get the transaction status for this
      connection. Range of return values different for each driver type.

  * ping()
    - Implement this method to verify the connection is alive by sending a
      lightweight query (e.g. SELECT 1) to the server.  Returns True if the
      server responds, False otherwise.  Unlike connected(), this detects
      stale or half-open TCP connections that were silently dropped.  When
      a query is already in progress or the connection is inside a
      transaction block, the probe is skipped and True is returned (the
      connection is evidently alive).

  * _release()
    - Implement this method to release the connection object. This should not
      be directly called using the connection object itself.

    NOTE: Please use BaseDriver.release_connection(...) for releasing the
          connection object for better memory management, and connection pool
```

(continues on next page)

(continued from previous page)

```
        management.

    * _wait(conn)
      - Implement this method to wait for asynchronous connection to finish the
        execution, hence - it must be a blocking call.

    * _wait_timeout(conn, time)
      - Implement this method to wait for asynchronous connection with timeout.
        This must be a non blocking call.

    * poll(formatted_exception_msg, no_result)
      - Implement this method to poll the data of query running on asynchronous
        connection.

    * cancel_transaction(conn_id, did=None)
      - Implement this method to cancel the running transaction.

    * messages()
      - Implement this method to return the list of the messages/notices from
        the database server.

    * rows_affected()
      - Implement this method to get the rows affected by the last command
        executed on the server.
    """

    ASYNC_OK = 1
    ASYNC_READ_TIMEOUT = 2
    ASYNC_WRITE_TIMEOUT = 3
    ASYNC_NOT_CONNECTED = 4
    ASYNC_EXECUTION_ABORTED = 5
    ASYNC_TIMEOUT = 0.2
    ASYNC_WAIT_TIMEOUT = 2
    ASYNC_NOTICE_MAXLENGTH = 100000

    @abstractmethod
    def connect(self, **kwargs):
        pass

    @abstractmethod
    def execute_scalar(self, query, params=None,
                       formatted_exception_msg=False):
        pass

    @abstractmethod
    def execute_async(self, query, params=None,
                      formatted_exception_msg=True):
        pass

    @abstractmethod
    def execute_void(self, query, params=None,
                     formatted_exception_msg=False):
```

(continues on next page)

(continued from previous page)

```
        pass

    @abstractmethod
    def execute_2darray(self, query, params=None,
                        formatted_exception_msg=False, prepare=None):
        pass

    @abstractmethod
    def execute_dict(self, query, params=None,
                     formatted_exception_msg=False):
        pass

    @abstractmethod
    def async_fetchmany_2darray(self, records=-1,
                                formatted_exception_msg=False):
        pass

    @abstractmethod
    def connected(self):
        pass

    @abstractmethod
    def reset(self):
        pass

    @abstractmethod
    def transaction_status(self):
        pass

    @abstractmethod
    def ping(self):
        """
        Check if the connection is actually alive by sending a lightweight
        query to the server.  Returns True if alive, False otherwise.
        """
        pass

    @abstractmethod
    def _release(self):
        pass

    @abstractmethod
    def _wait(self, conn):
        pass

    @abstractmethod
    def _wait_timeout(self, conn, time):
        pass

    @abstractmethod
    def poll(self, formatted_exception_msg=True, no_result=False):
        pass
```

(continues on next page)

(continued from previous page)

```
    @abstractmethod
    def status_message(self):
        pass

    @abstractmethod
    def rows_affected(self):
        pass

    @abstractmethod
    def cancel_transaction(self, conn_id, did=None):
        pass
```

13.5 Code Review Notes

This document lists a number of standard items that will be checked during the review process for any changes submitted for inclusion in pgAdmin.

- Ensure all code follows the pgAdmin *Coding Standards*.
- Ensure all code has unit test coverage and API/feature test coverage where appropriate.
- Copyright years must be correct and properly formatted (to make it easy to make bulk updates every year). The start date should always be 2013, and the end year the current year, e.g.

  Copyright (C) 2013 - 2026, The pgAdmin Development Team
- Ensure there's a blank line immediately following any copyright headers.
- Include PyDoc comments for functions, classes and modules. Node modules should be """Implements the XXXX node""".
- Ensure that any generated SQL does not have any leading or trailing blank lines and consistently uses 4 space indents for nice formatting.
- Don't special-case any Slony objects. pgAdmin 4 will have no direct knowledge of Slony, unlike pgAdmin 3.
- If you copy/paste modules, please ensure any comments are properly updated.
- Read all comments, and ensure they make sense and provide useful commentary on the code.
- Ensure that field labels both use PostgreSQL parlance, but also are descriptive. A good example is the "Init" field on an FTS Template - Init is the PG term, but adding the word "Function" after it makes it much more descriptive.
- Re-use code whereever possible, but factor it out into a suitably central location - don't copy and paste it unless modifications are required!
- Format code nicely to make it readable. Break up logical chunks of code with blank lines, and comment well to describe what different sections of code are for or pertain to.
- Ensure that form validation works correctly and is consistent with other dialogues in the way errors are displayed.
- On dialogues with Schema or Owner fields, pre-set the default values to the current schema/user as appropriate. In general, if there are common or sensible default values available, put them in the fields for the user.
- 1 Pull Request == 1 feature. If you need to fix/update existing infrastructure in your change, it's usually easier if it's in a separate Pull Request. Pull Requests containing multiple new features or unrelated changes are likely to be rejected.

- Ensure the change is fully functional, and works! If you wish to send a work in progress (WIP) change that is not intended for commit, instead of submitting a Pull Request, send either as a link to a repository fork or a patch to the pgadmin-hackers@postgresql.org mailing list, clearly stating that it's a WIP, and noting what does or does not yet work.

13.6 Translations

pgAdmin supports multiple languages using the Flask-Babel Python module. A list of supported languages is included in the **web/config.py** configuration file and must be updated whenever languages are added or removed with ISO 639-1 (two letter) language codes. The codes are named **$LANG** in this document.

13.6.1 Translation Marking

Strings can be marked for translation in either Python code (using **gettext**()) or Jinja templates (using _()). Here are some examples that show how this is achieved.

Python:

```
errormsg = gettext('No server group name was specified')
```

Jinja:

```
<input type="submit" value="{{ _('Change Password') }}">
```

```
<title>{{ _('%(appname)s Password Change', appname=config.APP_NAME) }}</title>
```

```
define(['sources/gettext', ...], function(gettext, ...){
    ...
    var alert = alertify.prompt(
        gettext('Password Change'),
        gettext('New password for %(userName)s', {userName: 'jsmith' }),
        ...
    )
})
```

13.6.2 Updating and Merging

Whenever new strings are added to the application, the template catalogue (**web/pgadmin/messages.pot**) and the existing translation catalogues (**web/pgadmin/translations/$LANG/LC_MESSAGES/messages.po**) must be updated and compiled. This can be achieved using the following commands from the **web** directory in the Python virtual environment for pgAdmin:

```
(pgadmin4) user$ pybabel extract -F babel.cfg -o pgadmin/messages.pot pgadmin
```

Once the template has been updated it needs to be merged into the existing message catalogues:

```
(pgadmin4) user$ pybabel update -i pgadmin/messages.pot -d pgadmin/translations
```

Finally, the message catalogues can be compiled for use:

```
(pgadmin4) user$ pybabel compile -d pgadmin/translations
```

13.6.3 Adding a New Language

Adding a new language is simple. First, add the language name and identifier to **web/config.py**:

```
# Languages we support in the UI
LANGUAGES = {
    'en': 'English',
    'zh': 'Chinese (Simplified)',
    'de': 'German',
    'pl': 'Polish'
}
```

Then, create the new message catalogue from the **web** directory in the source tree in the Python virtual environment for pgAdmin:

```
(pgadmin4) user$ pybabel init -i pgadmin/messages.pot -d pgadmin/translations -l $LANG
```

CHAPTER 14

Release Notes

pgAdmin release notes provide information on the features and improvements in each release. This page includes release notes for major releases and minor (bugfix) releases. Select your version from the list below to see the release notes for it.

14.1 Version 9.19

Release date: 2026-10-29

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.18.

Warning

In server mode, free-text Password Exec Commands are no longer run, and `ENABLE_SERVER_PASS_EXEC_CMD` is deprecated and ignored. Administrators now define the permitted commands by name in `SERVER_PASSEXEC_COMMANDS`, and users choose one of those names in the server properties. Configure `SERVER_PASSEXEC_COMMANDS` **before** the first start after upgrading: on that start, each existing command that exactly matches a configured entry is converted to its name, and every other command is cleared, which cannot be undone. If the setting is empty, the conversion is postponed and a warning is logged at each start. See `config.py` and the server dialog documentation for details.

Note

Users who do not own a shared server never inherit the owner's password file; it is treated like the owner's password, SSH key and SSL client files. Each user can set their own password file on their copy of the server, and a file that everyone should use can be placed in a `SHARED_STORAGE` directory and referenced as `Name:/.pgpass`.

Note

In desktop mode, when an SSH tunnel is configured with an identity file or a password, pgAdmin no longer also offers keys from the SSH agent; the agent is still used when neither is configured. In server mode, SSH tunnels never use the SSH agent, or the keys and configuration in the `~/.ssh` directory of the account pgAdmin runs as, so a tunnel that relied on them must be given an identity file or password on the server.

Note

On Python 3.10 and later, pgAdmin now requires Flask-Security-Too 5.8.3 or later, which fixes an open redirect (GHSA-ccgp-pv8r-95wm). This matters to anyone installing pgAdmin from the Python wheel into an existing environment. Python 3.9 installations remain on the Flask-Security-Too 5.6 series.

14.1.1 Supported Database Servers

PostgreSQL: 14, 15, 16, 17 and 18

EDB Advanced Server: 14, 15, 16, 17 and 18

14.1.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.6

14.1.3 New features

Issue #2018 - Add a Statistics node for creating and managing extended statistics.
Issue #2363 - Allow data to be edited through simple auto-updatable views in View/Edit Data.
Issue #3205 - Allow Query Tool results to be saved as JSON or XML, as well as CSV.
Issue #3834 - Add a keyboard shortcut to duplicate the current line or selection in the SQL editor.
Issue #4128 - Allow the encoding of Query Tool result files to be chosen.
Issue #4129 - Add a 'copy with headers' option for Query Tool results.
Issue #5691 - Close dialogs with the Escape key.
Issue #6695 - Allow a byte order mark to be added to Query Tool result files.
Issue #7167 - Allow dialogs such as Sort/Filter to be saved and closed with the Enter key.
Issue #8647 - Allow shift + click to extend the cell range selection in the Query Tool results grid.
Issue #9057 - Support UNLOGGED partitioned tables correctly, which PostgreSQL 18 no longer allows to be created or altered.
Issue #9064 - Add the PostgreSQL 18 pg_dump options to the Backup and Backup Server dialogs.
Issue #9066 - Add the PostgreSQL 18 pg_restore options to the Restore dialog.
Issue #9212 - Show fill factor, TOAST tuple target and parallel workers in the table Properties panel.
Issue #9264 - Move the 'Returns a set?' option to the Definition tab in the Function dialog.
Issue #9704 - Allow an OAuth2 claim to restrict which shared servers a user can see, configured through `OAUTH2_SERVER_GROUP_CLAIM` and `OAUTH2_SERVER_GROUP_CLAIM_MAPPING`.
Issue #9975 - Allow the login page to be skipped when OAuth2 is the only authentication source, using `OAUTH2_AUTO_LOGIN` and `OAUTH2_LOGOUT_URL`.
Issue #10148 - Add support for managing pg_timetable chains and tasks.

Issue #10249 - Replace free-text Password Exec Commands in server mode with an administrator-defined allowlist, `SERVER_PASSEXEC_COMMANDS`. Commands run without a shell, with a reduced environment, and receive the pgAdmin user's identity in `PGADMIN_PASSEXEC_*` variables; users of a shared server inherit the owner's command by default.

Issue #10473 - Add a macOS 26 layered app icon with dark, clear and tinted variants.

Issue #10499 - Add pgEdge Starfleet to the Deploy Cloud Instance wizard, for creating Starfleet Managed databases.

Issue #10503 - Add numpad zoom shortcuts to the Desktop View menu.

14.1.4 Housekeeping

Issue #5369 - Clarify the configuration files documentation.

Issue #9230 - Rename the server 'Change Password' option to 'Change Server Password', and the user menu option to 'Change pgAdmin Password', so the two can no longer be confused.

Issue #9331 - Remove unused Google API documents, Babel locale data and packaging tools from the packages.

Issue #9524 - Document running the container with rootless Podman, and the `PUID` and `PGID` environment variables.

Issue #10363 - Enforce `--immutable` on every yarn install, in CI and the release builds, to harden the supply chain.

Issue #10546 - Fix the flaky `test_windows_pty_failures` test counting psql output from other tests.

Issue #10552 - Add a test for Reset discarding pending SQL editor values in dialogs.

Issue #10553 - Make the server tests restore the shared test fixture after themselves.

Issue #10601 - Remove the dead tree `loadfail` handler from `browser.js`.

Issue #10602 - Fix the Jest `addNewDatagridRow` helper so schema UI specs actually add a row.

14.1.5 Bug fixes

Issue #5940 - Fix View/Edit Data failing on SQL_ASCII databases when a name contains a backslash followed by 'u' or 'U'.

Issue #6090 - Refresh a stale server connection manager when a server id is reused, so one user's session can no longer pick up settings from another server.

Issue #6231 - Generate a single GRANT statement for roles with identical privileges.

Issue #6481 - Fix index and constraint columns not being shown when their names require quoting.

Issue #6652 - Fix Schema Diff treating functions that differ only in OUT arguments or return type as unrelated objects.

Issue #6671 - Allow the emailed MFA code to be re-entered after an invalid code is entered.

Issue #7232 - Fix the tab switching shortcuts not working whilst focus is inside the PSQL, Query, ERD or Schema Diff tools.

Issue #7612 - Fix the server context menu showing database options after the tree state is restored.

Issue #7619 - Fix Query Tool autocomplete running as the wrong user, or failing, after changing the connection to a different user.

Issue #8015 - Re-sort renamed server groups and other nodes in the Object Explorer instead of waiting for a reload.

Issue #8144 - Connect the server when changing the Query Tool connection after it was disconnected.

Issue #8529 - Rewrite the container entrypoint using bash features, and pass values to the embedded Python safely, so an email address containing an apostrophe works and a validation error stops the container rather than passing silently.

Issue #8664 - Fix debugger messages from successive steps running together on one line.

Issue #8991 - Fix BEGIN, COMMIT and ROLLBACK silently failing in the Query Tool under server cursor mode.

Issue #9130 - Select the adjacent tab when the active tab is closed, rather than the left-most.

Issue #9450 - Allow roles holding ADMIN OPTION to manage Group Role membership.

Issue #9603 - Restore the per-tab toolbar options when Query Tool tabs are restored on relaunch.

Issue #9624 - Fix a database's label staying at '[Disconnecting…]' when disconnecting it fails.

Issue #9630 - Fix the parameter value dropdown keeping stale options when the parameter name is changed.

Issue #9672 - Fix View/Edit Data not handling generated columns properly.

Issue #9784 - Fix modal dialogs losing keyboard focus to a tool iframe loading in the background.

Issue #9798 - Fix the collation and ctype query error for databases with a non-default LC_COLLATE.

Issue #9814 - Disable the SSH agent when an SSH tunnel identity file or password is provided.

Issue #9818 - Keep the AI Assistant's intermediate responses instead of replacing them with placeholder messages.

Issue #9836 - Fix the CREATE TABLE script ignoring the UNLOGGED attribute of a partition.

Issue #9838 - Fix formatting a view's SQL being treated as a column change that drops and re-creates the view.

Issue #9865 - Fix modal dialogs being hidden from assistive technology by `aria-hidden` on the application root.

Issue #9890 - Fix ERD tables becoming immovable after a Shift-drag selection.

Issue #9921 - Fix Azure and Google authentication in the cloud deployment wizard.

Issue #9984 - Report an unreachable external configuration database, or a malformed `CONFIG_DATABASE_URI`, as a failed check rather than an unhandled exception.

Issue #10031 - Fix Query Tool tabs running their query automatically after a session restore.

Issue #10103 - Exclude non-editable alias and expression columns when saving edited rows in the Query Tool.

Issue #10136 - Restore tags for standard users on shared servers, and never inherit the owner's password file.

Issue #10143 - Fix switching back to a dialog tab containing a data grid being slow, by skipping virtualisation for small grids.

Issue #10226 - Restore remembering the last visited directory in the desktop file dialogs.

Issue #10251 - Fix invalid SQL from the Maintenance dialog for REINDEX … CONCURRENTLY.

Issue #10254 - Fix the Object Explorer shortcut not moving keyboard focus into the tree.

Issue #10273 - Fix the dashboard transactions per second graph being wrong for refresh rates other than one second.

Issue #10292 - Fix Schema Diff scripts that convert a column to or from SERIAL.

Issue #10301 - Drop the scaffolding default partition after Schema Diff rebuilds a partitioned table.

Issue #10310 - Fix the Statistics node failing to list its children in Object Explorer.

Issue #10334 - Add Caddy reverse proxy configuration examples to the documentation.

Issue #10347 - Fix the selected UI language not persisting beyond the request that set it in server mode.

Issue #10348 - Fix OpenAI streaming tool calls being split into two entries in the AI Assistant.

Issue #10349 - Fix the OAuth2 userinfo request crashing when `OAUTH2_USERINFO_ENDPOINT` is set to None.

Issue #10350 - Fix the MAINTAIN privilege being silently dropped for views and materialised views on PostgreSQL 17 and later.

Issue #10357 - Fix the cursor jumping to the start of SQL fields in dialogs when keys are pressed together.

Issue #10364 - Explain Docker Compose quoting for `PGADMIN_CONFIG_*` values in the container documentation.

Issue #10386 - Stop the Query Tool spinner, and its idle CPU use, whilst a password prompt is open.

Issue #10401 - Show default privileges in the Database properties panel.

Issue #10409 - Include the authenticated user in the access log on logout.

Issue #10414 - Fix the Linux packages shipping a stray copy of Python as `venv/bin/python`, which stopped the DEB package installing on Ubuntu 26.04.

Issue #10415 - Prefer the user's email address as the Gravatar identifier.

Issue #10418 - Remove the dead `usr` parameter from Query Tool connection URLs.

Issue #10419 - Fix Kerberos login failures returning a JSON 500 response, and first-time automatically created Kerberos logins being rejected.

Issue #10422 - Fix Schema Diff repeating unchanged column comments and identity options.

Issue #10424 - Fix Reset Layout dropping Query Tool tabs from the saved application state.

Issue #10428 - Fix connections crashing on Windows with an access violation, and the utilities failing to find `gssapi64.dll`, by staging the Kerberos runtime next to libpq.

Issue #10446 - Fix Schema Diff reporting identical tables as different when a foreign key's referenced table has a dropped column.

Issue #10449 - Honour the password file in the Change Server Password dialog, rather than requiring the current password.

Issue #10462 - Fix duplicated content when opening large non-UTF-8 files in the Query Tool.

Issue #10463 - Pass the target database, and every supported connection parameter, to the utilities, so a database set in a service file no longer overrides the one selected.

Issue #10470 - Remove inherited columns from the Columns tab when their parent table is removed after reopening a table.

Issue #10482 - Allow saving files through symbolic links in desktop mode, and stop forcing 0600 permissions on them there.

Issue #10485 - Fix 'Cannot have two HTML5 backends at the same time' errors in dialogs containing a data grid.

Issue #10511 - Fix the Dashboard Logs tab failing on multi-byte characters split across read chunks.

Issue #10527 - Write the cloud deployment wizard's AWS, Azure and Google credentials through to the session store.

Issue #10531 - Fix the Query Tool saving files that were loaded as latin-1 back as UTF-8.

Issue #10534 - Fix the hardcoded table OID in the column properties query, which broke inherited column details.

Issue #10547 - Fix valid escapes below U+0100 being rewritten in SQL_ASCII data and names.

Issue #10548 - Fix negative identity column options being dropped from the generated SQL.

Issue #10549 - Fix Schema Diff not removing a column comment that exists only in the target.

Issue #10550 - Fix changing an identity column's START value also restarting its sequence.

Issue #10551 - Fix the cursor jumping to the start of SQL fields in dialogs after a quick edit and undo.

Issue #10554 - Fix column properties reporting an arbitrary parent for columns merged from several parents.

Issue #10573 - Fix Query Tool state save/restore failing on installations with a legacy `SECRET_KEY`.

Issue #10584 - Preserve explicit 24-hour mode in date-time picker popups.

Issue #10597 - Fix Schema Diff treating a function whose input argument was renamed as two unrelated functions.

Issue #10598 - Keep the Query Tool execute options when its transaction is re-created.

Issue #10600 - Revert the Query Tool execute option checkboxes when changing an option fails.

Issue #10603 - Fix the Query Tool not re-running the query after reconnecting at a password prompt.

Issue #10604 - Report a failed autocomplete reconnect in the Query Tool instead of ignoring it.

Issue #10607 - Fix Query Tool autocomplete objects being shared between sessions that use the same transaction id.

Issue #10612 - Free Query Tool autocomplete objects when an idle session's connections are released.

Issue #10613 - Reconnect a lost Query Tool connection as the user and role it was changed to.

Issue #10614 - Keep external pages out of the desktop runtime's privileged windows and confine non-prompted downloads to the downloads directory.

Issue #10618 - Keep Query Tool execution disabled until a restored tab's execute options reach the server.

Issue #10645 - Fix connection redirection in the materialized view refresh, where the target database's name was passed straight to psql's `--dbname`: because libpq expands a value containing an equals sign into a full connection string, a database named like `host=... port=...`, which any role with only CREATEDB can create, redirected psql to a server of the creator's choosing and leaked the connecting user's saved password (CVE-2026-116252). The name is now passed through the same connection-information helper as the Backup, Restore, Maintenance and Import/Export tools, so libpq treats it strictly as a database name. Reported by Bae Seung-won (@baeseungwon1010).

Issue #10646 - Fix a user's other sessions surviving a password change, which left a session an attacker already held valid after the password was changed or reset (CVE-2026-116251). A self-service change now rotates the user's `fs_uniquifier`, logging out every other session while the changing session stays signed in with its database connections, and saved passwords, including those of shared servers, are re-encrypted under the new key, with any that cannot be decrypted cleared, and all of them cleared if re-encryption fails. An administrator reset (including `setup.py update-user`) also rotates `fs_uniquifier`, ending all of that user's sessions, but does not re-encrypt their saved passwords. Reported by Zohaib.

Issue #10647 - Fix time-of-check to time-of-use symlink races in Import/Export Servers and the File Manager's upload, save and file-open paths, where a path validated against the user's storage directory was then opened by name, so a symbolic link swapped in at the file or any parent directory in between let an export overwrite, or an import read, a file outside the storage directory (CVE-2026-116250). In server mode on POSIX the file is now opened by walking down from the storage directory one component at a time with `O_NOFOLLOW`; new files are created with mode 0600 and only regular files are read, opened non-blocking so a FIFO cannot hang the request. Symbolic links inside a storage directory are now refused, even when they point elsewhere inside it. Windows and desktop mode are unchanged, so the race remains there. Reported by MUTED CYBERSECURITY S.L.

Issue #10648 - Fix the same symlink races in the files handed to Backup, Restore and Import/Export Data, where the validated path was passed to pg_dump, pg_dumpall, pg_restore or psql, which opened it by name later, extending the fix for the vulnerability tracked in Issue #10647. In server mode on POSIX pgAdmin now opens the file itself with the descriptor-relative `O_NOFOLLOW` walk, accepts only a regular file and hands the utility `/dev/fd/N`, and new backup and export files are created with mode 0600. This applies on Linux only, and not to directory-format Backup and Restore, where the utility opens the files inside the directory by name; on macOS and the BSDs the file is checked safely but the utility still reopens it by name.

Issue #10649 - Refuse hard links and FIFOs in the symlink-race fixes of Issue #10647 and Issue #10648, since `O_NOFOLLOW` stops only symbolic links: in server mode on POSIX, a file with more than one link is refused, for reading as well as before it is truncated for writing, and a FIFO can no longer hang an upload, save or export; Windows is not covered. The Import/Export Servers, save, Backup, Restore and Import/Export Data handlers also return the reason for a failure instead of text containing the absolute storage path.

Issue #10650 - Fix connection file paths escaping the user's storage directory, where a password file, SSL certificate, key or CRL, or SSH tunnel identity file such as `../<another user>/.pgpass` was joined to the storage directory after stripping only leading slashes, so a user could connect with another user's credentials or key, and where `sslkeylogfile` was copied into the connection string unchanged, letting libpq create or append a file as the pgAdmin service account (CVE-2026-116249). In server mode the resolved path, with symbolic links followed, must now stay inside the user's storage directory or the named shared storage directory, and `sslkeylogfile` is confined the same way. Connection parameter keys are also validated against the libpq keyword list, since a crafted key could smuggle its own `keyword=value` pairs past these checks. Servers whose file paths reach outside the storage directory, through `..` or a symbolic link, stop connecting until the files are moved into it or into a `SHARED_STORAGE` directory.

Issue #10651 - Fix any user able to register a server being able to share it with every other user in server mode, because the create and update endpoints stored whatever `shared` value they were sent, and the servers.json import removed a non-administrator's shared entries only after validation, so an early error left them in place (CVE-2026-116248). Such requests are now refused with a 403, and the import prunes and skips a non-administrator's shared entries before validating. The restriction is not retroactive: servers shared by non-administrators before the upgrade stay shared until the owner un-shares them or an administrator clears the `shared` column in the configuration database, and pgAdmin only logs a warning about each of them at startup, so administrators should review those servers and un-share any that should not be shared. `Shared` in a servers.json import must now be the JSON value `true`, and a file that fails validation is refused as a whole.

Issue #10652 - Stop libpq using the pgAdmin service account's own client files in server mode: when a server had no password file, client certificate or client key configured, libpq fell back to the service account's `~/.pgpass`, `~/.postgresql/postgresql.crt` and `~/.postgresql/postgresql.key` (or `PGPASSFILE`, `PGSSLCERT` and `PGSSLKEY`), letting any user connect with the service account's saved passwords or client certificate (CVE-2026-116247). In server mode each of these parameters is now always given a value, the user's own file or a path that can never be opened, in the connection string and for the utilities. Server mode deployments relying on the service account's files, or on `passfile`, `sslcert` or `sslkey` in a connection service entry, must configure them on each server instead, and a server with a client certificate must also have a client key.

Issue #10653 - Fix server passwords being left in pgAdmin's own process environment, where the password handed to psql and to the utilities was written into `os.environ` and never removed, so another user's later psql session or utility inherited it and libpq used it for any connection made without a password of its own (CVE-2026-116246). The password now goes only into the environment of the process that needs it.

Issue #10654 - Restrict connection services in server mode, where any user could set a server's service, or a `service` connection parameter, to an entry in the service account's connection service file and connect with that entry's credentials, and where a `PGPASSWORD` or `PGSERVICE` variable set for that account was used for every connection (CVE-2026-116245). A service may now only be used if the administrator lists it in the new `SERVER_MODE_ALLOWED_SERVICES` setting, which is empty by default; the `servicefile` parameter is refused, and `PGPASSWORD` and `PGSERVICE` are removed from pgAdmin's environment at startup. `setup.py load-servers` also refuses an unlisted service. In server mode, servers that use a service stop connecting until the administrator lists it in `SERVER_MODE_ALLOWED_SERVICES` in `config_local.py`, ideally before upgrading. Listing a service shares its credentials with every pgAdmin user, so list only services intended for everyone.

Issue #10655 - Stop libpq using the pgAdmin service account's Kerberos credentials in server mode, where removing `KRB5CCNAME` let the Kerberos library fall back to the service account's default credential cache or client keytab (or its logon, through SSPI on Windows), so any user could answer a server's GSSAPI request as the service account's principal (CVE-2026-116244). In server mode `KRB5CCNAME` and `KRB5_CLIENT_KTNAME` now point at a file that cannot exist, except that a user who logged in with Kerberos gets their own delegated `KRB5CCNAME` when connecting to a server with Kerberos authentication enabled. Every other connection also gets `gssencmode=disable` and, with libpq 16 or later, `require_auth=!gss,!sspi`; without `require_auth`, SSPI and gssproxy are not stopped, so upgrade the libpq used by pgAdmin and its utilities to 16 or later. A server whose `require_auth` allows only GSSAPI or SSPI is refused unless the user logged in with Kerberos. A service listed in `SERVER_MODE_ALLOWED_SERVICES` takes precedence for psql and the utilities, so it must not set `require_auth`, `gssencmode` or `gsslib`.

Issue #10656 - Fix the utility binary-path guard accepting a path under `SHARED_STORAGE`, which ordinary users can write to, so a user could point a server type's binary path at a file placed there and have pgAdmin execute it (CVE-2026-116243). Every `SHARED_STORAGE` entry is now rejected alongside `STORAGE_DIR`, after expanding `$DIR` and `..` and resolving symbolic links, so an existing binary path under a shared storage directory stops working. An empty `STORAGE_DIR` is not covered. Reported by Harsh Singh.

Issue #10662 - Stop SSH tunnels using the pgAdmin service account's own SSH identity, where

sshtunnel always loaded the unencrypted private keys in the service account's ~/.ssh, read its ~/.ssh/config and could use its ssh-agent, so any user could configure a tunnel that authenticated with the service account's key (CVE-2026-116242). In server mode the tunnel no longer reads those keys or that configuration, or uses the agent, and an identity file that cannot be found in the user's storage is reported. Tunnels relying on the service account's key, config or agent must have an identity file in the user's storage or a password configured on the server.

Issue #10663 - Fix OS command injection in the Import/Export Data tool, where a query-based export could pass a crafted query past the \copy (...) parenthesis-balance guard through a backslash inside a double-quoted identifier, which psql treats as an escape when standard_conforming_strings is off, exposing a live TO PROGRAM clause that runs an arbitrary command on the pgAdmin host, an incomplete fix for CVE-2026-17566 (CVE-2026-116241). A backslash inside a double-quoted identifier is now rejected, and so is a backslash or null byte in the schema, table or column names of an export or import, which reached the same \copy command through qtIdent(). Reported by Yonghwa Lee (Xint by Theori).

Issue #10674 - Fix the File Manager and the storage-path tools acting on a different path from the one that was checked (CVE-2026-116240): opening, saving and listing files, download, delete, rename, create-folder and upload could name files outside the user's storage directory, or in another user's directory whose name begins with the same characters. Every File Manager and storage-path caller now acts on the absolute path that was checked, and in server mode on POSIX files are opened relative to the storage directory without following symbolic links, so symbolic links to directories and hard-linked files inside it can no longer be opened, downloaded or renamed through. The storage directory itself can no longer be deleted.

Issue #10675 - Fix LDAP and Kerberos authentication logging a user in to a different account that shared their username: Kerberos and LDAP looked the account up by username alone, or accepted the account Flask-Security's internal validation had matched by the email typed, so a Kerberos or LDAP user could be logged in as an Internal account, including the initial administrator, or as another user (CVE-2026-116239). Accounts are now looked up by the authenticated username and the source that authenticated them, and only internal authentication logs in an account from its own form. Webserver users whose username matches an Internal account, and LDAP users with capitals in their username, now log in correctly, and setup.py can update a user without a role and add one without --role. Users who relied on being logged in to an Internal account of the same name now need an account of their own source. Reported by Yves Soete of Blacksight LLC (@yssoe).

Issue #10676 - Fix bypasses of the failed-login limit and of pgAdmin's own login, password change and password reset checks, where a username in another case or a wrong internal password with LDAP or Webserver authentication also configured was never counted, and where Flask-Security's own /login, /verify, /change, /reset and /reset/<token> views accepted submissions that skipped the failed-login count and lock, the change password permission, the re-encryption of saved passwords, and the internal-account check on resets (CVE-2026-116238). Every failed internal login is now counted (when MAX_LOGIN_ATTEMPTS is set) and only internal authentication is locked, so a locked Internal account no longer blocks other sources. A login form that posts a password is no longer passed to Kerberos, OAuth2 or Webserver authentication, submissions to Flask-Security's views are refused with 405, and password resets act only on the internal account.

14.2 Version 9.18

Release date: 2026-09-17

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.17.

14.2.1 Supported Database Servers

PostgreSQL: 14, 15, 16, 17 and 18

EDB Advanced Server: 14, 15, 16, 17 and 18

14.2.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.4

14.2.3 New features

Issue #9631 - Collapse and restore the Object Explorer by re-clicking the current workspace icon, in the manner of the VS Code side bar, remembering the choice across refreshes. A keyboard shortcut, Ctrl+Alt+B by default, does the same thing and can be changed through the new `toggle_object_explorer` preference.

14.2.4 Housekeeping

Issue #10221 - Skip importing and initialising the kerberos, ldap, mfa, oauth2 and webserver authentication providers unless `SERVER_MODE` is set, leaving desktop mode with internal authentication alone.

Issue #10247 - Relax the `azure-mgmt-resource` pin to allow 24.0.0, and aggregate the third-party JavaScript and Python dependency bumps for this release.

Issue #10293 - Make the Schema Diff regression test assert its own generated script, which it previously swallowed, so invalid generated SQL can no longer pass silently.

14.2.5 Bug fixes

Issue #9226 - Accept `SharedUsername` when importing a shared server from a servers.json definition, instead of insisting on `Username` for every server.

Issue #10155 - Share concurrent identical GET requests behind `getNodeAjaxOptions()` so a wide table's Columns tab no longer fires one duplicate `get_types` request per column row.

Issue #10179 - Fix inherited columns in the Table dialog being editable and deletable: a column already inherited from a parent carries `inheritedfromtable` while one fetched interactively through 'Inherited from table(s)' carries `inheritedfrom` and has no `attnum` yet, and only the latter was checked, after an `isNew()` short-circuit that treated the attnum-less rows as new.

Issue #10180 - Fix the Data type dropdown on the expanded Definition tab of the Table dialog offering every type, ignoring the allowed-type restriction already applied to the inline editor.

Issue #10214 - Fix the `existingSecret` path in the Helm deployment template.

Issue #10235 - Remove a trailing quote from the Windows installer's `ProductVersion`, which was stamped as e.g. `9.17"`.

Issue #10236 - Fix Schema Diff reporting false differences for SERIAL/BIGSERIAL columns by ignoring the owned sequence's oid, and fix the invalid `ALTER COLUMN ... TYPE bigserial` SQL generated when such a column genuinely differs.

Issue #10237 - Fix a `replace() argument 2 must be str, not None` crash when a per-server Password Exec Command is used with a service-only (pg_service.conf) connection, which leaves host, port and username unset.

Issue #10239 - Remove a redundant `passlib` pin that conflicts with the indirectly required `libpass`.

Issue #10252 - Fix the argument grid on the Definition tab of a user-defined function or procedure refusing to delete, or add, a row in edit mode.

Issue #10295 - Reinstate dependency ordering of the script Schema Diff generates, which had been lost since the React port left `dependLevel` unset.

Issue #10297 - Fix Schema Diff duplicating any column that also differs when it recreates a foreign table.

Issue #10298 - Fix Schema Diff generating SQL that PostgreSQL rejects when a sequence's MINVALUE is raised above its current value.

Issue #10300 - Fix a foreign table column added by Schema Diff losing its collation.

Issue #10302 - Fix Schema Diff injecting whitespace into an applied function or procedure body, which left a whitespace-only difference behind.

Issue #10303 - Report a Schema Diff comparison that fails part way through as a failure, rather than as a success.

Issue #10309 - Reject an empty or null `Username` when importing a non-shared server, which previously imported cleanly and left a server libpq would silently authenticate as the OS account running pgAdmin.

Issue #10311 - Fix login being impossible against Flask-Security-Too 5.8.2, which corrected a long-standing inversion in `UserMixin.is_locked()` that `User.is_locked()` had been written against.

Issue #10341 - Omit the redundant `TABLESPACE pg_default` clause from generated index SQL, which was invalid on a partitioned table.

Issue #10383 - Fix an authentication bypass in Webserver authentication mode, where `get_user()` fell back to reading the configured `WEBSERVER_REMOTE_USER` name from the request headers when it was absent from the WSGI environment, letting any client that could reach pgAdmin assert any identity, including an administrator's (CVE-2026-86863). Header-asserted identity is now opt-in, restricted to a configured list of trusted proxies with an optional shared secret, and refused for accounts whose authentication source is not `webserver`. Reported by Sanghyeon Lee (@h9e0n).

Issue #10384 - Fix argument and connection-string injection in the Backup tool, where the client-supplied database name was appended to the pg_dump argument vector as a bare positional argument: because getopt_long permutes arguments, a value beginning with a dash supplied further options such as `--file`, overriding the storage-confined output path, and because libpq expands a database name containing an equals sign into a full connection string, one could also redirect the connection to an attacker-controlled host and exfiltrate the stored password (CVE-2026-86864). The database name is now passed through the `PGDATABASE` environment variable instead. Reported by Sanghyeon Lee (@h9e0n) and Hitesh Jambhale.

Issue #10385 - Fix a time-of-check to time-of-use flaw in the File Manager's `save_file` endpoint, which backs saving from the Query Tool and ERD: the requested path was validated with `check_access_permission()` and then opened with a plain `open()`, so a symbolic link planted in between was followed, writing outside the storage directory. This is the sink CVE-2026-7819's hardening of the separate upload path did not cover (CVE-2026-86861). Reported by sec-rex.

Issue #10388 - Fix connection-string injection in the Restore and Maintenance tools, where the client-supplied database name was passed straight to `--dbname`: libpq expands a database name containing an equals sign into a full connection string, whose embedded keywords override the `--host` and `--port` pgAdmin supplies, so the connection - and the stored password exported in `PGPASSWORD` - could be redirected to a server of the caller's choosing (CVE-2026-86862). The database name is now passed through the `PGDATABASE` environment variable, which libpq never expands. Found by Hitesh

Jambhale.

Issue #10393 - Render the Validate binary path dialog as HTML, instead of showing the raw markup.

Issue #10420 - Refuse HTTP redirects on LLM API requests, rather than following a `Location` header on to a destination `ALLOWED_LLM_API_URLS` was never applied to. This is hardening rather than a fix for an exploitable flaw, since returning the redirect at all requires control of a host already on the allowlist. Reported by Ziya Abdullayev.

14.2.6 Dependencies

Non-breaking `dependabot` and audit-driven bumps aggregated for v9.18.

Python:

`Authlib` 1.7.* -> 1.8.*

`azure-mgmt-resource` ==25.0.0 -> >=24.0.0,<26.0.0

`certifi` 2026.6.17 -> 2026.7.22

`cryptography` 49.0.* -> 50.0.*

`Flask-Security-Too` 5.8.* -> >=5.8.2,<5.9

`google-auth-oauthlib` 1.4.0 -> 1.4.1

`gssapi` 1.11.* -> 1.12.*

`passlib` 1.* pin removed (redundant, and conflicting with `libpass`)

`psycopg[c]` 3.3.4 -> 3.3.5

`selenium` (`web/regression`) 4.45.0 -> 4.48.0

`setuptools` 83.* -> 84.*

`testscenarios` (`web/regression`) 0.6.2 -> 0.7.0

`typer` 0.26.* -> 0.27.*

Skipped: `paramiko` 3 -> 5 (blocked on `sshtunnel`'s `paramiko.DSSKey` usage) and `azure-mgmt-resource` 26.0.0 (drops Python 3.9 support)

JavaScript (`web/`):

`@babel/*` toolchain (core, eslint-parser, eslint-plugin, plugin-syntax-jsx, plugin-transform-class-properties, plugin-transform-object-rest-spread, plugin-transform-runtime, preset-env, preset-react, preset-typescript) -> 7.29.7

`@mui/icons-material` / `@mui/material` 7.3.10 -> 7.3.11

`@mui/x-date-pickers` 8.28.3 -> 8.29.3

`@tanstack/react-query` 5.101.4 -> 5.102.8

`@tanstack/react-virtual` 3.13.24 -> 3.14.10

`@testing-library/jest-dom` 6.9.1 -> 6.10.0

`@testing-library/react` 16.3.2 -> 16.3.3

`@testing-library/user-event` 14.6.1 -> 14.6.3

`@types/react` 19.2.17 -> 19.2.18

`@types/react-dom` 19.2.3 -> 19.2.5

`anti-trojan-source` 1.12.0 -> 1.12.2

`axios` 1.18.1 -> 1.20.0

`codemirror` 6.0.2 -> 6.65.7

`core-js` 3.49.0 -> 3.50.0

`css-loader` 7.1.4 -> 7.1.5

`diff-arrays-of-objects` 1.1.10 -> 1.1.11

`dompurify` 3.4.12 -> 3.4.14

- eslint 9.39.4 -> 9.39.5
- eslint-plugin-jest 29.15.5 -> 29.16.6
- globals 17.7.0 -> 17.12.0
- hotkeys-js 4.0.4 -> 4.0.7
- image-minimizer-webpack-plugin 4.1.4 -> 5.0.0
- ip-address 10.2.0 -> 10.7.0
- jest / jest-environment-jsdom 30.4.2 / 30.4.1 -> 30.5.1
- lossless-json 4.3.0 -> 4.3.1
- marked 18.0.7 -> 18.0.11
- papaparse 5.5.4 -> 5.7.0
- postcss 8.5.20 -> 8.5.26
- rc-dock 4.0.0-alpha.2 -> 4.0.0-alpha.3
- react / react-dom 19.2.7 -> 19.2.8
- react-arborist 3.5.0 -> 3.16.0
- react-draggable 4.7.0 -> 4.7.1
- sharp 0.35.3 -> 0.35.4
- svgo 4.0.2 -> 4.1.0
- svgo-loader 4.0.0 -> 5.0.0
- typescript-eslint 8.65.0 -> 8.69.0
- use-resize-observer 9.1.0 -> 10.0.0
- vanilla-jsoneditor 3.12.0 -> 3.13.0
- webpack-bundle-analyzer 5.3.1 -> 5.3.2
- zustand 5.0.14 -> 5.0.15
- Transitive advisory bumps: brace-expansion, fast-uri, js-yaml, shell-quote, socket.io-parser, tar
- Held back: @simonwep/pickr 1.10.x (webpack production-bundle interop break), Babel 8, and webpack 5.110.3 (npm-quarantined at bump time)

JavaScript (runtime/):

- axios 1.18.1 -> 1.19.0
- electron 43.1.1 -> 43.4.0
- eslint 10.7.0 -> 10.8.1
- globals 17.7.0 -> 17.11.0
- ip-address 10.2.0 -> 10.3.1
- postcss 8.5.20 -> 8.5.23
- Transitive advisory bumps: brace-expansion, fast-uri, undici

14.3 Version 9.17

Release date: 2026-07-30

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.16.

14.3.1 Supported Database Servers

PostgreSQL: 14, 15, 16, 17 and 18

EDB Advanced Server: 14, 15, 16, 17 and 18

14.3.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.4

14.3.3 New features

Issue #9990 - Include the authenticated user's identity in the HTTP access log.

Issue #9942 - Add an opt-in Gateway API HTTPRoute template to the Helm chart as an alternative to the existing Ingress.

Issue #10104 - Add a preference to cap the row count fetched by the plain "View Data" action, so it is usable on large tables without always doing a full `SELECT *`.

Issue #10142 - Add support for a custom XYZ tile provider (URL, name, CRS, attribution, max zoom) in the Geometry Viewer, alongside the existing built-in base layers.

14.3.4 Housekeeping

Issue #10077 - Centralize shared-server-group visibility and access-control logic, and adjust the ServerGroup-to-Server/SharedServer model relationships.

Issue #10093 - Add a basic starter contributing guide.

Issue #10135 - Fail the macOS appbundle build if any bundled library links outside the bundle, and scan all Mach-O binaries for bundle linkage rather than only files named `.so`/`.dylib`.

Issue #10154 - Pin the sonarqube-scan-action GitHub workflow to a full commit SHA instead of a mutable branch ref, to harden against supply-chain tampering.

Issue #10138 - Update the Simplified Chinese (zh_Hans_CN) translation to match the wording used in the interface.

Issue #10156 - Pin the Yarn version used by the build scripts to the `packageManager` field, rather than whatever Yarn happens to be on the builder's PATH.

Issue #10176 - Bump JavaScript and Python third-party dependencies, including axios, webpack, react, electron, and certifi.

14.3.5 Bug fixes

Issue #10053 - Warn when OAuth2 provider settings are misplaced at the top level of the config instead of under `OAUTH2_CONFIG`.

Issue #10100 - Fix Schema Diff's "Generate Script" and the browser tree's CREATE Script view emitting wrong SQL for SERIAL/identity columns, by detecting column-owned sequences via pg_depend instead of guessing the sequence name.

Issue #10102 - Fix a Schema Diff result-status filter chip showing "No difference found" after being toggled off and back on, even when real differences exist.

Issue #10106 - Fix the Object Explorer briefly showing the literal HTML markup instead of a greyed-out "[Disconnecting…]" label when disconnecting a server or database.

Issue #10107 - Detect a selected-but-unusable OS keyring and fall back gracefully instead of failing.

Issue #10109 - Fix ALT+F5 ("Execute query at cursor") doing nothing when the cursor is on or near a statement that is not highlighted, in a Query Tool tab with multiple statements separated by blank lines.

Issue #10110 - Stop the googleapiclient cloud-deployment dependency from pulling in the system oauth2client package.

Issue #10117 - Fix a "'Response' object is not iterable" crash when expanding a Trigger node under a Table to view its trigger function, and report the correct error message on a node.sql failure in that flow.

Issue #10158 - Honor the selected EOL sequence when copying query text to the clipboard.

Issue #10187 - Fix the object browser's extension UI breaking under PostgreSQL 19's extension catalog changes.

Issue #10190 - Fix a tool-permission bypass where a user denied the Query Tool, Grant Wizard, or Schema Diff permission could still drive that tool's backend routes and Socket.IO handlers directly, since the permission check was applied only to a single "front door" route per tool. Also fixes a non-owner triggering an adhoc connection against another user's shared server persisting a new server record still owned by that other user (CVE-2026-17350). Reported by LXY.

Issue #10191 - Fix OS command injection in the MASTER_PASSWORD_HOOK feature, where an externally-sourced username (e.g. via OAuth2/OIDC, Kerberos, or webserver authentication) containing shell metacharacters could execute arbitrary commands as the pgAdmin service account when the configured hook string uses `%u` (CVE-2026-17347). Reported by Thiago Pereira.

Issue #10192 - Fix a lexer-differential bypass of the AI Assistant's read-only transaction guard, where sqlparse's string-literal lexing disagreed with PostgreSQL's own parser under `standard_conforming_strings = on`, letting a crafted multi-statement payload smuggle a COMMIT past the intended read-only wrapper, an incomplete fix for CVE-2026-12045 (CVE-2026-17351). Reported by Kai Aizen.

Issue #10193 - Fix SQL injection in the Index Statistics all-indexes listing and the Publications/Subscriptions Dependencies views, where an apostrophe in a table, index, publication, or subscription name broke out of an unescaped template interpolation, an incomplete fix for CVE-2026-12044 (CVE-2026-17346). Reported by Hung Tran Quoc (@rampage0010).

Issue #10194 - Fix several Constraints, Preferences, Debugger, and Schema Diff routes missing the `@pga_login_required` decorator, making them reachable without authentication in server mode, an incomplete fix for CVE-2026-12046 (CVE-2026-17348). Reported by Hung Tran Quoc (@rampage0010).

Issue #10200 - Fix an adhoc server connection cloning another user's stored database credentials (password, save password flag, tunnel password) alongside ownership, letting a non-owner who cloned another user's shared server connect using that user's saved database password (CVE-2026-17349).

Issue #10213 - Fix OS command injection in the Import/Export Data tool, where a query-based export could pass a crafted query string past the `\copy (...)` parenthesis-balance guard by exploiting a backslash-escape mismatch with psql's default `standard_conforming_strings = on` behaviour, exposing a live `TO PROGRAM` clause for arbitrary command execution (CVE-2026-17566). Reported by Arpit Jain.

14.3.6 Additional changes (no associated issue)

Dependencies

Non-breaking `dependabot` and audit-driven bumps aggregated for v9.17.

Python:

- `certifi` 2026.5.20 -> 2026.6.17

JavaScript (`web/`):

- `@babel/core` 7.29.0 -> 7.29.6
- `@date-io/date-fns` 3.x -> 3.2.1
- `@szhsin/react-menu` 4.5.1 -> 4.5.2
- `@tanstack/react-query` 5.100.9 -> 5.101.4
- `@types/react` 19.2.14 -> 19.2.17
- `ajv` 8.18.0 -> 8.20.0
- `anti-trojan-source` 1.8.1 -> 1.12.0
- `autoprefixer` 10.5.0 -> 10.5.4
- `axios` 1.16.0 -> 1.18.1
- `core-js` added as an explicit direct dependency (3.49.0), previously relied on transitively via pickr
- `date-fns` 4.1.0 -> 4.4.0
- `dompurify` 3.4.1 -> 3.4.12
- `eslint-plugin-jest` 29.15.2 -> 29.15.5
- `globals` 17.5.0 -> 17.7.0
- `hotkeys-js` 4.0.3 -> 4.0.4
- `html-to-image` 1.11.11 -> 1.11.13
- `ip-address` 10.1.1 -> 10.2.0
- `jest` / `jest-environment-jsdom` 30.3.0 -> 30.4.2 / 30.4.1
- `marked` 18.0.2 -> 18.0.7
- `moment-timezone` 0.6.2 -> 0.6.3
- `papaparse` 5.5.3 -> 5.5.4
- `postcss` 8.5.10/8.5.14 -> 8.5.20
- `react` / `react-dom` 19.2.5 -> 19.2.7
- `react-checkbox-tree` 2.0.1 -> 2.0.2
- `react-draggable` 4.5.0 -> 4.7.0
- `react-timer-hook` 4.0.5 -> 4.0.6
- `sharp` 0.34.4 -> 0.35.3
- `sql-formatter` 15.7.3 -> 15.8.2
- `svgo` 4.0.1 -> 4.0.2
- `terser-webpack-plugin` 5.5.0 -> 5.6.1
- `typescript-eslint` 8.59.0 -> 8.65.0
- `webpack` 5.106.2 -> 5.108.4
- `webpack-bundle-analyzer` 5.3.0 -> 5.3.1
- `zustand` 5.0.12 -> 5.0.14
- Transitive advisory bumps: `brace-expansion`, `form-data`, `undici`, `js-yaml`
- Reverted `azure-mgmt-resource` to avoid a breaking import-path change in `pgadmin/misc/cloud/azure`

JavaScript (`runtime/`):

`electron` 42.3.3 -> 43.1.1
`eslint` 10.4.1 -> 10.7.0
`globals` 17.6.0 -> 17.7.0
`axios` 1.18.0 -> 1.18.1
`ip-address` 10.1.1 -> 10.2.0
`postcss` 8.5.10 -> 8.5.20
Pinned `packageManager` to `yarn@4.15.0`

14.4 Version 9.16

Release date: 2026-06-18

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.15.

Warning

Starting with this release, when a server connection is configured with both an external password-exec command and a passfile, pgAdmin now uses the passfile and ignores the password-exec command. Previously the password-exec command took precedence. A warning is written to the log when the password-exec command is ignored in favour of the passfile.

14.4.1 Supported Database Servers

PostgreSQL: 14, 15, 16, 17 and 18

EDB Advanced Server: 14, 15, 16, 17 and 18

14.4.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.4

14.4.3 New features

Issue #2431 - Added an option to colourize panel and tab headers based on the connected server's colour, making it easier to tell which server a tab is connected to at a glance.
Issue #7641 - Allow the OAuth2 login button icon to use any Font Awesome style (e.g. `fas fa-key`), not only brand icons.
Issue #9301 - Added a "Back to login" link to the Forgot Password and Reset Password pages.
Issue #9626 - Add support for the TOAST tuple target storage parameter in the Materialized View dialog.
Issue #9646 - Make the init container security context in the Helm chart configurable via containerSecurityContext, consistent with the main container.
Issue #9699 - Add support for closing a tab with a middle-click on its title.

14.4.4 Housekeeping

Issue #9817 - Correct the macOS Replace keyboard shortcut documented in the Query Tool toolbar reference.

Issue #9866 - Fix a typo in the PGPASS_FILE environment-variable documentation and clarify its behaviour.

Issue #9917 - Update the Italian translation.

Issue #9959 - Bump Electron in the desktop runtime from 41.5.0 to 42.1.0 and pin the packaged Electron version.

Issue #9981 - Clarify the SSH tunnel "Prompt for identity file password?" switch label and help text to indicate it applies only to identity-file authentication.

Issue #10014 - Document the Kubernetes init-container tag-mismatch and RollingUpdate hazards on shared data volumes.

Issue #10018 - Remove the EDB BigAnimal cloud deployment support.

Issue #10023 - Bump JavaScript and Python third-party dependencies, including cryptography, axios, shell-quote, and assorted dependabot lockfile updates.

Issue #10049 - Bump vulnerable transitive dependencies (tar, flatted) to clear security advisories.

Issue #10050 - Rebase the version-specific SQL templates so the default targets PostgreSQL 14, the oldest supported server version, dropping the obsolete sub-14 template buckets.

Issue #10063 - Strip the foreign-architecture slice from the macOS bundle so single-arch builds no longer ship the universal2 Python framework's unused arm64/x86_64 code.

Issue #10094 - Update the Italian translation for v9.16.

14.4.5 Bug fixes

Issue #6308 - Fix the infinite loading spinner after an idle database connection is silently dropped, by detecting stale connections and offering a reconnect dialog.

Issue #7346 - Fixed an issue where preferences set via the CLI (setup.py set-prefs) were not validated, so invalid values were stored silently; CLI preference values are now validated against the preference type and rejected (and reported) if invalid.

Issue #7596 - Fix the Query Tool turning into a blank white screen when the runtime has a malformed default locale, by guarding the Query History date/time formatting against the resulting RangeError.

Issue #8318 - Fixed an error ("i.default.find(…) is undefined") that prevented deleting a table or relationship link in the ERD tool when a foreign key referenced a column that had been renamed.

Issue #9060 - Fixed an issue in the Create Table dialog where renaming a column did not update the column references in foreign key and unique constraint definitions for the new table.

Issue #9091 - Fix the Query Tool re-prompting for an unsaved password in a loop and rejecting the re-entered password, by caching the entered password on the server manager when the primary connection is already established.

Issue #9128 - Fixed an issue where the object breadcrumbs popup blocked clicks on the object explorer items beneath it.

Issue #9595 - Fix missing ALTER … SET DEFAULT statements for inherited columns in the generated table SQL/EDIT script.

Issue #9677 - Fix the Unlogged table toggle in table properties not generating any ALTER TABLE … SET LOGGED/UNLOGGED statement.

Issue #9701 - Ensure pgAdmin uses psycopg3 rather than psycopg2 when connecting to the configuration database via PGADMIN_CONFIG_CONFIG_DATABASE_URI.

Issue #9744 - Fix a View/Edit Data crash when the session contains a transaction object that is not filter-capable (e.g. left by the Query Tool or persisted by an older version), which could prevent the desktop application from loading after an upgrade.

Issue #9762 - Fix the "Cannot read properties of undefined (reading 'map')" crash in the desktop runtime when a menu refresh is triggered before the application menus have been received.

Issue #9766 - Fixed an issue where a server's custom foreground colour was not applied to the object counts (children count) and column type labels shown in the object explorer.

Issue #9782 - Optimise pgAdmin startup time by replacing the fixed server-ping interval with adaptive pinging that backs off when no servers are configured.

Issue #9806 - Fixed an issue where generated font and image filenames contained a double dot (e.g. `Roboto-Bold..ttf`) due to the webpack asset filename template.

Issue #9828 - Fix tool calls failing against OpenAI-compatible providers that emit empty/null name, arguments, or id fields in streaming continuation deltas.

Issue #9829 - Fixed installation on Python 3.9 (e.g. RHEL/Rocky/AlmaLinux 8 and 9) failing with "No module named 'pkg_resources'" by pinning setuptools below the version that dropped pkg_resources for Python 3.9.

Issue #9854 - Fix the JSON editor stripping trailing fractional zeros (e.g. 10.00) and rewriting large integers in jsonb values, which corrupted unmodified numbers when saving.

Issue #9864 - Fixed a regression where the rectangular (block/column) text selection in the code editor stopped working; restored the default Alt+drag selection without re-introducing the crosshair cursor on Alt+F5 (#9570).

Issue #9868 - Warn before opening a very large JSON/JSONB value in the data grid cell editor, which could freeze pgAdmin, and let the user choose whether to proceed.

Issue #9875 - Fixed an issue where EXPLAIN and EXPLAIN ANALYZE failed to execute when blank lines separated clauses in the SQL query.

Issue #9810 - Use the ServerManager's passfile for the credential gate in connect() so the check matches the passfile actually used for the connection, and warn on conflicting passfile/passexec settings.

Issue #9892 - Fix blank difference counts on the top-level group rows in Schema Diff.

Issue #9896 - Fix invalid DDL reconstruction for SERIAL columns in Schema Diff and the generated SQL/CREATE Script so the output round-trips on a clean target.

Issue #9933 - Remove the administrator-role bypass from the server-access helpers so the access-control checks added in 9.15 (CVE-2026-7813) are enforced uniformly. The Administrator role manages pgAdmin itself, not other users' database connections.

Issue #9935 - Fix "Illegal instruction" crash on startup of the Linux DEB and RPM packages on older x86_64 CPUs by pinning the psycopg C extension build to the x86-64 baseline.

Issue #9936 - Fix the AI panel silently falling back to the default provider when a custom LLM API URL or key file was set, and allow self-hosted LLM endpoints on any loopback port.

Issue #9939 - Fix saving a newly-added row in the Query Tool failing when the result set includes expression or alias columns that are not real columns of the underlying table.

Issue #9952 - Ship libpq-oauth-18.so and libcurl in the Docker image so PostgreSQL 18 OAuth connections work out of the box.

Issue #9976 - Fix a startup migration crash (NoSuchTableError) when an old configuration database contains a stale foreign-key reference.

Issue #9984 - Fix the Docker entrypoint mishandling a quoted PGADMIN_CONFIG_CONFIG_DATABASE_URI, which caused a SQLAlchemy parse error and silently skipped PGADMIN_DEFAULT_EMAIL/PASSWORD setup.

Issue #9985 - Make CAP_NET_BIND_SERVICE optional in the Docker image so the container works on restricted runtimes that disable that capability.

Issue #9987 - Fix "AttributeError: 'PgAdmin' object has no attribute 'login_manager'" crash when running setup.py user-management commands (add-user, update-user) from the CLI.

Issue #9988 - Provide an actionable error when 'openid' is in OAUTH2_SCOPE but OAUTH2_SERVER_METADATA_URL is not set, instead of a cryptic Authlib failure.

Issue #10013 - Fix pg_attribute filtering by attname returning the wrong attnum when the same column

name exists in multiple tables.

Issue #10022 - Fix AI Assistant read-only transaction bypass that allowed prompt-injected multi-statement payloads to commit out of the READ ONLY wrapper and execute arbitrary SQL, chaining to RCE via COPY … TO PROGRAM on a superuser connection (CVE-2026-12045). Reported by Isaac Chen.

Issue #10026 - Fix SQL injection in the named restore point endpoint where the user-supplied restore point name was interpolated into SQL via str.format() instead of being passed as a bound parameter (CVE-2026-12050). Reported by Geo.

Issue #10027 - Fix the spurious "Crypt key is missing" error and logged traceback in the Query Tool new-connection endpoints after a backend restart, by surfacing it as the standard CRYPTKEY_MISSING response so the client recovers transparently.

Issue #10028 - Fix open redirect in the multi-factor authentication flow via an unvalidated 'next' parameter that allowed a crafted link to redirect an authenticated victim to an attacker-controlled host (CVE-2026-12049). Reported by Mai Phạm Hiền.

Issue #10029 - Fixed a regression where the rectangular (block/column) text selection in the code editor stopped working; restored the default Alt+drag selection without re-introducing the crosshair cursor on Alt+F5 (#9570).

Issue #10030 - Accept prepare and binary keyword arguments in DictCursor.execute() so callers using the modern psycopg API no longer raise TypeError.

Issue #10059 - Fix the generated SQL for editing a SQL-language function/procedure whose body contains the word "return" (e.g. a RETURNING clause), which was wrongly treated as a SQL-standard body and produced a statement without the AS $BODY$ wrapper.

Issue #10068 - Fix critical stored cross-site scripting where PostgreSQL server error text and Explain plan-node content passed through html-react-parser across notifier toasts, form errors, modal alerts, and the Explain visualiser. Because pgAdmin's default Content-Security-Policy allows inline script and an iframe `srcdoc` inherits the embedding origin, the injected JavaScript ran same-origin to the victim's authenticated pgAdmin session and could read every saved server connection credential and issue arbitrary SQL against every server the victim was connected to (CVE-2026-12048). Reported by Fernando Bortotti.

Issue #10069 - Fix HTML injection in the cloud deployment module (RDS, Azure, Google) where SDK exception text was forwarded to the browser unsanitised and rendered through html-react-parser in the Cloud Wizard (CVE-2026-12047). Reported by Fernando Bortotti.

Issue #10072 - Fix two SQL Editor endpoints (close and update_connection) missing the `@pga_login_required` decorator, making them reachable without authentication in server mode and exposing a pickle deserialization sink (CVE-2026-12046). Reported by Fernando Bortotti.

Issue #10078 - Fix SQL injection across sixteen dialog templates that rendered `COMMENT ON ... IS '<description>'` and the related `pgstattuple/pgstatindex` stats sinks, where a low-privilege user could plant a table or index name containing an apostrophe and a superuser viewing statistics on the object would trigger SQL execution under the superuser role. The fix switches the affected templates to the `qtLiteral` escape filter and rewrites the `pgstattuple/pgstatindex` calls to address the relation via OID with a `::oid::regclass` cast, eliminating the embedded string-literal call form entirely. Also hardens `qtLiteral` to raise instead of silently returning raw values when `conn` is falsy (CVE-2026-12044). Reported by Jasser Chebbi.

14.4.6 Additional changes (no associated issue)

Dependencies

Non-breaking `dependabot` updates aggregated for v9.16.

Python:

- `certifi` 2026.4.22 -> 2026.5.20
- `cryptography` 47.0 -> 49.0
- `Flask-Security-Too` 5.4 -> 5.6 (`python_version <= '3.9'`)
- `google-auth-oauthlib` 1.3.1 -> 1.4.0 (`python_version > '3.9'`; Python 3.9 stays on 1.3.1)
- `requests` >=2.33.1 -> >=2.34.2 (`python_version > '3.9'`)
- `safety` >=3.7.0 -> >=3.8.1
- `selenium` 4.43.0 -> 4.44.0
- `testscenarios` 0.6.1 -> 0.6.2 (`python_version > '3.9'`)
- `typer` 0.25 -> 0.26 (`python_version > '3.9'`)
- `urllib3` 2.6 -> 2.7 (`python_version > '3.9'`)

JavaScript (`web/`):

- `@tanstack/react-query` 5.100.5 -> 5.100.9
- `ip-address` 10.1.0 -> 10.1.1
- `postcss` 8.5.12 -> 8.5.14

JavaScript (`runtime/`):

- `axios` 1.16.0 -> 1.18.0
- `electron` 41.5.0 -> 42.3.3
- `eslint` 10.3.0 -> 10.4.1

14.5 Version 9.15

Release date: 2026-05-11

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.14.

14.5.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16, 17 and 18

EDB Advanced Server: 13, 14, 15, 16, 17 and 18

14.5.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.2

14.5.3 New features

Issue #9657 - Allow the container image to run as a non-default user via the PUID and PGID environment variables.

14.5.4 Housekeeping

Issue #9764 - Update the Swedish translation.

Issue #9827 - Bump Python and JavaScript dependencies.

Issue #9832 - Fix the Czech translation for 'Refresh'.

Issue #9834 - Bump runtime dependencies and upgrade ESLint to v10.

Issue #9839 - Update the Russian translation.

Issue #9870 - Bump runtime and development dependencies.

Issue #9873 - Use an `<OWNER>` placeholder in resql tests instead of a hardcoded 'postgres' role to support non-default superuser names.

Issue #9893 - Update the Spanish translation.

Issue #9906 - Update the Italian translation.

14.5.5 Bug fixes

Issue #9656 - Use absolute paths for `a2enmod` and `a2enconf` in the Debian setup script so it works when `/usr/sbin` is not on PATH.

Issue #9830 - Fix cross-user data access and shared-server privilege escalation in server mode (CVE-2026-7813). Also applies the `@with_object_filters` access-control decorator to `ServerNode.list`.

Issue #9835 - Tighten Shared Server feature parity, owner-only field handling, and write guards as a follow-up to the data-isolation hardening.

Issue #9865 - Fix stored cross-site scripting (XSS) via crafted PostgreSQL object names rendered in the Browser Tree and Explain Visualizer (CVE-2026-7814). Reported by Fahar Abbas.

Issue #9898 - Fix SQL injection in Maintenance tool option values (CVE-2026-7815). Reported by j3seer.

Issue #9899 - Fix OS command injection in Import/Export query export (CVE-2026-7816). Reported by Chung Kim (chungkn), OneMount Group.

Issue #9900 - Fix local-file inclusion and server-side request forgery in LLM API configuration endpoints (CVE-2026-7817). Reported by j3seer.

Issue #9901 - Fix unsafe deserialization in the session manager that could lead to remote code execution (CVE-2026-7818). Also encrypts session files at rest using Fernet, restricts session-file permissions to 0o600, switches the session-digest default from SHA-1 to SHA-256, drops several non-roundtrippable live objects from the session (`AuthSourceManager` and the Azure, RDS, Google Cloud, and BigAnimal cloud-provider instances), tightens DATA_DIR file and directory permissions at creation, creates `pgadmin4.log` with mode 0o600, hardens `EnhancedRotatingFileHandler._open` against rotation failures, and bounds the `user_info_server` prompt retry loop so a non-interactive caller cannot spin forever. Reported by Fernando Bortotti.

Issue #9902 - Fix symlink-based path traversal in the file manager (CVE-2026-7819). Reported by Fernando Bortotti.

Issue #9904 - Fix account-lockout bypass on Flask-Security's default `/login` view by overriding `User.is_active` and `User.is_locked()` so the `locked` field is honored on every authentication path (CVE-2026-7820). Reported by Fernando Bortotti.

14.5.6 Additional changes (no associated issue)

The commits below did not have a dedicated GitHub issue. They are listed here for transparency.

Bug fixes

`1518b0828` - Restore the SERVER_MODE python-test path and fix two endpoint regressions surfaced by it.

`d57acce35` - Harden validation, preference, and connection-params paths against pre-existing edge cases.

Test-suite stability

`a11d289bd` - Harden `click_modal` backdrop wait and `open_query_tool` stale-element retry in feature tests.

`a50a553b0` - Feature tests use `sys.executable`; sync `yarn.lock` to `package.json`.

`0fad04de8` - PSQL socket tests use the authenticated tester; the role-dependencies test skips cleanly on auth failure.

`1f7194924` - Harden six regression tests against environmental drift.

`dc61039e9` - Quote the username in the views/mview test helper for dotted local roles.

`9b29bc203` - Quote the username in the types/compound-triggers test helpers for dotted local roles.

`504775de8` - Quote the username in the user-mappings test helper for dotted local roles.

`208541cc4` - `ImportExportServersTestCase` uses `sys.executable` instead of a bare `python` and surfaces subprocess errors instead of swallowing them as a misleading JSON-parse failure.

Refactoring

`6f4f28def` - Factor the WTForms-error-to-JSON conversion into a helper and drop a dead import.

Documentation

`9923eefca` - Clarify in `login.rst` and `ldap.rst` that `MAX_LOGIN_ATTEMPTS` applies only to the `INTERNAL` authentication source. Operators using LDAP, OAuth2, Kerberos, or Webserver auth should rely on the upstream identity provider's lockout policy and reverse-proxy request rate-limiting.

Dependencies

Non-breaking `dependabot` updates aggregated for v9.15.

Python:

- `boto3` 1.42 -> 1.43 (`python_version > '3.9'`; Python 3.9 stays on 1.42)
- `cryptography` 46.0 -> 47.0
- `psycopg` 3.3.3 -> 3.3.4 (`python_version >= '3.10'`)
- `pycodestyle` >=2.5.0 -> >=2.14.0
- `requests` >=2.21.0 -> >=2.33.1
- `safety` >=1.9.0 -> >=3.7.0
- `testtools` 2.8.7 -> 2.9.1
- `typer` 0.24 -> 0.25 (`python > '3.9'`)

JavaScript (`web/`):

- `@tanstack/react-query` 5.90 -> 5.100.5
- `axios` 1.15.2 -> 1.16.0
- `moment-timezone` 0.6.0 -> 0.6.2
- `postcss` 8.5.6 -> 8.5.12

JavaScript (`runtime/`):

- `axios` 1.15.2 -> 1.16.0
- `electron` 41.3.0 -> 41.5.0
- `eslint` 10.2.1 -> 10.3.0
- `globals` 17.5.0 -> 17.6.0

14.6 Version 9.14

Release date: 2026-04-02

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.13.

14.6.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16, 17 and 18

EDB Advanced Server: 13, 14, 15, 16, 17 and 18

14.6.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.2

14.6.3 New features

Issue #4011 - Added support to download binary data from result grid.

Issue #9703 - Added support for custom LLM provider URLs for OpenAI and Anthropic, allowing use of OpenAI-compatible providers such as LM Studio, EXO, and LiteLLM.

Issue #9709 - Fixed an issue where AI features (AI Assistant tab, AI Reports menus, and AI Preferences) were visible in the UI even when LLM_ENABLED is set to False.

Issue #9738 - Allow copying of text from the AI Assistant chat panel.

14.6.4 Housekeeping

14.6.5 Bug fixes

Issue #8992 - Fixed an issue where selecting all in the Query Tool's Messages tab would select the entire page content.

Issue #9279 - Fixed an issue where OAuth2 authentication fails with 'object has no attribute' if OAUTH2_AUTO_CREATE_USER is False.

Issue #9392 - Ensure that the Geometry Viewer refreshes when re-running queries or switching geometry columns, preventing stale data from being displayed.

Issue #9457 - Fixed Process Watcher garbled text on Windows with non-UTF-8 locales.

Issue #9570 - Fixed an issue where ALT+F5 for executing a query in the Query Tool shows a crosshair cursor icon for rectangular selection.

Issue #9648 - Fixed an issue where the default fillfactor value for B-tree indexes was incorrect.

Issue #9694 - Fixed an issue where AI Reports are grayed out after setting an API key by auto-selecting the default provider.

Issue #9696 - Fixed an issue where AI Assistant does not notify that No API Key or Provider is Set.

Issue #9702 - Fixed misleading AI activity messages that could be mistaken for actual database operations.

Issue #9719 - Fixed an issue where AI Reports fail with OpenAI models that do not support the temperature parameter.

Issue #9721 - Fixed an issue where permissions page is not completely accessible on full scroll.

Issue #9729 - Fixed an issue where some LLM models would not use database tools in the AI assistant, instead returning text descriptions of tool calls.

Issue #9732 - Improve the AI Assistant user prompt to be more descriptive of the actual functionality.

Issue #9734 - Fixed an issue where LLM responses are not streamed or rendered properly in the AI Assistant.

Issue #9736 - Fix an issue where the AI Assistant was not retaining conversation context between messages, with chat history compaction to manage token budgets.

Issue #9740 - Fixed an issue where the AI Assistant input textbox sometimes swallows the first character of input.

Issue #9758 - Clarify where the LLM API key files should be.

Issue #9789 - Fixed an issue where the Query tool kept prompting for a password when using a shared server.

Issue #9795 - Support /v1/responses for OpenAI models.

14.7 Version 9.13

Release date: 2026-03-05

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.12.

14.7.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16, 17 and 18

EDB Advanced Server: 13, 14, 15, 16, 17 and 18

14.7.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.0

14.7.3 New features

Issue #229 - Allow users to customize "OF TYPE" columns during table creation.
Issue #5578 - No FK are shown in diagram created from existing tables in the ERD Tool.
Issue #6386 - Add support for 'ONLY' in Index creation dialog.
Issue #8198 - Allow "drag-n-drop" for only user chosen tables, and show relations between them.
Issue #9229 - Load predefined users from a JSON file through command line.
Issue #9641 - Core LLM integration infrastructure, AI reports for security, schema, and performance, AI chat for the Query Tool, and AI Insights for EXPLAIN.

14.7.4 Housekeeping

14.7.5 Bug fixes

Issue #7578 - Fixed an issue where the 'Quote strings only' configuration was ignored when downloading the result set.
Issue #8988 - Fixed an issue where tools settings changed by the users were not restored on application relaunch.
Issue #9258 - Fixed an issue where modifying a shared server incorrectly updated the original server details.
Issue #9484 - Fixed an issue where a long name in ERD table node was not breaking into multiple lines.
Issue #9486 - Fixed an issue where column comments were not displayed in the SQL tab for materialised views.
Issue #9572 - Fix an issue where deployment of helm chart crashing with operation not permitted.
Issue #9583 - Fix translation compilation.
Issue #9649 - Fix broken checkbox selection in backup dialog objects tree.
Issue #9651 - Fixed an issue in file dialog where rename was not working.

14.8 Version 9.12

Release date: 2026-02-05

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.11.

Warning

Starting with this release, pgAdmin Windows installers are signed with a new code signing certificate. When installing or running pgAdmin on Windows, you should verify that the digital signature shows the certificate name as **"Open Source Developer, David John Page"**. This certificate will be used for this and future releases.

14.8.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16, 17 and 18

EDB Advanced Server: 13, 14, 15, 16, 17 and 18

14.8.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.0

14.8.3 New features

Issue #6451 - Add new options like INHERIT and SET to the Role's membership tab.
Issue #8890 - Add a new button in the query tool data output toolbar to get entire range of data.
Issue #9292 - Enhance OAUTH2 and OIDC authentication support with improved claims handling and configuration options.

14.8.4 Housekeeping

14.8.5 Bug fixes

Issue #8916 - Warn user of unsaved data output edits before page navigation.
Issue #8987 - Fix Query Tool state restoration for new connections and queries.
Issue #9074 - Fix pg_restore logs to distinguish UI sync issues from actual failures.
Issue #9110 - Optimize checkbox selection logic in backup dialog objects tree.
Issue #9196 - Fixed an issue where double click to open a file in the file manager is not working.
Issue #9223 - Upgrade ID column in the database table to BigInteger to support large OID values.
Issue #9235 - Fixed an issue where "View/Edit Data" shortcut opened "First 100 rows" instead of "All Rows".
Issue #9258 - Ensure saved shared server passwords are re-encrypted on password change.
Issue #9260 - Fixed an issue where data filter dialog removes newline character when sending SQL to the query tool.
Issue #9285 - Fixed an issue where the dashboard freezes on initial render when there is a high number of locks.
Issue #9293 - Fixed the SSL certificate issue while checking for the upgrade.
Issue #9332 - Fixed a sorting issue in the system stats memory usage table.

Issue #9350 - Disable Parameters and Membership fields when object is not new for Login and group roles.

Issue #9380 - Fixed an issue where the Query History panel would auto-scroll to the top and did not preserve the scroll bar position for the selected entry.

Issue #9402 - Fixed an issue where pgAdmin4 app on macOS cannot auto-update while running on a read-only volume even if present in the Applications folder.

Issue #9500 - Fixed an issue where connection parameters were using localized values instead of literal values, causing connection failures.

Issue #9518 - Mask the secret key for restrict option in the process watcher when restoring plain SQL file (CVE-2026-1707).

Issue #9522 - Ensure the container deployment supports boolean values in yaml format.

Issue #9552 - Ensure that the tooltip for the password cell is not visible.

Issue #9553 - Fix pgAdmin fails when performing Backup/Restore on a PostgreSQL connection defined exclusively via pg_service.conf.

Issue #9567 - Update menu bar documentation.

14.9 Version 9.11

Release date: 2025-12-11

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.10.

14.9.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16, 17 and 18

EDB Advanced Server: 13, 14, 15, 16, 17 and 18

14.9.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.0

14.9.3 New features

Issue #6388 - Add support of DEPENDS/NO DEPENDS ON EXTENSION for INDEX.

Issue #6390 - Add support of DEPENDS/NO DEPENDS ON EXTENSION for MATERIALIZED VIEW.

Issue #8968 - Add support for showing the column data type beside column name in the object explorer.

Issue #9263 - Added Ubuntu 25.10 and Fedora 43

Issue #9345 - Add conditional TLS support for the Ingress in the Helm chart.

14.9.4 Housekeeping

14.9.5 Bug fixes

Issue #9036 - Fixed an issue on type casting of default string function/procedure arguments in debugger tool.

Issue #9155 - Fix pkg_resources deprecation warning by migrating Docker base image to python:3-alpine from alpine:latest.

Issue #9297 - Fixed an issue where EXPLAIN should run on query under cursor if no text is selected.

Issue #9351 - Fixed an issue where opening file in Query Tool does not retain file name in tab.

Issue #9354 - Fixed an issue where connection is failing via Query Tool/PSQL Tool workspaces.

Issue #9368 - Plain SQL restore runs with 'restrict' option to prevent harmful psql meta-commands (CVE-2025-13780).

Issue #9372 - Fixed an issue where copying highlighted text in the query tool data output cell editor would copy the complete string.

Issue #9373 - Fixed an issue where copying a single cell should not add quoting.

Issue #9393 - Fix the Helm chart server definition and change the app version.

Issue #9399 - Specify the correct hostname placeholder for the Password Exec command.

Issue #9408 - Ensure the proper handling of extra volume mount configurations in the Helm deployment template by correcting the configuration value references.

14.10 Version 9.10

Release date: 2025-11-13

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.9.

14.10.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16, 17 and 18

EDB Advanced Server: 13, 14, 15, 16, 17 and 18

14.10.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 18.0

14.10.3 New features

Issue #4306 - Added the ability to search for tables and automatically bring them into view in the ERD tool.

Issue #6391 - Add support of DEPENDS/NO DEPENDS ON EXTENSION for PROCEDURE.

Issue #6698 - Add support for setting image download resolution in the ERD tool.

Issue #7885 - Add support for displaying detailed Citus query plans instead of 'Custom Scan' placeholder.

Issue #8912 - Add support for formatting .pgerd ERD project file.

14.10.4 Housekeeping

Issue #8676 - Migrate pgAdmin UI to use React 19.

14.10.5 Bug fixes

Issue #8504 - Fixed an issue where data output column resize is not sticking in Safari.
Issue #9117 - Fixed an issue where Schema Diff does not ignore Tablespace for indexes.
Issue #9132 - Fixed an issue where the 2FA window redirected to the login page after session expiration.
Issue #9233 - Fixed an issue where the Select All option on the columns tab of import/export data was not working in languages other than English.
Issue #9240 - Fixed an issue where the Debian build process failed with a "Sphinx module not found" error when using a Python virtual environment.
Issue #9281 - Fixed an issue where the last used storage directory was reset to blank, leading to access denied errors during backup or restore operations.
Issue #9304 - Fixed an issue that prevented assigning multiple users to an RLS policy.
Issue #9320 - Fixed remote code execution vulnerability when restoring PLAIN-format SQL dumps in server mode (CVE-2025-12762).
Issue #9323 - Fixed Command injection vulnerability allowing arbitrary command execution on Windows (CVE-2025-12763).
Issue #9324 - Fixed LDAP authentication flow vulnerable to TLS certificate verification bypass (CVE-2025-12765).
Issue #9325 - Fixed LDAP injection vulnerability in LDAP authentication flow (CVE-2025-12764).

14.11 Version 9.9

Release date: 2025-10-16

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.8.

14.11.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16, 17 and 18

EDB Advanced Server: 13, 14, 15, 16 and 17

14.11.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.5

14.11.3 New features

Issue #6385 - Add support of DEPENDS/NO DEPENDS ON EXTENSION for ALTER FUNCTION.
Issue #6394 - Added "MULTIRANGE_TYPE_NAME" option while creating a Range Type.
Issue #6395 - Added "SUBSCRIPT" option while creating a External Type.
Issue #6996 - Added option to skip the password dialog when using an identity file.
Issue #8932 - Added 'failover' and 'two_phase' parameter support in CREATE/ALTER SUBSCRIPTION for PostgreSQL v17+.
Issue #9225 - Add support for initializing the pgAdmin4 Kubernetes Helm chart.

14.11.4 Housekeeping

14.11.5 Bug fixes

Issue #9098 - Fixed an issue where the query tool displayed 'default' instead of 'null' for null text data in the data output.
Issue #9125 - Fixed an issue where the pgAdmin configuration database wasn't being created on a fresh install when an external database was used for the configuration.
Issue #9157 - Fixed an issue where shortcuts are not working as expected on multiple keyboard layouts.
Issue #9158 - Fixed an issue where saving the newly changed preferences was not reflecting on the preferences tab.

14.12 Version 9.8

Release date: 2025-09-04

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.7.

14.12.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.12.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.5

14.12.3 New features

Issue #6396 - Add menu items for truncating foreign tables.
Issue #7928 - Added Debian Trixie as a supported platform for pgAdmin.
Issue #8891 - Allow user to configure security related gunicorn parameters.
Issue #9093 - Change the default pgAdmin theme to System.

14.12.4 Housekeeping

Issue #7448 - Remove usage of BrowserFS as it is deprecated.

14.12.5 Bug fixes

Issue #9090 - Pin Paramiko to version 3.5.1 to fix the DSSKey error introduced in the latest release.
Issue #9095 - Fixed an issue where pgAdmin config migration was failing while upgrading to v9.7.
Issue #9114 - Fixed Cross-Origin Opener Policy (COOP) vulnerability in the OAuth 2.0 authentication flow (CVE-2025-9636).
Issue #9116 - Fixed an issue where editor shortcuts fail when using Option key combinations on macOS, due to macOS treating Option+Key as a different key input.

14.13 Version 9.7

Release date: 2025-08-21

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.6.

14.13.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.13.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.2

14.13.3 New features

Issue #5766 - Add support for automatic updates in the pgAdmin 4 Desktop application on macOS.
Issue #6456 - Added GENERIC_PLAN, MEMORY, SERIALIZE option to EXPLAIN/EXPLAIN ANALYZE command.
Issue #8712 - Add support for changing cursor blink rate within the editors.
Issue #8917 - Add support for server tag-based filtering in the Object Explorer.
Issue #8931 - Added support for builtin locale provider while creating Collation.

14.13.4 Housekeeping

Issue #6384 - Replace keyword PROCEDURE with FUNCTION while creating trigger and event trigger.
Issue #8861 - Introduced an 'Editor' preferences category and migrated all editor related settings into it.

14.13.5 Bug fixes

Issue #7057 - Fixed an issue where custom column widths in the result grid of Query Tool or View/Edit Data were reset after re-executing a query.

Issue #7617 - Fixed the issue where updating the name of a table column does not reflect in the corresponding primary key constraint.

Issue #8149 - Fixed an issue where pgAdmin failed to update the server connection status when the server was disconnected in the background and a refresh was performed on that server.

Issue #8650 - Make Dashboard tables to be vertically resizable.

Issue #8756 - Fixed an issue in Firefox where the query window would shift to the left after opening the history tab or selecting a column header in the results grid.

Issue #8864 - Fixed an issue where CPU usage was very high on Windows when opening the psql tool.

Issue #8867 - Ensure DB restriction type is preserved while import and export server.

Issue #8969 - Fixed incorrect behaviour of the option deduplicate items after creating the index.

Issue #8971 - Added PKEY index in the index statistics summary.

Issue #9073 - Fixed an issue where adding breakpoints caused errors, and stepping out of a nested function removed breakpoints from the parent function.

Issue #9007 - Ensure the scratch pad in the Query Tool is not restored after it is closed.

Issue #9008 - Update the documentation for parameters that require file paths.

Issue #9047 - Fixed an issue where downloading images on the ERD tool was not working in desktop mode.

Issue #9067 - Ensure that disabling "Save Application State" in Preferences prevents tool data from being saved and stops it from being restored on application restart.

14.14 Version 9.6

Release date: 2025-07-25

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.5.

14.14.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.14.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.2

14.14.3 New features

Issue #1923 - Ensure that keyboard shortcuts are displayed in tooltips, context menus, and the main menu.
Issue #5797 - Implemented a server-side cursor to enhance performance when retrieving large datasets.
Issue #7979 - Added support for setting a custom SESSION_DIGEST_METHOD in pgAdmin 4 to facilitate FIPS compliance.
Issue #8941 - Enable the PKCE workflow for OAuth 2 authentication.

14.14.4 Housekeeping

Issue #8828 - Ensure that pgAdmin 4 is compatible with PG/EPAS v18.
Issue #8958 - Use 'Drop' instead of 'Delete' for object commands to make destructive actions more deliberate.

14.14.5 Bug fixes

Issue #8420 - Fixed an issue where windows installer is not signing tmp files generated by InnoSetup.
Issue #8675 - Fixed an issue in the Search Objects tool where selecting a node occasionally selected an incorrect node.
Issue #8901 - Improved the application state restoration by leveraging rc-dock layout and ensure the order and layout of tabs is maintained on restore.
Issue #8907 - Fixed an issue where json editor in result grid was crashing if null value is set in the json editor.
Issue #8914 - Update zstd library link to 1.5.7 in Dockerfile.

14.15 Version 9.5

Release date: 2025-06-30

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.4.

14.15.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.15.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.2

14.15.3 New features

Issue #1926 - Add a new permission to allow disabling "Change Password" feature for a pgAdmin role.

Issue #1947 - Added role-based restrictions for editing server connections.

Issue #2659 - Added support for customizing keyboard shortcuts in the Query Tool's Edit menu.

Issue #2864 - Add a search box to enable searching within the preferences tab.

Issue #3319 - Added support to preserve the workspace, query windows, and pgAdmin state during an abrupt shutdown or restart.

Issue #6743 - Open preferences in a new tab instead of a dialog for better user experience.

Issue #8665 - Supports JSON logging for gunicorn process within Docker.

14.15.4 Housekeeping

14.15.5 Bug fixes

Issue #6118 - Improved PL/pgSQL code folding and support nested blocks.

Issue #7173 - Add a flag to allow access to system Python packages on recent Linux distributions.

Issue #7466 - Fixed an issue where utilities such as pg_dump and pg_restore failed to log error messages when required dependency files were missing.

Issue #8032 - Fixed an issue where the Schema Diff Tool incorrectly reported differences due to variations in the order of the privileges.

Issue #8235 - Fixed an issue in SQL syntax highlighting where the same color was used for both variable names and datatypes.

Issue #8691 - Fixed an issue in the query tool where using multiple cursors to copy text resulted in only the first line being copied.

Issue #8803 - Ensure that Keyboard shortcuts for save and download actions should not called when their respective UI buttons are disabled.

Issue #8808 - Fixed an issue where data export using a query opened the wrong dialog type.

Issue #8809 - Fixed an issue where data export using a query failed when the query contained a newline character.

Issue #8830 - Fixed a UI layout issue that occurred after upgrading from pgAdmin v9.2 when all tabs had been closed prior to the upgrade.

Issue #8834 - Fixed an issue where the Columns node was not visible under Catalog Objects.

14.16 Version 9.4

Release date: 2025-05-29

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.3.

14.16.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.16.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.2

14.16.3 New features

Issue #3369 - Enabled large file downloads for desktop users within the query tool.

Issue #8583 - Add all missing options to the Import/Export Data functionality, and update the syntax of the COPY command to align with the latest standards.

Issue #8681 - Add support for exporting table data based on a custom query.

14.16.4 Housekeeping

14.16.5 Bug fixes

Issue #6510 - Fixed an issue where the result grid slowed down when any column contained a large amount of data.

Issue #6564 - Fix the issue where an error is displayed when a table is dropped while a query is running.

Issue #6968 - Fixed an issue where the options key was not working as expected in the PSQL tool.

Issue #7926 - Fixed an issue where correct error message not displayed when sql statement contains Arabic letters.

Issue #8595 - Enhance contrast for selected and hovered items in the Object Explorer to improve visibility and accessibility.

Issue #8607 - Fixed an issue where the query tool returns “cannot unpack non-iterable Response object” when running any query with a database name change.

Issue #8608 - Handle result grid data changes in View/Edit Data mode by automatically reconnecting to the server if a disconnection occurs.

Issue #8668 - Implement API fetch error display for select dropdown.

Issue #8711 - Fixed an issue where light theme briefly appears when pgAdmin loads or tools open, even when a dark or system UI theme is preferred.

Issue #8713 - Fixed issues related to column range selection using shift + click.

Issue #8760 - Fixed an issue where pgAdmin failed to focus when previously unfocused and then quit.

14.17 Version 9.3

Release date: 2025-04-30

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.2.

14.17.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.17.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.2

14.17.3 New features

Issue #2256 - Add support for type constructors for PostGIS spatial types.
Issue #2767 - Added ability to use SQL in the "DB Restriction" field.
Issue #7310 - Add support for custom roles and role permissions management in pgAdmin.
Issue #8629 - Added support for font ligatures.

14.17.4 Housekeeping

14.17.5 Bug fixes

Issue #3688 - Add Cache-Control no-cache,no-store,must-revalidate header to dynamically generated utils.js file.
Issue #5266 - Fixed an issue where shift + click on rows/columns for range selection did not work in the query tool data output window.
Issue #8443 - Fixed an issue where the debugger hangs when stepping into nested function/procedure.
Issue #8497 - Fixed an issue where the scroll position in the Object Explorer was not retained when switching workspaces.
Issue #8556 - Ensure that graph data is updated even when the Dashboard tab is inactive.
Issue #8572 - Fixed an issue where Ctrl/Cmd+A in cell editor would select all rows.
Issue #8613 - Fixed an issue where drag and drop function with no parameters does not work.
Issue #8627 - Fixed an issue where changes to foreign key constraints were not detected in the schema diff.
Issue #8628 - Change the shortcut for canceling a running query as it conflicts with the shortcut to open a new query tool.
Issue #8630 - Fixed an issue where filtering on a view caused an error.
Issue #8632 - Fixed an issue where the query tool went blank when converting history dates to the appropriate locale format.
Issue #8636 - Ensure that the server list is alphabetically sorted in the Query Tool/PSQL workspace.
Issue #8651 - Fixed an issue where the user management tab is not opening in the classic layout.
Issue #8652 - Allow OAuth 2 login using the username claim if the email is absent from the user profile.

14.18 Version 9.2

Release date: 2025-04-03

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.1.

14.18.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.18.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.2

14.18.3 New features

Issue #0392 - Added an ability to configure the font family for SQL editors.
Issue #4194 - Added support to automatically open a file after it is downloaded in the desktop mode.
Issue #4503 - Added support for post-connection SQL execution, which will be run automatically on each connection made to any database of the server.
Issue #5871 - Add support for restoring plain SQL database dumps.
Issue #8034 - Added support for creating Directory nodes in EPAS.
Issue #8449 - Change icon buttons to show tooltip even when disabled.
Issue #8540 - Add an option to load/replace the servers.json file on each container startup.
Issue #8574 - Open user management in a separate tab instead of a dialog to enhance UI/UX.

14.18.4 Housekeeping

Issue #8545 - Added Security.md file.

14.18.5 Bug fixes

Issue #8316 - Ensure that modal dialogs are not triggered more than once to avoid duplicates.
Issue #8355 - Change session files garbage collection strategy.
Issue #8362 - Fixed an issue where pgAdmin should fallback to main screen if the last opened screen is disconnected.
Issue #8437 - Fixed an issue where the PSQL terminal displays keyname for non alphanumeric keys.
Issue #8462 - Fixed an issue where geometries in the geometry viewer will render partially when the container was resized.
Issue #8473 - Change the stop/terminate icon at all the places for better UX.
Issue #8479 - Fixed an issue where the Schema Diff was not displaying the difference query when a table had a UNIQUE NULLS NOT DISTINCT constraint.
Issue #8483 - Fixed an issue where the query tool data grid did not respect the default value for columns of domain type when the domain had a default value.
Issue #8514 - Ensure the newly added parameters in the server dialog are incorporated into the Import/Export Servers functionality.

Issue #8546 - Fixed an issue where updating the grantee was not correctly applying the privileges.
Issue #8577 - Fixed an issue where the upgrade_check API returned an unexpected keyword argument 'cafile' due to changes in the urllib package supporting Python v3.13.
Issue #8597 - Fixed an issue where delete/rename was done on wrong file after sorting in Storage Manager.
Issue #8602 - Fixed an XSS vulnerability issue in the Query Tool and View/Edit Data (CVE-2025-2946).
Issue #8603 - Fixed a remote code execution issue in the Query Tool and Cloud Deployment (CVE-2025-2945).
Issue #8623 - Fixed an issue where query tool is crashing on macOS 15.4 due to a locale issue.

14.19 Version 9.1

Release date: 2025-02-28

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v9.0.

14.19.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.19.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.2

14.19.3 New features

Issue #1235 - Added an option to open the file in a new tab within the query tool.
Issue #5128 - Add support for one to one relationship in the ERD tool.
Issue #8436 - Enable the ability to close the 'Welcome' tab in the Query Tool/PSQL Workspace.

14.19.4 Housekeeping

Issue #8068 - Added support for Python 3.13

14.19.5 Bug fixes

Issue #8181 - Fixed an issue where pgAdmin does not support pg_vector column length/precision.
Issue #8296 - Fixed an issue where pasting text containing JSON data into the query tool grid would result in incorrect parsing.
Issue #8341 - Fixed an issue where the query tool was not treating IDENTITY columns as columns with default values when inserting new rows.
Issue #8389 - Fixed an issue where the ERD tool fails to open a saved file containing parent-child relationship within the same table.
Issue #8410 - Fixed Docker image entrypoint.sh email validation.

Issue #8418 - Fixed an issue where the User Management and Change Password dialogs were hidden when selecting a menu while a workspace other than 'Default' was active.

Issue #8430 - Fixed an issue where the column order displayed was incorrect for exclusion constraints with multiple columns.

Issue #8435 - Ensure the saved passwords are decrypted with the correct encryption key for external authentication in server mode.

Issue #8439 - Fixed an issue where drop-down menus were hidden behind the dock.

Issue #8460 - Fixed an issue where deleting rows in the query tool would delete all rows in the table when 'Select All Remaining Rows' was used.

14.20 Version 9.0

Release date: 2025-02-06

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.14.

14.20.1 Supported Database Servers

PostgreSQL: 13, 14, 15, 16 and 17

EDB Advanced Server: 13, 14, 15, 16 and 17

14.20.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.0

14.20.3 New features

Issue #6513 - Change button labels and color in delete confirmation dialog for all objects to improve UX.

Issue #7708 - Enhanced pgAdmin 4 with support for Workspace layouts.

Issue #8332 - Added the MAINTAIN privilege for PostgreSQL version 17 and above.

Issue #8391 - Add support for OAuth2 profile array response, which also takes care of the GitHub Private Email ID issue.

14.20.4 Housekeeping

Issue #8249 - Show the python version used for the pgAdmin server in the about dialog.

14.20.5 Bug fixes

Issue #3273 - Change the logic of setval function, so that the next nextval of sequence will return exactly the specified value.

Issue #5204 - Fixed an issue where pgadmin cannot install into path with non ASCII characters.

Issue #6044 - Fixed an issue where filter dialog save fails when the PostgreSQL server/database connection is lost.

Issue #6968 - Fixed an issue where option key was not registering in PSQL tool.

Issue #8072 - Fixed an issue where Schema Diff not produce difference script for Index definition with where condition.

Issue #8142 - Correct the documentation for the MFA configuration.

Issue #8165 - Fixed an issue where error message from the database server need space between two sentences.

Issue #8199 - Fixed an issue where query tool throws utf-8 decode error when using cursor with binary data.

Issue #8208 - Allow deleting the entry while creating/adding new label to enumeration type.

Issue #8209 - Fixed an issue where properties dialog throwing an error for Materialized View.

Issue #8254 - Fix a formatting issue in View/Edit tool generated SQL where some filters are applied.

Issue #8255 - Fixed an issue where tooltip on a dropdown button is blocking access to dropdown menu.

Issue #8256 - Fix the error occurring while loading preferences on startup.

Issue #8273 - Fixed an issue where copying query tool output cell is not working if any SQL text is selected.

Issue #8299 - Ensure master password pop up is not shown on setting MASTER_PASSWORD_REQUIRED to false.

Issue #8309 - Remove the option "With no data (concurrently)" from Refresh MATERIALIZED VIEW context menu.

Issue #8320 - Fix an issue where wrong information is shown after using the filter on the Dashboard> State tab.

Issue #8365 - Fixed an issue where PSQL tool is not opening if database name have HTML characters in the name.

Issue #8369 - Fixed an issue where Default Privileges and Privileges not working correctly.

Issue #8408 - Fixed an issue where quotes were missing in the CREATE script for the tablespace.

14.21 Version 8.14

Release date: 2024-12-12

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.13.

14.21.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, 16 and 17

EDB Advanced Server: 12, 13, 14, 15, 16 and 17

14.21.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.0

14.21.3 New features

Issue #3317 - Allow setting NULL ordering for columns in view/edit data filter dialog.
Issue #3751 - Show auto-complete column names in filtered rows dialog of table and filter options of view/edit data tool.
Issue #5786 - Allow the use of a pgpass file in the pgAdmin container via Docker secrets.
Issue #6592 - Fixed multiple issues and improved ERD auto-layout.
Issue #6794 - Add support for passing connection details as placeholders in the passexec command.
Issue #7330 - Add support to deploy pgAdmin in a container with readOnlyRootFilesystem to true.
Issue #8095 - Added support for a builtin locale provider in the Database dialog.
Issue #8192 - Added support for adding tags on a server node.

14.21.4 Housekeeping

14.21.5 Bug fixes

Issue #5099 - Fixed an issue where Ctrl/Cmd + A was not selecting all data in query tool data grid.
Issue #7384 - Fixed an issue where querying a foreign table gives the error 'ForeignTableCommand' object has no attribute 'auto_commit'.
Issue #7486 - Fixed an issue where indent with space was not aligning to next tab position.
Issue #7809 - Fixed an issue where pgAdmin crashes on accessing the dashboard state tab when database is super busy.
Issue #7865 - Fixed an issue related to the query tool update connection after the server disconnected from the object explorer.
Issue #7892 - Fixed an issue where a column name change in the edit dialog of the table node does not show the updated column name.
Issue #8010 - Fixed an issue where query tool should show results and messages only from the last executed query.
Issue #8028 - Fixed an issue where query tool throws syntax error if a newly added row is untouched and saved.
Issue #8065 - Ensure the crypt key is retrieved correctly on backend server restart.
Issue #8098 - Fixed an issue in schema diff where an error message popup was showing some garbage without any info.
Issue #8127 - Fixed an issue where query tool should not prompt for unsaved changes when there are no changes.
Issue #8134 - Add a user preference to enable/disable alternating row background colors in the data output of query tool.
Issue #8157 - Fixed an issue where doing Ctrl/Cmd+C on a selected text in a cell editor of data output in the query tool copied the complete text.
Issue #8158 - Fixed an issue where auto-width of wide columns in data output is incorrectly calculated.
Issue #8215 - Ensure correct custom SSL certificate passed in connection string.

14.22 Version 8.13

Release date: 2024-11-14

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.12.

14.22.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, 16 and 17

EDB Advanced Server: 12, 13, 14, 15, and 16

14.22.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 17.0

14.22.3 New features

Issue #1780 - Replace infinite scrolling with pagination in query tool data output for better UX and performance.
Issue #1984 - Add an object menu option to disconnect all server and database connections.
Issue #2874 - Alternate the background color of rows to enhance readability.
Issue #5869 - Allow to pass PGADMIN_CONFIG_CONFIG_DATABASE_URI from docker secrets.
Issue #6016 - Format dashboard graph metrics for better readability.
Issue #7393 - Added support for auto-detecting and setting the End-of-line character (LF/CRLF) in the query tool editor.
Issue #7863 - Make the background color for the serial number and header cells distinct.

14.22.4 Housekeeping

Issue #8061 - Updated the react-menu library from v2 to v4.
Issue #8077 - Remove bootstrap from the runtime code.
Issue #8102 - Remove the dependency on python packages eventlet and greenlet.

14.22.5 Bug fixes

Issue #5307 - Fixed an issue to allow the Enter key to save data in the result grid text editor.
Issue #7289 - Move 'About pgAdmin 4' to app menu on macOS.
Issue #7655 - Fixed an issue where the query tool was crashing when an empty geometry was being rendered.
Issue #7837 - Fixed an issue where role properties were not loading.
Issue #7883 - Fix multiple issues related to debugger params dialog input.
Issue #7919 - Fixed an issue where the dock layout was not saved upon closing a tab.
Issue #7920 - Fixed an issue where the copy shortcut CTRL +C was not working in the Query Tool data grid.
Issue #7955 - Fixed an issue where Dashboard tab showing 'Something went wrong'.
Issue #7957 - Fixed an issue where cursor selection is not visible in the PSQL tool.

Issue #7965 - Allow OAuth2 params OAUTH2_NAME, OAUTH2_DISPLAY_NAME, OAUTH2_ICON, OAUTH2_BUTTON_COLOR to be optional.

Issue #7988 - Add appropriate minimum width and height setting for desktop apps to avoid app accidentally going below visibility levels.

Issue #7993 - Fixed an issue where graphical explain keeps the node details open even after plan changed.

Issue #8007 - Fixed an issue in the debugger where function arguments of the character data type were being truncated.

Issue #8013 - Fix the issue where rows do not retain shading when scrolling.

Issue #8022 - Use PG17 as the default in the container.

14.23 Version 8.12

Release date: 2024-09-23

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.11.

14.23.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, 16 and 17

EDB Advanced Server: 12, 13, 14, 15, and 16

14.23.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.4

14.23.3 New features

Issue #1900 - Added feature to restore preferences to their default values.

Issue #6222 - Add a new config variable - ALLOW_SPECIAL_EMAIL_DOMAINS to allow special domains for pgAdmin user emails.

Issue #7293 - Allow running non-continuous selected SQL code blocks in the query tool.

14.23.4 Housekeeping

Issue #7884 - Improved the extendability of the SchemaView and DataGridView.

14.23.5 Bug fixes

Issue #6502 - Fix the query tool restore connection issue on the server disconnection from the left side object explorer.

Issue #7076 - Revamp the current password saving implementation to a keyring and reduce repeated OS user password prompts.

Issue #7571 - Fixed an issue where users could not use pgAdmin if they did not have access to the management database.

Issue #7811 - Fixed an issue where servers listed in the servers.json file were being reimported upon container restart.

Issue #7839 - Added support for OIDC based OAuth2 authentication.

Issue #7878 - Fixed an issue where cursor moves to end of line when editing input fields.

Issue #7890 - Fixed an issue where "Quit App" confirmation modal in desktop app is not respecting "Confirm on close or refresh?".

Issue #7895 - Fixed an issue where different client backend shows all SQL are same.

Issue #7945 - Fixed a security issue where the OAuth2 client ID and secret exposed through the web browser (CVE-2024-9014).

14.24 Version 8.11

Release date: 2024-08-22

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.10.

14.24.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, 16 and 17

EDB Advanced Server: 12, 13, 14, 15, and 16

14.24.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.3

14.24.3 New features

Issue #2046 - Add a home button to the geometry viewer to set original zoom level when the viewer was opened.

14.24.4 Housekeeping

Issue #7705 - Upgrade react-data-grid fork to latest and change pgAdmin accordingly.

Issue #7776 - Introduce custom React Hook useSchemaState to simplify SchemaView component.

14.24.5 Bug fixes

Issue #7499 - Fixed an issue where refreshing the Schema Diff tool opened in a new tab caused an error.

Issue #7540 - Fix server heartbeat logging error after deleting the server.

Issue #7682 - Fixed an issue where the Generate Script ignored filter conditions when a parent node was selected.

Issue #7683 - Fixed an issue where delete object(shortcut key) affecting both text and Object Explorer items.

Issue #7688 - Fix an issue where ERD tool should to be able to open saved pgerd file when using keyboard shortcuts.

Issue #7728 - Updated the documentation for web server authentication.

Issue #7737 - Fixed an issue where the REVOKE statement in the create script was throwing an error if the role contained special characters.

Issue #7748 - Improve code highlighting in query editor.
Issue #7754 - Fix an issue where the wheel package is not getting installed on the arm64-based macOS version < 14.
Issue #7772 - Fixed an issue where column resizing is not working in search objects dialog.
Issue #7775 - Fixed an issue where the value in the find box is not updating with selected text in editor if find is already open and re-triggered.
Issue #7793 - Fixed paths for Flatpak broken after Electron changes.

14.25 Version 8.10

Release date: 2024-07-29

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.9.

14.25.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, 16 and 17

EDB Advanced Server: 12, 13, 14, 15, and 16

14.25.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.3

14.25.3 New features

Issue #3981 - Add support for Postgres Server Logs for Text, CSV and JSON format in plain and tabular formats. Upgrade React to version 18.
Issue #6572 - Add a keyboard shortcut to close active tab panel.
Issue #7530 - Add support for highlighting selection matches in the query editor.

14.25.4 Housekeeping

Issue #7494 - Replace pgAdmin NW.js container with Electron container.
Issue #7501 - Updated to the latest version of the Notistack library.
Issue #7537 - Ensure that pgAdmin 4 is compatible with PostgreSQL v17.
Issue #7607 - Automatically apply virtualization in the DataGridView of SchemaView if the schema contains only one collection.
Issue #7623 - Add the git commit hash details to the About dialog.

14.25.5 Bug fixes

Issue #3199 - Fixed an issue where paste operation in query tool data grid should skip bytea columns and put the value as NULL instead.

Issue #4165 - Fixed an issue where the taskbar icon appeared as a red square for the query tool and schema diff when opened in a new window.

Issue #5345 - Fix issue with missing new added records in download file.

Issue #5610 - Fixed an issue where the File Open dialog did not show files without a dot extension.

Issue #6548 - Ensure pgAdmin never makes network requests to Google etc.

Issue #6571 - Fixed an issue where pop-up notifications from Object Explorer wouldn't get dismissed automatically if the Query Tool was opened.

Issue #7035 - Fixed the permission denied issue for functions of the pgstattuple extension when accessing statistics with a non-admin user.

Issue #7219 - Ensure processes related notifiers disappears.

Issue #7297 - Updated entrypoint.sh to utilize the email-validator package for email validation.

Issue #7511 - Fixed an issue where users could not insert characters at the desired location, as it was added to the end of the line.

Issue #7554 - Fixed an issue where sorting the database activity table on the dashboard by any column caused the details to expand in the wrong position.

Issue #7618 - Fix an issue where the preferences JSON file has no effect when an external database is used.

Issue #7626 - Fixed an issue where theme preview under theme options was broken in pgAdmin server mode.

Issue #7627 - Fixed an issue where users could not autofill their saved passwords in the connect server dialog in the browser.

Issue #7638 - Fixed an issue where Generate Script button should be disabled if no objects are selected in the schema diff result.

Issue #7639 - Fixed an issue where ERD Open/Save shorcuts were not working on Windows/Linux.

Issue #7660 - Add a precautionary check for the query tool connection cursor to fix the error 'NoneType' object has no attribute '_query'.

Issue #7662 - Fixed an issue where boolean values in node details of graphical explain plan were not interpreted correctly.

Issue #7663 - Fixed an issue where Reassign/Drop Owned dialog not opening for Role.

Issue #7679 - Ensure pgadmin does not try to connect to the server if saved password is not available.

Issue #7681 - Ensure that pgAdmin works when opened in an iframe.

14.26 Version 8.9

Release date: 2024-06-27

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.8.

14.26.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.26.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.3

14.26.3 New features

Issue #5932 - Provide option to set theme based on OS theme preference.

14.26.4 Housekeeping

Issue #7363 - Remove the usage of MUI makeStyles as it doesn't support React 18.

14.26.5 Bug fixes

Issue #6357 - Disable the query tool editor input if any SQL is being loaded to prevent users from typing.
Issue #7241 - Fixed an issue where resizable data editors in query tool should not be allowed to resize beyond the app window bounds.
Issue #7295 - Fixed new line indentation in query editor and add a user preference to disable it.
Issue #7306 - Ensure that a user can connect to a server using SSL certificates and identity files from a shared storage.
Issue #7316 - Fixed an issue where object explorer toolbar button not showing shortcut in the tooltip.
Issue #7414 - Add support for comments on RLS policy object.
Issue #7476 - Fixed an issue where changing a column name should reflect in all the constraints in table object dialog and ERD table dialog.
Issue #7481 - Fixed an issue where dark theme shows white background when all tabs are closed.
Issue #7516 - Ensure preferences can be loaded using preferences.json.
Issue #7523 - Fixed an issue where the schema diff incorrectly marked tables as different due to schema-qualified trigger functions in the trigger definitions.
Issue #7528 - Fixed an issue where backslash breaks syntax highlighting.
Issue #7536 - Search Objects dialog should focus on search input on open.
Issue #7542 - Fixed incorrect sorting of size in statistics tab.
Issue #7555 - Fixed an issue where query tool shortcuts for find/replace are not working.
Issue #7556 - Fixed migration failure while using external database.
Issue #7593 - Fixed an issue where query tool auto-complete stops working after connection change.
Issue #7605 - Fix the permissions issue in the pgAdmin installation directory on Debian and RHEL-8 platforms (CVE-2024-6238).
Issue #7616 - Fixed an issue where delete button in Users data was enabled for incorrect rows.

14.27 Version 8.8

Release date: 2024-06-06

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.7.

14.27.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.27.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.3

14.27.3 New features

14.27.4 Housekeeping

14.27.5 Bug fixes

Issue #5785 - Fix an issue where user authentication fails with special characters in password.
Issue #7480 - Fixed an issue where canceling a query without privilege does not display any message on query tool.
Issue #7520 - Fix the issue where docker with SSL v8.7 fails to start.
Issue #7524 - Fixed an issue where the size displayed as 'NaN B' for all databases in the statistics tab.
Issue #7526 - Fixed an issue where backup and restore operations failed with the error 'This build does not support compression with gzip'.

14.28 Version 8.7

Release date: 2024-05-30

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.6.

14.28.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.28.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.3

14.28.3 New features

Issue #4735 - Added support for the 'Add to macros' feature and fixed various usability issues.
Issue #6841 - Added support for executing the query at the cursor position in the query tool.
Issue #7192 - Changes in Query Tool, Debugger, and ERD Tool shortcuts to remove the use of Accesskey which will allow them to be customized.
Issue #7215 - Added support for viewing PGD Clusters.
Issue #7411 - Enhance the Delete dialog by highlighting the names of the objects to be deleted in bold.
Issue #7437 - Added support for platform Ubuntu 24.04 and Fedora 40.

14.28.4 Housekeeping

Issue #7419 - Upgrade react-table from v7 to v8.
Issue #7472 - Replace the current FontAwesome based PSQL tool icon with MUI Terminal icon.

14.28.5 Bug fixes

Issue #5762 - Ensure that Schema Diff does not indicate a table as different when the trigger names are the same but the trigger function body is different.
Issue #5849 - Disable ERD for system catalogs.
Issue #6060 - Disable Debugger for system catalogs.
Issue #6086 - Fixed an issue where drag and drop publication and subscription name in SQL editors was not working.
Issue #6464 - Fixed an issue of the pgAdmin window size increasing each time it was reopened.
Issue #7349 - Update the documentation for preferences dialog and keyboard shortcuts.
Issue #7439 - Fixed an issue where pgAdmin fails to start when Ubuntu OS is upgraded to a major version.
Issue #7458 - Remove query info notifier timeout field from Query Tool Preferences Dialog.
Issue #7485 - Fixed incorrect highlighting for C-Style escape strings in SQL editor.
Issue #7487 - Fixed an issue where the recover password button was enabled even when no email was provided.
Issue #7500 - Fixed an issue where resetting the password from the password reset link was not working.

14.29 Version 8.6

Release date: 2024-05-02

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.5.

14.29.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.29.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.1

14.29.3 New features

Issue #6728 - Added the new columns "last_seq_scan" and "last_idx_scan" from the pg_stat_all_tables and pg_stat_all_indexes tables respectively to the Statistics tab.

Issue #7163 - Added support for excluding multiple tables while taking Backup.

14.29.4 Housekeeping

Issue #7213 - Update UI library MUI from v4 to v5, more details here

Issue #7362 - Upgraded Flask, Flask-Security-Too, Werkzeug, and other dependencies, ensuring compatibility with Python 3.7.

14.29.5 Bug fixes

Issue #2410 - Fixed all input boxes in pgAdmin to show browser auto-fill only where it is relevant.

Issue #7173 - Install dbus-python, an in-direct dependency of the Keyring package as a system package for Debian platforms.

Issue #7275 - Fixed an issue where debugger was not scrolling automatically on stepping.

Issue #7282 - Fixed an XSS vulnerability in the /settings/store endpoint (CVE-2024-4216).

Issue #7294 - Fixed an issue where double dollar quoted code is treated as string in syntax highlighter.

Issue #7317 - Fixed an issue where pressing backspace should remove the spaces and not the entire tab width, on enabling 'Use spaces?' in the preferences.

Issue #7334 - Fixed an issue where incorrect select/exec scripts were generated for functions/procedures.

Issue #7372 - Fixed an issue where connection to the database is not automatically re-established after connectivity drop.

Issue #7384 - Fixed an issue when closing the view data second tab; it raises the error that the 'ViewCommand' object has no attribute 'auto_commit'.

Issue #7390 - Fixed violates check constraint issue when creating a pgAgent schedule.

Issue #7425 - Fixed Multi-Factor Authentication bypass vulnerability (CVE-2024-4215).

14.30 Version 8.5

Release date: 2024-04-04

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.5.

14.30.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.30.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.1

14.30.3 New features

Issue #5611 - Added support for provider, deterministic, version and RULES parameter while creating collation.

Issue #7098 - Added support for EDB Job Scheduler.

Issue #7216 - Added support for viewing Log Streaming replication Based Clusters.

Issue #7221 - Added support for UNIX socket in entrypoint.sh for Docker implementation.

14.30.4 Housekeeping

14.30.5 Bug fixes

Issue #4413 - Fixed an issue in Schema Diff where Columns with sequences get altered unnecessarily.

Issue #7111 - Fixed an issue where user was unable to share a newly registered server.

Issue #7116 - Bug fixes and improvements in pgAdmin CLI.

Issue #7139 - Fixed an issue where the 'Save Password' option for SSH tunneling password was consistently disabled.

Issue #7165 - Fixed schema diff wrong query generation for table, foreign table and sequence.

Issue #7210 - Fixed an issue where table properties were not updating from properties dialog.

Issue #7218 - Fixed an issue where maximize icon is missing from query tool panel.

Issue #7229 - Fix an issue in table dialog where changing column name was not syncing table constraints appropriately.

Issue #7248 - Fixed rollback and commit button activation on execute button click.

Issue #7255 - Fixed an issue where taking backup of a shared server was using server owner's user name.

Issue #7262 - Fix an issue in editor where replace option in query tool edit menu is not working on non-Mac OS.

Issue #7268 - Fix an issue in editor where Format SQL shortcut and multiline selection are not working.

Issue #7269 - Fix an issue in editor where "Use Spaces?" Preference of Editor is not working.

Issue #7271 - Fixed an issue where Triggers, Rules, Indexes were absent from the Schema Diff when comparing views.

Issue #7277 - Fix an issue in query tool where toggle case of selected text loses selection.

Issue #7299 - Fix query tool autocomplete results when cursor is in between the SQL query.

Issue #7305 - Fix an issue in query tool where custom keyboard shortcuts are not working for some.
Issue #7304 - Fixed the issue where the update-user CLI command doesn't change the password.
Issue #7308 - Fixed issue related to email authentication of Two-factor authentication.
Issue #7326 - Fixed a remote code execution issue in the validate binary path (CVE-2024-3116).

14.31 Version 8.4

Release date: 2024-03-07

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.3.

14.31.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.31.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.1

14.31.3 New features

Issue #6058 - Allow preferences customization using a configuration file.
Issue #7138 - Add support for JSON log format.
Issue #7204 - Add –yes option for skipping the confirmation prompt while deleting the user via CLI for scripting purpose.

14.31.4 Housekeeping

Issue #7097 - Upgrade CodeMirror from version 5 to 6.
Issue #7148 - Added documentation for Dashboard's System Statistics tab.
Issue #7187 - Separate the application name, branding & version information from the configuration file.
Issue #7234 - Upgrade python packages cryptography to 42.0.x and Flask-Security-Too to 5.3.x.

14.31.5 Bug fixes

Issue #6792 - Fix multiple issues where PasswordExecCommand was not working in server mode and PasswordExecCommand was not loaded when importing servers.
Issue #6808 - Fix the tabbed panel backward/forward shortcut for tabs.
Issue #7027 - Fixed an issue where dependencies and dependents were not showing if a composite type is used as an attribute in another composite type.
Issue #7164 - Fix an issue where constraint check control is enabled in the edit table dialog.
Issue #7165 - Fix an issue where the scripts created by generate script of Schema diff for Table with sequence was not working earlier.
Issue #7193 - Ensure that the OAuth2 session is logged out when users log out from pgAdmin.

Issue #7217 - Remove role related checks on the UI dashboard when terminating session/query and let PostgreSQL take care of it.

Issue #7225 - Fix an issue where type column in dependents/dependencies tab is not showing correct label.

Issue #7258 - Unsafe Deserialization and Remote Code Execution by an Authenticated user in pgAdmin 4 (CVE-2024-2044).

14.32 Version 8.3

Release date: 2024-02-09

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.2.

14.32.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.32.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.0

14.32.3 New features

Issue #4419 - Allow drag-n-drop columns collection tree node as comma separated columns.

Issue #6380 - Added support to rename columns in Views.

Issue #6392 - Added BYPASSRLS|NOBYPASSRLS option while creating a Role.

Issue #6450 - Added support for column storage syntax while creating table.

Issue #6557 - Use COOKIE_DEFAULT_PATH or SCRIPT_NAME in session cookie path.

Issue #6792 - Added configurable parameter to enable support for PasswordExecCommand in server mode.

14.32.4 Housekeeping

14.32.5 Bug fixes

Issue #5083 - Fixed an issue where format sql was messing up operator. Included many other feature changes, more details here

Issue #6785 - Fixed an issue where formatting inserts empty lines in specific case.

Issue #7053 - Add support for selecting a schema in the backup database dialog with no tables, mviews, views or foreign tables.

Issue #7055 - Fixed a UI border issue on the dependencies tab for columns with icon.

Issue #7073 - Fixed an issue where multiple errors were showing if user does not have connect privileges.

Issue #7085 - Fixed an issue where group membership information was displayed incorrectly.

Issue #7113 - Ensure that the correct SQL is generated when changing the column data type to “char”.

Issue #7153 - Fixed an issue pgAdmin fails to launch due to inconsistent PATH variable name on windows.

Issue #7166 - Fix a backend server error when creating a named restore point.
Issue #7175 - Fix wrong default for FORCE_LOWER in the FLASK_GRAVATAR module.

14.33 Version 8.2

Release date: 2024-01-11

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.1.

14.33.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.33.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.0

14.33.3 New features

Issue #2483 - Administer pgAdmin Users and Preferences Using the Command Line Interface (CLI).
Issue #5908 - Allow users to convert View/Edit table into a Query tool to enable editing the SQL generated.
Issue #6085 - Added copy server support, allowing the duplication of existing servers with the option to make certain modifications.
Issue #7016 - Added keep-alive support for SSH sessions when connecting to a PostgreSQL server via an SSH tunnel.

14.33.4 Housekeeping

Issue #6926 - Ensure that eventlet's subprocess should be used following the resolution of an issue with Python 3.12 by eventlet.

14.33.5 Bug fixes

Issue #6193 - Fixed an issue where query tool title did not change after "Save As" until any new change is made.
Issue #6781 - Fixed an issue where export servers was not adding extension if not specified.
Issue #6815 - Fixed an issue where pgAdmin imports servers to the wrong accounts for the external authentication.
Issue #7002 - Fixed an issue where an error occurred in the SQL tab when using an extended index(pgroonga).
Issue #7041 - Fixed an issue where changes done to a node using edit dialog are not reflecting on the properties tab if the properties tab is active.
Issue #7059 - Fixed an issue where DB Restrictions were not visible on the server dialog.
Issue #7061 - Ensure that the 'Dbo' schema is displayed as a regular schema rather than a system catalog schema.

Issue #7062 - Introduce LDAP configuration parameter LDAP_IGNORE_MALFORMED_SCHEMA to ignore fetching schema from the LDAP server.
Issue #7064 - Fixed an error-'amname' when generating ERD for database containing partition tables.
Issue #7066 - Fixed an issue where object explorer last tree state was not saving.
Issue #7070 - Fixed an issue where pgAgent job schedule dialog is not opening for edit.
Issue #7078 - Fixed an issue where user is not able to cancel or terminate active queries from dashboard.
Issue #7082 - Fixed browser autocomplete related issues on pgAdmin authentication related pages.
Issue #7091 - Fixed an issue where auto commit/rollback setting not persisting across query tool connection change.
Issue #7104 - Fixed an issue where Schema Diff not generating difference for missing columns.

14.34 Version 8.1

Release date: 2023-12-14

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v8.0.

14.34.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.34.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.0

14.34.3 New features

Issue #4580 - Add support for generating ERD for a schema.
Issue #6854 - Add support for creating a function with custom return type.

14.34.4 Housekeeping

Issue #6991 - Fixed several accessibility-related issues for enhanced usability.

14.34.5 Bug fixes

Issue #5471 - Ensure focus is not changed to ssh tunnel password input when user explicitly focus on server password input.
Issue #6095 - Provide a way to bypass the SSL cert verification for OAuth2 provider.
Issue #6488 - Fixed an issue where database name was missing in an error message if name contains any special characters.
Issue #6717 - Ensure that indexes created by constraints are visible in the object explorer when "Show system objects" is enabled.
Issue #6803 - Fixed an issue where reading process logs throws an error when DATA_DIR is moved to a networked drive.

Issue #6814 - Remove the 'Close Window' submenu specifically for OSX to prevent unintended closure of the entire application.

Issue #6842 - Rename all references of 'Execute query' to 'Execute script' to be more relevant.

Issue #6887 - Fixed an issue where syntax error was not highlighting in query tool.

Issue #6921 - Fixed an issue where on entering full screen, the option label is not changed to 'Exit Full Screen' in desktop mode.

Issue #6950 - Ensure that the Authentication Source in the drop-down of the UserManagement dialog aligns with the entries specified for AUTHENTICATION_SOURCES in the configuration file.

Issue #6958 - Reverse engineer serial columns when generating ERD for database/table.

Issue #6964 - Fixed an issue where the Schema was not visible in the dropdown for table properties or when creating a new table.

Issue #6968 - Fixed an issue where option key was not registering in PSQL tool.

Issue #6984 - Fixed an issue where the Vacuum option INDEX_CLEANUP have an incorrect value ('AUTO') for database versions < 14.

Issue #6989 - Fixed an issue where the pgAdmin page went blank when clicking the delete button in the User Management dialog.

Issue #7000 - Ensure that correct timezone is set for Docker deployments.

Issue #7011 - Fixed an issue where all rows and filter rows buttons of object explorer toolbar were disabled for views and other supported nodes.

Issue #7017 - Fixed an issue where schema diff tool is not loading preferences on start.

14.35 Version 8.0

Release date: 2023-11-23

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.8.

14.35.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14, 15, and 16

14.35.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.0

14.35.3 New features

Issue #2821 - Have close buttons on individual panel tabs instead of common.

Issue #4733 - Allow closing all the tabs, including SQL and Properties.

Issue #5394 - Changes in the context menu on panel tabs - Add close, close all and close others menu items.

14.35.4 Housekeeping

Issue #6441 - Update app bundle built to use notarytool instead of altool.
Issue #6479 - Replace the current layout library wcDocker with ReactJS based rc-dock.
Issue #6850 - Upgrade Flask, Werkzeug and other modules depends on the latest version of Flask.

14.35.5 Bug fixes

Issue #2986 - Fix an issue where the scroll position of panels was not remembered on Firefox.
Issue #5770 - Add DROP SQL for foreign keys in SQL generated by ERD when using WITH DROP option.
Issue #5807 - Fixed an issue where psql was not taking the role used to connect in server properties.
Issue #6017 - Fixed an issue where Geometry Viewer renders geometry incorrectly after trying to view 3D or non-4326 SRID geometry.
Issue #6459 - Fix the sorting of size on the statistics panel.
Issue #6487 - Fixed restoration of query tool database connection after dropping and re-creating the database with the same name.
Issue #6602 - Fix an issue where the default server-group is being deleted if the load-server json file contains no servers.
Issue #6720 - Fix an issue of the incorrect format (no indent) of SQL stored functions/procedures.
Issue #6769 - Server config information in the about dialog should be only visible to admin users.
Issue #6784 - Fixed an issue where Schema Diff does not work when the user language is set to any language other than English in Preferences.
Issue #6817 - Fixed the query generated when creating subscription where copy_data parameter was missing.
Issue #6820 - Ensure backup/restore/maintenance works with invalid pgpass file parameter.
Issue #6835 - Fix an issue where OAUTH_ADDITIONAL_CLAIMS does not recognise AzureAD with > 150 groups.
Issue #6840 - Fixed circular import error occurring while deploying cloud PostgreSQL instance from pgAdmin.
Issue #6874 - Fix an issue where the browser window stuck on spinning with an Oauth user without email.
Issue #6875 - Fix an issue where import/export data is not working for shared servers.
Issue #6877 - Remove the max length of 255 from password exec command in server configuration dialog.
Issue #6884 - Remove gettext from empty strings in the title of the storage graph.
Issue #6902 - Fixed an issue where the change server password is not working in desktop mode.
Issue #6904 - Fix a crash issue occurring when debugging a function with arguments when using pgAdmin with external config database.
Issue #6920 - Fix an issue in ERD tool where SQL generated is missing columns for the table.
Issue #6934 - Clear the password field in the config database on clear saved server password.
Issue #6962 - Fixed an issue where the data type of the array type was not visible for the column in the Foreign Table dialog.

14.36 Version 7.8

Release date: 2023-10-19

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.7.

14.36.1 Supported Database Servers

PostgreSQL: 12, 13, 14, 15, and 16

EDB Advanced Server: 12, 13, 14 and 15

14.36.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 16.0

14.36.3 New features

Issue #640 - Add support for foreign table's new functionality for PG 11 and above.
Issue #6229 - Allow setting custom username for shared servers, with default as username of server being shared.
Issue #6373 - Add 'GENERATED ALWAYS AS..' option while creating column constraints for Foreign Table.
Issue #6797 - GUI representation of the system's activity using the 'system_stats' extension.
Issue #6802 - Added 'load_balance_hosts' connection string parameter for PG 16 and above.

14.36.4 Housekeeping

Issue #6782 - Use PG16 as the default PostgreSQL version.

14.36.5 Bug fixes

Issue #4995 - Fixed an issue in ERD tool where the downloaded images have a few links cut.
Issue #5749 - Fixed an issue where user was not able to assign new/old columns as primary key once column with primary key is deleted.
Issue #6285 - Add support for setting prepare threshold in server connection.
Issue #6482 - Fixed an issue where the wrong message "Current database has been moved or renamed" is displayed when debugging any function.
Issue #6538 - Fixed an issue where Processes tab displays wrong server name in some scenario.
Issue #6579 - Fix an issue where global/native keyboard shortcuts are not working when any cell of data output grid has focus.
Issue #6666 - Fixed query history slowness issue by storing query only for those having certain threshold max length.
Issue #6674 - Fix an issue where foreign table column name becomes "none" if the user changes any column data type.
Issue #6718 - Pin the cryptography version to fix PyO3 modules initialisation error.
Issue #6790 - Ensure that the backup works properly for PG 16 on the latest docker image.

Issue #6799 - Fixed an issue where the user is unable to select objects on the backup dialog due to tree flickering.

Issue #6836 - Fixed an issue where non-super PostgreSQL users are not able to terminate their own connections from dashboard.

Issue #6851 - Fix an issue where scale in columns is not allowed to have value as 0 or below.

Issue #6858 - Fix an issue in graphical explain plan where query tool crashes when the plan has parallel workers details and sort node is clicked for details.

Issue #6865 - Fix an issue where user login is not working if username/email contains single quote in server mode.

14.37 Version 7.7

Release date: 2023-09-21

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.6.

14.37.1 Supported Database Servers

PostgreSQL: 11, 12, 13, 14 and 15

EDB Advanced Server: 11, 12, 13, 14 and 15

14.37.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.4

14.37.3 New features

Issue #642 - Added support to select/deselect objects in the Backup dialog.

Issue #4805 - Added all the new options of the 'WITH' clause in the subscription dialog.

Issue #6378 - Added USING method while creating the table.

Issue #6379 - Added compression method option while creating a column.

Issue #6383 - Added Strategy, Locale Provider, ICU Locale, ICU Rules, and OID options while creating a database.

Issue #6400 - Added USING method while creating the materialized view.

Issue #6736 - Add support for additional ID token claim checks for OAuth 2 authentication.

14.37.4 Housekeeping

Issue #2411 - Added the 'data type' column in the properties tab of the Columns collection node.

14.37.5 Bug fixes

Issue #6274 - Fix an issue where user is not able to change the password when SMTP is not configured.
Issue #6704 - Ensure user is redirected to login page after failed login.
Issue #6712 - Ensure that Materialized view size fields in "Statistics" should be human-readable.
Issue #6730 - Fix an issue where changing the password shows success but the new password is not working.
Issue #6738 - Fix an issue where login form doesn't appear if internal auth source is removed.
Issue #6764 - Fix a security related issue where an authenticated user can run remote command using validate binary path API (CVE-2023-5002).

14.38 Version 7.6

Release date: 2023-08-24

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.5.

14.38.1 Supported Database Servers

PostgreSQL: 11, 12, 13, 14 and 15

EDB Advanced Server: 11, 12, 13, 14 and 15

14.38.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.3

14.38.3 New features

Issue #2595 - Added Expression to CREATE INDEX.
Issue #3942 - Added cascade option while creating an extension.
Issue #5759 - Added 'Ignore Grants' option in the schema diff tool.
Issue #6004 - Added 'Ignore Tablespace' option in the schema diff tool.
Issue #6375 - Added support for ALTER INDEX column statistics.
Issue #6376 - Added unlogged option while creating a sequence.
Issue #6377 - Added all like options while creating a table.
Issue #6381 - Added support for SYSTEM, CONCURRENTLY and TABLESPACE options in REINDEX.
Issue #6382 - Added WAL option to EXPLAIN ANALYZE command.
Issue #6397 - Added new/missing options to the VACUUM command.
Issue #6415 - Added SKIP_LOCKED and BUFFER_USAGE_LIMIT option to Analyze command.
Issue #6448 - Add support for TRUNCATE trigger in foreign table.
Issue #6595 - Ensure that Schema Diff comparison results should be displayed in the sorted order.

14.38.4 Housekeeping

Issue #3702 - Generate software bill of materials as part of the package builds.
Issue #6588 - Added support for PostgreSQL and EPAS 16 to ensure it works without any errors.

14.38.5 Bug fixes

Issue #5454 - Fix incorrect redirection URL after authentication by removing fixed value set to SCRIPT_NAME environment variable in pgAdmin4.wsgi file.
Issue #6208 - Allow changing the POOL_SIZE and MAX_OVERFLOW config values of the pgAdmin config DB connection pool.
Issue #6252 - Fix an issue where query tool on shared server is throwing error if the pgAdmin config DB is external.
Issue #6420 - Fix the query tool issue where raise Notice from func/proc or code blocks are no longer displayed live.
Issue #6500 - Fix the issue where query tool window turns blank if the user tries to generate a graph on the result.
Issue #6624 - Fix an issue where changing MFA_SUPPORTED_METHODS breaks the MFA validation.
Issue #6630 - Fix an issue where pgAdmin 7.5 fails to render table SQL with extension loaded index method.
Issue #6639 - Fix an issue where cycle syntax was not added in SQL when creating new sequence from UI.
Issue #6651 - Fix an issue where the SET directive is excluded from the function header in the schema diff tool.
Issue #6660 - Fix a query tool error 'pgAdminThread' object has no attribute 'native_id'.
Issue #6664 - Ensure keyboard shortcut for query execution is disabled when query execution is in progress.

14.39 Version 7.5

Release date: 2023-07-27

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.4.

14.39.1 Supported Database Servers

PostgreSQL: 11, 12, 13, 14 and 15

EDB Advanced Server: 11, 12, 13, 14 and 15

14.39.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.3

14.39.3 New features

Issue #6369 - Added support to detach partitions using concurrently and finalize.
Issue #6374 - Added all supported index storage parameters while creating an index.
Issue #6416 - Added new/missing parameters to pg_dumpall (Backup Server).
Issue #6417 - Added new/missing parameters to pg_dump (Backup Objects).
Issue #6562 - Added new/missing parameters to pg_restore.

14.39.4 Housekeeping

Issue #6295 - Remove Bootstrap and jQuery from authentication pages and rewrite them in ReactJS.
Issue #6323 - Enable cluster deployment with gp3 volume for AWS & BigAnimal cloud providers.
Issue #6423 - Clarify the LICENSE file to indicate that it is the PostgreSQL Licence.
Issue #6532 - Remove unsupported PostgreSQL versions from the container.

14.39.5 Bug fixes

Issue #6163 - Fix an issue where queries can't complete execution.
Issue #6165 - Fixed an issue where Import Export not working when using pgpassfile.
Issue #6317 - Fix an issue where queries longer than 1 minute get stuck - Container 7.1
Issue #6356 - Fix an issue where queries get stuck with auto-completion enabled.
Issue #6364 - Fixed Query Tool/ PSQL tool tab title not getting updated on database rename.
Issue #6406 - Ensure user gets proper error if incorrect credentials are entered while authenticating AWS.
Issue #6489 - Fix an issue where the edit server fails in desktop mode if the server password is not stored.
Issue #6499 - Ensure that Backup, Restore, and Maintenance should work properly when pgpass file is used.
Issue #6501 - Fix the query tool auto-complete issue on the server reconnection.
Issue #6502 - Fix the query tool restore connection issue.
Issue #6509 - Fix the reconnecton issue if the PostgreSQL server is restarted from the backend.
Issue #6514 - Fix the connection and stability issues since v7, possibly related to background schema changes.
Issue #6515 - Fixed an issue where the query tool is unable to execute a query on Postgres 10 and below versions.
Issue #6524 - Fix the lost connection error in v7.4.
Issue #6531 - Fixed an issue where pgAdmin failed to setup role with hyphens in name.
Issue #6537 - Fixed an issue where filters are not working and query history shows empty queries.
Issue #6544 - Fix an issue where adding a sub-folder inside a folder is not working as expected in File Manager.
Issue #6556 - Fix an error 'list' object has no attribute 'strip' while attempting to populate auto-complete manually the first time.
Issue #6558 - Fixed an issue where ERD Tool can't load the saved pgerd file from Shared Storage.
Issue #6582 - Fix an issue where inserting more than 10 rows does not work correctly in View Data; only parts end up in the table.

14.40 Version 7.4

Release date: 2023-06-29

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.3.

14.40.1 Supported Database Servers

PostgreSQL: 11, 12, 13, 14 and 15

EDB Advanced Server: 11, 12, 13, 14 and 15

14.40.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.3

14.40.3 New features

Issue #6367 - Added support to drop databases using the 'WITH (FORCE)' option.
Issue #6368 - Add "[NULLS [NOT] DISTINCT]" option while creating an Index.
Issue #6370 - Added 'OR REPLACE' clause while creating trigger.
Issue #6371 - Added security_invoker option while creating a view.

14.40.4 Housekeeping

14.40.5 Bug fixes

Issue #5306 - Fix an issue where object explorer tree crashes occasionally.
Issue #6065 - Ensure that query tool shortcuts are working properly.
Issue #6258 - Add Password exec command and Expiration time to server export JSON and also allow them to import.
Issue #6266 - When opening pgAdmin the layout should be auto reset if it is corrupted. Reset layout menu should work if layout is corrupted while using pgAdmin.
Issue #6291 - Fix an issue where loading more rows indicator will not disappear if connection is lost.
Issue #6340 - Fix an encoding error when connecting through Pgbouncer.
Issue #6352 - Fix an issue where explain plan details is showing HTML escaped characters.
Issue #6354 - Fixed an issue where queries with temporary tables in the same transaction is not working.
Issue #6363 - Fixed an issue where preview images for themes were not loading.
Issue #6420 - Fix raise notice from func/proc or code blocks are no longer displayed live.
Issue #6431 - Fix an issue where PSQL is not working if the database name have quotes or double quotes.
Issue #6435 - Fix an issue where all the menus are enabled when pgAdmin is opened and no object is selected in the object explorer.

14.41 Version 7.3

Release date: 2023-06-06

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.2.

14.41.1 Supported Database Servers

PostgreSQL: 11, 12, 13, 14 and 15

EDB Advanced Server: 11, 12, 13, 14 and 15

14.41.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.3

14.41.3 New features

14.41.4 Housekeeping

14.41.5 Bug fixes

Issue #6136 - Fix an issue where editing a database object de-selects it on the browser tree.
Issue #6341 - Ensure that SSH Tunnel should work properly after upgrading to 7.2 from 7.1
Issue #6342 - Fixed an issue where pgadmin is unable to take the defined role.
Issue #6345 - Fixed an issue where Foreign Key with 3 or more columns are shown in the wrong order in SQL and Properties.
Issue #6353 - Ensure that the master password dialog should not be visible if the parameter MASTER_PASSWORD_REQUIRED is set to False.

14.42 Version 7.2

Release date: 2023-06-01

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.1.

14.42.1 Supported Database Servers

PostgreSQL: 11, 12, 13, 14 and 15

EDB Advanced Server: 11, 12, 13, 14 and 15

14.42.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.2

14.42.3 New features

Issue #3831 - Add Option to only show active connections on Dashboard.
Issue #4769 - Allow pgAdmin to retrive master password from external script/program.
Issue #5048 - Add an option to hide/show empty object collection nodes.
Issue #5123 - Added support to use standard OS secret store to save server/ssh tunnel passwords instead of master password in pgAdmin desktop mode.
Issue #5868 - Implement new PostgreSQL 15 features in publication dialog and SQL.

14.42.4 Housekeeping

14.42.5 Bug fixes

Issue #5789 - Fixed an issue where Foreign Key columns are shown in the wrong order in SQL and Properties.
Issue #5817 - Ensure that a new row should be added on top in the User Management dialog.
Issue #5926 - Fixed an issue where REVOKE ALL DDL in table SQL was added only for one role.
Issue #6003 - Indicate the user if all the server's children nodes are hidden from the preferences setting.
Issue #6026 - Tools menu should be toggled for "pause replay of wal" and "resume replay of wal".
Issue #6043 - Make the 'Connect to server' dialog a modal dialog.
Issue #6080 - pgAdmin icon not showing on taskbar on Windows 10.
Issue #6127 - Fixed an issue where properties were not visible for FTS Parsers, FTS Templates, MViews, and Rules in Catalog objects.
Issue #6147 - Heartbeat is getting logged, though no server is connected in pgAdmin.
Issue #6204 - Ensure that name can't be empty in edit mode for Primary Key and Index.
Issue #6221 - Fix circular reference error for the multirange data types in the query tool.
Issue #6247 - Fixed an issue where PSQL tool prompts for password if using password exec command.
Issue #6253 - Fix an issue in the register server when setting the role, an arbitrary SQL query can be fired.
Issue #6267 - Ensure the user is able to log in if the specified OAUTH2_USERNAME_CLAIM is present in the OAuth2 profile.
Issue #6278 - Use dependent instead of dependant in the message.
Issue #6279 - Fix incorrect number of foreign tables displayed. Show column comments in RE-SQL.
Issue #6280 - View SQL tab not quoting column comments.
Issue #6281 - VarChar Field Sizes are missing from Query's Grid header.
Issue #6331 - Separate multiple Blocking PIDs with delimiter on Dashboard.

14.43 Version 7.1

Release date: 2023-05-04

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v7.0.

14.43.1 Supported Database Servers

PostgreSQL: 11, 12, 13, 14 and 15

EDB Advanced Server: 11, 12, 13, 14 and 15

14.43.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.2

14.43.3 New features

Issue #2078 - Show object breadcrumbs path along with its comment on object hover.
Issue #3275 - Allow on demand record count setting to be changed per user using preferences.
Issue #3316 - Added support to show statistics for materialized views.
Issue #3318 - Added support to create an unnamed index.

14.43.4 Housekeeping

14.43.5 Bug fixes

Issue #5044 - Fixed an issue where query tool hangs for some time when multiple columns are selected to open geometry viewer.
Issue #5777 - Fixed an issue where the browser tree state is not remembered when reopening pgAdmin.
Issue #5820 - Fixed an issue where collation was set to none if we remove it while creating partitioned table.
Issue #5922 - Ensure that when pasting a row in query tool grid, default value is used for autogenerated/serial columns.
Issue #6059 - Show proper message if the debugger is stopped by the user.
Issue #6075 - Ensure that the save button is enabled when registering a new server fails due to an API error.
Issue #6077 - The search object, query tool, and psql tool menu should not be displayed for pgAgent.
Issue #6120 - Fixed error occurring while logging out from pgAdmin keeping a query tool opened.
Issue #6128 - Fix a SQL error occurring on roles dependents SQL.
Issue #6130 - Ensure to quote the primary key value if needed while deleting rows from the table.
Issue #6137 - Fixed error occurring while dumping the servers from CLI.
Issue #6138 - Throw an appropriate error when a table for which View/Edit data is open, is deleted, and query is executed.
Issue #6151 - Ensure that internal users are able to login when auth sources are [ldap, internal].
Issue #6158 - Fixed an issue with the properties tab not getting updated if the user updates the selected node.
Issue #6159 - Ensure that the ERD tool should work with the external database after moving to psycopg3.

Issue #6180 - Fixed an issue where PSQL is not working if the PGUSER env variable is set and service file is used for server connection details.

Issue #6183 - Mac crash when you press Command-Shift-C.

Issue #6189 - Fix an issue in View SQL when column level privileges are set with multiple roles.

Issue #6191 - Fixed an issue where Reset Password is not working after upgrading to latest flask-security-too.

Issue #6234 - Usernames/roles with special character are not double quoted when assigning privileges.

14.44 Version 7.0

Release date: 2023-04-13

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.21.

14.44.1 Supported Database Servers

PostgreSQL: 11, 12, 13, 14 and 15

EDB Advanced Server: 11, 12, 13, 14 and 15

14.44.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.2

14.44.3 New features

Issue #3298 - Auto expand row edit form when a new row is added for Primary Key, Foreign Key, Unique Constraint and Exclusion Constraint.

Issue #5014 - Added support for mounting shared storage in server mode.

Issue #5022 - Add a note on top of keyboard shortcuts preferences to show the Accesskey of the browser.

Issue #5750 - Added capability to deploy PostgreSQL servers on Google Cloud.

Issue #5805 - Added support of BigAnimal v3 API.

Issue #5854 - On pressing Ctrl+C on a tree object, copy the fully qualified name to clipboard.

Issue #5855 - Added option to create unique constraint with nulls not distinct.

14.44.4 Housekeeping

Issue #4734 - Rename the "Properties…" context menu option of the objects to "Edit Object…" and the "Browser" tree to "Object Explorer".

Issue #5011 - Upgrade from psycopg2 to psycopg3.

Issue #5701 - Remove Bootstrap and jQuery usage.

Issue #5830 - Add .ts and .tsx files under linter and fix linter issues.

Issue #5901 - Update SQLAlchemy, Flask, Flask-SQLAlchemy, and other packages to current versions.

14.44.5 Bug fixes

Issue #4423 - Fixed an issue where list of tables is not displayed in a SQL_ASCII database.

Issue #4784 - Handle errors occurring during decoding UTF-8 encoded query result data which contains ascii characters.

Issue #4884 - Fixed an issue where it is not possible to import csv data to tables having columns with german umlauts in their name.

Issue #4891 - Fixed 'rawunicodeescape' codec can't decode issue in a SQL_ASCII database.

Issue #5504 - Fixed an issue where incorrect view of text[] fields in query and table results when use other then UTF8 (win1251) codepage and symbols.

Issue #5735 - Show appropriate error message when master password is not set instead of 'Crypt key missing'.

Issue #5775 - Display the 'No menu available for this object' message if the selected tree node does not have any options.

Issue #5824 - Ensure that the user's storage directory is created when the users are created, as well as for those users whose directories have not yet been created.

Issue #5833 - Fixed an issue where user MFA entry was not getting delete after deleting a user.

Issue #5834 - Fixed issue where pgAgent jobs were not getting dropped from properties tab.

Issue #5874 - Make "using" and "with check" fields a textarea in the RLS policy.

Issue #5894 - Use fetch instead of axios to close connections in SQLEditor, ERD, Schema Diff and Debugger to ensure it completes.

Issue #5904 - Fixed an issue where the count query should not be triggered when the estimated count is less than zero.

Issue #5907 - Validate user inputs provided in configuration files before starting pgadmin server.

Issue #5916 - Fix an issue in search objects where objects were unable to locate occasionally.

Issue #5919 - While restoring the database connections due to lost server connection, ensure that the databases which were previously connected are only reconnected.

Issue #5921 - Ensure that when pasting rows the rows are added right below the selected rows for copying.

Issue #5929 - Dashboard graph Y-axis width should increase with label.

Issue #5934 - Ensure that default values are set only for insert statement if user does not provide any values, in case of updating existing values to blank it should be set to null.

Issue #5941 - Fixed an issue where migration on external database is not working.

Issue #5943 - Use http for SVG namespace URLs which were changed to https for SonarQube fixes.

Issue #5952 - Ensure that the schema diff tool should not allow comparison between Postgres Server and EDB Postgres Advanced Server.

Issue #5953 - Fixed error while executing continue in debugging session after some time of debug execution.

Issue #5955 - Fix an issue where query tool is stuck when running query after discarding changed data.

Issue #5958 - Fix an issue where new dashboard graphs are partially following theme colors.

Issue #5959 - Fix an issue where Backup, Restore, and Maintenance not working if connection timeout is set in the server dialog.

Issue #6018 - Change the foreground color of the code mirror text for Dark Theme.

Issue #6093 - Fix the dependents SQL of Roles which is throwing a type casting error on PostgreSQL 15.

Issue #6100 - Fixed the LDAP authentication issue for the simultaneous login attempts.(CVE-2023-1907)

Issue #6109 - Fixed asyncio random task error messages in Query tool.

Issue #6122 - Fixed CSV export from Query Tool results does not include all columns for multiple CTEs.

14.45 Version 6.21

Release date: 2023-03-09

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.20.

14.45.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13, 14 and 15

EDB Advanced Server: 10, 11, 12, 13, 14 and 15

14.45.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.1

14.45.3 New features

Issue #5832 - Allow changing cardinality notation in ERD to use Chen notation.
Issue #5842 - Add additional logging for successful logins and user creation.

14.45.4 Housekeeping

14.45.5 Bug fixes

Issue #5269 - Ensure that the schema diff tool should pick up the change in the column grants.
Issue #5685 - Ensure that Grant column permission to a view is visible in the SQL tab.
Issue #5747 - Ensure that content on the DDL comparison panel should get refreshed on selecting the object using the up and down arrow keys.
Issue #5756 - Fix for query tool prompting for unsaved changes even if no changes have been made.
Issue #5758 - Fixed an issue where lock layout menu was not in sync with preferences.
Issue #5760 - Fixed an issue where query was not pasted to editor after trojan source warning.
Issue #5764 - Fix an issue where the maintenance dialog for Materialized View gives an error.
Issue #5773 - Fixed an issue where Clear Saved Password should be disabled if the password is already cleared.
Issue #5790 - Fixed an issue where the user can't create trigger AFTER UPDATE OF.
Issue #5803 - Fix an issue where query tool is stripping spaces in grid cell.
Issue #5810 - Fix an issue where sequence owner is remove on sequence edit.
Issue #5822 - Do not allow to save invalid JSON in query tool JSON editor.
Issue #5847 - Fixed an issue where pgAdmin failed to connect when the Postgres password included special characters.
Issue #5870 - Ensure that the database migration does not fail with a NoSuchTableError exception.
Issue #5872 - Handle MERGE operation in query tool explain introduced in PostgreSQL 15.
Issue #5889 - Fixed an issue where the database server is not connected using a service file.
Issue #5909 - Fixed an issue where the file name in the query tool tab was not changing if another file is opened.

14.46 Version 6.20

Release date: 2023-02-09

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.19.

14.46.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13, 14 and 15

EDB Advanced Server: 10, 11, 12, 13, 14 and 15

14.46.2 Bundled PostgreSQL Utilities

psql, **pg_dump**, **pg_dumpall**, **pg_restore**: 15.1

14.46.3 New features

Issue #4728 - Added support for setting PostgreSQL connection parameters.

14.46.4 Housekeeping

Issue #4320 - Added bundled PG utilities in the release note.
Issue #5525 - Upgrade Flask-Migrate to 4.x.
Issue #5723 - Improve performance by removing signal-based zoom-in, zoom-out, etc functionality from the runtime environment.
Issue #5794 - Use uplot for Dashboard graphs to reduce CPU usage.

14.46.5 Bug fixes

Issue #5532 - Fixed an issue where the client cert location was not stored on the shared servers.
Issue #5567 - Fix orphan database connections resulting in an inability to connect to databases.
Issue #5702 - Fix an issue where role is used as username for newly added servers when opening query tool.
Issue #5705 - Ensure that all parts of the application recommend and enforce the same length of passwords.
Issue #5732 - Fixed an issue where Kerberos authentication to the server is not imported/exported.
Issue #5733 - Ensure that the system columns should not visible in the import/export data.
Issue #5746 - Increase the length of the value column of the setting table.
Issue #5748 - Fixed console error while attaching the partition.
Issue #5751 - Fix failing import servers CLI due to vulnerability fix.
Issue #5761 - Fix an issue where drag and drop object names is not working.
Issue #5763 - Ensure that keyboard hotkey to open query tool and search object should work properly.
Issue #5781 - Fixed an issue where Query history is not getting loaded with external database.
Issue #5796 - Ensure nested menu items are shown in quick search result.

14.47 Version 6.19

Release date: 2023-01-17

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.18.

14.47.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13, 14 and 15

EDB Advanced Server: 10, 11, 12, 13, 14 and 15

14.47.2 New features

Issue #5569 - Added support of AWS provider for BigAnimal cloud deployment.

14.47.3 Housekeeping

Issue #5563 - Allow YouTube video demo links to be added to appropriate pgAdmin documentation.
Issue #5615 - Rewrite pgAdmin main menu bar to use React.

14.47.4 Bug fixes

Issue #5487 - Fixed an issue where incorrect password used with shared server.
Issue #5541 - Ensure the browser tree does not freeze while rendering 10k+ nodes/objects.
Issue #5542 - Fixed an issue updating the schema node de-select the node in the tree if only one schema is present in the collection node.
Issue #5559 - Fixed tree flickering issue on scroll.
Issue #5577 - Fixed an issue where the default value of string for columns should wrap in quotes in the create script.
Issue #5586 - Fix the webserver and internal authentication setup issue.
Issue #5613 - Ensure the appbundle has correct permissions so that pgAdmin can be accessed by users other than owner.
Issue #5622 - Fixed an issue where the ignore owner flag is not working for some cases in the Schema Diff.
Issue #5626 - Fixed an issue where actions performed on the tree node should update the context menu options.
Issue #5627 - Ensure that the submenus under the trigger's context menu are enabled/disabled correctly.
Issue #5640 - Update boto3 & botocore to the latest version.
Issue #5641 - Fixed an issue where Geometry viewer does not show popup when columns are less than 3.
Issue #5647 - Fixed an issue where row count notification was disappearing automatically.
Issue #5661 - Fix select dropdown border issue.
Issue #5666 - Fixed a missing "jwks_uri" in metadata error that occurred when logging in with an oAuth2 provider like Azure or Google.
Issue #5675 - Fixed an issue where rename panel was losing focus when trying to add name if input box is empty.
Issue #5734 - Ensure that the authenticated users can't access each other's directories and files by providing relative paths.(CVE-2023-0241)

14.48 Version 6.18

Release date: 2022-12-19

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.17.

14.48.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13, 14 and 15

EDB Advanced Server: 10, 11, 12, 13, 14 and 15

14.48.2 New features

Issue #4088 - Enhancements to the ERD when selecting a relationship.
Issue #5503 - Added native menu support in desktop mode.

14.48.3 Housekeeping

14.48.4 Bug fixes

Issue #5453 - Fixed an issue where Transaction IDs were not found in session in the Query Tool.
Issue #5470 - Fixed an issue where tablespace was missing on partition tables in SQL.
Issue #5536 - Fixed an issue where properties tab was refreshing on tab change even if the selected node is same.
Issue #5551 - Fixed an issue with auto-complete not working as expected with double quotes.
Issue #5564 - Ensure that table statistics are sorted by size.
Issue #5598 - Fixed an issue while updating server node info removes the clear saved password menu.
Issue #5603 - Fixed an issue where master password was not set correctly with external config database.
Issue #5606 - Fixed an error in the collation create script for PG-15.
Issue #5629 - Fixed BigAnimal authentication aborted issue.
Issue #5637 - Ensure that the BigAnimal displays PG version 11-14 for Oracle compatible databases type.
Issue #5645 - Fixed a typo.

14.49 Version 6.17

Release date: 2022-12-02

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.16.

14.49.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13, 14 and 15

EDB Advanced Server: 10, 11, 12, 13, 14 and 15

14.49.2 New features

14.49.3 Housekeeping

Issue #5147 - Update the BigAnimal API version to V2.
Issue #5493 - Remove all traces of Backbone and Underscore.

14.49.4 Bug fixes

Issue #5488 - Fixed an issue where the wrong schema is displayed for a foreign key in the schema diff tool.
Issue #5495 - Ensure that the query history date format in Desktop mode matches the format of the locale of the pgadmin server.
Issue #5505 - Fixed an issue where the CSV file would not download if the CSV quote character length exceeded 1.
Issue #5513 - Ensure that DATA_DIR dependent folders/files are automatically created inside the specified DATA_DIR if they are not specified separately in the configuration file.
Issue #5539 - Improved error message to make it easier for users to understand.
Issue #5548 - Fixed an issue where editor position was wrong when editing data from result grid.
Issue #5575 - Ensure the query tool is launched successfully for the servers registered with the PostgreSQL service.
Issue #5593 - Ensure that only authorized and authenticated users can validate binary paths (CVE-2022-4223).

14.50 Version 6.16

Release date: 2022-11-18

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.15.

14.50.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13, 14 and 15

EDB Advanced Server: 10, 11, 12, 13, 14 and 15

14.50.2 New features

Issue #1832 - Added support for storing configurations of pgAdmin in an external database.
Issue #4756 - Added the ability to generate ERDs for tables.
Issue #5468 - Add the possibility to configure the Oauth2 claim which is used for the pgAdmin username.

14.50.3 Housekeeping

14.50.4 Bug fixes

Issue #2174 - Ensure that the browser tree should auto scroll to the selected node when expanding the server node.
Issue #4841 - Use SocketIO instead of REST for schema diff compare.
Issue #5066 - Ensure that users can use custom characters as CSV field separators/CSV quotes when downloading query results.
Issue #5058 - Ensure that the save button should be disabled by default on the Sort/Filter dialog in the query tool.
Issue #5098 - Fix an issue where the save button is enabled when the table properties dialog is opened.
Issue #5122 - Ensure that the spinner should be visible on the browser tree on node refresh.
Issue #5149 - Ensure the Generate ERD option is hidden if the connection to the database is not allowed.
Issue #5206 - Reposition the select dropdown when the browser is resized.
Issue #5281 - Ensure that autocomplete works properly with objects starting with double quotes.
Issue #5344 - Ensure that pgAdmin routes should have the SCRIPT_NAME prefix.
Issue #5424 - Ensure that the appropriate permissions are set on the key file before trying an SSL connection with the server in server mode.
Issue #5429 - Fixed an issue where parameters for roles were not visible.
Issue #5452 - The container deployment document should include the server.json file format.
Issue #5455 - Fixed an issue where the dependents tab wasn't working for PG 15.
Issue #5458 - Ensure that the browser path column in the search object shows the complete path.
Issue #5463 - Fixed an issue where the result grid was not working properly while trying to edit data by hitting Enter key.
Issue #5465 - Fixed an issue where the screen was freezing while closing the wcDocker panel.
Issue #5473 - Fixed an issue where AutoComplete was not working correctly due to incorrect regex.
Issue #5475 - Fixed an issue where the 'Confirm on close or refresh' setting was ignored when closing the query/ERD tool opened in the new tab.
Issue #5507 - Fixed an issue where pgadmin does not respect reverse proxy any more.
Issue #5521 - Fixed SocketIO calls when pgAdmin 4 server is running from a sub directory.
Issue #5522 - Ensure that the load file paths are children of the storage directory.
Issue #5533 - Use the shared server username when opening query tool.
Issue #5535 - Fixed an issue where the 'save_password' column threw an error for the shared server when using an external database.
Issue #5537 - Ensure that the correct error message in ERD for permission denied should be shown.

14.51 Version 6.15

Release date: 2022-10-20

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.14.

14.51.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13, 14 and 15

EDB Advanced Server: 10, 11, 12, 13, 14 and 15

14.51.2 New features

Issue #3491 - Added support for IAM token based authentication for AWS RDS or Azure DB.
Issue #4392 - Added support to specify the background fill color to the table nodes in the ERD tool.
Issue #4994 - Allow reordering table columns using drag and drop in ERD Tool.
Issue #4997 - Add option to generate SQL with DROP table DDL in ERD Tool.
Issue #5304 - Added high availability options to AWS deployment.
Issue #5390 - Expose the Gunicorn limit_request_line parameter in the container, with the default set to the maximum 8190.

14.51.3 Housekeeping

Issue #5065 - Use SocketIO instead of REST for fetching database tables data in ERD.
Issue #5293 - Ensure that the tooltips are consistent throughout the entire application.
Issue #5357 - Remove Python's 'Six' package completely.

14.51.4 Bug fixes

Issue #5101 - Ensure consistent orderings for ACLS when comparing schemas in the schema diff.
Issue #5132 - Ensure that the result grid column should take width as pre preferences setting on first execution.
Issue #5133 - Fixed an exception occur while taking backup and SSL certificates/keys are not found in the specified path.
Issue #5145 - Fixed intermittent error shown while OAuth2 login.
Issue #5167 - Ensure that the path to the psqlrc file is correct when multiple users open the PSQL tool at the same time.
Issue #5188 - Ensure that the continue/start button should be disabled if the user stops the Debugger for the procedures.
Issue #5210 - Ensure that the query tool creates a new tab with the appropriate user when pressing Alt+Shift+Q.
Issue #5212 - Added the close button for all the notifications of the notistack.
Issue #5249 - Added the ability to display the selected text from the query tool in the find/replace box.
Issue #5261 - Ensure that the search filter should be cleared when a new row is added to the user management.
Issue #5262 - Ensure that the user management dialog should not allow the same email addresses with different letter casings when creating users.

Issue #5277 - Fixed XSS vulnerability issues.
Issue #5296 - Ensure that the scroll position should be preserved for the result set in the query tool on tab change.
Issue #5308 - Ensure that the default value for a column should be used if it is made empty.
Issue #5327 - Fixed an issue where user was unable to select privileges in Safari.
Issue #5332 - Fixed console warning shown while updating database node from browser tree.
Issue #5338 - Fixed an issue where the prompt is not visible when clicking on the 'save results to file' button on the large data.
Issue #5352 - Fixed error occurring while LDAP authentication for a user with multiple email attributes.
Issue #5364 - Fixed an issue where notifications disappeared quickly.
Issue #5367 - Ensure that the correct value should be returned if an exception occurs while decoding the password.
Issue #5368 - Fixed the issue while downloading the file from the file manager.
Issue #5386 - Ensure that the login form is hidden if the authentication source is OAuth2 or Kerberos.
Issue #5397 - Fixed an issue where the password recovery link was not working.
Issue #5402 - Ensure that scroll bar on browser tree should be visible on windows resize.
Issue #5405 - Fixed the cross-site scripting vulnerability.
Issue #5427 - Fixed an issue where filtered rows were not working.

14.52 Version 6.14

Release date: 2022-09-22

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.13.

14.52.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13 and 14

EDB Advanced Server: 10, 11, 12, 13 and 14

14.52.2 New features

14.52.3 Housekeeping

Issue #4059 - Port schema diff to React. (RM #6133)
Issue #4060 - Remove Backgrid and Backform. (RM #6134)
Issue #5035 - Port the remaining components of the ERD Tool to React. (RM #7343)
Issue #5120 - Updated keyboard shortcut documentation. (RM #7446)
Issue #5260 - Remove Alertify from pgAdmin completely. (RM #7619)
Issue #5263 - Port search object dialog to React. (RM #7622)

14.52.4 Bug fixes

Issue #5144 - Ensure that if BigAnimal authentication is aborted, API calls should be stopped. (RM #7472)

Issue #5209 - Fixed an issue where pgAdmin failed to start due to bin path migration. (RM #7557)

Issue #5230 - Fixed an issue where backup does not work due to parameter 'preexec_fn' no longer being supported. (RM #7580)

Issue #5250 - Ensure that the browser tree should be refreshed after changing the ownership. (RM #7607)

Issue #5274 - Fixed the error message displayed when clicking the cloud server for which deployment is in progress. (RM #7636)

Issue #5275 - Fixed an issue where the wrong SQL displayed in difference if the user create an RLS policy on the table without a column. (RM #7637)

Issue #5282 - Ensure that the dump servers functionality works from setup.py. (RM #7644)

Issue #5284 - Ensure that the Import/Export server menu option is visible. (RM #7646)

Issue #5286 - Fixed API test case for change password in the server mode. (RM #7648)

Issue #5287 - Fixed an issue with the non-visibility of columns added prior to import/export data. (RM #7649)

Issue #5292 - Fixed an issue where textarea of the JSON Editor does not resize with dialog. (RM #7656)

Issue #5299 - Fixed ModuleNotFoundError when running setup.py to load/dump servers. (RM #7663)

Issue #5323 - Replace the language selection 'Brazilian' with 'Portuguese (Brazilian). (RM #7693)

Issue #5325 - Fixed an issue where server names with special characters are not displayed correctly in the process tab. (RM #7695)

Issue #5333 - Fixed an issue where ERD throws an error if variable is added to the column. (RM #7709)

Issue #5342 - Fixed an error while saving changes to the ERD table.

Issue #5343 - Fixes a redirect vulnerability when the user opens the pgAdmin URL.

14.53 Version 6.13

Release date: 2022-08-25

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.12.

14.53.1 Supported Database Servers

PostgreSQL: 10, 11, 12, 13 and 14

EDB Advanced Server: 10, 11, 12, 13 and 14

14.53.2 New features

Issue #3709 - Added support to show all background processes in separate panel.

Issue #7387 - Added support to create triggers from existing trigger functions in EPAS.

14.53.3 Housekeeping

Issue #7344 - Port Role Reassign dialog to React.
Issue #7345 - Port User Management dialog to React.
Issue #7404 - Port process watcher to React.
Issue #7462 - Remove the SQL files for the unsupported versions of the database server.
Issue #7567 - Port About dialog to React.
Issue #7568 - Port change user password and 2FA dialog to React.
Issue #7590 - Port change ownership dialog to React.
Issue #7595 - Update the container base image to Alpine 3.16 (with Python 3.10.5).
Issue #7602 - Fixed improper parsing of HTTP requests in Pallets Werkzeug v2.1.0 and below (CVE-2022-29361).

14.53.4 Bug fixes

Issue #7452 - Ensure that an error is thrown if clipboard access is not provided and change the copy rows shortcut.
Issue #7468 - Fixed an issue where the History tab is getting blank and showing an error after some queries are executed.
Issue #7481 - Fixed an issue where OWNED BY was incorrectly set to NONE when adding user privileges on the sequence.
Issue #7497 - Fixed an issue with the error message being displayed at the right place for Azure deployments.
Issue #7521 - Fixed an issue where the Query Editor loses focus when saving a query (Alt+s).
Issue #7527 - Fixed API test cases for Postgres 14.4.
Issue #7540 - Ensure that rename panel should work on view/edit panels.
Issue #7563 - Fixed an issue where autocomplete is not working after clearing the query editor.
Issue #7573 - Ensure that autocomplete does not appear when navigating code using arrow keys.
Issue #7575 - Fixed an issue where Alt-Shift-Q didn't work after creating a new query.
Issue #7579 - Fixed an issue where copy and pasting a row in the results grid doesn't set the default for boolean.
Issue #7586 - Fixed an issue with rendering geometry when selecting a complete column.
Issue #7587 - Ensure that the children of information_schema and pg_catalog node should be displayed.
Issue #7591 - Fixed column "none" does not exist issue, while comparing schema objects.
Issue #7596 - Fixed an issue where schema diff did not pick up the change in RLS policy.
Issue #7608 - Fixed an issue where the cloud deployment wizard creates the cluster with the High Availability even if that option is not selected.
Issue #7611 - Ensure that schema diff maintains view ownership when view definitions are modified.
Issue #7614 - Fixed crypt key is missing issue when logout from the pgAdmin.
Issue #7616 - Ensure that the next button should be disabled if the password did not match for Azure deployment.
Issue #7617 - Fixed an issue where Azure cloud deployment failed.
Issue #7625 - Fixed Spanish translations typo.
Issue #7630 - Ensure that If the trigger function definition is changed, drop and recreate the trigger in the schema diff.
Issue #7632 - Fixed an issue where a user could not authenticate using Azure CLI on OSX.
Issue #7633 - Ensure that the autofocus is on the input control for the master password and server password dialogs.

Issue #7641 - Pin Flask-SocketIO <= v5.2.0. The latest version does not support Werkzeug in production environments.

14.54 Version 6.12

Release date: 2022-07-28

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.11.

14.54.1 New features

Issue #4488 - Added option to trigger autocomplete on key press in the query tool.
Issue #4607 - Allow users to delete files/folders from the storage manager.
Issue #7389 - Allow users to search within the file/storage manager.
Issue #7486 - Added support for visualizing the graphs using Stacked Line, Bar, and Stacked Bar charts in the query tool.
Issue #7487 - Added support for visualise the graph using a Pie chart in the query tool.

14.54.2 Housekeeping

Issue #7313 - Port the file/storage manager to React.
Issue #7341 - Port change password dialog to React.
Issue #7342 - Port Master Password dialog to React.
Issue #7492 - Removing dynamic module loading and replacing it with static loading.
Issue #7546 - Port named restore point dialog to React.

14.54.3 Bug fixes

Issue #7428 - Preserve the settings set by the user in the import/export data dialog.
Issue #7471 - Ensure that the splash screen can be moved.
Issue #7508 - Fixed an issue where comments on indexes are not displayed.
Issue #7512 - Ensure that notices should not disappear from the messages tab.
Issue #7517 - Enable the start debugging button once execution is completed.
Issue #7518 - Ensure that dashboard graph API is not called after the panel has been closed.
Issue #7519 - Ensure that geometry should be shown for all the selected cells.
Issue #7520 - Fixed the JSON editor issue of hiding the first record.
Issue #7522 - Added support for Azure PostgreSQL deployment in server mode.
Issue #7523 - Fixed typo error for Statistics on the table header.
Issue #7524 - Fixed an issue where new folders cannot be created in the save dialog.

14.55 Version 6.11

Release date: 2022-06-30

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.10.

14.55.1 New features

Issue #2647 - Added mouse over indication for breakpoint area in the Debugger.
Issue #2648 - Added search text option to the Debugger panel.
Issue #7178 - Added capability to deploy PostgreSQL servers on Microsoft Azure.
Issue #7332 - Added support for passing password using Docker Secret to Docker images.
Issue #7351 - Added the option 'Show template databases?' to display template databases regardless of the setting of 'Show system objects?'.
Issue #7485 - Added support for visualise the graph using a Line chart in the query tool.

14.55.2 Housekeeping

Issue #6132 - Port Debugger to React.
Issue #7315 - Updates documentation for the Traefik v2 container deployment.
Issue #7411 - Update pgcli to latest release 3.4.1.
Issue #7469 - Upgrade Chartjs to the latest 3.8.0.

14.55.3 Bug fixes

Issue #7423 - Fixed an issue where there is no setting to turn off notifications in the Query Tool.
Issue #7440 - Fixed an issue where passwords entered in the 'Connect To Server' dialog were truncated.
Issue #7441 - Ensure that the Query Editor should be focused when switching between query tool tabs.
Issue #7443 - Fixed and issue where 'Use spaces' not working in the query tool.
Issue #7453 - Fixed an issue where the Database restriction is not working.
Issue #7460 - Fixed an issue where pgAdmin stuck while creating a new index.
Issue #7461 - Fixed an issue where the connection wasn't being closed when the user switched to a new connection and closed the query tool.
Issue #7468 - Skip the history records if the JSON info can't be parsed instead of showing 'No history'.
Issue #7502 - Fixed an issue where an error message is displayed when creating the new database.
Issue #7506 - Fixed permission denied error when deploying PostgreSQL in Azure using Docker.

14.56 Version 6.10

Release date: 2022-06-02

This release contains a number of bug fixes and new features since the release of pgAdmin 4 v6.9.

14.56.1 New features

Issue #7364 - Added the ability to resize columns on dashboard tables.

14.56.2 Housekeeping

Issue #7283 - PG 15 compatibility issues fixed.
Issue #7337 - Port connect server password dialog to React.

14.56.3 Bug fixes

Issue #6962 - Fixed the browser tree overlapping nodes and expansion issue.
Issue #7002 - Added the ability to detect and warn users about bidirectional Unicode characters.
Issue #7347 - Ensure that when Authentication buttons are disabled their text is visible in the Dark and High contrast theme.
Issue #7368 - Ensure that unwanted APIs should not be getting called for BigAnimal.
Issue #7372 - Tell Docker to always pull the latest base images when building containers.
Issue #7373 - Fixed an issue with geometry window zoom mouse scroll not working.
Issue #7374 - Fixed an issue when switching between connections in the Query Tool dropdown, the background and foreground colors should be changed.
Issue #7376 - Fixed an issue where a popup for unsaved changes appears when clicking on the open file button for a blank query editor.
Issue #7380 - Added support for multi-cell selection in the query tool grid.
Issue #7383 - Fixed an issue where Preferences are not saved when the dialog is maximized.
Issue #7388 - Fixed an issue where an error message fills the entire window if the query is long.
Issue #7393 - Ensure that the editor position should not get changed once it is opened.
Issue #7394 - Fixed an issue where geometry is not visible when a single cell is selected.
Issue #7399 - Added missing toggle case keyboard shortcuts to the query tool.
Issue #7402 - Ensure that Dashboard graphs should be refreshed on changing the node from the browser tree.
Issue #7403 - Fixed an issue where comments on domain constraints were not visible when selecting a domain node.
Issue #7405 - Ensure that null values are accepted for the numeric columns in react-data-grid.
Issue #7408 - Fixed an issue when a table has a column with an array type with length or precision, the column type is not selected while editing the table.

14.57 Version 6.9

Release date: 2022-05-12

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.8.

14.57.1 New features

Issue #3253 - Added status bar to the Query Tool.
Issue #3989 - Ensure that row numbers should be visible in view when scrolling horizontally.
Issue #6830 - Relocate GIS Viewer Button to the Left Side of the Results Table.
Issue #7179 - Added capability to deploy PostgreSQL servers on EDB BigAnimal.
Issue #7282 - Added options 'Ignore owner' and 'Ignore whitespace' to the schema diff panel.
Issue #7325 - Added support for Azure AD OAUTH2 authentication.

14.57.2 Housekeeping

Issue #6131 - Port query tool to React.
Issue #6746 - Improve the Kerberos Documentation.
Issue #7255 - Ensure the database and schema restriction controls are not shown as a drop-down.
Issue #7340 - Port data filter dialog to React.

14.57.3 Bug fixes

Issue #6725 - Fixed an issue where the Query tool opens on minimum size if the user opens multiple query tool Window quickly.
Issue #6958 - Only set permissions on the storage directory upon creation.
Issue #7026 - Fixed an issue where the Browser panel is not completely viewable.
Issue #7168 - Improvement to the Geometry Viewer popup to change the size of the result tables when column names are quite long.
Issue #7187 - Fixed an issue where the downloaded ERD diagram was 0 bytes.
Issue #7188 - Fixed an issue where the connection bar is not visible.
Issue #7231 - Don't strip binaries when packaging them in the server RPM as this might break cpython modules.
Issue #7252 - Ensure that Columns should always be visible in the import/export dialog.
Issue #7260 - Fixed an issue where an Empty message popup after running a query.
Issue #7262 - Ensure that Autocomplete should work after changing the connection.
Issue #7294 - Fixed an issue where the copy and paste row does not work if the first column contains no data.
Issue #7296 - Ensure that after deleting multiple objects from the properties panel, the browser tree should be refreshed.
Issue #7299 - Fixed sorting issue in the statistics panel.
Issue #7305 - Fixed an issue where the Dashboard Server Activity was showing old queries as active.
Issue #7307 - Fixed an issue where the table showed duplicate columns when creating multiple sequences on the same column.
Issue #7308 - Ensure that sorting should be preserved on refresh for Server Activity.
Issue #7322 - Fixed an issue while creating a new database throwing an error that failed to retrieve data.
Issue #7333 - Fixed an issue where the drag and drop table in ERD throws an error.
Issue #7339 - Ensure that the Dashboard column sort order should be remembered when the refresh button is clicked.

14.58 Version 6.8

Release date: 2022-04-07

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.7.

14.58.1 New features

Issue #7215 - Added transaction start time to Server activity sessions view.
Issue #7249 - Added support for unique keys in ERD.
Issue #7257 - Support running the container under OpenShift with alternate UIDs.

14.58.2 Housekeeping

Issue #7132 - Port Properties panel for collection node, Dashboard, and SQL panel in React.
Issue #7149 - Port preferences dialog to React.

14.58.3 Bug fixes

Issue #4256 - Fixed an issue where SQL for revoke statements are not shown for databases.
Issue #5836 - Adds a new LDAP authentication configuration parameter that indicates the case sensitivity of the LDAP schema/server.
Issue #6960 - Ensure that the master password dialog is popped up if the crypt key is missing.
Issue #7059 - Fixed an issue where the error is shown on logout when the authentication source is oauth2.
Issue #7176 - Fixed an issue where the browser tree state was not preserved correctly.
Issue #7197 - Fixed an issue where foreign key relationships do not update when the primary key is modified.
Issue #7216 - Ensure that the values of certain fields are prettified in the statistics tab for collection nodes.
Issue #7221 - Ensure objects depending on extensions are not displayed in Schema Diff.
Issue #7238 - Fixed an issue where foreign key is not removed even if the referred table is removed in ERD.
Issue #7239 - Fixed an issue where the newly added table is not visible under the Tables node on refresh.
Issue #7261 - Correct typo in the documentation.
Issue #7263 - Fixed schema diff issue where function's difference DDL was showing incorrectly when arguments had default values with commas.
Issue #7264 - Ensure that the correct user should be selected in the new connection dialog.
Issue #7265 - Fixed schema diff issue in which the option 'null' doesn't appear in the DDL statement for the foreign table.
Issue #7267 - Fixed an issue where unexpected error messages are displayed when users change the language via preferences.
Issue #7269 - Ensure that pgAdmin4 should work with latest jinja2 version.
Issue #7275 - Fixed 'Cannot read properties of undefined' error while creating the table via the ERD tool.

14.59 Version 6.7

Release date: 2022-03-14

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.6.

Note

Security Release

Please note that this release includes a security update to fix an issue where a user could upload files to directories outside of their storage directory, when using pgAdmin running in server mode.

Users running pgAdmin in server mode, including the standard container based distribution, should upgrade to this release as soon as possible.

This issue does not affect users running in desktop mode.

14.59.1 Bug fixes

Issue #7220 - Fixed a schema diff issue where difference SQL isn't generated when foreign key values for a table differ.

Issue #7228 - Fixed a schema diff issue where string separator '_$PGADMIN$_' is visible for identical user mappings.

Issue #7230 - Fixed an issue where pgAdmin 4 took ~75 seconds to display the 'Starting pgAdmin' text on the splash screen.

Issue #7233 - Ensure that upload paths are children of the storage directory (CVE-2022-0959).

14.60 Version 6.6

Release date: 2022-03-10

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.5.

14.60.1 New features

Issue #7177 - Added capability to deploy PostgreSQL servers on Amazon RDS.

14.60.2 Housekeeping

Issue #7180 - Rename the menu 'Disconnect Database' to 'Disconnect from database'.

14.60.3 Bug fixes

Issue #6956 - Fixed a schema diff issue in which user mappings were not compared correctly.
Issue #6991 - Fixed an issue where pgadmin cannot connect to LDAP when STARTTLS is required before bind.
Issue #6999 - Fixed an issue where a warning is flashed every time for an email address when authentication sources are internal and ldap.
Issue #7105 - Fixed an issue where the parent partition table was not displayed during autocomplete.
Issue #7124 - Fixed the schema diff issue where tables have different column positions and a column has a default value.
Issue #7152 - Added comments column for the functions collection node.
Issue #7172 - Allow users to scroll and enter input when there is a validation error.
Issue #7173 - Fixed an issue where the User Management dialog is not opening.
Issue #7181 - Ensure that the user should be able to add new server with unix socket connection.
Issue #7186 - Fixes an issue where the connect server/database menu was not updated correctly.
Issue #7202 - Ensure that Flask-Security-Too is using the latest version.

14.61 Version 6.5

Release date: 2022-02-11

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.4.

14.61.1 New features

Issue #7139 - Added support to open SQL help, Dialog help, and online help in an external web browser.

14.61.2 Housekeeping

Issue #7016 - Port Dependent, dependencies, statistics panel to React.
Issue #7017 - Port Import/Export dialog to React.
Issue #7163 - Rename the menu 'Disconnect Server' to 'Disconnect from server'.

14.61.3 Bug fixes

Issue #6916 - Added flag in runtime to disable GPU hardware acceleration.
Issue #7035 - Fixed an issue where connections keep open to (closed) connections on the initial connection to the database server.
Issue #7085 - Ensure that Partitioned tables should be visible correctly when creating multiple partition levels.
Issue #7086 - Correct documentation for 'Add named restore point'.
Issue #7100 - Fixed an issue where the Browser tree gets disappears when scrolling sequences.
Issue #7109 - Make the size blank for all the directories in the file select dialog.
Issue #7110 - Ensure that cursor should be focused on the first options of the Utility dialogs.
Issue #7118 - Ensure that JSON files should be downloaded properly from the storage manager.
Issue #7123 - Fixed an issue where restore generates incorrect options for the schema.
Issue #7126 - Fixed an issue where the F2 Function key removes browser panel contents.
Issue #7127 - Added validation for Hostname in the server dialog.

Issue #7135 - Enforce the minimum Windows version that the installer will run on.
Issue #7136 - Fixed an issue where the query tool is displaying an incorrect label.
Issue #7142 - Fixed an issue where a warning message was shown after database creation/modification.
Issue #7145 - Ensure that owner should be ignored while comparing extensions.
Issue #7146 - Fixed event trigger comparing issue in Schema Diff tool.
Issue #7150 - Fixed an issue when uploading a CSV throwing an error in the Desktop mode.
Issue #7151 - Fixed value error in the restore dialog.
Issue #7154 - Ensure that the layout should not be reset if a query tool is opened and pgAdmin is restarted.

14.62 Version 6.4

Release date: 2022-01-13

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.3.

14.62.1 New features

Issue #4803 - Added support to import/export server groups and servers from GUI.

14.62.2 Housekeeping

Issue #7018 - Port Restore dialog to React.
Issue #7019 - Port Maintenance dialog to React.

14.62.3 Bug fixes

Issue #6745 - Fixed an issue where Tablespace is created though an error is shown on the dialog.
Issue #7003 - Fixed an issue where Explain Analyze shows negative exclusive time.
Issue #7034 - Fixed an issue where Columns with default value not showing when adding a new row.
Issue #7075 - Ensure that help should be visible properly for Procedures.
Issue #7077 - Fixed an issue where the Owner is not displayed in the reverse engineering SQL for Procedures.
Issue #7078 - Fixed an issue where an operation error message pop up showing the database object's name incorrectly.
Issue #7081 - Fixed an issue in SQL generation for PostgreSQL-14 functions.
Issue #7093 - Fixed an issue where SubPlans may overlap other nodes & make them inaccessible in Graphical EXPLAIN View.
Issue #7096 - Ensure that Truncate and Reset statistics should work.
Issue #7102 - Fixed a schema diff issue where generated script adds unwanted line endings for Functions/Procedures/Trigger Functions.

14.63 Version 6.3

Release date: 2021-12-16

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.2.

14.63.1 New features

Issue #6543 - Added support for Two-factor authentication for improving security.
Issue #6872 - Include GSSAPI support in the PostgreSQL libraries and utilities on macOS.
Issue #7039 - Added support to disable the auto-discovery of the database servers.

14.63.2 Housekeeping

Issue #6088 - Replace Flask-BabelEx with Flask-Babel.
Issue #6984 - Port Backup Global, Backup Server, and Backup object dialog in React.
Issue #7004 - Replaced alertifyjs notifiers with React-based notistack.
Issue #7010 - Upgrade Flask to version 2.
Issue #7053 - Replace Alertify alert and confirm with React-based model dialog.

14.63.3 Bug fixes

Issue #6840 - Fixed an issue where tooltip data are not displaying on downloaded graphical explain plan.
Issue #6877 - Fixed schema diff owner related issue.
Issue #6906 - Fixed an issue where referenced table drop-down should be disabled in foreign key -> columns after one row is added.
Issue #6955 - Ensure that sort order should be maintained when renaming a server group.
Issue #6957 - Fixed schema diff related some issues.
Issue #6963 - Ensure that the user should be allowed to set the schema of an extension while creating it.
Issue #6978 - Increase the width of the scrollbars.
Issue #6986 - Fixed an issue where the user can't debug function with timestamp parameter.
Issue #6989 - Fixed an issue where the Change Password menu option is missing for internal authentication source when more than one authentication source is defined.
Issue #7005 - Fixed an issue where On-demand rows throw an error when any row cell is edited and saved it then scroll to get more rows.
Issue #7006 - Ensure that Python 3.10 and the latest eventlet dependency should not break the application.
Issue #7013 - Fix an RPM build issue that could lead to a conflict with python3 at installation.
Issue #7015 - Fixed an issue where the error is thrown while creating a new server using Add New Server from the dashboard while tree item is not selected.
Issue #7020 - Ensure that statue message should not hide the last line of messages when running a long query.
Issue #7024 - Fixed an issue where reverse engineering SQL is wrong for Aggregate.
Issue #7029 - Correct the SQL definition for function/procedure with the Atomic keyword in PG14.
Issue #7031 - Fixed an issue where SQLite database definition is wrong because the USER_ID FK references the table user_old which is not available.
Issue #7040 - Add "section" to the Debian package control files.
Issue #7044 - Update the dropzone version to 5.9.3 and Flask-SQLAlchemy to 2.5.*.
Issue #7046 - Fixed some accessibility issues.

Issue #7048 - Fixed unhashable type issue while opening the about dialog.
Issue #7064 - Ensure that the Owner should not be disabled while creating the procedure.
Issue #7071 - Fixed an issue where confirmation pop-up is hidden behind Reassign/Drop Owned Dialog.

14.64 Version 6.2

Release date: 2021-11-18

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.1.

14.64.1 New features

Issue #3834 - Added support of Aggregate and Operator node in view-only mode.
Issue #6953 - Ensure that users should be able to modify the REMOTE_USER environment variable as per their environment by introducing the new config parameter WEBSERVER_REMOTE_USER.

14.64.2 Housekeeping

14.64.3 Bug fixes

Issue #5427 - Fixed pgAdmin freezing issue by providing the error message for the operation that can't perform due to lock on the particular table.
Issue #6780 - Ensure that columns should be merged if the newly added column is present in the parent table.
Issue #6809 - Fixed an issue where pgAdmin is not opening properly.
Issue #6832 - Ensure that internal authentication when combined with other authentication providers, the order of internal source should not matter while picking up the provider.
Issue #6845 - Ensure that inherit table icon should be visible properly in the tree view.
Issue #6859 - Fixed an issue where properties panel is not updated when any object is added from the browser tree.
Issue #6896 - Ensure that the user should be able to navigate browser tree objects using arrow keys from keyboard.
Issue #6905 - Fixed an issue where database nodes are not getting loaded behind a reverse proxy with SSL.
Issue #6925 - Fixed SQL syntax error if select "Custom auto-vacuum" option and not set Autovacuum option to Yes or No.
Issue #6939 - Fixed an issue where older server group name displayed in the confirmation pop-up when the user removes server group.
Issue #6944 - Fixed an issue where JSON editor preview colours have inappropriate contrast in dark mode.
Issue #6945 - Fixed JSON Editor scrolling issue in code mode.
Issue #6940 - Fixed an issue where user details are not shown when the non-admin user tries to connect to the shared server.
Issue #6949 - Ensure that dialog should be opened when clicking on Reassign/Drop owned menu.
Issue #6954 - Ensure that changing themes should work on Windows when system high contrast mode is enabled.
Issue #6972 - Ensure that the Binary path for PG14 should be visible in the preferences.
Issue #6974 - Added operators and aggregates in search objects.
Issue #6976 - Fixed an issue where textarea should be allowed to resize and have more than 255 chars.
Issue #6981 - Fixed an issue where SQL for index shows the same column multiple times.
Issue #6988 - Reset the layout if pgAdmin4 detects the layout is in an inconsistent state.

14.65 Version 6.1

Release date: 2021-10-21

This release contains a number of bug fixes and new features since the release of pgAdmin4 6.0.

14.65.1 New features

Issue #4596 - Added support for indent guides in the browser tree.
Issue #6081 - Added support for advanced table fields like the foreign key, primary key in the ERD tool.
Issue #6241 - Added support to allow tables to be dragged to ERD Tool.
Issue #6529 - Added index creation when generating SQL in the ERD tool.
Issue #6657 - Added support for authentication via the webserver (REMOTE_USER).
Issue #6794 - Added support to enable/disable rules.

14.65.2 Housekeeping

14.65.3 Bug fixes

Issue #6719 - Fixed OAuth2 integration redirect issue.
Issue #6754 - Ensure that query highlighting color in the query tool should be less intensive.
Issue #6776 - Changed the label 'Inherits Tables?' to 'Is inherited?' as it misleading in the properties panel.
Issue #6790 - Fixed an issue where the user is unable to create an index with concurrently keyword.
Issue #6797 - Remove an extra blank line at the start of the SQL for function, procedure, and trigger function.
Issue #6802 - Fixed the issue of editing triggers for advanced servers.
Issue #6828 - Fixed an issue where the tree is not scrolling to the object selected from the search result.
Issue #6858 - Fixed object delete issue from the properties tab for the collection nodes.
Issue #6876 - Ensure that the Dashboard should get updated after connecting to the server.
Issue #6881 - Fixed an issue where the browser tree doesn't show all contents on changing resolution.
Issue #6882 - Ensure that columns should be displayed in the order of creation instead of alphabetical order in the browser tree.
Issue #6890 - Fixed background colour issue in the browser tree.
Issue #6891 - Added support for composite foreign keys in the ERD tool.
Issue #6900 - Fixed an issue where exclusion constraint cannot be created from table dialog if the access method name is changed once.
Issue #6905 - Fixed an issue where the users are unable to load the databases behind an HTTP reverse proxy.
Issue #6908 - Fixed an issue where each click to refresh the collection node, the number of objects decreasing by tens or more.
Issue #6912 - Fixed browser tree sort order regression issue.
Issue #6915 - Fixed an issue where the blank string is stored instead of NULL in the server table of SQLite database.
Issue #6928 - Ensure that the master password should be prompt when MASTER_PASSWORD_REQUIRED is set to True and AUTHENTICATION_SOURCES is webserver.
Issue #6929 - Ensure that only the table node should be allowed to drop on the ERD tool.
Issue #6930 - Fixed an issue where the existing server group is disappeared on rename it.
Issue #6935 - Fixed an issue where the wrong SQL is generated when deleting and renaming table columns together.

14.66 Version 6.0

Release date: 2021-10-07

This release contains a number of bug fixes and new features since the release of pgAdmin4 5.7.

14.66.1 New features

Issue #4211 - Added support for OWNED BY Clause for sequences.

14.66.2 Housekeeping

Issue #5741 - Revisit all the CREATE and DROP DDL's to add appropriate 'IF EXISTS', 'CASCADE' and 'CREATE OR REPLACE'.
Issue #6129 - Port browser tree to React.
Issue #6588 - Port object nodes and properties dialogs to React.
Issue #6687 - Port Grant Wizard to react.
Issue #6692 - Remove GPDB support completely.

14.66.3 Bug fixes

Issue #2097 - Fixed an issue where grant wizard is unresponsive if the database size is huge.
Issue #2546 - Added support to create the Partitioned table using COLLATE and opclass.
Issue #3827 - Ensure that in the Query History tab, query details should be scrollable.
Issue #6712 - Fixed an issue where collapse and expand arrows mismatch in case of nested IF.
Issue #6713 - Fixed an issue where the last message is not visible in the Debugger.
Issue #6723 - Updated query error row selection color as per dark theme style guide.
Issue #6724 - Fixed an issue where the drop cascade button enables for Databases.
Issue #6736 - Fixed an issue where Refresh view options are not working for materialized view.
Issue #6755 - Fixed keyerror issue in schema diff for 'attnum' and 'edit_types' parameter.
Issue #6759 - Ensure that RLS names should not be editable in the collection node of properties tab.
Issue #6798 - Fixed an issue where Execute button of the query tool gets disabled once we change anything in the data grid.
Issue #6834 - Ensure that SQL help should work for EPAS servers.

14.67 Version 5.7

Release date: 2021-09-09

This release contains a number of bug fixes and new features since the release of pgAdmin4 5.6.

14.67.1 New features

Issue #2538 - Added support for the truncate table with restart identity.
Issue #4264 - Make code folding case insensitive in the code mirror.
Issue #4629 - Added database and server information on the Maintenance process watcher dialog.
Issue #6495 - Allow the referenced table to be the same as the local table in one to many relationship for ERD Tool.
Issue #6625 - Make closing tabs to be smarter by focusing on the appropriate tab when the user closed a tab.
Issue #6691 - Set PSQLRC and PSQL_HISTORY env vars to apt. user storage path in the server mode.

14.67.2 Housekeeping

14.67.3 Bug fixes

Issue #4567 - Fixed an issue where privileges were revoked using SQL query on objects like tables that do not correctly show in SQL tab.
Issue #4815 - Fixed an issue where the user can not paste the updated table header in safari 12 and 13 browsers.
Issue #5849 - Ensure that trigger function SQL should have 'create or replace function' instead of 'create function' only.
Issue #6419 - Fixed blank screen issue on windows and also made changes to use NWjs manifest for remembering window size.
Issue #6531 - Fixed the export image issue where relation lines are over the nodes.
Issue #6544 - Fixed width limitation issue in PSQL tool window.
Issue #6564 - Fixed an issue where columns with sequences get altered unnecessarily with a schema diff tool.
Issue #6570 - Ensure that the lock panel should not be blocked for larger records.
Issue #6572 - Partially fixes the data output panel display issue.
Issue #6620 - Fixed an issue where whitespace in function bodies was not applied while generating the script using Schema Diff.
Issue #6627 - Introduced OAUTH2_SCOPE variable for the Oauth2 scope configuration.
Issue #6641 - Enables pgAdmin to retrieve user permissions in case of nested roles which helps to terminate the session for AWS RDS.
Issue #6663 - Fixed no attribute '_asdict' error when connecting the database server.
Issue #6668 - Fixed errors related to HTML tags shown in the error message for JSON editor.
Issue #6671 - Fixed UnboundLocalError where local variable 'user_id' referenced before assignment.
Issue #6682 - Renamed 'Auto rollback?' to 'Auto rollback on error?'.
Issue #6684 - Fixed the JSON editor issue of hiding the first record.
Issue #6685 - Ensure that deleting a database should not automatically connect to the next database.
Issue #6704 - Ensure that pgAdmin should not fail at login due to a special character in the hostname.
Issue #6710 - Fixed an issue where multiple query tool tabs getting closed for the single close event.

14.68 Version 5.6

Release date: 2021-08-12

This release contains a number of bug fixes and new features since the release of pgAdmin4 5.5.

14.68.1 New features

Issue #4904 - Added support to copy SQL from main window to query tool.
Issue #5198 - Added support for formatted JSON viewer/editor when interacting with data in a JSON column.

14.68.2 Housekeeping

Issue #6622 - Rename the "Resize by data?" to "Columns sized by" and disabled the 'Maximum column width' button if 'Columns sized by' is set to 'Column data'.

14.68.3 Bug fixes

Issue #6337 - Ensure that the login account should be locked after N number of attempts. N is configurable using the 'MAX_LOGIN_ATTEMPTS' parameter.
Issue #6369 - Fixed CSRF errors for stale sessions by increasing the session expiration time for desktop mode.
Issue #6448 - Fixed an issue in the search object when searching in 'all types' or 'subscription' if the user doesn't have access to the subscription.
Issue #6574 - Fixed an issue where paste is not working through Right-Click option on PSQL.
Issue #6580 - Fixed TypeError 'NoneType' object is not sub scriptable.
Issue #6586 - Fixed incorrect tablespace options in the drop-down for move objects dialog.
Issue #6618 - Fixed an issue where the titles in query tabs are different.
Issue #6619 - Fixed incorrect binary path issue when the user deletes the binary path from the preferences.
Issue #6643 - Ensure that all the required options should be loaded when the Range data type is selected while creating a custom data type.
Issue #6650 - Fixed dashboard server activity issue when active_since parameter is None.
Issue #6664 - Fixed an issue where even if the user is locked, he can reset the password and can login into pgAdmin.

14.69 Version 5.5

Release date: 2021-07-15

This release contains a number of bug fixes and new features since the release of pgAdmin4 5.4.

14.69.1 New features

Issue #1975 - Highlighted long running queries on the dashboards.
Issue #3893 - Added support for Reassign/Drop Owned for login roles.
Issue #3920 - Do not block the query editor window when running a query.
Issue #5940 - Added support for OAuth 2 authentication.
Issue #6559 - Added option to provide maximum width of the column when 'Resize by data?' option in the preferences is set to True.

14.69.2 Housekeeping

14.69.3 Bug fixes

Issue #4189 - Ensure that the Data Output panel can be snapped back after it is detached.
Issue #6388 - Fixed replace keyboard shortcut issue in the query tool on the normal keyboard layout.
Issue #6398 - Fixed an issue where detaching the query editor panel gives a blank white panel.
Issue #6427 - Remove leading whitespace and replace it with '[...] ' in the Query Tool data grid so cells don't look empty.
Issue #6448 - Fixed an issue in the search object when searching in 'all types' or 'subscription' if the user doesn't have access to the subscription.
Issue #6489 - Fixed an issue where Execute/Refresh button should not be disabled when we run the empty query.
Issue #6505 - Fixed an issue where the New Connection Drop Down has lost default maintenance database, auto-select, and tab-through functionality.
Issue #6536 - Fixed directory selection issue with the folder dialog.
Issue #6541 - Ensure that setting 'Open in new browser tab' should be visible, it should not be based on the value of 'ENABLE_PSQL'.
Issue #6547 - Fixed copy/paste issues for PSQL tool terminal.
Issue #6550 - Disable email deliverability check that was introduced in flask-security-too by default to maintain backwards compatibility.
Issue #6555 - Fixed Czech translation string for 'Login' keyword.
Issue #6557 - Fixed an issue where incorrect column name listed in the properties of Index.

14.70 Version 5.4

Release date: 2021-06-17

This release contains a number of bug fixes and new features since the release of pgAdmin4 5.3.

14.70.1 New features

Issue #1561 - Added browse button to select the binary path in the Preferences.
Issue #1591 - Added Grant Wizard option under Package node.
Issue #2341 - Added support to launch PSQL for the connected database server.
Issue #4064 - Added window maximize/restore functionality for properties dialog.
Issue #5370 - Added support to set the binary path for the different database server versions.
Issue #6231 - Added OS, Browser, Configuration details in the About dialog.
Issue #6395 - Added support for rotating the pgAdmin log file on the basis of size and age.
Issue #6524 - Support non-admin installation on Windows.

14.70.2 Housekeeping

Issue #4622 - Added RESQL/MSQL test cases for Table and its child nodes.
Issue #6225 - Updated Flask-Security-Too to the latest v4.
Issue #6460 - Added a mechanism to detect a corrupt/broken config database file.

14.70.3 Bug fixes

Issue #4203 - Fixed the issue of renaming the database by another user.
Issue #6404 - Ensure that the Query Tool connection string should not be changed as per the 'Query Tool tab title'.
Issue #6466 - Ensure that the user should be able to add members in Login/Role group while creating it.
Issue #6469 - Ensure that the calendar control should be disabled in the properties panel for Role.
Issue #6473 - Disable browser password saving in the runtime.
Issue #6478 - Fixed duplicate SQL issue for tables with more than one partition.
Issue #6482 - Fixed an issue where the Foreground Color property of server dialog does not work.
Issue #6513 - Fixed an issue where pgAdmin does not open after password reset in server mode.
Issue #6520 - Fixed an issue where a decimal number is appended for character varying fields while downloading the data in CSV format.

14.71 Version 5.3

Release date: 2021-05-20

This release contains a number of bug fixes and new features since the release of pgAdmin4 5.2.

14.71.1 New features

Issue #5954 - Added support to set auto width of columns by content size in the data output window.
Issue #6158 - Added support to connect PostgreSQL servers via Kerberos authentication.
Issue #6397 - Added "IF NOT EXISTS" clause while creating tables and partition tables which is convenient while using the ERD tool.

14.71.2 Housekeeping

14.71.3 Bug fixes

Issue #4436 - Fixed an issue where drag and drop object is not correct in codemirror for properties dialog.
Issue #5477 - Added support for cache bust webpack chunk files.
Issue #5555 - Fixed an issue where data is displayed in the wrong order when executing the query repeatedly.
Issue #5776 - Ensure that while connecting to the server using SSPI login, it should not prompt for the password.
Issue #6329 - Fixed an issue where the wrong SQL is showing for the child partition tables.
Issue #6341 - Fixed an issue where CSV download quotes the numeric columns.
Issue #6355 - Ensure that pgAdmin should not allow opening external files that are dragged into it.
Issue #6377 - Fixed an issue where schema diff does not create DROP DEFAULT statement for columns.
Issue #6385 - Ensure that Backup and Restore should work on shared servers.
Issue #6392 - Fixed an issue where the filter 'Include/Exclude By Selection' not working for null values.
Issue #6399 - Ensure that the user should not be able to add duplicate panels.
Issue #6407 - Added support for the creation of Nested Table and Varying Array Type for Advanced Server.
Issue #6408 - Fixed ModuleNotFoundError when running setup.py from outside of the root.
Issue #6409 - Fixed an issue where the current debug line is not visible in the 'Dark' theme.
Issue #6413 - Fixed an issue where duplicate columns are visible in the browser tree, which is owned by two sequences.
Issue #6414 - Fixed an issue where the Help message not displaying correctly on Login/Group role.
Issue #6416 - Added comment column in the properties panel for View and Materialized View collection node.
Issue #6417 - Fixed an issue where query editor is not being closed if the user clicks on the 'Don't Save' button.
Issue #6420 - Ensure that pgAdmin4 shut down completely on the Quit command.
Issue #6443 - Fixed an issue where file dialog showing incorrect files for the selected file types.
Issue #6444 - Fixed an issue where the user is not warned if Kerberos ticket expiration is less than 30 min while initiating a global backup.
Issue #6445 - Ensure that proper identification should be there when the server is connected using Kerberos or without Kerberos.

14.72 Version 5.2

Release date: 2021-04-22

This release contains a number of bug fixes and new features since the release of pgAdmin4 5.1.

14.72.1 New features

14.72.2 Housekeeping

Issue #5319 - Improve code coverage and API test cases for Server module.

14.72.3 Bug fixes

Issue #4001 - Updated docs and screenshots to cover the Notifications tab on the Query Tool.
Issue #5519 - Ensure that the query tool tab should be closed after server disconnection when auto-commit/auto-rollback is set to false.
Issue #5908 - Fixed an issue where shortcut keys are not working with manage macro.
Issue #6076 - Fixed an issue where correct error not thrown while importing servers and JSON file has incorrect/insufficient keys.
Issue #6082 - Ensure that the user should not be to change the connection when a long query is running.
Issue #6107 - Fixed flickering issue of the input box on check constraints.
Issue #6161 - Fixed an issue where the cursor shifts its focus to the wrong window for all the query tool related model dialogs.
Issue #6220 - Corrected the syntax for 'CREATE TRIGGER', use 'EXECUTE FUNCTION' instead of 'EXECUTE PROCEDURE' from v11 onwards.
Issue #6274 - Ensure that the strings in the LDAP auth module are translatable.
Issue #6293 - Fixed an issue where the procedure creation is failed when providing the Volatility option.
Issue #6306 - Fixed an issue while selecting the row which was deleted just before the selection operation.
Issue #6325 - Ensure that the file format for the storage manager should be 'All files' and for other dialogs, it should remember the last selected format.
Issue #6327 - Ensure that while comparing domains check function dependencies should be considered in schema diff.
Issue #6333 - Fixed sizing issue of help dialog for Query Tool and ERD Tool when open in the new browser tab.
Issue #6334 - Fixed SQL panel black screen issue when detaching it in runtime.
Issue #6338 - Added missing dependency 'xdg-utils' for the desktop packages in RPM and Debian.
Issue #6344 - Fixed cannot unpack non-iterable response object error when selecting any partition.
Issue #6356 - Mark the Apache HTTPD config file as such in the web DEB and RPM packages.
Issue #6367 - Fixed an issue where the Save button is enabled by default when open the table's properties dialog on PG 9.5.
Issue #6375 - Fixed an issue where users are unable to see data of the partitions using the View/Edit data option.
Issue #6376 - Fixed an issue where a connection warning should be displayed on the user clicks on explain or explain analyze and the database server is disconnected from the browser tree.
Issue #6379 - Fixed an issue where foreign data wrapper properties are not visible if the host option contains two host addresses.

14.73 Version 5.1

Release date: 2021-03-25

This release contains a number of bug fixes and new features since the release of pgAdmin4 5.0.

14.73.1 New features

Issue #5404 - Show the login roles that are members of a group role be shown when examining a group role.
Issue #6212 - Make the container distribution a multi-arch build with x86_64 and Arm64 support.
Issue #6268 - Make 'kerberos' an optional feature in the Python wheel, to avoid the need to install MIT Kerberos on the system by default.
Issue #6270 - Added '–replace' option in Import server to replace the list of servers with the newly imported one.
Issue #6271 - Added zoom scaling options with keyboard shortcuts in runtime.

14.73.2 Housekeeping

Issue #3976 - Use schema qualification while accessing the catalog objects.
Issue #6176 - Make the 'Save Data Changes' icon to be more intuitive.

14.73.3 Bug fixes

Issue #4014 - Fixed alignment issue under preferences for the German language.
Issue #4020 - Fixed color issue on the statistics tab for collection node in the safari browser.
Issue #4438 - Fixed an issue where adding/updating records fails if the table name contains percent sign.
Issue #4784 - Ensure that autovacuum and analyze scale factors should be editable with more than two decimals.
Issue #4847 - Fixed an issue where % displayed twice in explain analyze for query and table.
Issue #4849 - Rename text 'table' with 'relation' in the statistic tab for explain analyze.
Issue #4959 - Fixed an issue where the properties tab for collection nodes is unresponsive after switching the tabs.
Issue #5073 - Fixed an issue where the Save button is enabled for functions/procedures by default when open the properties dialog.
Issue #5119 - Fixed an issue where hanging symlinks in a directory cause select file dialog to break.
Issue #5467 - Allow underscores in the Windows installation path.
Issue #5628 - Remove the "launch now" option in the Windows installer, as UAC could cause it to run as an elevated user.
Issue #5810 - Ensure that cell content being auto selected when editing the cell data.
Issue #5869 - Ensure that SQL formatter should not add extra tabs and format the SQL correctly.
Issue #6018 - Fixed encoding issue when database encoding set to SQL_ASCII and name of the column is in ASCII character.
Issue #6159 - Ensure that the user should be able to kill the session from Dashboard if the user has a 'pg_signal_backend' role.
Issue #6206 - Ensure that the view/edit data panel should not be opened for unsupported nodes using the keyboard shortcut.
Issue #6227 - Ensure PGADMIN_DEFAULT_EMAIL looks sane when initialising a container deployment.
Issue #6228 - Improve the web setup script for Linux to make the platform detection more robust and overrideable.
Issue #6233 - Ensure that SQL formatter should not use tab size if 'Use spaces?' set to false.
Issue #6253 - Fixed an issue where the user is unable to create a subscription if the host/IP address for connection is 127.0.0.1.
Issue #6259 - Ensure that proper error message should be shown on the properties and statistics tab in case of insufficient privileges for a subscription.
Issue #6260 - Fixed an issue where the 'Create Slot' option is disabled in case of the same IP/host provided but the port is different.
Issue #6269 - Ensure the Python interpreter used by the runtime ignores user site-packages.

Issue #6272 - Fixed an issue where the user is not able to change the connection in Query Tool when any SQL file is opened.
Issue #6279 - Ensure that the venv activation scripts have the correct path in them on Linux.
Issue #6281 - Fixed an issue where schema diff showing wrong SQL when comparing triggers with different when clause.
Issue #6286 - Ensure that the template database should be visible while creating the database.
Issue #6292 - Fixed string index out of range error where the dependent tab is in focus and selecting any publication or table.
Issue #6294 - Fixed an issue where the dependent tab throwing an error when selecting any login/group role.
Issue #6307 - Fixed an issue where the incorrect values visible in the dependents tab for publication.
Issue #6312 - Fixed an issue where copy/paste rows in view data paste the wrong value for boolean type.
Issue #6316 - Ensure that the primary key should be visible properly in the table dialog.
Issue #6317 - Ensure that toggle buttons are accessible by most screen readers.
Issue #6322 - Fixed an issue where the top menu disappears when entering into the full screen for minimum screen resolution.
Issue #6323 - Ensure that the grantor name should be visible properly for the security tab in the table dialog.

14.74 Version 5.0

Release date: 2021-02-25

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.30.

14.74.1 New features

Issue #5091 - Make Statistics, Dependencies, Dependants tabs closable and the user can add them back using the 'Add panel' option.
Issue #5912 - Added support for Logical Replication.
Issue #5967 - Implemented runtime using NWjs to open pgAdmin4 in a standalone window instead of the system tray and web browser.
Issue #6148 - Added Quick Search functionality for menu items and help articles.
Issue #6153 - Added publication and subscription support in Schema Diff.
Issue #6170 - Ensure logs are not stored in the container, and only sent to the console.

14.74.2 Housekeeping

Issue #5017 - Use cheroot as the default production server for pgAdmin4.
Issue #6145 - Documentation of Logical Replication.
Issue #6195 - Documentation of runtime with NWjs.
Issue #6196 - Documentation of Quick Search support.
Issue #6207 - Updated the JS dependencies to the latest.

14.74.3 Bug fixes

Issue #5809 - Fixed an issue where the focus is not properly set on the filter text editor after closing the error dialog.
Issue #5871 - Ensure that username should be visible in the 'Connect to Server' popup when service and user name both specified.
Issue #6045 - Fixed autocomplete issue where it is not showing any suggestions if the schema name contains escape characters.
Issue #6087 - Fixed an issue where the dependencies tab showing multiple owners for the objects having shared dependencies.
Issue #6117 - Fixed an issue where the user is unable to update column-level privileges from the security tab.
Issue #6143 - Fixed an issue where shared server entries not getting deleted from SQLite database if the user gets deleted.
Issue #6157 - Fixed an issue where strike-through is not visible for rows selected for deletion after scrolling.
Issue #6163 - Fixed an issue where Zoom to fit button only works if the diagram is larger than the canvas.
Issue #6164 - Ensure that the diagram should not vanish entirely if zooming out too far in ERD.
Issue #6177 - Fixed an issue while downloading ERD images in Safari and Firefox.
Issue #6178 - Fixed an issue where the user unable to change the background color for a server.
Issue #6179 - Fixed an issue where Generate SQL displayed twice in the ERD tool.
Issue #6180 - Updated missing documentation for the 'Download Image' option in ERD.
Issue #6187 - Limit the upgrade check to run once per day.
Issue #6193 - Ensure that ERD throws a warning before closing unsaved changes if open in a new tab.
Issue #6197 - Fixed an issue where the ERD image is not properly downloaded.
Issue #6201 - Added SSL support for creating a subscription.
Issue #6208 - Fixed an issue where utility(Backup, Maintenance, ...) jobs are failing when the log level is set to DEBUG.
Issue #6230 - Fixed an issue where the user is not able to create the subscription.
Issue #6250 - Ensure DEB/RPM packages depend on the same version of each other.

14.75 Version 4.30

Release date: 2021-01-28

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.29.

14.75.1 New features

Issue #1802 - Added ERD Diagram support with basic table fields, primary key, foreign key, and DDL SQL generation.
Issue #5457 - Added support for Kerberos authentication, using SPNEGO to forward the Kerberos tickets through a browser.
Issue #6147 - Documentation of Kerberos support.
Issue #6152 - Documentation of ERD Diagram support.
Issue #6160 - Add a container option (PGADMIN_DISABLE_POSTFIX) to disable the Postfix server.

14.75.2 Housekeeping

Issue #5338 - Improve code coverage and API test cases for pgAgent.
Issue #6052 - Added connected pgAdmin user and connection name in the log file.
Issue #6079 - Updated mimetype from 'text/javascript' to 'application/javascript' as 'text/javascript' is obsolete.
Issue #6162 - Include PostgreSQL 13 utilities in the container.

14.75.3 Bug fixes

Issue #5282 - Added 'Count Rows' option to the partition sub tables.
Issue #5488 - Improve the explain plan details by showing popup instead of tooltip on clicking of the specified node.
Issue #5571 - Added support for expression in exclusion constraints.
Issue #5829 - Fixed incorrect log information for AUTHENTICATION_SOURCES.
Issue #5875 - Ensure that the 'template1' database should not be visible after pg_upgrade.
Issue #5905 - Fixed an issue where the Save button is enabled by default in Macro.
Issue #5906 - Remove extra line after Manage Macros menu while clearing all macros.
Issue #5907 - Ensure that 'Clear All Rows' should not work if there is no existing macro available and the user does not specify any value.
Issue #5929 - Fixed an issue where the server is disconnected error message displayed if the user creates Macro with invalid SQL.
Issue #5965 - Ensure that the macro query result should be download properly.
Issue #5973 - Added appropriate help message and a placeholder for letting users know about the account password expiry for Login/Group Role.
Issue #5997 - Updated Flask-BabelEx to the latest.
Issue #6046 - Fixed an issue where the state of the Save File icon does not match the dirty editor indicator.
Issue #6047 - Fixed an issue where the dirty indicator stays active even if all changes were undone.
Issue #6058 - Ensure that the rename panel should be disabled when the SQL file opened in the query tool.
Issue #6061 - Fixed extra parentheses issue around joins for Views.
Issue #6065 - Fixed accessibility issues in schema diff module.
Issue #6069 - Fixed an issue on refreshing files in Query Tool.
Issue #6075 - Fixed an issue where Non-admin user is unable to view shared server created using service.
Issue #6077 - Fixed accessibility issues in various dialogs.
Issue #6084 - Fixed TypeError exception in schema diff when selected any identical object.
Issue #6096 - Updated deployment documentation, refer correctly to uWSGI where Gunicorn had been referenced.
Issue #6098 - Fixed an issue of deleting records when the user tries to delete multiple records.
Issue #6120 - Ensure that the user should be able to specify an older date for the account expiration of the role/user.
Issue #6121 - Fixed an issue where the database list in the new connection window is not visible.
Issue #6122 - Added informative message when there is no difference found for schema diff.
Issue #6128 - Fixed an issue where sequences are not created.
Issue #6140 - Ensure that verbose logs should be visible for Utility(Backup, Maintenance) jobs.
Issue #6144 - Ensure that the current value of the sequence should be ignored while comparing using schema diff.

14.76 Version 4.29

Release date: 2020-12-10

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.28.

14.76.1 New features

14.76.2 Housekeeping

Issue #5328 - Improve code coverage and API test cases for Foreign Tables.
Issue #5337 - Improve code coverage and API test cases for Views and Materialized Views.
Issue #5343 - Improve code coverage and API test cases for Debugger.
Issue #6062 - Ensure that code coverage should cover class and function declarations.

14.76.3 Bug fixes

Issue #5886 - Fixed false error is shown while adding a new foreign key from the table dialog when a foreign key already exists with Auto FK Index set to true.
Issue #5943 - Ensure that folder rename should work properly in Storage Manager.
Issue #5974 - Fixed an issue where the debugger's custom tab title not applied when opened in the new browser tab.
Issue #5978 - Fixed an issue where dynamic tab title has not applied the first time for debugger panel.
Issue #5982 - Fixed documentation issue where JSON is not valid.
Issue #5983 - Added the appropriate server icon based on the server type in the new connection dialog.
Issue #5985 - Fixed an issue where the process watcher dialog throws an error for the database server which is already removed.
Issue #5991 - Ensure that dirty indicator (*) should not be visible when renaming the tabs.
Issue #5992 - Fixed an issue where escape character is shown when the server/database name has some special characters.
Issue #5998 - Fixed an issue where schema diff doesn't show the result of compare if source schema has tables with RLS.
Issue #6003 - Fixed an issue where an illegal argument is showing for trigger SQL when a trigger is created for View.
Issue #6022 - Fixed an issue where shared servers import is failing.
Issue #6072 - Fixed DLL load failed while importing bcrypt.

14.77 Version 4.28

Release date: 2020-11-12

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.27.

14.77.1 New features

Issue #3318 - Added support to download utility files at the client-side.
Issue #4230 - Added support to rename query tool and debugger tabs title.
Issue #4231 - Added support for dynamic tab size.
Issue #4232 - Added tab title placeholder for Query Tool, View/Edit Data, and Debugger.
Issue #5891 - Added support to compare schemas and databases in schema diff.

14.77.2 Housekeeping

Issue #5938 - Documentation of Storage Manager.

14.77.3 Bug fixes

Issue #4639 - Ensure that some fields should be disabled for the trigger in edit mode.
Issue #5736 - Fixed an issue where the validation error message is shown twice.
Issue #5760 - Ensure that non-superuser should be able to debug the function.
Issue #5842 - Ensure that query history should be listed by date/time in descending order.
Issue #5858 - Ensure that search object functionality works with case insensitive string.
Issue #5895 - Fixed an issue where the suffix for Toast table size is not visible in the Statistics tab.
Issue #5911 - Ensure that macros should be run on the older version of Safari and Chrome.
Issue #5914 - Fixed an issue where a mismatch in the value of 'Estimated row' for functions.
Issue #5919 - Added security related enhancements.
Issue #5923 - Fixed an issue where non-closeable tabs are getting closed.
Issue #5950 - Fixed an issue where a long file name is not visible on the process watcher dialog.
Issue #5953 - Fixed an issue where connection to the server is on wait state if a different user is provided.
Issue #5959 - Ensure that Grant Wizard should include foreign tables.

14.78 Version 4.27

Release date: 2020-10-15

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.26.

14.78.1 New features

Issue #1402 - Added Macro support.
Issue #2519 - Added support to view trigger function under the respective trigger node.
Issue #3794 - Allow user to change the database connection from an open query tool tab.
Issue #5200 - Added support to ignore the owner while comparing objects in the Schema Diff tool.
Issue #5857 - Added documentation for Macro support.

14.78.2 Housekeeping

Issue #5330 - Improve code coverage and API test cases for Functions.
Issue #5395 - Added RESQL/MSQL test cases for Functions.
Issue #5497 - Merged the latest code of 'pgcli' used for the autocomplete feature.

14.78.3 Bug fixes

Issue #4806 - Added useful message when the explain plan is not used and empty.
Issue #4855 - Fixed an issue where file extension is stripped on renaming a file.
Issue #5131 - Ensure that 'ctrl + a' shortcut does not move the cursor in SQL editor.
Issue #5417 - Fixed and improve API test cases for the schema diff tool.
Issue #5739 - Ensure that the import/export feature should work with SSH Tunnel.
Issue #5802 - Remove maximum length on the password field in the server dialog.
Issue #5807 - Fixed an issue where a column is renamed and then removed, then the drop SQL query takes the wrong column name.
Issue #5826 - Fixed an issue where schema diff is showing identical table as different due to default vacuum settings.
Issue #5830 - Fixed reverse engineering SQL where parenthesis is not properly arranged for View/MView definition.
Issue #5835 - Fixed 'can't execute an empty query' message if the user change the option of Auto FK Index.
Issue #5839 - Ensure that multiple extensions can be dropped from the properties tab.
Issue #5841 - Fixed an issue where the server is not able to connect using the service.
Issue #5843 - Fixed an issue where the 'PARALLEL UNSAFE' option is missing from reverse engineering SQL of function/procedure.
Issue #5845 - Fixed an issue where the query tool is not fetching more than 1000 rows for the table does not have any primary key.
Issue #5853 - Fixed an issue where 'Rows X' column values were not visible properly for Explain Analyze in Dark theme.
Issue #5855 - Ensure that the user should be able to change the start value of the existing sequence.
Issue #5861 - Ensure that the 'Remove Server' option should be visible in the context menu.
Issue #5867 - Fixed an issue where some properties are not being updated correctly for the shared server.
Issue #5882 - Fixed invalid literal issue when fetching dependencies for Materialized View.
Issue #5885 - Fixed an issue where the user is unable to change the macro name.

14.79 Version 4.26

Release date: 2020-09-17

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.25.

14.79.1 New features

Issue #2042 - Added SQL Formatter support in Query Tool.
Issue #4059 - Added a new button to the query tool toolbar to open a new query tool window.
Issue #4979 - Added shared server support for admin users.
Issue #5772 - Warn the user when connecting to a server that is older than pgAdmin supports.

14.79.2 Housekeeping

Issue #5332 - Improve code coverage and API test cases for Columns and Constraints (Index, Foreign Key, Check, Exclusion).
Issue #5344 - Improve code coverage and API test cases for Grant Wizard.
Issue #5774 - Improve code coverage and API test cases for Tables.
Issue #5792 - Added documentation for shared server support.

14.79.3 Bug fixes

Issue #4216 - Ensure that schema names starting with 'pg' should be visible in browser tree when standard_conforming_strings is set to off.
Issue #5426 - Adjusted the height of jobstep code block to use maximum space.
Issue #5652 - Modified the 'Commit' and 'Rollback' query tool button icons.
Issue #5722 - Ensure that the user should be able to drop the database even if it is connected.
Issue #5732 - Fixed some accessibility issues.
Issue #5734 - Update the description of GIN and GiST indexes in the documentation.
Issue #5746 - Fixed an issue where –load-server does not allow loading connections that use pg_services.
Issue #5748 - Fixed incorrect reverse engineering SQL for Foreign key when creating a table.
Issue #5751 - Enable the 'Configure' and 'View log' menu option when the server taking longer than usual time to start.
Issue #5754 - Fixed an issue where schema diff is not working when providing the options to Foreign Data Wrapper, Foreign Server, and User Mapping.
Issue #5764 - Fixed SQL for Row Level Security which is incorrectly generated.
Issue #5765 - Fixed an issue in the query tool when columns are having the same name as javascript object internal functions.
Issue #5766 - Fixed string indices must be integers issue for PostgreSQL < 9.3.
Issue #5773 - Fixed an issue where the application ignores the fixed port configuration value.
Issue #5775 - Ensure that 'setup-web.sh' should work in Debian 10.
Issue #5779 - Remove illegal argument from trigger function in trigger DDL statement.
Issue #5794 - Fixed excessive CPU usage by stopping the indefinite growth of the graph dataset.
Issue #5815 - Fixed an issue where clicking on the 'Generate script' button shows a forever spinner due to pop up blocker.
Issue #5816 - Ensure that the 'CREATE SCHEMA' statement should be present in the generated script if the schema is not present in the target database.
Issue #5820 - Fixed an issue while refreshing Resource Group.
Issue #5833 - Fixed an issue where custom sequences are not visible when show system objects are set to false.
Issue #5834 - Ensure that the 'Remove Server Group' option is available in the context menu.

14.80 Version 4.25

Release date: 2020-08-20

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.24.

14.80.1 New features

Issue #3904 - Replace charting library Flotr2 with ChartJS using React.
Issue #5126 - Modified schema diff tool to compare two databases instead of two schemas.
Issue #5610 - Add a –yes command line option to setup-web.sh to allow non-interactive use.

14.80.2 Housekeeping

Issue #5324 - Improve code coverage and API test cases for Foreign Servers and User Mappings.
Issue #5327 - Improve code coverage and API test cases for Schemas.
Issue #5336 - Improve code coverage and API test cases for Types.
Issue #5700 - Remove old Python 2 compatibility code.
Issue #5731 - Upgrade font awesome from v4 to v5.

14.80.3 Bug fixes

Issue #3767 - Ensure that the original file format should be retained when saving the same file in SQL editor.
Issue #3791 - Added missing comments in reverse engineering SQL for each column of a View.
Issue #4123 - Fixed an issue where debugger doesn't work if the search path is set other than 'public'.
Issue #4361 - Fixed ssh tunnel hang issue when the user tries to disconnect the server.
Issue #4387 - Fixed an issue where the user is not able to insert the data if the table and columns name contains special characters.
Issue #4810 - Fixed an issue where the user is not able to save the new row if the table is empty.
Issue #5429 - Ensure that the Dictionaries drop-down shows all the dictionaries in the FTS configuration dialog.
Issue #5490 - Make the runtime configuration dialog non-modal.
Issue #5526 - Fixed an issue where copying and pasting a cell with multiple line data will result in multiple rows.
Issue #5567 - Fixed an issue where conversion of bytea to the binary string results in an error.
Issue #5604 - Fixed an issue where the entire logs is in red text when the user runs backup and restore.
Issue #5632 - Ensure that the user will be able to modify the start value of the Identity column.
Issue #5646 - Ensure that RLS Policy node should be searchable using search object.
Issue #5664 - Fixed an issue where 'ALTER VIEW' statement is missing when the user sets the default value of a column for View.
Issue #5670 - Fixed an issue where the error message does not have a close button on utility dialogs.
Issue #5689 - Added the 'ORDER BY' clause for the privileges type to fix schema diff issue.
Issue #5708 - Correct TLS certificate filename in the container deployment docs.
Issue #5710 - Fixed an issue when comparing the table with a trigger throwing error in schema diff.
Issue #5713 - Corrected DROP SQL syntax for catalog.
Issue #5716 - Fixed an issue where ajax call continues to fire even after disconnecting the database server.
Issue #5724 - Clarify some of the differences when running in server mode in the docs.

Issue #5730 - Resolve schema diff dependencies by selecting the appropriate node automatically and maintain the order in the generated script.

14.81 Version 4.24

Release date: 2020-07-23

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.23.

14.81.1 New features

Issue #5235 - Support configuration files that are external to the application installation.
Issue #5484 - Added support for LDAP authentication with different DN by setting the dedicated user for the LDAP connection.
Issue #5583 - Added support for schema level restriction.
Issue #5601 - Added RLS Policy support in Schema Diff.
Issue #5622 - Added support for permissive/restricted policy type while creating RLS Policy.
Issue #5650 - Added support for LDAP anonymous binding.
Issue #5653 - Added High Contrast theme support.

14.81.2 Housekeeping

Issue #5323 - Improve code coverage and API test cases for Foreign Data Wrapper.
Issue #5326 - Improve code coverage and API test cases for Domain and Domain Constraints.
Issue #5329 - Improve code coverage and API test cases for FTS Configuration, FTS Parser, FTS Dictionaries, and FTS Template.

14.81.3 Bug fixes

Issue #3814 - Fixed issue of error message not getting displayed when filename is empty for backup, restore, and import/export.
Issue #3851 - Add proper indentation to the code while generating functions, procedures, and trigger functions.
Issue #4235 - Fixed tab indent issue on a selection of lines is deleting the content when 'use spaces == true' in the preferences.
Issue #5137 - Fixed save button enable issue when focusing in and out of numeric input field.
Issue #5287 - Fixed dark theme-related CSS and modify the color codes.
Issue #5414 - Use QStandardPaths::AppLocalDataLocation in the runtime to determine where to store runtime logs.
Issue #5463 - Fixed an issue where CSV download quotes numeric columns.
Issue #5470 - Fixed backgrid row hover issue where on hover background color is set for edit and delete cell only.
Issue #5530 - Ensure that the referenced table should be displayed on foreign key constraints.
Issue #5554 - Replace the runtime themes with ones that don't have sizing issues.
Issue #5569 - Fixed reverse engineered SQL for partitions when storage parameters are specified.
Issue #5577 - Include LICENSE and DEPENDENCIES [inventory] files in official packages.
Issue #5621 - Remove extra brackets from reverse engineering SQL of RLS Policy.
Issue #5629 - Fixed an issue where the user is able to edit properties when some of the collection nodes are selected.
Issue #5630 - Fixed an issue where installation of pgadmin4 not working on 32-bit Windows.

Issue #5631 - Fixed 'cant execute empty query' issue when remove the value of 'USING' or 'WITH CHECK' option of RLS Policy.

Issue #5633 - Ensure that create RLS Policy menu should not be visible for catalog objects.

Issue #5647 - Fixed an issue where difference DDL is showing the wrong SQL when changing the policy owner.

Issue #5662 - Fixed accessibility issue where few dialogs are not rendering properly when we zoomed in browser window 200% and screen resolution is low.

Issue #5666 - Added missing dependencies/dependent and corrected some wrongly identified.

Issue #5673 - Fixed an issue where fetching the schema throws an error if the database is not connected in Schema Diff.

Issue #5675 - Fixed CSRF errors when pgAdmin opened in an iframe on safari browser.

Issue #5677 - Fixed text color issue in explain analyze for the Dark theme.

Issue #5686 - Fixed issue where the user was not able to update policy if the policy is created with space.

14.82 Version 4.23

Release date: 2020-06-25

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.22.

14.82.1 New features

Issue #5468 - Added option to ignore the whitespaces while comparing objects in schema diff.

Issue #5500 - Added server group name while selecting servers in schema diff.

Issue #5516 - Added support of Row Security Policies.

Issue #5576 - Improve error messaging if the storage and log directories cannot be created.

14.82.2 Housekeeping

Issue #5325 - Improve code coverage and API test cases for Collations.

Issue #5574 - Cleanup Windows build scripts and ensure Windows x64 builds will work.

Issue #5581 - Documentation of Row Level Security Policies.

14.82.3 Bug fixes

Issue #3591 - Ensure that the query tool should display the proper error message while terminating the active session.

Issue #3669 - Ensure that proper error should be displayed for the deleted node.

Issue #3787 - Disabled the Stop process button after clicking it and added a message 'Terminating the process…' to notify the user.

Issue #4226 - Fixed an issue where select all checkbox only selects the first 50 tables.

Issue #5416 - Ensure that the query tool panel gets closed when clicking on the 'Don't Save' button.

Issue #5465 - Fixed an issue where the Edge browser version is showing wrong and warning message gets displayed.

Issue #5492 - Fixed an issue where the search object is unable to locate inherited tables and constraint filters are not working.

Issue #5507 - Fixed connection and version number detection issue when the database server is upgraded.

Issue #5521 - Fixed an issue when dumping servers from a desktop pgAdmin app by providing an option '–sqlite-path'.

Issue #5539 - Fixed typo in exception keyword.
Issue #5584 - Fixed an issue where two identical tables showing different by schema diff tool.
Issue #5592 - Ensure that pgadmin should be able to connect to the server which has password more than 1000 characters.

14.83 Version 4.22

Release date: 2020-05-28

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.21.

14.83.1 New features

Issue #5452 - Added connected pgAdmin user and connection name in the log file.
Issue #5489 - Show the startup log as well as the server log in the runtime's log viewer.

14.83.2 Housekeeping

Issue #5255 - Implement Selenium Grid to run multiple tests across different browsers, operating systems, and machines in parallel.
Issue #5333 - Improve code coverage and API test cases for Indexes.
Issue #5334 - Improve code coverage and API test cases for the Rules module.
Issue #5335 - Improve code coverage and API test cases for Triggers and Compound Triggers.
Issue #5443 - Remove support for Python 2.
Issue #5444 - Cleanup Python detection in the runtime project file.
Issue #5455 - Refactor pgAdmin4.py so it can be imported and is a lot more readable.
Issue #5493 - Search object UI improvements.
Issue #5525 - Cleanup and refactor the macOS build scripts.
Issue #5552 - Update dependencies in the Docker container.
Issue #5553 - Remove PG 9.4 utilities from the Docker container as it's now out of support.

14.83.3 Bug fixes

Issue #3694 - Gracefully informed the user that the database is already connected when they click on "Connect Database…".
Issue #4033 - Fixed an issue where clicking on the cross button of the alert box on the login page is not working.
Issue #4099 - Fixed the SQL help issue for EDB Postgres Advanced Server.
Issue #4223 - Ensure that maintenance job should be worked properly for indexes under a materialized view.
Issue #4279 - Ensure that file browse "home" button should point to $HOME rather than /.
Issue #4840 - Ensure that 'With OID' option should be disabled while taking backup of database server version 12 and above.
Issue #5001 - Fixed invalid literal issue when removing the connection limit for the existing role.
Issue #5052 - Fixed internal server error when clicking on Triggers -> 'Enable All' for partitions.
Issue #5398 - Fixed generated SQL issue for auto vacuum options.
Issue #5422 - Ensure that the dependencies tab shows correct information for Synonyms.
Issue #5434 - Fixed an issue where the newly added table is not alphabetically added to the tree.

Issue #5440 - Fixed list sorting issue in the schema diff tool.
Issue #5449 - Fixed an issue while comparing the two identical schemas using the schema diff tool.
Issue #5450 - Fixed an issue when renaming the column not added in the proper order.
Issue #5466 - Correct ipv4 "all interfaces" address in the container docs, per Frank Limpert.
Issue #5469 - Fixed an issue where select2 hover is inconsistent for the SSL field in create server dialog.
Issue #5473 - Fixed post-login redirect location when running in server mode under a non-default root.
Issue #5480 - Fixed an issue where the background job creation fails if there is only a version-specific python binary available in PATH.
Issue #5481 - Fixed data truncation issue when updating the data of type character with length.
Issue #5487 - Fixed an issue where if LDAP_SEARCH_BASE_DN is not set then, the value for LDAP_BASE_DN will be considered.
Issue #5496 - Fixed an issue where clicking on Select All button, not selecting all the options in pgAgent job scheduler.
Issue #5503 - Clarify and correct the docs on enabling the pl/debugger plugin on the server.
Issue #5510 - Fixed Unicode decode error 'utf-8' codec can't decode byte.

14.84 Version 4.21

Release date: 2020-04-30

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.20.

14.84.1 New features

Issue #2172 - Added search object functionality.
Issue #2186 - Added LDAP authentication support.
Issue #4636 - Added job step and job schedule disable icons to identify it quickly within the browser tree.
Issue #5181 - Added support for parameter toast_tuple_target and parallel_workers of the table.
Issue #5263 - Added support of Foreign Tables to the Schema Diff.
Issue #5264 - Added support of Packages, Sequences and Synonyms to the Schema Diff.
Issue #5348 - Documentation of LDAP authentication support.
Issue #5353 - Added an option to prevent a browser tab being opened at startup.
Issue #5399 - Warn the user if an unsupported, deprecated or unknown browser is detected.

14.84.2 Housekeeping

Issue #4620 - Add Reverse Engineered and Modified SQL tests for procedures.
Issue #4623 - Add Reverse Engineered and Modified SQL tests for pgAgent jobs.

14.84.3 Bug fixes

Issue #1257 - Ensure all object types have a "System XXX?" property.
Issue #2813 - Ensure that the password prompt should not be visible if the database server is in trust authentication mode.
Issue #3495 - Fixed an issue where the query tool unable to load the file which contains the BOM marker.
Issue #3523 - Fixed an issue where right-clicking a browser object does not apply to the object on which right-click was fired.
Issue #3645 - Ensure that the start and end date should be deleted when clear the selection for pgAgent Job.
Issue #3900 - Added multiple drop/delete functionality for the table constraints.
Issue #3947 - Fixed copy-paste row issues in View/Edit Data.
Issue #3972 - Modified keyboard shortcuts in Query Tool for OSX native support.
Issue #3988 - Fixed cursor disappeared issue in the query editor for some of the characters when zoomed out.
Issue #4180 - Fixed mouse click issue where it does not select an object in Browser unless the pointer is over the object.
Issue #4206 - Ensure that the grant wizard should be closed on pressing the ESC key.
Issue #4292 - Added dark mode support for the configuration dialog on Windows/macOS runtime.
Issue #4440 - Ensure the DROP statements in reverse engineered SQL are properly quoted for all objects.
Issue #4445 - Ensure all object names in the title line of the reverse-engineered SQL are not quoted.
Issue #4504 - Fixed an issue where like options should be disabled if the relation is not selected while creating a table.
Issue #4512 - Fixed calendar opening issue on the exception tab inside the schedules tab of pgAgent.
Issue #4545 - Fixed an issue wherein grant wizard the last object is not selectable.
Issue #4573 - Ensure that if the delimiter is set other than comma then download the file as '.txt' file.
Issue #4684 - Fixed encoding issue while saving data in encoded charset other than 'utf-8'.
Issue #4709 - Added schema-qualified dictionary names in FTS configuration to avoid confusion of duplicate names.
Issue #4856 - Enable the save button by default when a query tool is opened with CREATE or other scripts.
Issue #4858 - Fixed python exception error when user tries to download the CSV and there is a connection issue.
Issue #4864 - Make the configuration window in runtime to auto-resize.
Issue #4873 - Fixed an issue when changing the comments of the procedure with arguments gives error in case of overloading.
Issue #4946 - Fixed an issue when the user creates a temporary table with 'on commit drop as' clause.
Issue #4957 - Ensure that Constraint Trigger, Deferrable, Deferred option should be disabled when the user selects EDB-SPL function for the trigger.
Issue #4969 - Fixed an issue where changing the values of columns with JSONB or JSON types to NULL.
Issue #5007 - Ensure index dropdown should have existing indexes while creating unique constraints.
Issue #5043 - Fixed an issue where columns names should be visible in the order of their creation in the browser tree.
Issue #5053 - Fixed an issue where changing the columns in the existing view throws an error.
Issue #5157 - Ensure that default sort order should be using the primary key in View/Edit data.
Issue #5180 - Fixed an issue where the autovacuum_enabled parameter is added automatically in the RE-SQL when the table has been created using the WITH clause.
Issue #5210 - Ensure that text larger than underlying field size should not be truncated automatically.
Issue #5213 - Fixed an issue when the user performs refresh on a large size materialized view.

Issue #5227 - Fixed an issue where user cannot be added if many users are already exists.
Issue #5268 - Fixed generated SQL when any token in FTS Configuration or any option in FTS Dictionary is changed.
Issue #5270 - Ensure that OID should be shown in properties for Synonyms.
Issue #5275 - Fixed tab key navigation issue for parameters in table dialog.
Issue #5302 - Fixed an issue where difference SQL is not seen in the schema diff tool for Types.
Issue #5314 - Ensure that switch cell is in sync with switch control for accessibility.
Issue #5315 - Fixed an issue where schema diff showing changes in the identical domain constraints.
Issue #5350 - Fixed an issue where schema diff marks an identical table as different.
Issue #5351 - Fixed compilation warnings while building pgAdmin.
Issue #5352 - Fixed the rightmost and bottom tooltip crop issues in the explain query plan.
Issue #5356 - Fixed modified SQL issue while adding an exception in pgAgent job schedule.
Issue #5361 - Fixes an issue where pgAdmin4 GUI does not display properly in IE 11.
Issue #5362 - Fixed an issue where the identical packages and sequences visible as different in the schema diff tool.
Issue #5366 - Added alert message to Reset Layout if any of the panels from Query Tool failed to load.
Issue #5371 - Fixed tab key navigation for some dialogs.
Issue #5375 - Fixed an issue where the Mode cell of argument grid does not appear completely in the Functions dialog.
Issue #5383 - Fixed syntax error while refreshing the existing synonyms.
Issue #5387 - Fixed an issue where the mode is not shown in the properties dialog of functions/procedures if all the arguments are “IN” arguments.
Issue #5396 - Fixed an issue where the search object module unable to locate the object in the browser tree.
Issue #5400 - Fixed internal server error when the database server is logged in with non-super user.
Issue #5401 - Fixed search object issue when the object name contains special characters.
Issue #5402 - Fixed an issue where the checkbox is not visible on Configuration dialog in runtime for the dark theme.
Issue #5409 - Fixed validation issue in Synonyms node.
Issue #5410 - Fixed an issue while removing the package body showing wrong modified SQL.
Issue #5415 - Ensure that the query tool context menu should work on the collection nodes.
Issue #5419 - Ensure that the user should not be able to change the authentication source.
Issue #5420 - Ensure error should be handled properly when LDAP user is created with the same name.
Issue #5430 - Added title to the login page.
Issue #5432 - Fixed an issue where an internal user is not created if the authentication source is set to internal and ldap.
Issue #5439 - Fixed an issue where the user is not able to create a server if login with an LDAP account.
Issue #5441 - Fixed an issue where the search object not able to locate pg_toast_* tables in the pg_toast schema.
Issue #5447 - Fixed failed to fetch utility error when click on refresh(any option) materialized view.

14.85 Version 4.20

Release date: 2020-04-02

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.19.

14.85.1 New features

Issue #5261 - Added support of Collation, FTS Configuration, FTS Dictionary, FTS Parser and FTS Template to the Schema Diff.
Issue #5262 - Added support of Domain, Domain Constraints and Types to the Schema Diff.

14.85.2 Housekeeping

Issue #5271 - Enhance the color of switch control for both light and dark theme.
Issue #5284 - Added and fixed gettext usage for better translation coverage.

14.85.3 Bug fixes

Issue #4237 - Fix an issue where the user can not change the value of DateTime picker control using keyboard.
Issue #4608 - Fixed some accessibility issues in the dialogs.
Issue #4942 - Fixed chrome driver download utility issue for Ubuntu.
Issue #5128 - Change some colors and opacity to comply with WCAG color contrast standards.
Issue #5143 - Fix an accessibility issue to maximize the panel for all alertify dialog.
Issue #5221 - Improve logic to get the DDL statements as a part of the comparison.
Issue #5241 - Fixed tab key navigation issue for Grant Wizard.
Issue #5279 - Fixed Unicode character issue causing error on Python2 environment.
Issue #5292 - Fixed focus color issue for Alertify dialog buttons.

14.86 Version 4.19

Release date: 2020-03-05

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.18.

14.86.1 New features

Issue #5154 - Added accessibility support in AlertifyJS.
Issue #5170 - Added Czech language support.
Issue #5179 - Added Python 3.8 support.

14.86.2 Housekeeping

Issue #5088 - Improve code coverage and API test cases for the Event Trigger module.
Issue #5133 - Improvements in the UI for both default and dark themes.
Issue #5176 - Enhance logging by tracking stdout and stderr of subprocess when log level set to DEBUG.
Issue #5185 - Added option to override the class name of a label tag for select2 control.

14.86.3 Bug fixes

Issue #4955 - Changed the color of selected and hovered item for Select2 dropdown.
Issue #4996 - Improve the style of the highlighted code after query execution for Dark mode.
Issue #5058 - Ensure that AlertifyJS should not be visible as a title for alert dialog.
Issue #5077 - Changed background pattern for geometry viewer to use #fff for all themes.
Issue #5101 - Fix an issue where debugger not showing all arguments anymore after hitting SQL error while debugging.
Issue #5107 - Set proper focus on tab navigation for file manager dialog.
Issue #5115 - Fix an issue where command and statements were parsed incorrectly for Rules.
Issue #5142 - Ensure that all the transactions should be canceled before closing the connections when a server is disconnected using pgAdmin.
Issue #5184 - Fixed Firefox monospaced issue by updating the font to the latest version.
Issue #5214 - Update Flask-SQLAlchemy and SQLAlchemy package which is not working on Windows with Python 3.8.
Issue #5215 - Fix syntax error when changing the event type for the existing rule.

14.87 Version 4.18

Release date: 2020-02-06

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.17.

14.87.1 New features

Issue #2554 - Added support for a multi-level partitioned table.
Issue #3452 - Added a Schema Diff tool to compare two schemas and generate a diff script.
Issue #4762 - Allow screen-reader to read label & description of non-textable elements.
Issue #4763 - Allow screen-reader to identify the alert errors.
Issue #4770 - Added labels and titles after parsing and validating all the pgAdmin4 web pages for accessibility.
Issue #4993 - Set input controls as read-only instead of disabled will allow tab navigation in the properties tab and also allow screen readers to read it.

14.87.2 Housekeeping

Issue #5049 - Improve code coverage and API test cases for the CAST module.
Issue #5050 - Improve code coverage and API test cases for the LANGUAGE module.
Issue #5071 - Improve the test framework to run for multiple classes defined in a single file.
Issue #5072 - Updated wcDocker package which includes aria-label accessibility improvements.
Issue #5096 - Replace node-sass with sass for SCSS compilation.

14.87.3 Bug fixes

Issue #3812 - Ensure that path file name should not disappear when changing ext from the dropdown in file explorer dialog.
Issue #4410 - Fixed an issue while editing char[] or character varying[] column from View/Edit data throwing an error.
Issue #4511 - Fixed an issue where Grant wizard unable to handle multiple objects when the query string parameter exceeds its limit.
Issue #4601 - Added tab navigation on close buttons for all the panels and create/properties dialog.
Issue #4827 - Fix column resizable issue in the file explorer dialog.
Issue #5000 - Logout the pgAdmin session when no user activity of mouse move, click or keypress.
Issue #5025 - Fix an issue where setting STORAGE_DIR to empty should show all the volumes on Windows in server mode.
Issue #5065 - Updated the incorrect icon used for the cast node on refresh.
Issue #5066 - Fix an issue where refreshing a package results in the change in the object completely.
Issue #5074 - Fix an issue where select, insert and update scripts on tables throwing an error.
Issue #5076 - Ensure Postfix starts in the container, now it runs as non-root by default.
Issue #5116 - Fixed an issue where Save Password control disappears after clicking on it while creating a server.

14.88 Version 4.17

Release date: 2020-01-09

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.16.

14.88.1 New features

Issue #4764 - Allow screen-reader to read relationship attributes in nested elements.
Issue #5060 - Ensure all binaries are securely signed and linked with the hardened runtime in the macOS bundle

14.88.2 Housekeeping

Issue #4988 - Refactored SQL of Table's and it's child nodes.
Issue #5023 - Refactored SQL of Views and Materialized Views.
Issue #5024 - Refactored SQL of Functions and Procedures.
Issue #5038 - Added support for on-demand loading of items in Select2.
Issue #5048 - Added code coverage tool for pgAdmin.

14.88.3 Bug fixes

Issue #4198 - Fix syntax highlighting in code mirror for backslash and escape constant.
Issue #4506 - Fix an issue where clicking on an empty textbox like fill factor or comments, considers it as change and enabled the save button.
Issue #4633 - Added support to view multilevel partitioned tables.
Issue #4842 - Ensure that constraints, indexes, rules, triggers, and compound triggers should be created on partitions.
Issue #4943 - Added more information to the 'Database connected/disconnected' message.
Issue #4950 - Ensure that the user should be able to select/modify tablespace for the partitioned table on v12 and above.
Issue #4999 - Rename some internal environment variables that could conflict with Kubernetes.
Issue #5004 - Fix vulnerability issues reported by 'yarn audit'. Replace the deprecated uglifyjs-webpack-plugin with a terser-webpack-plugin.
Issue #5008 - Ensure that the error message should not be displayed if Tablespace is not selected while creating the index.
Issue #5009 - Fix an issue where operator, access method and operator class is not visible for exclusion constraints.
Issue #5013 - Add a note to the documentation about the use of non-privileged ports on filesystems that don't support extended attributes when running the container.
Issue #5047 - Added tab navigation for tabs under explain panel in query tool.
Issue #5068 - Fix an issue where the table is not created with autovacuum_enabled and toast.autovacuum_enabled for PG/EPAS 12.

14.89 Version 4.16

Release date: 2019-12-12

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.15.

Warning

Warning: This release includes a change to the container distribution to run pgAdmin as a non-root user. Those users of the container who are running with mapped storage directories may need to change the ownership on the host machine, for example:

```
sudo chown -R 5050:5050 <host_directory>
```

14.89.1 New features

Issue #4396 - Warn the user on changing the definition of Materialized View about the loss of data and its dependent objects.
Issue #4435 - Allow drag and drop functionality for all the nodes under the database node, excluding collection nodes.
Issue #4711 - Use a 'play' icon for the Execute Query button in the Query Tool for greater consistency with other applications.
Issue #4772 - Added aria-label to provide an invisible label where a visible label cannot be used.
Issue #4773 - Added role="status" attribute to all the status messages for accessibility.
Issue #4939 - Run pgAdmin in the container as a non-root user (pgadmin, UID: 5050)
Issue #4944 - Allow Gunicorn logs in the container to be directed to a file specified through GUNICORN_ACCESS_LOGFILE.

Issue #4990 - Changed the open query tool and data filter icons.

14.89.2 Housekeeping

Issue #4696 - Add Reverse Engineered and Modified SQL tests for Materialized Views.
Issue #4807 - Refactored code of table and it's child nodes.
Issue #4938 - Refactored code of columns node.

14.89.3 Bug fixes

Issue #3538 - Fix issue where the Reset button does not get enabled till all the mandatory fields are provided in the dialog.
Issue #4220 - Fix scrolling issue in 'Users' dialog.
Issue #4516 - Remove the sorting of table headers with no labels.
Issue #4659 - Updated documentation for default privileges to clarify more on the grantor.
Issue #4674 - Fix query tool launch error if user name contains HTML characters. It's a regression.
Issue #4724 - Fix network disconnect issue while establishing the connection via SSH Tunnel and it impossible to expand the Servers node.
Issue #4761 - Fix an issue where the wrong type is displayed when changing the datatype from timestamp with time zone to timestamp without time zone.
Issue #4792 - Ensure that the superuser should be able to create database, as the superuser overrides all the access restrictions.
Issue #4818 - Fix server connection drops out issue in query tool.
Issue #4836 - Updated the json file name from 'servers.json' to 'pgadmin4/servers.json' in the container deployment section of the documentation.
Issue #4878 - Ensure that the superuser should be able to create role, as the superuser overrides all the access restrictions.
Issue #4893 - Fix reverse engineering SQL issue for partitions when specifying digits as comments.
Issue #4923 - Enhance the logic to change the label from 'Delete/Drop' to 'Remove' for the server and server group node.
Issue #4925 - Shown some text on process watcher till the initial logs are loaded.
Issue #4926 - Fix VPN network disconnect issue where pgAdmin4 hangs on expanding the Servers node.
Issue #4930 - Fix main window tab navigation accessibility issue.
Issue #4933 - Ensure that the Servers collection node should expand independently of server connections.
Issue #4934 - Fix the help button link on the User Management dialog.
Issue #4935 - Fix accessibility issues.
Issue #4947 - Fix XSS issue in explain and explain analyze for table and type which contain HTML.
Issue #4952 - Fix an issue of retrieving properties for Compound Triggers. It's a regression of #4006.
Issue #4953 - Fix an issue where pgAdmin4 unable to retrieve table node if the trigger is already disabled and the user clicks on Enable All.
Issue #4958 - Fix reverse engineering SQL issue for triggers when passed a single argument to trigger function.
Issue #4964 - Fix an issue where length and precision are not removed from table/column dialog.
Issue #4965 - Fix an issue where the Interval data type is not displayed in the properties dialog of table/column.
Issue #4966 - Fix 'Could not find the object on the server.' error while refreshing the check constraint.
Issue #4975 - Fix issue where the user can not switch the UI language. It's a regression of #4348.
Issue #4976 - Fix reverse engineering SQL issue where when clause is not visible for PG/EPAS 12.
Issue #4978 - Fix pgAdmin4 failed to start issue after upgrading to version 4.15.

Issue #4982 - Added statistics and storage information in reverse engineering SQL of table/column.
Issue #4985 - Fix an issue where the inherited table name with quotes did not escape correctly.
Issue #4991 - Fix an issue where context menu is open along with submenu and the focus is not on context menu or submenu.

14.90 Version 4.15

Release date: 2019-11-14

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.14.

14.90.1 New features

Issue #1974 - Added encrypted password in reverse engineered SQL for roles.
Issue #3741 - Added Dark(Beta) UI Theme option.
Issue #4006 - Support Enable Always and Enable Replica on triggers.
Issue #4351 - Add an option to request confirmation before cancelling/resetting changes on a Properties dialog.
Issue #4348 - Added support for custom theme creation and selection.

14.90.2 Housekeeping

14.90.3 Bug fixes

Issue #3130 - Ensure create new object dialog should be opened when alt+shift+n key is pressed on the collection node.
Issue #3279 - Fixed issue where Drop and Disconnect connection menu points are too close to each other.
Issue #3789 - Ensure context menus never get hidden below the menu bar.
Issue #3859 - Rename the context menu from 'Drop Server' to 'Remove Server'.
Issue #3913 - Ensure the correct "running at" agent is shown when a pgAgent job is executing.
Issue #3915 - Fix an issue in the Query Tool where shortcut keys could be ignored following a query error.
Issue #3999 - Fix the toggle case shortcut key combination.
Issue #4173 - Fix an issue where a black arrow-kind image is displaying at the background of browser tree images.
Issue #4191 - Ensure comments are shown in reverse engineered SQL for table partitions.
Issue #4242 - Handle NULL values appropriately when sorting backgrid tables.
Issue #4341 - Give appropriate error messages when the user tries to use an blank master password.
Issue #4451 - Remove arbitrary (and incorrect) requirement that composite types must have at least two members.
Issue #4459 - Don't quote bigints when copying them from the Query Tool results grid.
Issue #4482 - Ensure compression level is passed to pg_dump when backing up in directory format.
Issue #4483 - Ensure the number of jobs can be specified when backing up in directory format.
Issue #4564 - Ensure Javascript errors during Query Tool execution are reported as such and not as Ajax errors.
Issue #4610 - Suppress Enter key presses in Alertify dialogues when the come from Select2 controls to allow item selection with Enter.
Issue #4647 - Ensure that units are respected when sorting by file size in the File dialog.
Issue #4730 - Ensure all messages are retained in the Query Tool from long running queries.
Issue #4734 - Updated documentation for the delete row button that only strikeout the row instead of deleting it.
Issue #4779 - Updated documentation for the query tool toolbar buttons.

Issue #4835 - Fixed an issue where psql of v12 throwing "symbol not found" error while running Maintenance and Import/Export.
Issue #4845 - Fixed potential error in the properties dialog for the Code tab.
Issue #4850 - Fixed an issue where Datetimepicker control opens when clicking on the label.
Issue #4895 - Fixed potential issue in reset function for nested objects.
Issue #4896 - Fixed an issue where escape key not working to close the open/save file dialog.
Issue #4906 - Fixed an issue where keyboard shortcut for context menu is not working when using Firefox on CentOS7.
Issue #4924 - Fixed docker container exit issue occurs due to change in Gunicorn's latest version.

14.91 Version 4.14

Release date: 2019-10-17

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.13.

14.91.1 New features

Issue #3009 - Added Copy with headers functionality when copy data from Query Tool/View Data.
Issue #4778 - Implemented the Query Plan Analyser.
Issue #4823 - Include PostgreSQL 12 binaries in the container.

14.91.2 Housekeeping

Issue #4472 - Add Reverse Engineered and Modified SQL tests for Synonyms.
Issue #4628 - Add Reverse Engineered and Modified SQL tests for Unique Constraints.
Issue #4701 - Optimize Webpack to improve overall performance.

14.91.3 Bug fixes

Issue #3386 - Ensure backup a partition table should not backup the whole database.
Issue #4199 - Ensure that 'ENTER' key in the data filter should not run the query.
Issue #4590 - Fix issue where backup fails for schema name that needs quoting.
Issue #4728 - Highlighted the color of closing or opening parenthesis when user select them in CodeMirror.
Issue #4751 - Fix issue where export job fails when deselecting all the columns.
Issue #4753 - Fix an error where 'false' string is displayed when we add a new parameter in the Parameters tab, also clear the old value when the user changes the parameter name.
Issue #4755 - Ensure that pgAdmin should work behind reverse proxy if the inbuilt server is used as it is.
Issue #4756 - Fix issue where pgAdmin does not load completely if loaded in an iframe.
Issue #4760 - Ensure the search path should not be quoted for Database.
Issue #4768 - Ensure pgAdmin should work behind reverse proxy on a non standard port.
Issue #4769 - Fix query tool open issue on Internet Explorer.
Issue #4777 - Fix issue where query history is not visible in the query history tab.
Issue #4780 - Ensure the search path should not be quoted for Function, Procedure and Trigger Function.
Issue #4791 - Fix issue where VALID foreign keys show as NOT VALID in the SQL tab for tables.
Issue #4817 - Ensure the MAC OSX app should be notarized for Catalina.

14.92 Version 4.13

Release date: 2019-09-19

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.12.

14.92.1 New features

Issue #2828 - Added Gather Merge, Named Tuple Store Scan and Table Function Scan icon for explain module.
Issue #4553 - Don't wait for the database connection before rendering the Query Tool UI, for improved UX.
Issue #4651 - Allow configuration options to be set from the environment in the container distribution.
Issue #4667 - Ensure editable and read-only columns in Query Tool should be identified by icons and tooltips in the column header.
Issue #4691 - Add an Italian translation.
Issue #4752 - Refactor Dockerfile to avoid needing to run supporting scripts (i.e. 'docker build .' will work) and minimise layers.

14.92.2 Housekeeping

Issue #4575 - Add Reverse Engineered SQL tests for Schemas.
Issue #4576 - Add Reverse Engineered SQL tests for Views.
Issue #4600 - Add Reverse Engineered SQL tests for Rules.
Issue #4616 - Add Reverse Engineered and Modified SQL tests for Foreign Keys.
Issue #4617 - Add Reverse Engineered and Modified SQL tests for Foreign Servers.
Issue #4618 - Add Reverse Engineered and Modified SQL tests for Foreign Tables.
Issue #4619 - Add Reverse Engineered and Modified SQL tests for FTS Templates.
Issue #4621 - Add Reverse Engineered and Modified SQL tests for Indexes.
Issue #4624 - Add Reverse Engineered and Modified SQL tests for Primary Keys.
Issue #4627 - Add Reverse Engineered and Modified SQL tests for User Mappings.
Issue #4690 - Add Modified SQL tests for Resource Group.

14.92.3 Bug fixes

Issue #2706 - Added ProjectSet icon for explain module.
Issue #3778 - Ensure Boolean columns should be editable using keyboard keys.
Issue #3936 - Further code refactoring to stabilise the Feature Tests.
Issue #4381 - Fix an issue where oid column should not be pasted when copy/paste row is used on query output containing the oid column.
Issue #4408 - Fix display of validation error message in SlickGrid cells.
Issue #4412 - Fix issue where Validated switch option is inverted for the Foreign Key.
Issue #4419 - Fix a debugger error when using Python 2.7.
Issue #4461 - Fix error while importing data to a table using Import/Export dialog and providing "Not null columns" option.
Issue #4486 - Ensure View should be created with special characters.
Issue #4487 - Ensure Boolean columns should be editable in View/Edit data and Query Tool.
Issue #4577 - Fix an error that could be seen when click on any system column of a table.
Issue #4584 - Unescape HTML entities in database names in the Query Tool title bar.

Issue #4631 - Add editor options for plain text mode and to disable block folding to workaround rendering speed issues in CodeMirror with very large scripts.
Issue #4642 - Ensure port and username should not be mandatory when a service is provided.
Issue #4643 - Fix Truncate option deselect issue for compound triggers.
Issue #4644 - Fix length and precision enable/disable issue when changing the data type for Domain node.
Issue #4650 - Fix SQL tab issue for Views. It's a regression of compound triggers.
Issue #4657 - Fix PGADMIN_SERVER_JSON_FILE environment variable support in the container.
Issue #4663 - Fix exception in query history for python 2.7.
Issue #4674 - Fix query tool launch error if user name contain html characters.
Issue #4681 - Increase cache control max age for static files to improve performance over longer run.
Issue #4698 - Fix SQL issue of length and precision when changing the data type of Column.
Issue #4702 - Fix modified SQL for Index when reset the value of Fill factor and Clustered?.
Issue #4703 - Fix reversed engineered SQL for btree Index when provided sort order and NULLs.
Issue #4726 - Ensure sequence with negative value should be created.
Issue #4727 - Fix issue where EXEC script doesn't write the complete script for Procedures.
Issue #4736 - Fix query tool and view data issue with the Italian language.
Issue #4742 - Ensure Primary Key should be created with Index.
Issue #4750 - Fix query history exception for Python 3.6.

14.93 Version 4.12

Release date: 2019-08-22

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.11.

14.93.1 New features

Issue #4144 - Add support of Compound Triggers for EPAS 12+.
Issue #4333 - Add support for planner support functions in PostgreSQL 12+ functions.
Issue #4334 - Add support for generated columns in Postgres 12+.
Issue #4540 - Use the full tab space for CodeMirror instances on dialogues where appropriate.
Issue #4549 - Allow a banner to be displayed on the login and other related pages showing custom text.
Issue #4566 - Allow enhanced cookie protection to be disabled for compatibility with dynamically addressed hosting environments.
Issue #4570 - Add an optimisation to the internal code responsible for searching for treeview nodes.
Issue #4574 - Display the row count in the popup message when counting table rows, not just in the properties list.
Issue #4612 - Add support in query history to show internal queries generated by pgAdmin during save data operations.

14.93.2 Housekeeping

Issue #4546 - Add Reverse Engineered SQL tests for Columns.
Issue #4554 - Add Reverse Engineered SQL tests for Trigger Functions.
Issue #4555 - Add Reverse Engineered SQL tests for Exclusion Constraint.
Issue #4560 - Add a –modules option to the RE-SQL test suite to allow testing of specific object types.

14.93.3 Bug fixes

Issue #3605 - Fix issue where Deleting N number of rows makes first N number of rows disable.
Issue #4179 - Fix generation of reverse engineered SQL for tables with Greenplum 5.x.
Issue #4229 - Update wcDocker to allow the browser's context menu to be used except in tab strips and panel headers.
Issue #4401 - Ensure type names are properly encoded in the results grid.
Issue #4414 - Fix generation of reverse engineered SQL for partition table, partitions were shown as a child of indexes.
Issue #4489 - Update wcDocker to prevent window state loading creating blank dialogues.
Issue #4490 - Fix accessibility issue for checkbox in IE11.
Issue #4492 - Ensure the Query Tool doesn't throw an error when viewing the contents of a table with no columns.
Issue #4496 - Ensure columns can be created when they are IDENTITY fields with the CYCLE option enabled.
Issue #4497 - Ensure purely numeric comments can be saved on new columns.
Issue #4508 - Fix accessibility issue for Datetime cell in backgrid.
Issue #4520 - Ensure the query tool will work with older versions of psycopg2 than we officially support, albeit without updatable resultsets.
Issue #4525 - Ensure command tags are shown in the messages tab of the Query Tool.
Issue #4536 - Fix load on demand in View/Edit data mode.
Issue #4552 - Fix some errors thrown on the JS console when dragging text in the Query Tool.
Issue #4559 - Ensure triggers should be updated properly for EPAS server.
Issue #4565 - Fix the reverse engineered SQL for trigger functions with the WINDOW option selected.
Issue #4578 - Ensure enable trigger menu should be visible when trigger is disabled.
Issue #4581 - Ensure the comment on a Primary Key constraint can be edited under the Table node.
Issue #4582 - Fix console error when changing kind(SQL/BATCH) for pgAgent job step.
Issue #4585 - Fix double click issue to expand the contents of a cell if the resultset was not editable.
Issue #4586 - Fix generation of reverse engineered SQL for Rules.
Issue #4635 - Ensure compound triggers for event should be updated properly.
Issue #4638 - Ensure compound triggers should be displayed under Views.
Issue #4641 - Ensure Truncate option should be available for Compound Triggers.

14.94 Version 4.11

Release date: 2019-07-25

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.10.

14.94.1 New features

Issue #1760 - Add support for editing of resultsets in the Query Tool, if the data can be identified as updatable.
Issue #4318 - Set the mouse cursor appropriately based on the layout lock state.
Issue #4335 - Add EXPLAIN options for SETTINGS and SUMMARY.

14.94.2 Housekeeping

Issue #4415 - Add Reverse Engineered SQL tests for Roles and Resource Groups.
Issue #4441 - Add Reverse Engineered SQL tests for FDWs.
Issue #4452 - Add Reverse Engineered SQL tests for Languages.
Issue #4453 - Add Reverse Engineered SQL tests for Extensions.
Issue #4454 - Add Reverse Engineered SQL tests for FTS Configurations.
Issue #4456 - Add Reverse Engineered SQL tests for Packages.
Issue #4460 - Add Reverse Engineered SQL tests for FTS Dictionaries.
Issue #4463 - Add Reverse Engineered SQL tests for Domains.
Issue #4464 - Add Reverse Engineered SQL tests for Collations.
Issue #4468 - Add Reverse Engineered SQL tests for Types.
Issue #4469 - Add Reverse Engineered SQL tests for Sequences.
Issue #4471 - Add Reverse Engineered SQL tests for FTS Parsers.
Issue #4475 - Add Reverse Engineered SQL tests for Constraints.

14.94.3 Bug fixes

Issue #3919 - Allow keyboard navigation of all controls on subnode grids.
Issue #3996 - Fix dropping of pgAgent schedules through the Job properties.
Issue #4224 - Prevent flickering of large tooltips on the Graphical EXPLAIN canvas.
Issue #4389 - Fix an error that could be seen when editing column privileges.
Issue #4393 - Ensure parameter values are quoted when needed when editing roles.
Issue #4395 - EXPLAIN options should be Query Tool instance-specific.
Issue #4427 - Fix an error while retrieving json data from the table.
Issue #4428 - Fix 'malformed array literal' error when updating a pgAgent job.
Issue #4429 - Ensure drag/drop from the treeview works as expected on Firefox.
Issue #4437 - Fix table icon issue when updating any existing field.
Issue #4442 - Ensure browser should not be started by Selenium when feature tests are excluded from a test run.
Issue #4446 - Use ROLE consistently when generating RE-SQL for roles, not USER.
Issue #4448 - Fix an error seen when updating a connection string in a pgAgent job step.
Issue #4450 - Fix reverse engineered sql for Foreign Data Wrapper created on EPAS server in redwood mode.
Issue #4462 - Fix some minor UI issues on IE11.
Issue #4470 - Fix sequence reverse engineered SQL generation with quoted names on PG/EPAS 10+.
Issue #4484 - Fix an issue where Explain and Explain Analyze are not working, it's regression of #1760.
Issue #4485 - Fix an issue where Filter toolbar button is not working in view/edit data, it's regression of keyboard navigation.

14.95 Version 4.10

Release date: 2019-07-04

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.9.

14.95.1 New features

Issue #4139 - Allow some objects to be dragged/dropped into the Query Tool to insert their signature into the query text.
Issue #4400 - Allow the path to /pgadmin4/servers.json to be overridden in the container distribution.

14.95.2 Bug fixes

Issue #4403 - Ensure the browser close confirmation is only shown when closing a Query Tool which is running in a separate browser tab.
Issue #4404 - Prevent an error that may occur when editing data with an integer primary key.
Issue #4407 - Fix a quoting issue that caused a blank UI to be displayed when running in French.
Issue #4421 - Ensure the version comparision should be correct for windows installer.

14.96 Version 4.9

Release date: 2019-06-27

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.8.

14.96.1 New features

Issue #3174 - Visually distinguish simple tables from tables that are inherited and from which other tables are inherited.

14.96.2 Housekeeping

Issue #4202 - Add a framework for testing reversed engineered SQL and CRUD API endpoints.

14.96.3 Bug fixes

Issue #3994 - Fix issue where the dependencies tab for inherited tables/foreign keys shows partial text.
Issue #4036 - Allow editing of data where a primary key column includes a % sign in the value.
Issue #4171 - Fix issue where reverse engineered SQL was failing for foreign tables, if it had "=" in the options.
Issue #4195 - Fix keyboard navigation in "inner" tabsets such as the Query Tool and Debugger.
Issue #4228 - Ensure the correct label is used in panel headers when viewing filtered rows.
Issue #4253 - Fix issue where new column should be created with Default value.
Issue #4283 - Initial support for PostgreSQL 12.
Issue #4288 - Initial support for PostgreSQL 12.

Issue #4290 - Initial support for PostgreSQL 12.
Issue #4255 - Prevent the geometry viewer grabbing key presses when not in focus under Firefox, IE and Edge.
Issue #4306 - Prevent the "Please login to access this page" message displaying multiple times.
Issue #4310 - Ensure that the Return key can be used to submit the Master Password dialogue.
Issue #4317 - Ensure that browser auto-fill doesn't cause Help pages to be opened unexpectedly.
Issue #4320 - Fix issue where SSH tunnel connection using password is failing, it's regression of Master Password.
Issue #4329 - Fix an initialisation error when two functions with parameters are debugged in parallel.
Issue #4343 - Fix issue where property dialog of column should open properly for EPAS v12.
Issue #4345 - Capitalize the word 'export' used in Import/Export module.
Issue #4349 - Ensure strings are properly encoded in the Query History.
Issue #4350 - Ensure we include the CSRF token when uploading files.
Issue #4357 - Fix connection restoration issue when pgAdmin server is restarted and the page is refreshed.
Issue #4360 - Ensure the debugger control buttons are only enabled once initialisation is complete.
Issue #4362 - Remove additional "SETOF" included when generating CREATE scripts for trigger functions.
Issue #4365 - Fix help links for backup globals and backup server.
Issue #4367 - Fix an XSS issue seen in View/Edit data mode if a column name includes HTML.
Issue #4378 - Ensure Python escaping matched JS escaping and fix a minor XSS issue in the Query Tool that required superuser access to trigger.
Issue #4380 - Ensure that both columns and partitions can be edited at the same time in the table dialog.
Issue #4386 - Fix an XSS issue when username contains XSS vulnerable text.

14.97 Version 4.8

Release date: 2019-06-03

This release contains a number of bug fixes and new features since the release of pgAdmin4 4.7.

14.97.1 New features

Issue #2653 - Allow the UI layout to be fully locked or to prevent docking changes.

14.97.2 Bug fixes

Issue #4169 - Omit the geometry viewer in the Query Tool from layout saving.
Issue #4307 - Improve the performance of explain plan by embedding the images only when downloading it.
Issue #4308 - Fix the issue of accessing the SQL for Views and Materialized Views. Regression of pluralisation of folder names.

14.98 Version 4.7

Release date: 2019-05-30

This release contains a number of bug fixes since the release of pgAdmin4 4.6.

14.98.1 Bug fixes

Issue #3377 - In server mode, update all the saved server credentials when user password is changed.
Issue #3885 - Fix the responsive layout of the main menu bar.
Issue #4162 - Fix syntax error when adding more than one column to the existing table.
Issue #4164 - Fix file browser path issue which occurs when client is on Windows and server is on Mac/Linux.
Issue #4184 - Added Master Password to increase the security of saved passwords.
Issue #4194 - Fix accessibility issue for menu navigation.
Issue #4208 - Update the UI logo.
Issue #4217 - Fixed CSRF security vulnerability issue, per Alvin Lindstam
Issue #4218 - Properly assign dropdownParent in Select2 controls.
Issue #4219 - Ensure popper.js is installed when needed.
Issue #4227 - Fixed Tab key navigation for Maintenance dialog.
Issue #4244 - Fix Tab key issue for Toggle switch controls and button on the dialog footer in Safari browser.
Issue #4245 - Ensure that element should get highlighted when they get focus on using Tab key.
Issue #4246 - Fixed console error when subnode control is used in panels.
Issue #4261 - Stop using application/x-javascript as a mime type and use the RFC-compliant application/javascript instead.
Issue #4262 - Fixed error on displaying table properties of a table partitioned by list having a default partition.
Issue #4263 - Fix handling of JSON in the Query Tool with NULL elements.
Issue #4269 - Fix navigation of switch cells in grids.
Issue #4275 - Clarify wording for the NO INHERIT option on constraints, per Michel Feinstein.
Issue #4276 - Relax the permission check on the directory containing the config database, as it may fail in some environments such as OpenShift.
Issue #4278 - Prevent Backgrid Password cells from losing focus if the browser opens an autocomplete list.
Issue #4284 - Fix syntax error when creating a table with a serial column.

14.99 Version 4.6

Release date: 2019-05-02

This release contains a number of new features and fixes reported since the release of pgAdmin4 4.5

14.99.1 Features

Issue #4165 - Depend on psycopg2-binary in the Python wheel, rather than psycopg2.

14.99.2 Bug fixes

Issue #2392 - Ensure that on clicking Delete button should not delete rows immediately from the database server, it should be deleted when Save button will be clicked.
Issue #3327 - Ensure that newly added row in backgrid should be visible.
Issue #3582 - Ensure that JSON strings as comments should be added properly for all the objects.
Issue #3605 - Fix an issue where Deleting N number of rows makes first N number of rows disable.
Issue #3938 - Added support for Default Partition.
Issue #4087 - Fix an issue where 'GRANT UPDATE' sql should be displayed for default sequence privileges.
Issue #4101 - Ensure that confirmation dialog should be popped up before reload of query tool or debugger if it is opened in a new browser tab.
Issue #4104 - Ensure that record should be add/edited for root partition table with primary keys.
Issue #4121 - Fixed alignment issue of columns in definition section of Index node.
Issue #4134 - Fixed 'Location cannot be empty' error when open Tablespace properties.
Issue #4138 - Fix an issue where the dropdown becomes misaligned/displaced.
Issue #4154 - Ensure the treeview shows all sequences except those used to implement IDENTITY columns (which can be edited as part of the column). Show all if Show System Objects is enabled.
Issue #4160 - Fixed 'Increment value cannot be empty' error for existing tables.
Issue #4161 - Ensure that parameters of procedures for EPAS server 10 and below should be set/reset properly.
Issue #4163 - Prevent duplicate columns being included in reverse engineered SQL for tables.
Issue #4182 - Ensure sanity of the permissions on the storage and session directories and the config database.

14.100 Version 4.5

Release date: 2019-04-10

This release contains a number of new features and fixes reported since the release of pgAdmin4 4.4.

14.100.1 Bug fixes

Issue #2214 - Fixed 'Change Password' issue for SCRAM authentication.
Issue #3656 - Ensure that two consecutive SELECT statements should work properly.
Issue #4131 - Relabel the Save button on the datagrid text editor to avoid confusion with the actual Save button that updates the database.
Issue #4142 - Added recommended ESLinter checks.
Issue #4143 - Ensure that pgAdmin4 should work properly with psycopg2 v2.8

14.101 Version 4.4

Release date: 2019-04-04

This release contains a number of new features and fixes reported since the release of pgAdmin4 4.3.

Warning

This release includes a bug fix (Issue #3887) which will rename the per-user storage directories for existing users when running in server mode. Previously, saved SQL queries were stored under the *STORAGE_DIR* in a sub-directory named after the username part of the user's email address. From this version onwards, the full email address is used, with the @ replaced with an underscore. For example, in v.4.3 with *STORAGE_DIR* set to */var/lib/pgadmin4* user files may be stored in:

```
/var/lib/pgadmin4/storage/username/
```

With the fix, that directory will be renamed (or created for new users) as:

```
/var/lib/pgadmin4/storage/username_example.com/
```

14.101.1 Features

Issue #2001 - Add support for reverse proxied setups with Gunicorn, and document Gunicorn, uWSGI & NGINX configurations.
Issue #4017 - Make the Query Tool history persistent across sessions.
Issue #4018 - Remove the large and unnecessary dependency on React and 87 other related libraries.
Issue #4030 - Add support for IDENTITY columns.
Issue #4075 - Add an ePub doc build target.

14.101.2 Bug fixes

Issue #1269 - Fix naming inconsistency for the column and FTS parser modules.
Issue #2627 - Include inherited column comments and defaults in reverse engineered table SQL.
Issue #3104 - Improve a couple of German translations.
Issue #3887 - Use the user's full email address (not just the username part) as the basis for the storage directory name.
Issue #3968 - Update wcDocker to fix the issue where the Scratch Pad grows in size if the results panel is resized.
Issue #3995 - Avoid 'bogus varno' message from Postgres when viewing the SQL for a table with triggers.
Issue #4019 - Update all Python and JavaScript dependencies.
Issue #4037 - Include comment SQL for inherited columns in reverse engineered table SQL.
Issue #4050 - Make the WHEN field a CodeMirror control on the Event Trigger dialogue.
Issue #4052 - Fix the online help button on the resource group dialogue.
Issue #4053 - Enable the online help button on the index dialogue.
Issue #4054 - Handle resultsets with zero columns correctly in the Query Tool.
Issue #4058 - Include inherited columns in SELECT scripts.
Issue #4060 - Fix the latexpdf doc build.
Issue #4062 - Fix handling of numeric arrays in View/Edit Data.
Issue #4063 - Enlarge the grab handles for resizing dialogs etc.
Issue #4069 - Append the file suffix to filenames when needed in the File Create dialogue.
Issue #4071 - Ensure that Firefox prompts for a filename/location when downloading query results as a CSV file.
Issue #4073 - Change the CodeMirror active line background colour to $color-danger-lighter so it doesn't conflict with the selection colour.
Issue #4081 - Fix the RE-SQL syntax for roles with a VALID UNTIL clause.
Issue #4082 - Prevent an empty error message being shown when "downloading" a CREATE script using the CSV download.
Issue #4084 - Overhaul the layout saving code so it includes the Query Tool and Debugger, and stores the layout when change events are detected rather than (unreliably) on exit.
Issue #4085 - Display errors during CSV download from the Query Tool in the UI rather than putting them in the CSV file.
Issue #4090 - Improve the German translation for Backup Server.
Issue #4096 - Ensure the toolbar buttons are properly reset following a CSV download in the Query Tool.
Issue #4099 - Fix SQL help for EPAS 10+, and refactor the URL generation code into a testable function.
Issue #4100 - Ensure sequences can be created with increment, start, minimum and maximum options set.
Issue #4105 - Fix an issue where JSON data would not be rendered in the Query Tool.
Issue #4109 - Ensure View/Materialized View node should be visible after updating any property.
Issue #4110 - Fix custom autovacuum configuration for Materialized Views.

14.102 Version 4.3

Release date: 2019-03-07

This release contains a number of new features and fixes reported since the release of pgAdmin4 4.2

14.102.1 Features

Issue #1825 - Install a script to start pgAdmin (pgadmin4) from the command line when installed from the Python wheel.
Issue #2233 - Add a "scratch pad" to the Query Tool to hold text snippets whilst editing.
Issue #2418 - Add Commit and Rollback buttons to the Query Tool.
Issue #3439 - Allow X-FRAME-OPTIONS to be set for security. Default to SAMEORIGIN.
Issue #3559 - Automatically expand child nodes as well as the selected node on the treeview if there is only one.
Issue #3886 - Include multiple versions of the PG utilties in containers.
Issue #3991 - Update Alpine Linux version in the docker container.
Issue #4034 - Support double-click on Query Tool result grid column resize handles to auto-size to the content.

14.102.2 Bug fixes

Bug #3096 - Ensure size stats are prettified on the statistics tab when the UI language is not English.
Bug #3352 - Handle display of roles with expiration set to infinity correctly.
Bug #3418 - Allow editing of values in columns with the oid datatype which are not an actual row OID.
Bug #3544 - Make the Query Tool tab titles more concise and useful.
Bug #3587 - Fix support for bigint's in JSONB data.
Bug #3583 - Update CodeMirror to 5.43.0 to resolve issues with auto-indent.
Bug #3600 - Ensure JSON data isn't modified in-flight by psycopg2 when using View/Edit data.
Bug #3673 - Modify the Download as CSV option to use the same connection as the Query Tool its running in so temporary tables etc. can be used.
Bug #3873 - Fix context sub-menu alignment on Safari.
Bug #3890 - Update documentation screenshots as per new design.
Bug #3906 - Fix alignment of Close and Maximize button of Grant Wizard.
Bug #3911 - Add full support and testsfor all PG server side encodings.
Bug #3912 - Fix editing of table data with a JSON primary key.
Bug #3933 - Ignore exceptions in the logger.
Bug #3942 - Close connections gracefully when the user logs out of pgAdmin.
Bug #3946 - Fix alignment of checkbox to drop multiple schedules of pgAgent job.
Bug #3958 - Don't exclude SELECT statements from transaction management in the Query Tool in case they call data-modifying functions.
Bug #3959 - Optimise display of Dependencies and Dependents, and use on-demand loading of rows in batches of 100.
Bug #3963 - Fix alignment of import/export toggle switch.
Bug #3970 - Prevent an error when closing the Sort/Filter dialogue with an empty filter string.
Bug #3974 - Fix alignment of Connection type toggle switch of pgagent.
Bug #3981 - Fix the query to set bytea_output so that read-only standbys don't consider it a write query.
Bug #3982 - Add full support and testsfor all PG server side encodings.

Bug #3985 - Don't embed docs and external sites in iframes, to allow the external sites to set X-FRAME-OPTIONS = DENY for security.
Bug #3992 - Add full support and testsfor all PG server side encodings.
Bug #3998 - Custom-encode forward slashes in URL parameters as Apache HTTPD doesn't allow them in some cases.
Bug #4000 - Update CodeMirror to 5.43.0 to resolve issues with tab indent with use spaces enabled.
Bug #4013 - Ensure long queries don't cause errors when downloading CSV in the Query Tool.
Bug #4021 - Disable the editor and execute functions whilst queries are executing.
Bug #4022 - Fix an issue where importing servers fails if a group already exists for a different user.

14.103 Version 4.2

Release date: 2019-02-07

This release contains a number of fixes reported since the release of pgAdmin4 4.1

14.103.1 Bug fixes

Issue #3051 - Replace Bootstrap switch with Bootstrap4 toggle to improve the performance.
Issue #3272 - Replace the PyCrypto module with the cryptography module.
Issue #3453 - Fixed SQL for foreign table options.
Issue #3475 - Fixed execution time to show Hours part for long running queries in Query Tool.
Issue #3608 - Messages tab of Query Tool should be clear on subsequent execution of table/view using View/Edit Data.
Issue #3609 - Clear drop-down menu should be disabled for View/Edit Data.
Issue #3664 - Fixed Statistics panel hang issue for 1000+ tables.
Issue #3693 - Proper error should be thrown when server group is created with existing name.
Issue #3695 - Ensure long string should be wrap in alertify dialogs.
Issue #3697 - Ensure that output of the query should be displayed even if Data Output window is detached from the Query Tool.
Issue #3740 - Inline edbspl trigger functions should not be visible in Grant Wizard.
Issue #3774 - Proper SQL should be generated when create function with return type as custom type argument.
Issue #3800 - Ensure that database restriction of server dialog should work with special characters.
Issue #3811 - Ensure that Backup/Restore button should work on single click.
Issue #3837 - Fixed SQL for when clause while creating Trigger.
Issue #3838 - Proper SQL should be generated when creating/changing column with custom type argument.
Issue #3840 - Ensure that file format combo box value should be retained when hidden files checkbox is toggled.
Issue #3846 - Proper SQL should be generated when create procedure with custom type arguments.
Issue #3849 - Ensure that browser should warn before close or refresh.
Issue #3850 - Fixed EXEC script for procedures.
Issue #3853 - Proper SQL should be generated when create domain of type interval with precision.
Issue #3858 - Drop-down should be closed when click on any other toolbar button.
Issue #3862 - Fixed keyboard navigation for dialog tabs.
Issue #3865 - Increase frames splitter mouse hover area to make it easier to resize.
Issue #3871 - Fixed alignment of tree arrow icons for Internet Explorer.
Issue #3872 - Ensure object names in external process dialogues are properly escaped.
Issue #3891 - Correct order of Save and Cancel button for json/jsonb editing.

Issue #3897 - Data should be updated properly for FTS Configurations, FTS Dictionaries, FTS Parsers and FTS Templates.
Issue #3899 - Fixed unable to drop multiple Rules and Foreign Tables from properties tab.
Issue #3903 - Fixed Query Tool Initialization Error.
Issue #3908 - Fixed keyboard navigation for Select2 and Privilege cell in Backgrid.
Issue #3916 - Correct schema should be displayed in Materialized View dialog.
Issue #3927 - Fixed debugger issue for procedure inside package for EPAS servers.
Issue #3929 - Fix alignment of help messages in properties panels.
Issue #3932 - Fix alignment of submenu for Internet Explorer.
Issue #3935 - Ensure that grant wizard should list down functions for EPAS server running with no-redwood-compat mode.
Issue #3941 - Dashboard graph optimization.
Issue #3954 - Remove Python 2.6 code that's now obsolete.
Issue #3955 - Expose the bind address in the Docker container via PGADMIN_BIND_ADDRESS.
Issue #3961 - Exclude HTTPExceptions from the all_exception_handler as they should be returned as-is.

14.104 Version 4.1

Release date: 2019-01-15

This release contains a number of fixes reported since the release of pgAdmin4 4.0

14.104.1 Bug fixes

Issue #3505 - Fix SQL generated for tables with inherited columns.
Issue #3575 - Ensure the context menu works after a server is renamed.
Issue #3836 - Fix ordering of VACUUM options which changed in PG11.
Issue #3842 - Don't show system catalogs in the schemas property list unless show system objects is enabled.
Issue #3861 - Fix help for the backup/restore dialogues.
Issue #3866 - Ensure that last row of table data should be visible and user will be able to add new row.
Issue #3877 - Make the browser more robust in the face of multibyte characters in SQL_ASCII databases.

14.105 Version 4.0

Release date: 2019-01-10

This release contains a number of features and fixes reported since the release of pgAdmin4 3.6

14.105.1 Features

Issue #3589 - Allow query plans to be downloaded as an SVG file.
Issue #3692 - New UI design.
Issue #3801 - Allow servers to be pre-loaded into container deployments.

14.105.2 Bug fixes

Issue #3083 - Increase the size of the resize handle of the edit grid text pop-out.
Issue #3354 - Fix handling of array types as inputs to the debugger.
Issue #3433 - Fix an issue that could cause the Query Tool to fail to render.
Issue #3549 - Display event trigger functions correctly on EPAS.
Issue #3559 - Further improvements to treeview restoration.
Issue #3599 - Run Postfix in the container build so passwords can be reset etc.
Issue #3619 - Add titles to the code areas of the Query Tool and Debugger to ensure that panels can be re-docked within them.
Issue #3679 - Fix a webpack issue that could cause the Query Tool to fail to render.
Issue #3702 - Ensure we display the relation name (and not the OID) in the locks table wherever possible.
Issue #3711 - Fix an encoding issue in the Query Tool.
Issue #3726 - Include the WHERE clause on EXCLUDE constraints in RE-SQL.
Issue #3753 - Fix an issue when user define Cast from smallint->text is created.
Issue #3757 - Hide Radio buttons that should not be shown on the maintenance dialogue.
Issue #3780 - Ensure that null values handled properly in CSV download.
Issue #3796 - Tweak the wording on the Grant Wizard.
Issue #3797 - Prevent attempts to bulk-drop schema objects.
Issue #3798 - Ensure the browser toolbar buttons work in languages other than English.
Issue #3805 - Allow horizontal sizing of the edit grid text pop-out.
Issue #3809 - Ensure auto complete should works when first identifier in the FROM clause needs quoting.
Issue #3810 - Ensure auto complete should works for columns from a schema-qualified table.
Issue #3821 - Ensure identifiers are properly displayed in the plan viewer.
Issue #3830 - Make the setup process more robust against aborted executions.
Issue #3856 - Fixed an issue while creating export job.

14.106 Version 3.6

Release date: 2018-11-29

This release contains a number of features and fixes reported since the release of pgAdmin4 3.5

14.106.1 Features

Issue #1513 - Add support for dropping multiple objects at once from the collection Properties panel.
Issue #3772 - Add the ability to import and export server definitions from a config database.

14.106.2 Bug fixes

Issue #3016 - Ensure previous notices are not removed from the Messages tab in the Query Tool if an error occurs during query execution.
Issue #3029 - Allow the selection order to be preserved in the Select2 control to fix column ordering in data Import/Export.
Issue #3629 - Allow use of 0 (integer) and empty strings as parameters in the debugger.
Issue #3723 - Properly report errors when debugging cannot be started.
Issue #3734 - Prevent the debugger controls being pressed again before previous processing is complete.
Issue #3736 - Fix toggle breakpoints buttons in the debugger.
Issue #3742 - Fix changes to the NOT NULL and default value options in the Table Dialogue.
Issue #3746 - Fix dropping of multiple functions/procedures at once.

14.107 Version 3.5

Release date: 2018-11-01

This release contains a number of features and fixes reported since the release of pgAdmin4 3.4

14.107.1 Features

Issue #1253 - Save the treeview state periodically, and restore it automatically when reconnecting.
Issue #3562 - Migrate from Bootstrap 3 to Bootstrap 4.

14.107.2 Bug fixes

Issue #3232 - Ensure that Utilities(Backup/Restore/Maintenence/Import-Export) should not be started if binary path is wrong and also added 'Stop Process' button to cancel the process.
Issue #3638 - Fix syntax error when creating new pgAgent schedules with a start date/time and exception.
Issue #3674 - Cleanup session files periodically.
Issue #3660 - Rename the 'SQL Editor' section of the Preferences to 'Query Tool' as it applies to the whole tool, not just the editor.
Issue #3676 - Fix CREATE Script functionality for EDB-Wrapped functions.
Issue #3700 - Fix connection garbage collector.
Issue #3703 - Purge connections from the cache on logout.

Issue #3722 - Ensure that utility existence check should work for schema and other child objects while taking Backup/Restore.
Issue #3730 - Fixed fatal error while launching the pgAdmin4 3.5. Update the version of the Flask to 0.12.4 for release.

14.108 Version 3.4

Release date: 2018-10-04

This release contains a number of features and fixes reported since the release of pgAdmin4 3.3

14.108.1 Features

Issue #2927 - Move all CSS into SCSS files for consistency and ease of colour maintenance etc.
Issue #3514 - Add optional data point markers and mouse-over tooltips to display values on graphs.
Issue #3564 - Add shortcuts for View Data and the Query tool to the Browser header bar.

14.108.2 Bug fixes

Issue #3464 - Ensure the runtime can startup properly if there are wide characters in the logfile path on Windows.
Issue #3551 - Fix handling of backslashes in the edit grid.
Issue #3576 - Ensure queries are no longer executed when dashboards are closed.
Issue #3596 - Fix support for the CLOB datatype in EPAS.
Issue #3607 - Fix logic around validation and highlighting of Sort/Filter in the Query Tool.
Issue #3630 - Ensure auto-complete works for objects in schemas other than public and pg_catalog.
Issue #3657 - Ensure changes to Query Tool settings from the Preferences dialogue are applied before executing queries.
Issue #3658 - Swap the Schema and Schemas icons and Catalog and Catalogs icons that had been used the wrong way around.

14.109 Version 3.3

Release date: 2018-09-06

This release contains a number of features and fixes reported since the release of pgAdmin4 3.2

14.109.1 Features

Issue #1407 - Add a geometry viewer that can render PostGIS data on a blank canvas or various map sources.
Issue #3503 - Added new backup/restore options for PostgreSQL 11. Added dump options for 'pg_dumpall'.
Issue #3553 - Add a Spanish translation.

14.109.2 Bug fixes

Issue #3136 - Stabilise feature tests for continuous running on CI systems.
Issue #3191 - Fixed debugger execution issues.
Issue #3313 - Ensure 'select all' and 'unselect all' working properly for pgAgent schedule.
Issue #3325 - Fix sort/filter dialog issue where it incorrectly requires ASC/DESC.
Issue #3347 - Ensure backup should work with '–data-only' and '–schema-only' for any format.
Issue #3407 - Fix keyboard shortcuts layout in the preferences panel.
Issue #3420 - Merge pgcli code with version 1.10.3, which is used for auto complete feature.
Issue #3461 - Ensure that refreshing a node also updates the Property list.
Issue #3525 - Ensure that refresh button on dashboard should refresh the table.
Issue #3528 - Handle connection errors properly in the Query Tool.
Issue #3547 - Make session implementation thread safe
Issue #3548 - Ensure external table node should be visible only for GPDB.
Issue #3554 - Fix auto scrolling issue in debugger on step in and step out.
Issue #3558 - Fix sort/filter dialog editing issue.
Issue #3561 - Ensure sort/filter dialog should display proper message after losing database connection.
Issue #3578 - Ensure sql for Role should be visible in SQL panel for GPDB.
Issue #3579 - When building the Windows installer, copy system Python packages before installing dependencies to ensure we don't end up with older versions than intended.
Issue #3604 - Correct the documentation of View/Edit data.

14.110 Version 3.2

Release date: 2018-08-09

This release contains a number of features and fixes reported since the release of pgAdmin4 3.1

14.110.1 Features

Issue #2136 - Added version number for URL's to ensure that files are only cached on a per-version basis.
Issue #2214 - Add support for SCRAM password changes (requires psycopg2 >= 2.8).
Issue #3074 - Add support for reset saved password.
Issue #3397 - Add support for Trigger and JIT stats in the graphical query plan viewer.
Issue #3412 - Add support for primary key, foreign key, unique key, indexes and triggers on partitioned tables for PG/EPAS 11.
Issue #3506 - Allow the user to specify a fixed port number in the runtime to aid cookie whitelisting etc.
Issue #3510 - Add a menu option to the runtime to copy the appserver URL to the clipboard.

14.110.2 Bug fixes

Issue #3185 - Fix the upgrade check on macOS.
Issue #3191 - Fix a number of debugger execution issues.
Issue #3294 - Infrastructure (and changes to the Query Tool, Dashboards and Debugger) for realtime preference handling.
Issue #3309 - Fix Directory format support for backups.
Issue #3316 - Support running on systems without a system tray.
Issue #3319 - Cleanup and fix handling of Query Tool Cancel button status.
Issue #3363 - Fix restoring of restore options for sections.
Issue #3371 - Don't create a session when the /misc/ping test endpoint is called.
Issue #3446 - Various procedure/function related fixes for EPAS/PG 11.
Issue #3448 - Exclude system columns in Import/Export.
Issue #3457 - Fix debugging of procedures in EPAS packages.
Issue #3458 - pgAdmin4 should work with python 3.7.
Issue #3468 - Support SSH tunneling with keys that don't have a passphrase.
Issue #3471 - Ensure the SSH tunnel port number is honoured.
Issue #3511 - Add support to save and clear SSH Tunnel password.
Issue #3526 - COST statement should not be automatically duplicated after creating trigger function.
Issue #3527 - View Data->Filtered Rows dialog should be displayed.

14.111 Version 3.1

Release date: 2018-06-28

This release contains a number of features and fixes reported since the release of pgAdmin4 3.0

14.111.1 Features

Issue #1447 - Add support for SSH tunneled connections
Issue #2686 - Add an option to auto-complete keywords in upper case
Issue #3204 - Add support for LISTEN/NOTIFY in the Query Tool
Issue #3273 - Allow sorting in the file dialogue
Issue #3362 - Function and procedure support for PG11
Issue #3388 - Allow the connection timeout to be configured on a per-server basis

14.111.2 Bug fixes

Issue #1220 - Backup and Restore should not be started if database name contains "=" symbol
Issue #1221 - Maintenance should not be started if database name contains "=" symbol
Issue #3179 - Fix an error generating SQL for trigger functions
Issue #3238 - Standardise the error handling for parsing of JSON response messages from the server
Issue #3250 - Fix handling of SQL_ASCII data in the Query Tool
Issue #3257 - Catch errors when trying to EXPLAIN an invalid query
Issue #3277 - Ensure server cleanup on exit only happens if the server actually started up
Issue #3284 - F5 key should work to refresh Browser tree

Issue #3289 - Fix handling of SQL_ASCII data in the Query Tool
Issue #3290 - Close button added to the alertify message box, which pops up in case of backend error
Issue #3295 - Ensure the debugger gets focus when loaded so shortcut keys work as expected
Issue #3298 - Fixed Query Tool keyboard issue where arrow keys were not behaving as expected for execute options dropdown
Issue #3303 - Fix a Japanese translation error that could prevent the server starting up
Issue #3306 - Fixed display SQL of table with index for Greenplum database
Issue #3307 - Allow connections to servers with port numbers < 1024 which may be seen in container environments
Issue #3308 - Fixed issue where icon for Partitioned tables was the same as Non Partitioned tables for Greenplum database
Issue #3310 - Fixed layout of the alertify error message in the Query Tool
Issue #3324 - Fix the template loader to work reliably under Windows (fixing external tables under Greenplum)
Issue #3333 - Ensure the runtime core application is setup before trying to access any settings
Issue #3342 - Set SESSION_COOKIE_SAMESITE='Lax' per Flask recommendation to prevents sending cookies with CSRF-prone requests from external sites, such as submitting a form
Issue #3353 - Handle errors properly if they occur when renaming a database
Issue #3356 - Include the schema name on RE-SQL for packages
Issue #3374 - Fix autocomplete
Issue #3392 - Fix IPv6 support in the container build
Issue #3409 - Avoid an exception on GreenPlum when retrieving RE-SQL on a table
Issue #3411 - Fix a French translation error that could prevent the server starting up
Issue #3431 - Fix the RE-SQL generation for GreenPlum external tables

14.112 Version 3.0

Release date: 2018-03-22

This release contains a number of features and fixes reported since the release of pgAdmin4 2.1

14.112.1 Features

Issue #1894 - Allow sorting when viewing/editing data
Issue #1978 - Add the ability to enable/disable UI animations
Issue #2895 - Add keyboard navigation options for the main browser windows
Issue #2896 - Add keyboard navigation in Query tool module via Tab/Shift-Tab key
Issue #2897 - Support keyboard navigation in the debugger
Issue #2898 - Support tab navigation in dialogs
Issue #2899 - Add configurable shortcut keys for various common options in the main window
Issue #2901 - Configurable shortcuts in the Debugger
Issue #2904 - Ensure clickable images/buttons have appropriate tooltips for screen readers
Issue #2950 - Add a marker (*/pga4dash/*) to the dashboard queries to allow them to be more easily filtered from server logs
Issue #2951 - Allow dashboard tables and charts to be enabled/disabled
Issue #3004 - Support server and database statistics on Greenplum
Issue #3036 - Display partitions in Greenplum
Issue #3044 - Display functions in Greenplum
Issue #3086 - Rewrite the runtime as a tray-based server which can launch a web browser

Issue #3097 - Support EXPLAIN on Greenplum
Issue #3098 - Unvendorize REACT so no longer required in our source tree
Issue #3107 - Hide tablespace node on GPDB
Issue #3140 - Add support for connecting using pg_service.conf files
Issue #3168 - Support for external tables in GPDB
Issue #3182 - Update Jasmine to v3
Issue #3184 - Add a French translation
Issue #3195 - Pass the service name to external processes
Issue #3246 - Update container build to use Alpine Linux and Gunicorn instead of CentOS/Apache

In addition, various changes were made for PEP8 compliance

14.112.2 Bug fixes

Issue #1173 - Add a comment to the existing node
Issue #1925 - Fix issue resizing column widths not resizable in Query Tool after first query
Issue #2104 - Runtime update display file version and copyright year under installers properties
Issue #2249 - Application no longer hangs after reload in runtime
Issue #2251 - Runtime fixed OSX html scroll direction ignored in MacOS setup
Issue #2309 - Allow text selection/copying from disabled CodeMirror instances
Issue #2480 - Runtime update fix to Context Menus on Mac that do not work
Issue #2578 - Runtime update fix to HTML access keys that don't work
Issue #2581 - Fix keyboard shortcut for text selection
Issue #2677 - Update Elephant icon for pgAdmin4 on Windows
Issue #2776 - Fix unreadable font via Remote Desktop
Issue #2777 - Fix spacing issue on server tree
Issue #2783 - Runtime update fixed blank screen on Windows Desktop
Issue #2906 - Correct display issues on HiDPI screens
Issue #2961 - Issues when creating a pgAgent Schedule
Issue #2963 - Fix unicode handling in the external process tools and show the complete command in the process viewer
Issue #2980 - Copy text from the Query tool into the clipboard adds invisible characters
Issue #2981 - Support keyboard navigation in the debugger
Issue #2983 - Fix intermittent specified_version_number ValueError issue on restart
Issue #2985 - Fix drag and drop issues
Issue #2998 - Don't listen on port 443 if TLS is not enabled when launching the container
Issue #3001 - Runtime update fix scrolling with mouse wheel on mac pgAdmin 4.2.1
Issue #3002 - Fix block indent/outdent with configurable width
Issue #3003 - Runtime update fix copy to clipboard
Issue #3005 - Runtime update fix unable to select tabs in pgAdmin 4.2.1
Issue #3013 - Fix a minor UI issue on dashboard while displaying subnode control in Backgrid
Issue #3014 - Fix validation of sequence parameters
Issue #3015 - Support Properties on Greenplum databases
Issue #3016 - Ensure debug messages are available in "messages" window when error occurs
Issue #3021 - Update scan and index scan EXPLAIN icons for greater clarity
Issue #3027 - Ensure we capture notices raised by queries

Issue #3031 - Runtime issue causing double and single quotes not to work
Issue #3039 - Runtime issue causing wrong row counts on count column
Issue #3042 - Runtime issue causing empty dialog box when refreshing
Issue #3043 - Runtime issue causing word sizing in macOS High Sierra
Issue #3045 - Runtime issue causing copy cells issues copying cells for key binding
Issue #3046 - Fix connection status indicator on IE/FF
Issue #3050 - Correct display of RE-SQL for partitioned tables in Greenplum
Issue #3052 - Don't include sizes on primitive data types that shouldn't have them when modifying columns
Issue #3054 - Ensure the user can use keyboard shortcuts after using button controls such as Cancel, Open and Save
Issue #3057 - Update the regression tests to fix issues with Python 3.5 and PG 9.2
Issue #3058 - Fix on-click handling of treeview nodes that wasn't refreshing SQL/Dependencies/Dependents in some circumstances
Issue #3059 - Fix table statistics for Greenplum
Issue #3060 - Fix quoting of function names in RE-SQL
Issue #3066 - Ensure column names on indexes on views are properly quoted in RE-SQL
Issue #3067 - Prevent the filter dialog CodeMirror from overflowing onto the button bar of the dialog
Issue #3072 - Add a (configurable) limit to the number of pgAgent job history rows displayed on the statistics tab
Issue #3073 - Ensure the pgAgent job start/end time grid fields synchronise with the subnode control and validate correctly
Issue #3075 - Runtime issue causing Select, Update, and Insert script generation for a table fails to load
Issue #3077 - Remove dependency on standards_conforming_strings being enabled
Issue #3079 - Fix handling of tie/datetime array types when adding columns to a table
Issue #3080 - Fix alignment issues in keyboard shortcut options
Issue #3081 - Add missing reverse-engineered SQL header and drop statement for sequences
Issue #3090 - Ensure message severity is decoded when necessary by the driver
Issue #3094 - Ensure all messages are retrieved from the server in the Query Tool
Issue #3099 - Fix creation of tables and columns in GPDB
Issue #3105 - Ensure we can properly update rows with upper-case primary key columns
Issue #3135 - Insert rows correctly when a table has OIDs and a Primary Key in uppercase
Issue #3122 - Ensure SSL options are pushed down to external tools like pg_dump
Issue #3129 - Handle opening of non-UTF8 compatible files
Issue #3137 - Allow copying of SQL from the dashboard tables
Issue #3138 - Fix tablespace tests for Python 3.x
Issue #3150 - Fix function reserve SQL for GPDB
Issue #3157 - Fix unicode handling in the external process tools and show the complete command in the process viewer
Issue #3171 - Runtime issue causing inability to scroll in File Selector with trackpad on OSX
Issue #3176 - Disable function statistics on Greenplum
Issue #3180 - Ensure Indexes are displayed on PG 10 tables
Issue #3190 - Skip tests where appropriate on GPDB
Issue #3196 - Ensure the file manager properly escapes file & directory names
Issue #3197 - Appropriately set the cookie path
Issue #3200 - Ensure the host parameter is correctly pickup up from the service file
Issue #3219 - Update required ChromeDriver version for current versions of Chrome
Issue #3226 - Move the field error indicators in front of the affected fields so they don't obscure spinners or drop downs etc.
Issue #3244 - Show more granular timing info in the Query Tool history panel

Issue #3248 - Ensure Alertify dialogues are modal to prevent them being closed by mis-click

14.113 Version 2.1

Release date: 2018-01-11

This release contains a number of features and fixes reported since the release of pgAdmin4 2.0

14.113.1 Features

Issue #1383 - Allow connections to be coloured in the treeview and Query Tool
Issue #1489 - Improve user interface for selection query in Data Filter window
Issue #2368 - Improve data entry in Query Tool
Issue #2781 - Allow configuration of CSV and clipboard formatting of query results
Issue #2802 - Allow connections to be coloured in the treeview and Query Tool.
Issue #2810 - Allow files to be opened by double clicking on them within Query Tool
Issue #2845 - Make the "Save Changes" prompts in the Query Tool optional
Issue #2849 - Add support for editing data in tables with OIDs but no primary keys and updates the editor to retrieve all row values on save, thus immediately showing default values and allowing subsequent editing without a refresh

14.113.2 Bug fixes

Issue #1365 - Prevent the Windows installer accepting paths containing invalid characters
Issue #1366 - Fix /NOICONS switch in the windows installer
Issue #1436 - Fix issue with debugger which is failing for sub - procedure on PPAS 9.6
Issue #1749 - Fixes in pgAgent module including; 1) allowing start date earlier than end date when scheduling job, 2) Datetime picker not displaying in grid and 3) validation error not displaying propertly for Datetime control
Issue #2094 - Display relevant error messages when access is denied creating a schema
Issue #2098 - Cleanup some inconsistent error dialog titles
Issue #2258 - Fix handling of DATERANGE[] type
Issue #2278 - Display long names appropriately in dialogue headers
Issue #2443 - Confirm with the user before exiting the runtime
Issue #2524 - Fix debugging of self-referencing functions
Issue #2566 - Fix the Pause/Resume Replay of WAL files for PostgreSQL 10
Issue #2624 - Ensure the switch animation is consistent on the table dialogue and avoid displaying an error incorrectly
Issue #2651 - Ensure estimated rows are included correctly in CREATE script for functions
Issue #2679 - Getting started links does not open second time if User open any URL and Click on Close button with cross bar
Issue #2705 - User can add expirty date on Windows
Issue #2715 - Ensure we can download large files and keep the user informed about progress
Issue #2720 - Ensure password changes are successful if authenticating using a pgpass file
Issue #2726 - Ensure the auto-complete selection list can display longer names
Issue #2738 - Ensure line numbers form CodeMirror don't appear on top of menus
Issue #2748 - Format JSON/JSONB nicely when displaying it in the grid editor pop-up
Issue #2760 - When selecting an SSL cert or key, update only the expected path in the UI, not all of them

Issue #2765 - Do not decrypt the password when the password is 'None'. This should avoid the common but harmless exception "ValueError: IV must be 16 bytes long while decrypting the password."
Issue #2768 - Only allow specification of a pgpass file if libpq >= 10
Issue #2769 - Correct keyboard shortcut. Don't un-comment code with alt+. in the Query Tool. It's only supposed to respond to ctrl/cmd+
Issue #2772 - Remove external links from Panel's context menu
Issue #2778 - Ensure the datatype cache is updated when a domain is added
Issue #2779 - Ensure column collation isn't lost when changing field size
Issue #2780 - Ensure auto-indent honours the spaces/tabs config setting
Issue #2782 - Re-hash the way that we handle rendering of special types such as arrays
Issue #2787 - Quote the owner name when creating types
Issue #2806 - Attempt to decode database errors based on lc_messages
Issue #2811 - Display process output as it happens
Issue #2820 - Logs available when executing backup and restore
Issue #2821 - Attempt to decode database errors based on lc_messages
Issue #2822 - Re-hash the way that we handle rendering of special types such as arrays.
Issue #2824 - Fix a number of graphical explain rendering issues
Issue #2836 - Fix counted rows display in table properties
Issue #2842 - Fix a number of graphical explain rendering issues
Issue #2846 - Add an option to manually count rows in tables to render the properties
Issue #2854 - Fix utility output capture encoding
Issue #2859 - Allow form validation messages to be close in case the eclipse anything on the form
Issue #2866 - Ensure we don't show the full path on the server when using virtual filesystem roots in server mode for SSL certs
Issue #2875 - Ensure the scroll location is retains in the Query Tool data grid if the user changes tab and then returns
Issue #2877 - Remove the artificial limit of 4000 characters from text areas
Issue #2880 - Honour whitespace properly in the data grid
Issue #2881 - Fix support for time without timezone
Issue #2886 - Resolve issue where Insert failed when tried with default primary key value
Issue #2891 - Allow changing of the users password without leaving the app
Issue #2892 - Refuse password changes (and tell the user) if the notification email cannot be sent
Issue #2908 - Fix bundle creation on Windows which was failing due to rn line endings in code mirror
Issue #2918 - Add missing init.py to backports.csv when building the MSVC windows build
Issue #2920 - Push HTTPD logs to container stdout/stderr as appropriate
Issue #2921 - Fixes in pgAgent module including; 1) allowing start date earlier than end date when scheduling job, 2) Datetime picker not displaying in grid and 3) validation error not displaying propertly for Datetime control
Issue #2922 - Don't login the user with every request in desktop mode. Just do it once
Issue #2923 - Prevent the user pressing the select button in the file manager when it is supposed to be disabled
Issue #2924 - Cleanup the layout of the filter data dialogue
Issue #2928 - Prevent multiple connections to new slow-to-respond servers being initiated in error
Issue #2934 - Fix a reference before assignment error in the file dialogue
Issue #2937 - Prevent attempts to select directories as files in the file dialogue
Issue #2945 - Ensure invalid options can't be selected on triggers on views
Issue #2949 - Display complete SQL for FTS dictionaries
Issue #2952 - Don't try to render security URLs in desktop mode
Issue #2954 - Allow selection of validation error text
Issue #2974 - Clear the messages tab when running EXPLAIN/EXPLAIN ANALYZE

Issue #2993 - Fix view data for views/mat views

14.114 Version 2.0

Release date: 2017-10-05

This release contains a number of features and fixes reported since the release of pgAdmin4 1.6

14.114.1 Features

Issue #1918 - Add a field to the Server Dialogue allowing users to specify a subset of databases they'd like to see in the treeview
Issue #2135 - Significantly speed up loading of the application
Issue #2556 - Allow for slow vs. fast connection failures
Issue #2579 - Default the file browser view to list, and make it configurable
Issue #2597 - Allow queries to be cancelled from the dashboard and display additional info in the subnode control
Issue #2649 - Support use of SSL certificates for authentication
Issue #2650 - Support use of pgpass files
Issue #2662 - Ship with pre-configured paths that can work in both Server and Desktop modes out of the box
Issue #2689 - Update icons with new designs and remove from menus to de-clutter the UI

14.114.2 Bug fixes

Issue #1165 - Prevent continual polling for graph data on the dashboard if the server is disconnected
Issue #1697 - Update CodeMirror version
Issue #2043 - Properly handle trigger functions with parameters
Issue #2074 - Make $ quoting consistent
Issue #2080 - Fix issue where Browser hangs/crashes when loading data (using sql editor) from table which contains large blob data
Issue #2153 - Fix handline of large file uploads and properly show any errors that may occur
Issue #2168 - Update CodeMirror version
Issue #2170 - Support SSL in the regression tests
Issue #2324 - Fix PostGIS Datatypes in SQL tab, Create / Update dialogues for Table, Column, Foreign Table and Type node
Issue #2447 - Update CodeMirror version
Issue #2452 - Install pgadmin4-v1 1.5 on Centos7
Issue #2501 - Fix collation tests on Windows, replace use of default 'POSIX' collation with 'C' collation for testing
Issue #2541 - Fix issues using special keys on MacOS
Issue #2544 - Correct malformed query generated when using custom type
Issue #2551 - Show tablespace on partitions
Issue #2555 - Fix issue in Query Tool where messages were not displaying from functions/procedures properly
Issue #2557 - Tidy up tab styling
Issue #2558 - Prevent the tab bar being hidden when detached tabs are being closed
Issue #2559 - Stop tool buttons from changing their styling unexpectedly
Issue #2560 - Fix View 'CREATE Script' Problem
Issue #2562 - Update CodeMirror version

Issue #2563 - Fix paths under non-standard virtual directories
Issue #2566 - Fix Pause/Resume Replay of WAL files for PostgreSQL 10
Issue #2567 - Use the proper database connection to fetch the default priviledges in the properties tab of the database
Issue #2582 - Unset compression ratio if it is an empty string in Backup module
Issue #2586 - Cleanup feature tests
Issue #2590 - Allow navigation of query history using the arrow keys
Issue #2592 - Stop Flask from initialising service twice in Debug mode
Issue #2593 - Ensure babel-polyfill is loaded in older qWebKits
Issue #2594 - Fix disconnection of new databases
Issue #2596 - Define the proper NODE_ENV environment during running the webpack
Issue #2606 - Ensure role names are escaped in the membership control
Issue #2616 - Domain create dialog do not open and Font size issue in Security label control
Issue #2617 - Add missing pgagent file in webpack.config.js
Issue #2619 - Fix quoting of index column names on tables
Issue #2620 - Set database name to blank('') when job type is set to batch, while creating pgAgent job
Issue #2631 - Change mapping of cell from 'numeric' to 'integer' for integer control as numeric cell has been removed from the code
Issue #2633 - Fix pgAgent job step issues
Issue #2634 - Add New Server through Quick links
Issue #2637 - Fix Copy so it still works after query results have been copied
Issue #2641 - User management issues - styling and inability to edit users properly
Issue #2644 - Fix alertify notification messages where checkmark box disconnected from frame
Issue #2646 - Fix the path reference of load-node.gif which was referencing to vendor directory
Issue #2654 - Update datetime picker
Issue #2655 - Fix connection string validation for pgAgent jobs
Issue #2656 - Change Datetimepicker to expand from bottom in pgAgent so calendar does not get hidden
Issue #2657 - Fix syntax error while saving changes for start/end time, weekdays, monthdays, month, hours, minutes while updating the pgAgent Job
Issue #2659 - Fix issue where unable to add/update variables for columns of a table
Issue #2660 - Not able to select rows in History Tab
Issue #2668 - Fix RE-SQL for triggers with a single arg
Issue #2670 - Improve datamodel validations for default Validator if user (developer) does not implement validate function in datamodel
Issue #2671 - Fix array data type formating for bigint, real, float, double precision
Issue #2681 - Reset Query Tool options before running tests
Issue #2684 - Fix layout of password prompt dialogue
Issue #2691 - View data option is missing from pgAdmin4 2.0 version
Issue #2692 - Base type is missing for Domain on pgAdmin4
Issue #2693 - User list is not available on User mapping pgAdmin4
Issue #2698 - User can not create function due to missing return type
Issue #2699 - Filtered Rows issue on pgAdmin4
Issue #2700 - Cancel button is visible after query executed succesfully
Issue #2707 - Disable trigger button does not work on pgAdmin4
Issue #2708 - Tablespace name should displayed instead of %s(new_tablespace)s with Move Objects to another tablespace
Issue #2709 - Display user relations in schema prefixed by 'pg'
Issue #2713 - Fix an exception seen sometimes when the server is restarted

Issue #2742 - Ensure using an alternate role to connect to a database doesn't cause an error when checking recovery state.

14.115 Version 1.6

Release date: 2017-07-13

This release contains a number of features and fixes reported since the release of pgAdmin4 1.5

14.115.1 Features

Issue #1344 - Allow the Query Tool, Debugger and web browser tabs to be moved to different monitors as desired
Issue #1533 - Set focus on the first enabled field when a dialogue is opened
Issue #1535 - Teach dialogues about Escape to cancel, Enter to Save/OK, and F1 for help
Issue #1971 - Retain column sizing in the Query Tool results grid when the same query is re-run multiple times in a row
Issue #1972 - Prompt the user to save dirty queries rather than discard them for a more natural workflow
Issue #2137 - On-demand loading for the Query Tool results
Issue #2191 - Add support for the hostaddr connection parameter. This helps us play nicely with Kerberos/SSPI and friends
Issue #2282 - Overhaul the query history tab to allow browsing of the history and full query text
Issue #2379 - Support inserting multiple new rows into a table without clicking Save for each row
Issue #2485 - Add a shortcut to reset the zoom level in the runtime
Issue #2506 - Allow the user to close the dashboard panel
Issue #2513 - Add preferences to enable brace matching and brace closing in the SQL editors

14.115.2 Bug fixes

Issue #1126 - Various FTS dictionary cleanups
Issue #1229 - Fix default values and SQL formatting for event triggers
Issue #1466 - Prevent attempts to debug procedures with variadic arguments
Issue #1525 - Make $ quoting consistent
Issue #1575 - Properly display security labels on EPAS 9.2+
Issue #1795 - Fix validation for external and range types
Issue #1813 - List packages in PPAS 9.2-9.4 when creating synonyms
Issue #1831 - Fix server stats display for EPAS 9.2, where inet needs casting to text for concatenation
Issue #1851 - Reverse engineer SQL for table-returning functions correctly
Issue #1860 - Ensure default values are honoured when adding/editing columns
Issue #1888 - Fix various issues with pgAgent job steps and schedules
Issue #1889 - Fix various issues with pgAgent job steps and schedules
Issue #1890 - Fix various issues with pgAgent job steps and schedules
Issue #1920 - Ensure saved passwords are effective immediately, not just following a restart when first saved
Issue #1928 - Fix the handling of double precision[] type
Issue #1934 - Fix import/export to work as expected with TSV data
Issue #1999 - Handle warning correctly when saving query results to an unmounted USB drive

Issue #2013 - Increase the default size of the Grant Wizard to enable it to properly display privileges at the default size on smaller displays
Issue #2014 - To fix unexpected behaviour displayed if user stops debugging on package/procedure fire_emp
Issue #2043 - Properly handle trigger functions with parameters
Issue #2078 - Refresh the SQL editor view on resize to ensure the contents are re-rendered for the new viewport
Issue #2086 - Allow editing of the WITH ADMIN option of role membership
Issue #2113 - Correct the validation logic when modifying indexes/exclusion constraints
Issue #2116 - Enable dialogue help buttons on Language and Foreign Table dialogues
Issue #2142 - Fix canceling of Grant Wizard on Windows
Issue #2155 - Fix removal of sizes from column definitions
Issue #2162 - Allow non-superusers to debug their own functions and prevent them from setting global breakpoints
Issue #2242 - Fix an issue in NodeAjaxControl caching with cache-node field and add cache-node field in Trigger & Event trigger node so that whenever the user creates new Trigger Function we get new data from server in NodeAjaxControl
Issue #2280 - Handle procedure flags (IMMUTABLE STRICT SECURITY DEFINER PARALLEL RESTRICTED) properly in RE-SQL on EPAS
Issue #2324 - Fix the PostGIS Datatypes in SQL tab, Create / Update dialogues for Table, Column, Foreign Table and Type node
Issue #2344 - Fix issue with ctrl-c / ctrl-v not working in Query Tool
Issue #2348 - Fix issue when resizing columns in Query Too/View Data where all row/colums will select/deselect
Issue #2355 - Properly refresh the parent node when renaming children
Issue #2357 - Cache statistics more reliably
Issue #2381 - Fix the RE-SQL for for views to properly qualify trigger function names
Issue #2386 - Display and allow toggling of trigger enable/disable status from the trigger dialogue
Issue #2398 - Bypass the proxy server for local addresses on Windows
Issue #2400 - Cleanup handling of default/null values when data editing
Issue #2414 - Improve error handling in cases where the user tries to rename or create a server group that would duplicate an existing group
Issue #2417 - Order columns in multi-column pkeys correctly
Issue #2422 - Fix RE-SQL for rules which got the table name wrong in the header and DROP statement
Issue #2425 - Handle composite primary keys correctly when deleting rows in the Edit Grid
Issue #2426 - Allow creation of ENUM types with no members
Issue #2427 - Add numerous missing checks to ensure objects really exist when we think they do
Issue #2435 - Pass the database ID to the Query Tool when using the Script options
Issue #2436 - Ensure the last placeholder is included when generating UPDATE scripts for tables
Issue #2448 - Ensure that boolean checkboxes cycle values in the correct order
Issue #2450 - Fix error on the stats tab with PG10. Also, rename the 10.0_plus template directory to 10_plus to match the new versioning
Issue #2461 - Allow users to remove default values from columns properly
Issue #2468 - Fix issue where function create script won't compile
Issue #2470 - Fix an intermittent error seen during result polling
Issue #2476 - Improvements to the Query Results grid including improvements to the UI and allow copy/paste from sets of rows, columns or arbitrary blocks of cells
Issue #2477 - Ensure text editors render in an appropriate place on the results grid
Issue #2479 - No need for the menu icon to link to the homepage, as pgAdmin is a SPA
Issue #2482 - Use a more sensible name for Query Tool tabs
Issue #2486 - Ensure the feature tests use the correct test settings database
Issue #2487 - Maintain a client-side cache of preference values, populated using an async call

Issue #2489 - Fix clipboard handling with large datasets
Issue #2492 - Ensure the initial password is properly hashed during setup in web mode
Issue #2498 - Properly handle bytea[], and 'infinity'::real/real[]
Issue #2502 - Properly handle bytea[], and 'infinity'::real/real[]
Issue #2503 - Handle missing/dropped synonyms gracefully
Issue #2504 - Update MatView and pgAgent modules to work with recent integer/numeric changes
Issue #2507 - Ensure revoked public privileges are displayed in the RE-SQL for functions
Issue #2518 - Fix encoding issue when saving servers
Issue #2522 - Improve speed of Select All in the results grid
Issue #2527 - Fix deletion of table rows with the column definition having NOT NULL TRUE and HAS NO DEFAULT VALUE
Issue #2528 - Allow breakpoints to be set on triggers on views
Issue #2529 - Resolve a number of issues with domains and domain constraints
Issue #2532 - Refresh nodes correctly when there is a single child that is updated
Issue #2534 - Fix handling of CREATE TABLE OF <type>
Issue #2535 - Fix clear history functionality
Issue #2540 - Ensure the save password option is enabled when creating a server

14.116 Version 1.5

Release date: 2017-05-19

This release contains a number of features and fixes reported since the release of pgAdmin4 1.4.

14.116.1 Features

Issue #2216 - Allow column or row selection in the Query Tool

14.116.2 Bug fixes

Issue #2225 - Hide menu options for creating objects, if the object type is set to hidden. Includes Jasmine tests
Issue #2253 - Fix various issues in CSV file download feature
Issue #2257 - Improve handling of nulls and default values in the data editor
Issue #2271 - Don't change the trigger icon back to "enabled" when the trigger is updated when it's disabled
Issue #2284 - Allow creation of tables with pure numeric names
Issue #2292 - Only reconnect to databases that were previously connected
Issue #2314 - Fix various issues in CSV file download feature
Issue #2315 - Fix sorting of sizes on the statistics views by sorting raw values and prettifying on the client side. Includes Jasmine tests for the prettyfying function
Issue #2318 - Order foreign table columns correctly
Issue #2331 - Fix binary search algorithm so new treeview nodes are added in the correct position
Issue #2336 - Update inode info when refreshing treeview nodes.
Issue #2339 - Ensure the treeview can be scrolled horizontally
Issue #2350 - Fix handling of default parameters ordering in functions
Issue #2354 - Fix the Backup module where it was not working if user changes its preference language other than English

Issue #2356 - Ensure errors thrown when deleting rows in the Query Tool in edit mode are shown properly
Issue #2360 - Fix various issues in CSV file download feature
Issue #2369 - Support loading files with Unicode BOMs
Issue #2377 - Update psycopg2 version for PostgreSQL 10 compatibility
Issue #2379 - Make various improvements to the NULL/DEFAULT handling in the data editor
Issue #2405 - Ensure object names are properly escaped for external process management
Issue #2410 - Fix PostgreSQL 10.0 compatibility issues

14.117 Version 1.4

Release date: 2017-04-13

This release contains a number of features and fixes reported since the release of pgAdmin4 1.3.

14.117.1 Features

Issue #2232 - Add the ability to gray-out/disable the "Save Password" option when creating a connection to a server
Issue #2261 - Display table DDL for Greenplum in SQL tab
Issue #2320 - Added German translation

14.117.2 Bug fixes

Issue #2077 - Add missing "Run Now" option for pgAdmin jobs
Issue #2105 - Fix validation on the table dialogue so the Save button isn't enabled if the name is removed and autovac custom settings are enabled
Issue #2145 - Resolve the issue for restoring the table from the backup
Issue #2187 - Ensure the web/ directory is cleared before upgrading Windows installations
Issue #2190 - Allow users to select UI language at login or from Preferences rather than unpredictable behaviour from browsers
Issue #2226 - Show tooltips for disabled buttons to help user learning
Issue #2241 - Fix numeric control validation in nested schemas
Issue #2243 - Fix dropping of databases with Unicode names
Issue #2244 - Prevent an error being displayed if the user views data on a table with no columns
Issue #2246 - Add missing braces to reverse engineered SQL header block for Functions
Issue #2258 - Fix handling of DATERANGE[] type
Issue #2264 - Resolve error message *ExtDeprecationWarning* displayed on new pgAdmin4 setup for Python 3.4 on ubuntu 14.04 Linux 64
Issue #2265 - Resolved import/Export issue for a table
Issue #2274 - Properly handle truncated table names
Issue #2277 - Resolved various file-system encoding/decoding related cases
Issue #2281 - Ensure menus are updated after disconnecting a server
Issue #2283 - Check if cell is in multiselect mode before setting default selection of multiple values
Issue #2287 - Properly handle EXPLAIN queries entered directly by the user in the Query Tool
Issue #2291 - Fix error highlighting in the Query Tool
Issue #2299 - Fix usage of QString
Issue #2303 - Fix ascending/descending sort order in backgrid while clicking on the headers

Issue #2304 - Resolve the issue for restoring the table from the backup
Issue #2305 - Resolve the issue where Generic function qtLiteral was not adapting values properly when they contain non ascii characters
Issue #2310 - Fix Dialog Help where Query Tool/Debugger opens in new browser tab
Issue #2319 - Resolve issue where Click on pgAdmin4 logo leads to unauthorized error
Issue #2321 - Improved functionality of browser tree when adding new nodes if parent collection node has not loaded
Issue #2330 - Ensure the Query Tool displays but does not render HTML returned by the server in the results grid

14.118 Version 1.3

Release date: 2017-03-10

This release contains a number of features and fixes reported since the release of pgAdmin4 1.2.

14.118.1 Features

Issue #2036 - Query tool efficiency - SlickGrid result set format efficiency
Issue #2038 - Query tool efficiency - Incremental back off when polling
Issue #2163 - Make syntax highlighting more visible
Issue #2210 - Build a universal Python wheel instead of per-python-version ones
Issue #2215 - Improve visibility of syntax highlighting colours

14.118.2 Bug fixes

Issue #1796 - Add missing “Run Now” option for pgAdmin jobs
Issue #1797 - Resolve encoding issues with DATA_DIR
Issue #1914 - Resolved error utf8’ codec can’t decode byte
Issue #1983 - Fix bug in Sql query contains Arabic Charaters
Issue #2089 - Add PARALLEL SAFE|UNSAFE|RESTRICTED support
Issue #2115 - Fix exclusion constraint reverse engineered SQL
Issue #2119 - Fix display of long integers and decimals
Issue #2126 - Correct node labels in Preferences for EDB functions and procedures
Issue #2151 - Display un-sized varlen column types correctly in the Query Tool
Issue #2154 - Fix display of long integers and decimals
Issue #2159 - Resolve issue where Query editor is not working with Python2.6
Issue #2160 - Various encoding fixes to allow ‘ascii’ codec to decode byte 0xc3 in position 66: ordinal not in range(128)
Issue #2166 - Resolved import/Export issue for a table
Issue #2173 - Resolved issues where Sequences API test cases are not working in PG9.2 and PPAS9.2
Issue #2174 - Resolved various file-system encoding/decoding related cases
Issue #2185 - Removed sorting columns on the treeview
Issue #2192 - Fix startup complete tests to ensure we properly poll the server for completed startup
Issue #2198 - Fix function arguments when generating create SQL
Issue #2200 - Properly handle event trigger functions in different schemas
Issue #2201 - Fix renaming of check constraints when the table name is changed at the same time
Issue #2202 - Fix issue where Dependents query fails due to non ascii characters

Issue #2204 - Fixed issue where pgadmin 4 jobs not showing any activity
Issue #2205 - Fix display of boolean nulls in the Query Tool
Issue #2208 - Ensure primary key column names are quoted in View Data mode of the Query Tool
Issue #2212 - Ensure servers are deleted when their parent group is deleted
Issue #2213 - Enable right click on browser tree
Issue #2218 - Show the correct indeterminate state when editing new boolean values
Issue #2228 - Authenticate the runtime to the server
Issue #2230 - Prevent the Slonik logo obscuring the login dialogue on small displays in server mode

14.119 Version 1.2

Release date: 2017-02-10

This release contains a number of features and fixes reported since the release of pgAdmin4 1.1.

14.119.1 Features

Issue #1375 - Migrate the runtime to QtWebEngine from QtWebKit
Issue #1765 - Find and replace functionality with regexp and group replacement
Issue #1789 - Column width of data output panel should fit to data (as pgAdmin III)
Issue #1790 - [Web] Support setting a field's value to "null"
Issue #1848 - macOS appbundle is missing postgresql binaries for import etc.
Issue #1910 - Remember last used directory in the file manager
Issue #1911 - Direct path navigation in the file manager
Issue #1922 - Improve handling of corrupt configuration databases
Issue #1963 - Add a Chinese (Simplified) translation
Issue #1964 - Create a docs tarball along with the source tarball
Issue #2025 - Allow the SQL Editors to word-wrap
Issue #2124 - Create a template loader to simplify SQL template location, and remove duplicate templates

14.119.2 Bug fixes

Issue #1227 - Display improved error message for Debugger listener starting error and reset between executions
Issue #1267 - Fix issue where MINIFY_HTML doesn't work with the docs
Issue #1364 - Ensure dialogue control buttons are consistent
Issue #1394 - Fix Table dialogue column specification issues
Issue #1432 - Enhanced OSX File Browser
Issue #1585 - Cannot save scripts to the network
Issue #1599 - Ensure the grant wizard works with objects with special characters in the name
Issue #1603 - Fix quoting of objects names for external utilities.
Issue #1679 - Re-engineer the background process executor to avoid using sqlite as some builds of components it relies on do not support working in forked children
Issue #1680 - Render column headers at the correct width in the Query Tool under Firefox
Issue #1729 - Improve display of role options
Issue #1730 - Improve the display of role membership on both the properties panel and role dialogue
Issue #1745 - Ensure breakpoints are cleared properly when working with Debugger

Issue #1747 - Add newly created triggers to the treeview
Issue #1780 - Properly size the SQL Editor gutter as the width of the line numbers increases
Issue #1792 - List files and folders alphabetically
Issue #1800 - Handle the template property on databases appropriately
Issue #1801 - Handle databases with datallowconn == false
Issue #1807 - Properly detect when files have changed in the Query Tool and set flag accordingly
Issue #1830 - Fix a SQL error when reverse-engineering ROLE SQL on EPAS servers
Issue #1832 - Prevent attempts to access what may be an empty list in Dependancies tab
Issue #1840 - Enable/disable NULLs and ASC/DESC options for index columns and exclusion constraints appropriately
Issue #1842 - Show index columns in the correct order in RE-SQL
Issue #1855 - Ensure dialogue panels show their errors themselves, and not in the properties panel when creating Trigger Function
Issue #1865 - Properly schema qualify domains when reverse engineering SQL
Issue #1874 - Add file resources to the windows runtime
Issue #1893 - Fix refreshing of Unique constraints
Issue #1896 - Use the correct OID for retrieving properties of freshly created exclusion constraints
Issue #1899 - Properly quote role names when specifying function ownership
Issue #1909 - Handle startup errors more gracefully in the runtime
Issue #1912 - Properly format arguments passed by triggers to functions
Issue #1919 - Ensure all changes to rows are stored in the data editor
Issue #1924 - Ensure the check_option is only set when editing views when appropriate
Issue #1936 - Don't strip rn from "Download as CSV" batches of rows, as it leads to malformed data
Issue #1937 - Generate mSQL for new schemas correctly
Issue #1938 - Fix sorting of numerics in the statistics grids
Issue #1939 - Updated dynamic default for the window size (90% x 90%)
Issue #1949 - Ensure trigger function names are schema qualified in trigger RE-SQL
Issue #1951 - Fix issue where nnable to browse table columns when oid values exceeed max int
Issue #1953 - Add display messages and notices received in the Query Tool
Issue #1961 - Fix upgrade check on Python 3
Issue #1962 - Ensure treeview collection nodes are translated in the UI
Issue #1967 - Store layout changes on each adjustment
Issue #1976 - Prevent users selecting elements of the UI that shouldn't be selectable
Issue #1979 - Deal with Function arguments correctly in the properties dialogue
Issue #1986 - Fix various encoding issues with multibyte paths and filenames resulting in empty file save
Issue #1992 - Quote identifiers correctly in auto-complete
Issue #1994 - Update to show modifications in edit grid
Issue #2000 - Allow setting of effective_io_concurrency on tablespaces in 9.6+
Issue #2005 - Fix various mis-spellings of VACUUM
Issue #2006 - Fix error when modifying table name or set schema on tables with postgis geometry column
Issue #2007 - Correctly sort rows by the pkey when viewing first/last 100
Issue #2009 - Reset the column list properly if the access method is changed on an index to ensure error handling works correctly
Issue #2012 - Prevent attempts to create server groups with no name
Issue #2015 - Enable trigger option when user tries to change Row trigger value through properties section
Issue #2024 - Properly handle setting comments and other options on databases with allowconn = False
Issue #2026 - Improve detection of the pldbgapi extension and functions before allowing debugging

Issue #2027 - Fix inconsistent table styling
Issue #2028 - Fix display of double scrollbars on the grant wizard
Issue #2032 - Fix time formatting on dashboards
Issue #2033 - Show icons for unique and exclusion constraints in the dependency/dependents panels
Issue #2045 - Update copyright year on doc page
Issue #2046 - Fix error when setting up regression on Windows for pgadmin4
Issue #2047 - Ensure dialogues cannot be moved under the navbar
Issue #2061 - Enable/disable NULLs and ASC/DESC options for index columns and exclusion constraints appropriately
Issue #2065 - Improve display of columns of exclusion contraints and foreign keys in the properties lists
Issue #2069 - Correct tablespace displayed in table properties
Issue #2076 - Handle sized time/timestamp columns correctly
Issue #2109 - Update copyright year
Issue #2110 - Handle saved directories that no longer exist gracefully
Issue #2112 - Enable comments on Initial database through right Click
Issue #2133 - Fix display of graphical query plans for UPDATE/DELETE queries
Issue #2138 - Fix display of zeros in read-only grid editors
Issue #2139 - Fixed issue causing Message (Connection to the server has been lost.) displayed with Materialized view and view under sql tab
Issue #2152 - Fix handling of "char" columns
Issue #2156 - Added compatibility fixes for newer versions of Jinja2 (e.g. 2.9.5+)

14.120 Version 1.1

Release date: 2016-10-27

This release contains a number of features and fixes reported since the release of pgAdmin4 1.0;

14.120.1 Features

Issue #1328 - Add Python 3.5 Support
Issue #1859 - Include wait information on the activity tab of the dashboards

14.120.2 Bug fixes

Issue #1155 - Display the start value when the user creates sequence
Issue #1531 - Fix to update privileges for Views and Materials Views where "string indices must be integers error" displayed
Issue #1574 - Display SQL in SQL pane for security label in PG and EPAS server
Issue #1576 - Make security label option available in procedure properties
Issue #1577 - Make debug option available for package function and procedure
Issue #1596 - Correct spelling error from evnt_turncate to evnt_truncate
Issue #1599 - Ensure the grant wizard works with objects with special characters in the name
Issue #1622 - Fix issue using special characters when creating synonym
Issue #1728 - Properties refreshing after objects are edited
Issue #1739 - Prevent the user from trying to…..

Issue #1785 - Correctly identify server type upon first connection
Issue #1786 - Ensure errorModel unset property is set correctly when adding a new server
Issue #1808 - Set seconds to valid value in pgAgent job schedule
Issue #1817 - Display message "server does not support ssl" if server with ca-cert or ca-full added
Issue #1821 - Optionally sign both the Mac app bundle and the disk image
Issue #1822 - Handle non-ascii responses from the server when connecting
Issue #1823 - Attempt to sign the Windows installer, failing with a warning if there's no cert available
Issue #1824 - Add documenation for pgAgent
Issue #1835 - Allow users to choose SELECT permissions for tables and sequences in the grant wizard
Issue #1837 - Fix refreshing of FTS dictionaries which was causing error "Connection to the server has been lost"
Issue #1838 - Don't append new objects with the wrong parent in tree browser if the correct one isn't loaded
Issue #1843 - Function definition matches value returned from pg_get_functiondef()
Issue #1845 - Allow refreshing synonym node. Does not display message "Unimplemented method (node) for this url (/browser/synonym/nodes/1/7/14301/2200/test)"
Issue #1847 - Identify the collation correctly when reverse engineering table SQL. ERROR: schema "default" does not exist no longer displayed
Issue #1849 - Remove security keys from config.py/config_local.py
Issue #1857 - Fix error while renaming FTS dictionary and FTS template nodes
Issue #1858 - Ensure the File Manager honours the file type while traversing the directories.
Issue #1861 - Properly generate exclusion constraint SQL.
Issue #1863 - Correctly quote type names in reverse engineered SQL for tables
Issue #1864 - Fix layout of DateTimePicker control help message.
Issue #1867 - Allow package bodies to be dropped.
Issue #1868 - Resolved issue where Integer type of preferences are not updated
Issue #1872 - Fix the file manager when used under Python 3.
Issue #1877 - Ensure preferences values are stored properly.
Issue #1878 - Ensure steps and schedules can be created in empty jobs. ProgrammingError: can't adapt type 'Undefined' was displayed
Issue #1880 - Add new indexes to the correct parent on the treeview.

14.121 Version 1.0

Release date: 2016-09-29

The first major release of pgAdmin 4. With a more modern look and feel, this release includes the following features;

- Multiplatform
- Designed for multiple PostgreSQL versions and derivatives
- Extensive documentation
- Multiple deployment models
- Tools
- Routine maintenance
- Create, view and edit all common PostgreSQL objects
- Multibyte support

CHAPTER 15

Licence

pgAdmin is released under the PostgreSQL Licence, which is a liberal Open Source licence similar to BSD or MIT, and approved by the Open Source Initiative. The copyright for the project source code, website and documentation is attributed to the pgAdmin Development Team

pgAdmin 4

Copyright (C) 2013 - 2026, The pgAdmin Development Team

Permission to use, copy, modify, and distribute this software and its documentation for any purpose, without fee, and without a written agreement is hereby granted, provided that the above copyright notice and this paragraph and the following two paragraphs appear in all copies.

IN NO EVENT SHALL THE PGADMIN DEVELOPMENT TEAM BE LIABLE TO ANY PARTY FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS, ARISING OUT OF THE USE OF THIS SOFTWARE AND ITS DOCUMENTATION, EVEN IF THE PGADMIN DEVELOPMENT TEAM HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

THE PGADMIN DEVELOPMENT TEAM SPECIFICALLY DISCLAIMS ANY WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE SOFTWARE PROVIDED HEREUNDER IS ON AN "AS IS" BASIS, AND THE PGADMIN DEVELOPMENT TEAM HAS NO OBLIGATIONS TO PROVIDE MAINTENANCE, SUPPORT, UPDATES, ENHANCEMENTS, OR MODIFICATIONS.

Note

Postgres, PostgreSQL and the Slonik Logo are trademarks or registered trademarks of the PostgreSQL Community Association of Canada, and used with their permission.

Index

A

Add Named Restore Point Dialog, 441
AI Reports, 541
Amazon RDS Cloud Deployment, 151
Azure Database Cloud Deployment, 157

B

Backup and Restore, 463
Backup Dialog, 463
Backup Globals Dialog, 471
Backup Server Dialog, 472

C

Cast Dialog, 217
Change Ownership Dialog, 66
Change pgAdmin Password Dialog, 68
Change Server Password Dialog, 442
Check Dialog, 365
Clear Saved Passwords, 150
Code Overview, 572
Code Review Notes, 591
Coding Standards, 576
Collation Dialog, 234
Column Dialog, 368
Compound Trigger Dialog, 377
Configuration Files, 4
Connect to Server, 177
Connecting To A Server, 141
Connection Error, 178
Container Deployment, 46
Creating a pgAgent Job, 552
Creating or Modifying a Table, 365

D

Database Dialog, 187
DBMS Job, 222
DBMS Program, 227
DBMS Schedule, 232
Debugger, 483
Deployment, 4
Desktop Deployment, 30
Developer Tools, 483
Directory Dialog, 213
Domain Constraints Dialog, 242
Domain Dialog, 238

E

Enabling Kerberos Authentication, 73
Enabling LDAP Authentication, 70
Enabling OAUTH2 and OIDC Authentication, 76
Enabling two-factor authentication (*2FA*), 58
Enabling Webserver Authentication, 86
ERD Tool, 530
Event Trigger Dialog, 246
Exclusion Constraint Dialog, 382
Export Data Using Query Dialog, 445
Extension Dialog, 250
External database for pgAdmin user settings, 139

F

Foreign Data Wrapper Dialog, 252
Foreign key Dialog, 385
Foreign Server Dialog, 258
Foreign Table Dialog, 263
FTS Configuration Dialog, 270
FTS Dictionary Dialog, 273
FTS Parser Dialog, 278
FTS Template Dialog, 281
Function Dialog, 284

G

Getting Started, 3
Google Cloud SQL Deployment, 164
Grant Wizard, 443

I

Import/Export Data Dialog, 449

Import/Export Servers, 180
Index Dialog, 392
Installing pgAgent, 550

K

Keyboard Shortcuts, 133

L

Language Dialog, 291
Licence, 747
Lock/Restore Account, 69
Login Page, 57
Login/Group Role Dialog, 195

M

Maintenance Dialog, 454
Management Basics, 441
Managing Cluster Objects, 187
Managing Database Objects, 217
Master Password, 175
Materialized View Dialog, 295
Menu Bar, 89

O

Object Explorer Filter, 96

P

Package Dialog, 299
pgAdmin Project Contributions, 571
pgAgent, 549
PGD Replication Group Node Dialog, 208
PGD Replication Server Node Dialog, 209
pgEdge Starfleet Deployment, 170
pgTimeTable Chains, 563
PostgreSQL Cloud Deployment, 151
Preferences, 109
Primary key Dialog, 396
Procedure Dialog, 304
Processes, 547
PSQL Tool, 539
Publication Dialog, 312

Q

Query Tool, 489
Query Tool Toolbar, 492

R

Replica Node Dialog, 207
Resource Group Dialog, 193
Restore Dialog, 477
RLS Policy Dialog, 400
Role Reassign/Drop Own Dialog, 210
Rule Dialog, 403

S

Schema Dialog, 316
Schema Diff, 525
Search objects, 136
Sequence Dialog, 321
Server Deployment, 38
Server Dialog, 142
Server Group Dialog, 141
Statistics Dialog, 326
Storage Manager, 457
Submitting Pull Requests, 571
Subscription Dialog, 328
Synonym Dialog, 336

T

Tabbed Browser, 96
Table Dialog, 410
Tablespace Dialog, 202
Toolbar, 96
Translations, 592
Tree Control, 106
Trigger Dialog, 431
Trigger Function Dialog, 339
Type Dialog, 348

U

Unique Constraint Dialog, 437
User Interface, 88
User Management, 60
User Mapping Dialog, 356
Using EDB Job Scheduler, 220
Using pgAgent, 549

V

View Dialog, 359
View/Edit Data, 519
View/Edit Data Filter, 524